



FCC Part 15C Test Report

FCC ID: 2A5QJZENSTREAM

Applicant: Abbingdon Global Limited

Address: 79 SCARISBRICK NEW ROAD SOUTHPORT ENGLAND United Kingdom

Manufacturer: Abbingdon Global Limited

Address: 79 SCARISBRICK NEW ROAD SOUTHPORT ENGLAND United Kingdom

EUT: Media Player

Trade Mark: 

Model Number: ZEN STREAM

Date of Receipt: Mar. 14, 2022

Test Date: Mar. 14 - 25, 2022

Date of Report: Mar. 25, 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.407
ANSI C63.10:2013
KDB 789033 D02 v01r02

Test Result: Pass

Report Number: DL-20220324011E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1.SUMMARY OF TEST RESULTS.....	4
1.1 TEST FACILITY.....	5
1.2 MEASUREMENT UNCERTAINTY.....	5
2. GENERAL INFORMATION.....	6
2.1 GENERAL DESCRIPTION OF EUT.....	6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS.....	10
3.EMC EMISSION TEST.....	11
3.1 CONDUCTED EMISSION MEASUREMENT.....	11
3.1.1 POWER LINE CONDUCTED EMISSION Limits.....	11
3.1.2 TEST PROCEDURE.....	11
3.1.3 DEVIATION FROM TEST STANDARD.....	11
3.1.4 TEST SETUP.....	12
3.1.5 EUT OPERATING CONDITIONS.....	12
3.1.6 TEST RESULTS.....	13
3.2 RADIATED EMISSION MEASUREMENT.....	15
3.2.1 APPLICABLE STANDARD.....	15
3.2.2 CONFORMANCE LIMIT.....	15
3.2.3 MEASURING INSTRUMENTS.....	15
3.2.4 TEST CONFIGURATION.....	16
3.2.5 TEST PROCEDURE.....	17
4.POWER SPECTRAL DENSITY TEST.....	22
4.1 APPLIED PROCEDURES / LIMIT.....	22
4.2 TEST PROCEDURE.....	23
4.3 DEVIATION FROM STANDARD.....	23
4.4 TEST SETUP.....	23
4.5 EUT OPERATION CONDITIONS.....	23
4.6 TEST RESULTS.....	24
5. 26DB & 6DB EMISSION BANDWIDTH.....	30
5.1 APPLIED PROCEDURES / LIMIT.....	30
5.2 TEST PROCEDURE.....	30
5.3 EUT OPERATION CONDITIONS.....	31
5.4 TEST RESULTS.....	31
6.MAXIMUM CONDUCTED OUTPUT POWER.....	37



Table of Contents	Page
6.1 PPLIED PROCEDURES / LIMIT.....	37
6.2 TEST PROCEDURE.....	37
6.3 DEVIATION FROM STANDARD.....	38
6.4 TEST SETUP.....	38
6.5 EUT OPERATION CONDITIONS.....	38
6.6 TEST RESULTS.....	39
7.OUT OF BAND EMISSIONS.....	40
7.1 APPLICABLE STANDARD.....	40
7.2 TEST PROCEDURE.....	40
7.3 DEVIATION FROM STANDARD.....	40
7.4 TEST SETUP.....	40
7.5 EUT OPERATION CONDITIONS.....	41
7.6 TEST RESULTS.....	41
8.SPURIOUS RF CONDUCTED EMISSIONS.....	44
8.1 CONFORMANCE LIMIT.....	44
8.2 MEASURING INSTRUMENTS.....	44
8.3 TEST SETUP.....	44
8.4 TEST PROCEDURE.....	44
8.5 TEST RESULTS.....	44
9.Frequency Stability Measurement.....	45
9.1 LIMIT.....	45
9.2 TEST PROCEDURES.....	45
9.3 TEST SETUP LAYOUT.....	45
9.4 EUT OPERATION DURING TEST.....	45
9.5 TEST RESULTS.....	45
10.ANTENNA REQUIREMENT.....	51
11. TEST SETUP PHOTO.....	52
12. EUT CONSTRUCTIONAL DETAILS.....	52



1.SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)	Spurious Radiated Emissions	PASS	
15.207	Conducted Emission	PASS	
15.407 (a)(12) 15.1049	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	6 dB bandwidth	N/A	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
2.1051, 15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
2.1051, 15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	
15.407 (g)	Frequency Stability	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street
Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.:CN0118

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Media Player	
Test Model No.:	ZEN STREAM	
Sample ID:	220310139	
Serial No.:	N/A	
Model Different.:	N/A	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n (20MHz channel bandwidth) ☒ 802.11n (40MHz channel bandwidth) ☒ 802.11ac(80MHz channel bandwidth)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS7; 802.11ac(VHT80):NSS1, MCS0-MCS9
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n(HT20)/ac20; 5190-5230MHz for 802.11n(HT40)/ac40; 5210MHz for 802.11 ac80;
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40 in the 5190-5230 MHz band ; 1 channels for 802.11 ac80 in the 5210MHz band ;
Channel List	Please refer to the Note 2.	
Antenna Type:	Internal Antenna	
Antenna gain:	Ant :3dBi	
Antenna Type:	External Antenna	

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



802.11a/n/ac(20MHz) Frequency Channel							
Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

802.11n(40MHz) Frequency Channel

802.11n /ac(40MHz)Frequency Channel							
Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

802.11ac(80MHz) Frequency Channel	
Channel	Frequency (MHz)
42	5210



2.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Pretest Mode	Description
Mode 1	802.11a / ac 20/n 20 CH36/ CH40/ CH 48
Mode 2	802.11ac / n 40 CH38/ CH 46
Mode 3	802.11 ac80 CH 42


Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.


Test Software	Putty
Power level setup	<10dBm

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Conducted Emission



Radiated Emission



Conducted Spurious





2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Media Player	ifi	ZEN STREAM	N/A	EUT
AE-1	Notebook	lenovo	B40-80	MP07F6JD	AE
AE-2	adapter	ifi	LN-1530	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation & RF Conducted Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 22, 2021	Sep. 21, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 22, 2021	Sep. 21, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Sep. 22, 2021	Sep. 21, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 22, 2021	Sep. 21, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 22, 2021	Sep. 21, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 22, 2021	Sep. 21, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 22, 2021	Sep. 21, 2022
8	Amplifier (1GHz-40GHz)	全聚达	DLE-161	097	Sep. 22, 2021	Sep. 21, 2022
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 22, 2021	Sep. 21, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 22, 2021	Sep. 21, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 22, 2021	Sep. 21, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 22, 2021	Sep. 21, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 22, 2021	Sep. 21, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 22, 2021	Sep. 21, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 22, 2021	Sep. 21, 2022
16	Power Meter	Anritsu	ML2495A	N/A	Sep. 22, 2021	Sep. 21, 2022
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Audix	E3	6.101223a	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 22, 2021	Sep. 21, 2022
2	LISN	CYBERTEK	EM5040A	E185040014g	Sep. 22, 2021	Sep. 21, 2022
3	Test Cable	N/A	C01	N/A	Sep. 22, 2021	Sep. 21, 2022
4	Test Cable	N/A	C02	N/A	Sep. 22, 2021	Sep. 21, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 22, 2021	Sep. 21, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 22, 2021	Sep. 21, 2022
7	Power Meter	Anritsu	ML2495A	N/A	Sep. 22, 2021	Sep. 21, 2022
8	Software	Audix	E3	6.101223a	\	\



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

3.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

3.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation



3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.



3.1.6 TEST RESULTS

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Model:	ZEN STREAM




	Read Freq	LISN Level	Cable Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.15	28.40	9.63	0.05	38.08	55.91	-17.83	Average
2	0.15	41.17	9.63	0.05	50.85	65.91	-15.06	QP
3	0.21	31.81	9.64	0.05	41.50	53.40	-11.90	Average
4	0.21	43.38	9.64	0.05	53.07	63.40	-10.33	QP
5	0.41	23.44	9.67	0.05	33.16	47.68	-14.52	Average
6	0.41	34.21	9.67	0.05	43.93	57.68	-13.75	QP
7	0.46	28.49	9.68	0.05	38.22	46.67	-8.45	Average
8	0.46	31.29	9.68	0.05	41.02	56.67	-15.65	QP
9	0.48	33.39	9.69	0.05	43.13	46.36	-3.23	Average
10	0.48	34.27	9.69	0.05	44.01	56.36	-12.35	QP
11	1.07	19.41	9.61	0.06	29.08	46.00	-16.92	Average
12	1.07	29.63	9.61	0.06	39.30	56.00	-16.70	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Model:	ZEN STREAM



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.15	29.44	9.60	0.05	39.09	55.78	-16.69	Average
2	0.15	42.11	9.60	0.05	51.76	65.78	-14.02	QP
3	0.21	31.39	9.52	0.05	40.96	53.40	-12.44	Average
4	0.21	42.96	9.52	0.05	52.53	63.40	-10.87	QP
5	0.41	25.50	9.62	0.05	35.17	47.64	-12.47	Average
6	0.41	37.27	9.62	0.05	46.94	57.64	-10.70	QP
7	0.46	31.31	9.63	0.05	40.99	46.71	-5.72	Average
8	0.46	33.27	9.63	0.05	42.95	56.71	-13.76	QP
9	0.48	30.18	9.63	0.05	39.86	46.41	-6.55	Average
10	0.48	32.74	9.63	0.05	42.42	56.41	-13.99	QP
11	0.61	23.96	9.63	0.05	33.64	46.00	-12.36	Average
12	0.61	33.96	9.63	0.05	43.64	56.00	-12.36	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(d) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


1. For radiated emissions below 30MHz



2. For radiated emissions from 30MHz to 1000MHz



3. Radiated Emission Test-Up Frequency Above 1GHz





3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1/T

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.


3.2.6 TEST RESULT(Between 9KHz – 30MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.




Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Model:	ZEN STREAM





Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Model:	ZEN STREAM



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case802.11a mode

**Record the worst test data for Antenna B in report.**

Between 1GHz – 40GHz

Temperature :	26℃	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	5.2G TX- 802.11a		

802.11a

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:5180MHz									
V	10360.00	56.35	30.55	5.77	24.66	56.23	68.20	-17.77	PK
V	10360.00	47.21	30.55	5.77	24.66	47.09	54.00	-6.91	AV
V	15540.00	55.26	30.33	6.32	24.55	55.8	68.20	-18.2	PK
V	15540.00	45.69	30.33	6.32	24.55	46.23	54.00	-7.77	AV
V	20720.00	54.13	30.85	7.45	24.69	55.42	68.20	-18.58	PK
V	20720.00	43.16	30.85	7.45	24.69	44.45	54.00	-9.55	AV
V	25900.00	54.21	31.02	8.99	25.57	57.75	68.20	-16.25	PK
V	25900.00	42.56	31.02	8.99	25.57	46.1	54.00	-7.9	AV
H	10360.00	55.84	30.55	5.77	24.66	55.72	68.20	-18.28	PK
H	10360.00	46.32	30.55	5.77	24.66	46.2	54.00	-7.8	AV
H	15540.00	54.27	30.33	6.32	24.55	54.81	68.20	-19.19	PK
H	15540.00	44.12	30.33	6.32	24.55	44.66	54.00	-9.34	AV
H	20720.00	53.16	30.85	7.45	24.69	54.45	68.20	-19.55	PK
H	20720.00	41.25	30.85	7.45	24.69	42.54	54.00	-11.46	AV
H	25900.00	52.61	31.02	8.99	25.57	56.15	68.20	-17.85	PK
H	25900.00	40.36	31.02	8.99	25.57	43.9	54.00	-10.1	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Dete ctor Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:5200MHz									
V	10400.00	55.41	30.55	5.77	24.66	55.29	68.20	-18.71	PK
V	10400.00	46.32	30.55	5.77	24.66	46.2	54.00	-7.8	AV
V	15600.00	53.21	30.33	6.32	24.55	53.75	68.20	-20.25	PK
V	15600.00	42.63	30.33	6.32	24.55	43.17	54.00	-10.83	AV
V	20800.00	51.84	30.85	7.45	24.69	53.13	68.20	-20.87	PK
V	20800.00	41.23	30.85	7.45	24.69	42.52	54.00	-11.48	AV
V	26000.00	50.36	31.02	8.99	25.57	53.9	68.20	-20.1	PK
V	26000.00	39.68	31.02	8.99	25.57	43.22	54.00	-10.78	AV
H	10400.00	55.62	30.55	5.77	24.66	55.5	68.20	-18.5	PK
H	10400.00	47.18	30.55	5.77	24.66	47.06	54.00	-6.94	AV
H	15600.00	53.27	30.33	6.32	24.55	53.81	68.20	-20.19	PK
H	15600.00	43.16	30.33	6.32	24.55	43.7	54.00	-10.3	AV
H	20800.00	52.16	30.85	7.45	24.69	53.45	68.20	-20.55	PK
H	20800.00	42.31	30.85	7.45	24.69	43.6	54.00	-10.4	AV
H	26000.00	51.71	31.02	8.99	25.57	55.25	68.20	-18.75	PK
H	26000.00	36.59	31.02	8.99	25.57	40.13	54.00	-13.87	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:5240MHz									
V	10480.00	55.96	30.55	5.77	24.66	55.84	68.20	-18.16	PK
V	10480.00	45.36	30.55	5.77	24.66	45.24	54.00	-8.76	AV
V	15720.00	52.46	30.33	6.32	24.55	53	68.20	-21	PK
V	15720.00	42.69	30.33	6.32	24.55	43.23	54.00	-10.77	AV
V	20960.00	51.24	30.85	7.45	24.69	52.53	68.20	-21.47	PK
V	20960.00	41.23	30.85	7.45	24.69	42.52	54.00	-11.48	AV
V	26200.00	50.36	31.02	8.99	25.57	53.9	68.20	-20.1	PK
V	26200.00	41.27	31.02	8.99	25.57	44.81	54.00	-9.19	AV
H	10480.00	55.26	30.55	5.77	24.66	55.14	68.20	-18.86	PK
H	10480.00	45.16	30.55	5.77	24.66	45.04	54.00	-8.96	AV
H	15720.00	53.26	30.33	6.32	24.55	53.8	68.20	-20.2	PK
H	15720.00	42.63	30.33	6.32	24.55	43.17	54.00	-10.83	AV
H	20960.00	50.17	30.85	7.45	24.69	51.46	68.20	-22.54	PK
H	20960.00	39.56	30.85	7.45	24.69	40.85	54.00	-13.15	AV
H	26200.00	47.56	31.02	8.99	25.57	51.1	68.20	-22.9	PK
H	26200.00	36.46	31.02	8.99	25.57	40	54.00	-14	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The worst mode is 802.11a, only the worst data is recorded.



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(3)

Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.



4.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or <500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHz is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

Mode	Frequency	POWER SPECTRAL DENSITY TEST	Limit (dBm/MHz)
802.11 a	5180 MHz	0.643	11
	5200 MHz	1.670	11
	5240 MHz	1.338	11
802.11 ac20	5180 MHz	0.522	11
	5200 MHz	0.029	11
	5240 MHz	1.080	11
802.11 ac40	5190 MHz	-3.181	11
	5230 MHz	-2.997	11
802.11 ac80	5210 MHz	-5.489	11
802.11 n40	5190 MHz	-3.352	11
	5230 MHz	-3.242	11
802.11 n20	5180 MHz	0.050	11
	5200 MHz	1.763	11
	5240 MHz	0.094	11

[illegible]

Keysight Spectrum Analyzer - Sweep SA

RF 50 Ω AC

SENSE:INT

Avg Type: RMS
Avg/Hold: >100/100

TRACER 1 2 3 4 5
TYPE M W W W W W W W
DET A N N N N N N

PNO: Fast
IF Gain: Low

Trig: Free Run
Atten: 30 dB

Ref 20.00 dBm

Mkr1 5.203 99 GHz
1.670 dBm

10 dB/div
Log

Center 5.20000 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz²
Sweep 1.000 ms (1001 pts)
Span 30.00 MHz

Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr--CF
Mkr--Ref Lvl
More
1 of 2

Keysight Spectrum Analyzer - Swept SA

RF 50 Ω AC

SENSE:INT

Avg Type: RMS
Avg/Hold: >100/100

TRAC1 1 2 3 4 5
TYPE M W W W W W W W
DET A N N N N N N

PNO: Fast
IF Gain: Low

Trig: Free Run
Atten: 30 dB

10 dB/div
Log

Ref 20.00 dBm

Mkr1 5.236 55 GHz
1.338 dBm


Center 5.24000 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz*

Span 30.00 MHz
Sweep 1.000 ms (1001 pts)


MSO STATUS 1 of 2




(802.11ac20) PSD plot on channel 36




(802.11ac20) PSD plot on channel 40



(802.11ac20) PSD plot on channel 48





Keysight Spectrum Analyzer - Swept SA

RF 50 dB AC SENSE:INT

Avg Type: RMS
Avg/Hold: >100/100

TYPE: M
DET: A

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr1 5.180 GHz
-3.181 dBm

Mkr--CF

Mkr--Ref Lvl

More

1 of 2

Center 5.19000 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz

Span 60.00 MHz
Sweep 1.000 ms (1001 pts)

MSG STATUS

10 dB/div
Log

Ref 20.00 dBm

PNO: Fast
IFGain: Low

Trig: Free Run
Atten: 30 dB

1


The screenshot displays a Keysight Spectrum Analyzer interface. The main plot shows a signal trace with a peak marker labeled '1' at 5.225 GHz. The peak level is -2.997 dBm. The plot has a reference level of 20.00 dBm and a span of 60.00 MHz. The center frequency is 5.23000 GHz. The resolution bandwidth (RBW) is 1.0 MHz, and the video bandwidth (VBW) is 3.0 MHz. The sweep rate is 1.000 ms (1001 pts). The plot is in dBm/div and Log scale. The interface includes various control buttons and a status bar at the bottom.

Parameter	Value
Center Frequency	5.23000 GHz
Span	60.00 MHz
Resolution Bandwidth (RBW)	1.0 MHz
Video Bandwidth (VBW)	3.0 MHz
Sweep	1.000 ms (1001 pts)
Peak Marker 1 Frequency	5.225 GHz
Peak Marker 1 Level	-2.997 dBm
Reference Level	20.00 dBm


The screenshot displays the Keysight Spectrum Analyzer interface. At the top, the title bar reads "Keysight Spectrum Analyzer - Swept SA". The main display area shows a spectrum plot with a yellow trace. A green marker labeled "Mkr1" is positioned at 5.18479 GHz, indicating a level of -3.352 dBm. The plot has a logarithmic scale (Log) on the y-axis, ranging from -70.0 to 10.0 dB/div. The x-axis represents frequency, centered at 5.19000 GHz with a resolution bandwidth (RBW) of 1.0 MHz and a video bandwidth (VBW) of 3.0 MHz. The sweep range is 60.00 MHz, resulting in 1,000 measurement points.




(802.11n40) PSD plot on channel 46



(802.11ac80) PSD plot on channel 42




(802.11n20) PSD plot on channel 36






(802.11n20) PSD plot on channel 40



(802.11n20) PSD plot on channel 48





5. 26DB & 6DB EMISSION BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2 TEST PROCEDURE

- a) Set RBW = 100KHz.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.





5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

Test CH	-26dB Channel Bandwidth (MHz)						Limit (KHz)	Result
	802.11a	802.11ac(20)	802.11ac(40)	802.11ac(80)	802.11n(40)	802.11n(20)		
Lowest	20.29	19.95	39.94	/	38.83	19.46	>500	Pass
Middle	20.13	19.91	/	92.93	/	19.18		
Highest	20.24	19.83	39.83	/	38.76	19.20		



Test plot
(802.11a) Bandwidth plot on channel 36



(802.11a) Bandwidth plot on channel 40




(802.11a) Bandwidth plot on channel 48







(802.11 ac20) Bandwidth plot on channel 36



(802.11 ac20) Bandwidth plot on channel 40




(802.11 ac20) Bandwidth plot on channel 48







(802.11ac40) Bandwidth plot on channel 38



(802.11ac40) Bandwidth plot on channel 46




(802.11n40) Bandwidth plot on channel 38







(802.11n40) Bandwidth plot on channel 46



(802.11ac80) Bandwidth plot on channel 42




(802.11n20) Bandwidth plot on channel 36






(802.11 n20) Bandwidth plot on channel 40



(802.11 n20) Bandwidth plot on channel 48





6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

6.2 TEST PROCEDURE

The EUT was directly connected to the Power meter

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.¹ However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle ≥ 98 percent).
- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each



transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

Type	Frequency (MHz)	Maximum output power(dBm)	FCC Limit (dBm)	Result
802.11a	5180	4.654	24	Pass
	5200	4.688	24	Pass
	5240	5.557	24	Pass
802.11ac (20M)	5180	4.906	24	Pass
	5200	4.638	24	Pass
	5240	5.231	24	Pass
802.11ac (40M)	5190	3.577	24	Pass
	5230	4.025	24	Pass
802.11ac (80M)	5210	3.691	24	Pass
802.11n (40M)	5190	4.285	24	Pass
	5230	4.193	24	Pass
802.11n (20M)	5180	4.041	24	Pass
	5200	4.436	24	Pass
	5240	4.746	24	Pass



7. OUT OF BAND EMISSIONS

7.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

7.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP





7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


7.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz



5.180~5.240 GHz

(802.11a) Band Edge, Left Side




(802.11ac20) Band Edge, Left Side




(802.11a) Band Edge, Right Side




(802.11ac20) Band Edge, Right Side



(802.11n20) Band Edge, Left Side



(802.11n20) Band Edge, Right Side






5.180~5.240 GHz

(802.11ac40) Band Edge, Left Side




(802.11ac80) Band Edge



(802.11ac40) Band Edge, Right Side



(802.11n40) Band Edge, Left Side



(802.11n40) Band Edge, Right Side





8.SPURIOUS RF CONDUCTED EMISSIONS

8.1 CONFORMANCE LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

8.2 MEASURING INSTRUMENTS

The Measuring equipment is listed in the section 6.3 of this test report.

8.3 TEST SETUP



8.4 TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 26.5GHz.

8.5 TEST RESULTS

Remark: The measurement frequency range is from 30MHz to the 5th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Test plot as follows:

Remark: Not Applicable.



9. Frequency Stability Measurement

9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 106$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.

9.3 TEST SETUP LAYOUT



9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

9.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Mode :	TX

Record the worst test data for Antenna B in report.



5.2G

802.11a

Reference Frequency(Middle Channel): 5200 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	63	0.01089
40	15.0	51	0.00882
30	15.0	43	0.00743
20	15.0	32	0.00553
10	15.0	23	0.00398
0	15.0	26	0.00449
-10	15.0	22	0.00380
-20	15.0	36	0.00622
-30	15.0	43	0.00743

802.11ac20

Reference Frequency(Middle Channel): 5200MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	55	0.00951
40	15.0	42	0.00726
30	15.0	32	0.00553
20	15.0	24	0.00415
10	15.0	22	0.00380
0	15.0	12	0.00207
-10	15.0	13	0.00225
-20	15.0	21	0.00363
-30	15.0	32	0.00553



802.11ac40

Reference Frequency(Middle Channel): 5190MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	61	0.01053
40	15.0	54	0.00932
30	15.0	42	0.00725
20	15.0	44	0.00759
10	15.0	34	0.00587
0	15.0	32	0.00552
-10	15.0	34	0.00587
-20	15.0	42	0.00725
-30	15.0	51	0.00880

802.11ac80

Reference Frequency(Middle Channel): 5210MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	63	0.01091
40	15.0	52	0.00900
30	15.0	43	0.00745
20	15.0	41	0.00710
10	15.0	36	0.00623
0	15.0	32	0.00554
-10	15.0	34	0.00589
-20	15.0	43	0.00745
-30	15.0	52	0.00900



802.11n40

Reference Frequency(Middle Channel): 5190MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	60	0.01051
40	15.0	52	0.00900
30	15.0	41	0.00710
20	15.0	43	0.00745
10	15.0	34	0.00587
0	15.0	32	0.00552
-10	15.0	34	0.00587
-20	15.0	42	0.00725
-30	15.0	52	0.00900

802.11n20

Reference Frequency(Middle Channel): 5200MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF	Error (ppm)
50	15.0	54	0.00932
40	15.0	43	0.00745
30	15.0	34	0.00587
20	15.0	23	0.00398
10	15.0	22	0.00380
0	15.0	12	0.00207
-10	15.0	13	0.00225
-20	15.0	36	0.00622
-30	15.0	22	0.00380



So, Frequency Stability Versus Input Voltage is:

802.11a

Reference Frequency(Middle Channel): 5200 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	34	0.00588
	15.0	32	0.00553
	15.0	33	0.00570

802.11ac20

Reference Frequency(Middle Channel): 5200 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	55	0.00951
	15.0	21	0.00363
	15.0	43	0.00743

802.11ac40

Reference Frequency(Middle Channel): 5190 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	42	0.00725
	15.0	44	0.00759
	15.0	42	0.00725

802.11ac80

Reference Frequency(Middle Channel): 5210 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	42	0.00727
	15.0	44	0.00762
	15.0	42	0.00727

802.11n40

Reference Frequency(Middle Channel): 5190 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	43	0.00743
	15.0	44	0.00759
	15.0	42	0.00725



802.11ac20

Reference Frequency(Middle Channel): 5200 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency	Error (ppm)
20	15.0	44	0.00759
	15.0	32	0.00553
	15.0	43	0.00743



10.ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is external Antenna, the best case gain of the antenna is 3dBi, reference to the appendix II for details	



11. TEST SETUP PHOTO

Reference to the appendix I for details.

12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****