

Date : 2017-06-05 Page 1 of 101 No. : DM17050549

Applicant : Lil' Jammerz, LLC

2201 NW 30th Place Suite A, Pompano Beach, FL 33069, United

States

Supplier / Manufacturer: Shenzhen Junengtong Electronics Co., Ltd.

No.85 Rentian Industrial park, Fuyong, Bao'an District, Shenzhen,

Guangdong, China

Description of Sample(s): Submitted sample(s) said to be

Product: Bluetooth Speaker
Brand Name: Lil' Jammerz
Model No.: JNT-10

FCC ID: 2AMAT1022SRB

Date Samples Received: 2017-05-24

Date Tested : 2017-05-24 to 2017-06-01

Investigation Requested : Perform ElectroMagnetic Interference measurement in accordance

with FCC 47CFR [Codes of Federal Regulations] Part 15: 2015 and

ANSI C63.10:2013 for FCC Certification.

Conclusions: The submitted product COMPLIED with the requirements of Federal

Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described

above and on Section 2.2 in this Test Report.

Remarks : Bluetooth FHSS (GFSK/ π /4-DQPSK/8DPSK)



For and on behalf of STC (Dongguan) Company Limited

STC (Dongguan) Company Limited



Date : 2017-06-05 Page 2 of 101 No. : DM17050549

CONTENT:

Photograph(s) of Product

	Cover Content	Page 1 of 101 Page 2 of 101
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 3 of 101
1.2	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 101
1.3	Date of Order	Page 3 of 101
1.4	Submitted Sample(s)	Page 3 of 101
1.5	Test Duration	Page 3 of 101
1.6	Country of Origin	Page 3 of 101
1.7	RF Module Details	Page 4 of 101
1.8	Antenna Details	Page 4 of 101
<u>2.0</u>	Technical Details	
2.1	Investigations Requested	Page 5 of 101
2.2	Test Standards and Results Summary	Page 5 of 101
2.3	Table for Test Modes	Page 6 of 101
<u>3.0</u>	Test Results	
3.1	Emission	Page 7-97 of 101
Append List of	dix A Measurement Equipment	Page 98 of 101
Appen	dix B	D 00 101 - C10

STC (Dongguan) Company Limited

Page 99-101 of 101



Date: 2017-06-05 Page 3 of 101

No. : DM17050549

1.0 General Details

1.1 Test Laboratory

STC (Dongguan) Company Limited

EMC Laboratory

68 Fumin Nan Road, Dalang, Dongguan, Guangdong, China

Telephone: (86 769) 81119888 Fax: (86 769) 81116222

1.2 Equipment Under Test [EUT]

Description of Sample(s)

Product: Bluetooth Speaker

Manufacturer: Shenzhen Junengtong Electronics Co., Ltd.

No.85 Rentian Industrial park, Fuyong, Bao'an District,

Shenzhen, Guangdong, China

Brand Name: Lil' Jammerz Model Number: JNT-10

Rating: 5.0Vd.c. (Powered by USB port) / 3.7Vd.c Li-ion polymer

rechargeable battery

1.2.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Bluetooth Speaker. The transmission signal is digital modulated with channel frequency range 2402-2480MHz. The R.F. signal was modulated by IC; the type of modulation used was frequency hopping spread spectrum Modulation.

1.3 Date of Order

2017-05-24

1.4 Submitted Sample(s):

1 Sample

1.5 Test Duration

2017-05-24 to 2017-06-01

1.6 Country of Origin

China

STC (Dongguan) Company Limited



Date : 2017-06-05 Page 4 of 101

No. : DM17050549

1.7 RF Module Details

Module Model Number: CW668X Module FCC ID: N/A

Module Transmission Type: Bluetooth V4.2

Modulation: FHSS (GFSK / π /4-DQPSK/8DPSK)

Data Rates: 1MBps: GFSK

2 MBps: $\pi/4$ -DQPSK

3 MBps: 8DPSK

Frequency Range: 2400-2483.5MHz Carrier Frequencies: 2402MHz – 2480MHz

Module Specification (specification provided by manufacturer)

1.8 Antenna Details

Antenna Type: PCB antenna Antenna Gain: 1.2dBi



Date : 2017-06-05 Page 5 of 101 No. : DM17050549

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2015 Regulations and ANSI C63.10:2013 for FCC Certification. According FCC KDB 558074 DTS Measurement Guidance, Duty cycle \geq 98%. The device was realized by test software.

2.2 Test Standards and Results Summary Tables

EMISSION						
Results Summary						
Test Condition	Test Requirement	Test Method	Class /	Т	est Result	
			Severity	Pass	Failed	N/A
Maximum Peak Conducted Output Power	FCC 47CFR 15.247(b)(1)	ANSI C63.10: 2013	N/A			
Radiated Spurious Emissions	FCC 47CFR 15.209	ANSI C63.10: 2013	N/A			
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.10: 2013	N/A	\boxtimes		
Number of Hopping Frequency	FCC 47CFR 15.247 (b)(1)	ANSI C63.10: 2013	N/A	\boxtimes		
20dB Bandwidth	FCC 47CFR 15.247(a)(2)	ANSI C63.10: 2013	N/A	\boxtimes		
Hopping Channel Separation	FCC 47CFR 15.247(a)(1)	ANSI C63.10: 2013	N/A	\boxtimes		
Band-edge measurement (Radiated)	FCC 47CFR 15.247(d)	ANSI C63.10: 2013	N/A			
Pseudorandom Hopping Algorithm	FCC 47CFR 15.247(a)(1)	N/A	N/A			
Time of Occupancy (Dwell Time)	FCC 47CFR 15.247(a)(1)(iii)	ANSI C63.10: 2013	N/A			
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	\boxtimes		

Note: N/A - Not Applicable



Date : 2017-06-05 Page 6 of 101 No. : DM17050549

2.3 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item.

Investigation has been done on all the possible configurations for searching the worst cases.

The device was realized by test software.

The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power	GFSK / π/4-DQPSK/ 8DPSK	1MBps / 2MBps/ 3MBps
Hopping Channel Separation	GFSK / π/4-DQPSK/ 8DPSK	1MBps / 2MBps / 3MBps
Number of Hopping Frequency	GFSK / π/4-DQPSK/ 8DPSK	1MBps / 2MBps/ 3MBps
Time of Occupancy(Dwell Time)	8DPSK (DH1 / DH3 / DH5)	3MBps
Radiated Spurious Emissions	GFSK / π/4-DQPSK/ 8DPSK	1MBps / 2MBps /3MBps
Band-edge compliance of Conducted Emission	GFSK / π/4-DQPSK / 8DPSK	1MBps / 2MBps /3MBps



Date : 2017-06-05 Page 7 of 101 No. : DM17050549

3.0 Test Results

3.1 Emission

3.1.1 Maximum Peak Conducted Output Power

Test Requirement: FCC 47CFR 15.247(b) (1)
Test Method: ANSI C63.10: 2013

Test Date: 2017-05-26 Mode of Operation: Tx mode


Test Method:

A temporary antenna connector was soldered to the RF output. The RF output of the EUT was connected to the spectrum analyzer. All the attenuation or cable loss will be added to the measured maximum output power. The results are recorded in Watt.

Spectrum Analyzer Setting:

RBW = 3 MHz, VBW= 3MHz, Sweep = Auto, Span: Approximately five times the 20 dB bandwidth Detector = Peak, Trace = Max. hold

Test Setup:



Note: a temporary antenna connector was soldered to the RF output.



Date : 2017-06-05 Page 8 of 101

No. : DM17050549

Limits for Maximum Peak Conducted Output Power [FCC 47CFR 15.247]:

The maximum peak output power shall not exceeded the following limits: For Digital Transmission systems in 2400-2483.5 MHz Band: 125 Milliwatt Results of Bluetooth Communication mode (GFSK) (Fundamental Power): Pass

Results of Bluetooth Communication mode (GFSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000740

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000689

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000632

The maximum peak output power shall not exceeded the following limits: For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts

Results of Bluetooth Communication mode ($\pi/4$ -DQPSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000951

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000869

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000826

Results of Bluetooth Communication mode (8DPSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.001014

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000973

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000908

Calculated measurement uncertainty : 30MHz to 1GHz 1.7dB 1GHz to 18GHz 1.7dB

Remark:

- 1. All test data for each data rate were verified, but only the worst case was reported.
- 2. The EUT is programmed to transmit signals continuously for all testing.

STC (Dongguan) Company Limited




Date : 2017-06-05 Page 9 of 101

No. : DM17050549

Test plot of Maximum Peak Conducted Output Power:


Bluetooth Communication mode (GFSK, 2402MHz)





Date : 2017-06-05 Page 10 of 101 No. : DM17050549


Bluetooth Communication mode (GFSK, 2441MHz)





Date : 2017-06-05 Page 11 of 101 No. : DM17050549


Bluetooth Communication mode (GFSK, 2480MHz)





Date : 2017-06-05 Page 12 of 101 No. : DM17050549


Bluetooth Communication mode (π/4 DQPSK, 2402MHz)





Date : 2017-06-05 Page 13 of 101 No. : DM17050549


Bluetooth Communication mode (π/4 DQPSK, 2441MHz)





Date : 2017-06-05 Page 14 of 101 No. : DM17050549


Bluetooth Communication mode (π/4 DQPSK, 2480MHz)





Date : 2017-06-05 Page 15 of 101 No. : DM17050549


Bluetooth Communication mode (8DPSK, 2402MHz)





Date : 2017-06-05 Page 16 of 101 No. : DM17050549


Bluetooth Communication mode (8DPSK, 2441MHz)





Date : 2017-06-05 Page 17 of 101 No. : DM17050549

Bluetooth Communication mode (8DPSK, 2480MHz)





Date : 2017-06-05 Page 18 of 101 No. : DM17050549

3.1.2 Radiated Spurious Emissions

Test Requirement: FCC 47CFR 15.209
Test Method: ANSI C63.10:2013

Test Date: 2017-05-26

Mode of Operation: Tx mode / Bluetooth Communication mode (GFSK)

Test Method:

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

* Semi-anechoic chamber located on the STC (Dongguan) Company Ltd. 68 Fumin Nan Road, Dalang, Dongguan, Guangdong, PRC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 629686.



Date : 2017-06-05 Page 19 of 101 : DM17050549

Spectrum Analyzer Setting:

9KHz - 30MHz (Pk & Av) RBW: 10kHz

VBW: 30kHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold

30MHz - 1GHz (QP) RBW: 120kHz

> VBW: 120kHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold

Above 1GHz (Pk) RBW: 1MHz

> VBW: 1MHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold


Above 1GHz (Av) RBW: 1MHz

VBW: 10Hz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold

Test Setup:



Ground Plane

- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
 Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz hom antennas are used, 9kHz to 30MHz loop antennas are used.

STC (Dongguan) Company Limited



Date : 2017-06-05 Page 20 of 101 No. : DM17050549

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Frequency Range	Quasi-Peak Limits
[MHz]	[µV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of Tx mode (2402.0 MHz) (GFSK) (9kHz - 30MHz): Pass

Result of 14 mode (2 102.0 MHz) (G1 SIX) (5 KHz								
Field Strength of Spurious Emissions								
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	MHz dBuV dB/m dBuV/m uV/m uV/m							
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2402.0 MHz) (GFSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	dBμV/m	dBμV/m	$dB\mu V/m$				
4804.0	18.7	41.5	60.2	74.0	13.8	Vertical			
4804.0	16.2	42.4	58.6	74.0	15.4	Horizontal			
7206.0	14.8	45.1	59.9	74.0	14.1	Vertical			
7206.0	15.1	46.2	61.3	74.0	12.7	Horizontal			
9608.0	7.2	48.0	55.2	74.0	18.8	Vertical			
9608.0	6.2	48.8	55.0	74.0	19.0	Horizontal			
12010.0	4.2	51.8	56.0	74.0	18.0	Vertical			
12010.0	3.4	52.4	55.8	74.0	18.2	Horizontal			



Date : 2017-06-05 Page 21 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4804.0	4.0	41.5	45.5	54.0	8.5	Vertical			
4804.0	1.1	42.4	43.5	54.0	10.5	Horizontal			
7206.0	-0.4	45.1	44.7	54.0	9.3	Vertical			
7206.0	0.7	46.2	46.9	54.0	7.1	Horizontal			
9608.0	-7.4	48.0	40.6	54.0	13.4	Vertical			
9608.0	-8.7	48.8	40.1	54.0	13.9	Horizontal			
12010.0	-10.7	51.8	41.1	54.0	12.9	Vertical			
12010.0	-11.7	52.4	40.7	54.0	13.3	Horizontal			

Result of Tx mode (2441.0 MHz) (GFSK) (9kHz - 30MHz): Pass

	Field Strength of Spurious Emissions						
			Peak Value				
Frequency	Measured	Correction	Field	Field	Limit	E-Field	
	Level	Factor	Strength	Strength		Polarity	
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m		
	Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2441.0 MHz) (GFSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
1	Level @3m	Factor	Strength	@3m	C	Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4882.0	16.6	41.6	58.2	74.0	15.8	Vertical			
4882.0	17.0	42.5	59.5	74.0	14.5	Horizontal			
7323.0	4.2	53.2	57.4	74.0	16.6	Vertical			
7323.0	11.7	46.3	58.0	74.0	16.0	Horizontal			
9764.0	7.9	48.1	56.0	74.0	18.0	Vertical			
9764.0	6.2	48.9	55.1	74.0	18.9	Horizontal			
12205.0	3.8	51.6	55.4	74.0	18.6	Vertical			
12205.0	3.8	52.5	56.3	74.0	17.7	Horizontal			



Date : 2017-06-05 Page 22 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m	_	Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4882.0	1.7	41.6	43.3	54.0	10.7	Vertical			
4882.0	1.8	42.5	44.3	54.0	9.7	Horizontal			
7323.0	-3.0	45.2	42.2	54.0	11.8	Vertical			
7323.0	-3.1	46.3	43.2	54.0	10.8	Horizontal			
9764.0	-6.5	48.1	41.6	54.0	12.4	Vertical			
9764.0	-8.7	48.9	40.2	54.0	13.8	Horizontal			
12205.0	-11.2	51.6	40.4	54.0	13.6	Vertical			
12205.0	-11.5	52.5	41.0	54.0	13.0	Horizontal			

Result of Tx mode (2480.0 MHz) (GFSK) (9kHz - 30MHz): Pass

	Field Strength of Spurious Emissions						
			Peak Value				
Frequency	Measured	Correction	Field	Field	Limit	E-Field	
	Level	Factor	Strength	Strength		Polarity	
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m		
	Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2480.0 MHz) (GFSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4960.0	17.3	41.4	58.7	74.0	15.3	Vertical			
4960.0	14.9	42.7	57.6	74.0	16.4	Horizontal			
7440.0	12.5	45.6	58.1	74.0	15.9	Vertical			
7440.0	12.5	46.5	59.0	74.0	15.0	Horizontal			
9920.0	7	48.6	55.6	74.0	18.4	Vertical			
9920.0	5.5	49.7	55.2	74.0	18.8	Horizontal			
12400.0	4.4	51.7	56.1	74.0	17.9	Vertical			
12400.0	3.1	52.7	55.8	74.0	18.2	Horizontal			



Date : 2017-06-05 Page 23 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4960.0	2.1	41.4	43.5	54.0	10.5	Vertical			
4960.0	0.1	42.7	42.8	54.0	11.2	Horizontal			
7440.0	-2.4	45.6	43.2	54.0	10.8	Vertical			
7440.0	-2.2	46.5	44.3	54.0	9.7	Horizontal			
9920.0	-8.0	48.6	40.6	54.0	13.4	Vertical			
9920.0	-9.5	49.7	40.2	54.0	13.8	Horizontal			
12400.0	-10.0	51.7	41.7	54.0	12.3	Vertical			
12400.0	-11.6	52.7	41.1	54.0	12.9	Horizontal			

Result of Tx mode (2402.0 MHz) (π /4-DOPSK) (9kHz – 30MHz): Pass

ICSUIT OF TA IIIC	Acsult of 17 mode (2402.0 MHZ) (764-DQ1 SIX) (7KHZ S0MHZ). 1 ass							
Field Strength of Spurious Emissions								
			Peak Value					
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	MHz dBuV dB/m dBuV/m uV/m uV/m							
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2402.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	$dB\mu V$	dB/m	$dB\mu V/m$	$dB\mu V/m$	dBμV/m				
4804.0	17.7	41.5	59.2	74.0	14.8	Vertical			
4804.0	16.2	42.4	58.6	74.0	15.4	Horizontal			
7206.0	13.8	45.1	58.9	74.0	15.1	Vertical			
7206.0	12.1	46.2	58.3	74.0	15.7	Horizontal			
9608.0	7.6	48.0	55.6	74.0	18.4	Vertical			
9608.0	6.2	48.8	55.0	74.0	19.0	Horizontal			
12010.0	4.3	51.8	56.1	74.0	17.9	Vertical			
12010.0	6.5	52.4	58.9	74.0	15.1	Horizontal			



Date : 2017-06-05 Page 24 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4804.0	2.8	41.5	44.3	54.0	9.7	Vertical			
4804.0	0.9	42.4	43.3	54.0	10.7	Horizontal			
7206.0	-1.5	45.1	43.6	54.0	10.4	Vertical			
7206.0	-2.9	46.2	43.3	54.0	10.7	Horizontal			
9608.0	-7.9	48.0	40.1	54.0	13.9	Vertical			
9608.0	-9.5	48.8	39.3	54.0	14.7	Horizontal			
12010.0	-10.6	51.8	41.2	54.0	12.8	Vertical			
12010.0	-11.6	52.4	40.8	54.0	13.2	Horizontal			

Result of Tx mode (2441.0 MHz) (π /4-DQPSK) (9kHz – 30MHz): Pass

	Field Strength of Spurious Emissions							
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m			
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2441.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions								
	Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4882.0	17.4	41.6	59.0	74.0	15.0	Vertical			
4882.0	15.1	42.5	57.6	74.0	16.4	Horizontal			
7323.0	6.4	53.2	59.6	74.0	14.4	Vertical			
7323.0	11.2	46.3	57.5	74.0	16.5	Horizontal			
9764.0	7.2	48.1	55.3	74.0	18.7	Vertical			
9764.0	6.3	48.9	55.2	74.0	18.8	Horizontal			
12205.0	4.5	51.6	56.1	74.0	17.9	Vertical			
12205.0	3.4	52.5	55.9	74.0	18.1	Horizontal			



Date : 2017-06-05 Page 25 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4882.0	3.7	41.6	45.3	54.0	8.7	Vertical			
4882.0	0.1	42.5	42.6	54.0	11.4	Horizontal			
7323.0	-0.6	45.2	44.6	54.0	9.4	Vertical			
7323.0	-6.0	46.3	40.3	54.0	13.7	Horizontal			
9764.0	-7.4	48.1	40.7	54.0	13.3	Vertical			
9764.0	-8.8	48.9	40.1	54.0	13.9	Horizontal			
12205.0	-10.8	51.6	40.8	54.0	13.2	Vertical			
12205.0	-12.2	52.5	40.3	54.0	13.7	Horizontal			

Result of Tx mode (2480.0 MHz) (π /4-DQPSK) (9kHz – 30MHz): Pass

	Field Strength of Spurious Emissions							
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m			
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2480.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions								
	Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4960.0	16.3	41.4	57.7	74.0	16.3	Vertical			
4960.0	15.5	42.7	58.2	74.0	15.8	Horizontal			
7440.0	12.9	45.6	58.5	74.0	15.5	Vertical			
7440.0	12.3	46.5	58.8	74.0	15.2	Horizontal			
9920.0	7	48.6	55.6	74.0	18.4	Vertical			
9920.0	5.3	49.7	55.0	74.0	19.0	Horizontal			
12400.0	4.3	51.7	56.0	74.0	18.0	Vertical			
12400.0	3.2	52.7	55.9	74.0	18.1	Horizontal			



Date : 2017-06-05 Page 26 of 101 No. : DM17050549

	Field Strength of Spurious Emissions								
		A	verage Valu	e					
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4960.0	1.4	41.4	42.8	54.0	11.2	Vertical			
4960.0	0.6	42.7	43.3	54.0	10.7	Horizontal			
7440.0	-2.5	45.6	43.1	54.0	10.9	Vertical			
7440.0	-3.1	46.5	43.4	54.0	10.6	Horizontal			
9920.0	-8.4	48.6	40.2	54.0	13.8	Vertical			
9920.0	-9.8	49.7	39.9	54.0	14.1	Horizontal			
12400.0	-10.5	51.7	41.2	54.0	12.8	Vertical			
12400.0	-11.9	52.7	40.8	54.0	13.2	Horizontal			

Result of Tx mode (2402.0 MHz) (8DPSK) (9kHz - 30MHz): Pass

Result of 1x mode (2 102.0 MHz) (OD1 SH) (XHZ OMHIZ): 1 ass							
Field Strength of Spurious Emissions							
Peak Value							
Frequency	Measured	Correction	Field	Field	Limit	E-Field	
	Level	Factor	Strength	Strength		Polarity	
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m		
	Emissions	detected are i	nore than 20	dB below the	FCC Limits		

Result of Tx mode (2402.0 MHz) (8DPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	dBμV/m				
4804.0	17.7	41.5	59.2	74.0	14.8	Vertical			
4804.0	17.3	42.4	59.7	74.0	14.3	Horizontal			
7206.0	13.9	45.1	59.0	74.0	15.0	Vertical			
7206.0	12.8	46.2	59.0	74.0	15.0	Horizontal			
9608.0	7.4	48.0	55.4	74.0	18.6	Vertical			
9608.0	6.2	48.8	55.0	74.0	19.0	Horizontal			
12010.0	3.5	51.8	55.3	74.0	18.7	Vertical			
12010.0	3.9	52.4	56.3	74.0	17.7	Horizontal			



Date : 2017-06-05 Page 27 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m				
4804.0	2.7	41.5	44.2	54.0	9.8	Vertical			
4804.0	2.3	42.4	44.7	54.0	9.3	Horizontal			
7206.0	-1.3	45.1	43.8	54.0	10.2	Vertical			
7206.0	-2.2	46.2	44.0	54.0	10.0	Horizontal			
9608.0	-8.0	48.0	40.0	54.0	14.0	Vertical			
9608.0	-9.5	48.8	39.3	54.0	14.7	Horizontal			
12010.0	-12.6	51.8	39.2	54.0	14.8	Vertical			
12010.0	-10.7	52.4	41.7	54.0	12.3	Horizontal			

Result of Tx mode (2441.0 MHz) (8DPSK) (9kHz - 30MHz): Pass

	Field Strength of Spurious Emissions							
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m			
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2441.0 MHz) (8DPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field				
	Level @3m	Factor	Strength	@3m		Polarity				
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m					
4882.0	16.8	41.6	58.4	74.0	15.6	Vertical				
4882.0	16.0	42.5	58.5	74.0	15.5	Horizontal				
7323.0	4.4	53.2	57.6	74.0	16.4	Vertical				
7323.0	11.9	46.3	58.2	74.0	15.8	Horizontal				
9764.0	7.5	48.1	55.6	74.0	18.4	Vertical				
9764.0	6.6	48.9	55.5	74.0	18.5	Horizontal				
12205.0	3.7	51.6	55.3	74.0	18.7	Vertical				
12205.0	3.6	52.5	56.1	74.0	17.9	Horizontal				



Date : 2017-06-05 Page 28 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field				
	Level @3m	Factor	Strength	@3m	_	Polarity				
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m					
4882.0	1.8	41.6	43.4	54.0	10.6	Vertical				
4882.0	1.2	42.5	43.7	54.0	10.3	Horizontal				
7323.0	-2.3	45.2	42.9	54.0	11.1	Vertical				
7323.0	-4.0	46.3	42.3	54.0	11.7	Horizontal				
9764.0	-7.3	48.1	40.8	54.0	13.2	Vertical				
9764.0	-8.7	48.9	40.2	54.0	13.8	Horizontal				
12205.0	-11.4	51.6	40.2	54.0	13.8	Vertical				
12205.0	-10.8	52.5	41.7	54.0	12.3	Horizontal				

Result of Tx mode (2480.0 MHz) (8DPSK) (9kHz - 30MHz): Pass

	Field Strength of Spurious Emissions							
Peak Value								
Frequency	Measured	Correction	Field	Field	Limit	E-Field		
	Level	Factor	Strength	Strength		Polarity		
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m			
	Emissions detected are more than 20 dB below the FCC Limits							

Result of Tx mode (2480.0 MHz) (8DPSK) (Above 1GHz): Pass

	Field Strength of Spurious Emissions Peak Value										
Frequency	Measured	Correction	Field	Limit	Margin	E-Field					
	Level @3m	Factor	Strength	@3m		Polarity					
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m						
4960.0	16.6	41.4	58.0	74.0	16.0	Vertical					
4960.0	14.6	42.7	57.3	74.0	16.7	Horizontal					
7440.0	12.9	45.6	58.5	74.0	15.5	Vertical					
7440.0	11.8	46.5	58.3	74.0	15.7	Horizontal					
9920.0	6.6	48.6	55.2	74.0	18.8	Vertical					
9920.0	5.3	49.7	55.0	74.0	19.0	Horizontal					
12400.0	4.4	51.7	56.1	74.0	17.9	Vertical					
12400.0	3.1	52.7	55.8	74.0	18.2	Horizontal					



Date : 2017-06-05 Page 29 of 101 No. : DM17050549

	Field Strength of Spurious Emissions Average Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field				
	Level @3m	Factor	Strength	@3m		Polarity				
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m					
4960.0	1.3	41.4	42.7	54.0	11.3	Vertical				
4960.0	0.2	42.7	42.9	54.0	11.1	Horizontal				
7440.0	-2.3	45.6	43.3	54.0	10.7	Vertical				
7440.0	-3.3	46.5	43.2	54.0	10.8	Horizontal				
9920.0	-8.1	48.6	40.5	54.0	13.5	Vertical				
9920.0	-9.4	49.7	40.3	54.0	13.7	Horizontal				
12400.0	-10.6	51.7	41.1	54.0	12.9	Vertical				
12400.0	-11.8	52.7	40.9	54.0	13.1	Horizontal				

Note: Above 13GHz Emissions detected are more than 20 dB below the FCC Limits.

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz

* Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 9kHz-30MHz 3.3dB

30MHz -1GHz 4.6dB 1GHz -26GHz 4.4dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.



Date : 2017-06-05 Page 30 of 101 No. : DM17050549

Radiated Emissions Measurement:

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

Result: RF Radiated Emissions (Lowest)-GFSK

	Field Strength of Band-edge Compliance								
Peak Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$				
2390.0	18.5	36.8	55.3	74.0	18.7	Vertical			

	Field Strength of Band-edge Compliance								
Average Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$				
2390.0	5.2	36.8	42.0	54.0	12.0	Vertical			

Result: RF Radiated Emissions (Highest) -GFSK

resuit. Iti iti	tesure. It ituative Emissions (ingliest) of Six								
Field Strength of Band-edge Compliance									
Peak Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$				
2483.5	20.1	36.8	56.9	74.0	17.1	Vertical			

Field Strength of Band-edge Compliance								
Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field		
	Level @3m	Factor	Strength	@3m		Polarity		
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	dBμV/m			
2483.5	5.8	36.8	42.6	54.0	11.4	Vertical		



Date : 2017-06-05 Page 31 of 101

No. : DM17050549

Radiated Emissions Measurement:

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

Result: RF Radiated Emissions (Lowest) - $\pi/4$ -DOPSK

Field Strength of Band-edge Compliance								
Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field		
	Level @3m	Factor	Strength	@3m		Polarity		
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	dBμV/m			
2390.0	19.6	36.8	56.4	74.0	17.6	Vertical		

	Field Strength of Band-edge Compliance Average Value									
		<i>P</i>	verage valu	e						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field				
	Level @3m	Factor	Strength	@3m		Polarity				
MHz	dΒμV	dB/m	dBμV/m	$dB\mu V/m$	$dB\mu V/m$					
2390.0	6.0	36.8	42.8	54.0	11.2	Vertical				

Result: RF Radiated Emissions (Highest) -π/4-DOPSK

icouit. Iti iti	Active M. Manufer Emissions (Highest) W. D. D. S. K.								
	Field Strength of Band-edge Compliance								
Peak Value									
Frequency	Measured	Correction	Field	Limit	Margin	E-Field			
	Level @3m	Factor	Strength	@3m		Polarity			
MHz	dΒμV	dB/m	dBμV/m	$dB\mu V/m$	$dB\mu V/m$				
2483.5	19.1	36.8	55.9	74.0	18.1	Vertical			

Field Strength of Band-edge Compliance								
Average Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field		
	Level @3m	Factor	Strength	@3m		Polarity		
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$			
2483.5	5.5	36.8	42.3	54.0	11.7	Vertical		



Date : 2017-06-05 Page 32 of 101 No. : DM17050549

Radiated Emissions Measurement:

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

Result: RF Radiated Emissions (Lowest) - 8DPSK

	result. It ituation Emissions (Edwest) Ob 1511								
	Field Strength of Band-edge Compliance Peak Value								
l									
ĺ	Frequency	Measured	Correction	Field	Limit	Margin	E-Field		
		Level @3m	Factor	Strength	@3m		Polarity		
	MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$			
	2390.0	19.1	36.8	55.9	74.0	18.1	Vertical		

Field Strength of Band-edge Compliance							
Average Value							
Frequency	Measured	Correction	Field	Limit	Margin	E-Field	
	Level @3m	Factor	Strength	@3m		Polarity	
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	dBμV/m		
2390.0	5.1	36.8	41.9	54.0	12.1	Vertical	

Result: RF Radiated Emissions (Highest) -8DPSK


Tesut: Iti Itatatea Emissions (Highest) obi sit								
Field Strength of Band-edge Compliance								
Peak Value								
Frequency	Measured	Correction	Field	Limit	Margin	E-Field		
	Level @3m	Factor	Strength	@3m		Polarity		
MHz	dΒμV	dB/m	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$			
2483.5	18.9	36.8	55.7	74.0	18.3	Vertical		

Field Strength of Band-edge Compliance							
Average Value							
Frequency	Measured	Correction	Field	Limit	Margin	E-Field	
	Level @3m	Factor	Strength	@3m		Polarity	
MHz	dΒμV	dB/m	dBμV/m	$dB\mu V/m$	$dB\mu V/m$		
2483.5	6.1	36.8	42.9	54.0	11.1	Vertical	



Date : 2017-06-05 Page 33 of 101 No. : DM17050549


RF Radiated Emissions (Lowest)-GFSK





Date : 2017-06-05 Page 34 of 101 No. : DM17050549


RF Radiated Emissions (Highest)-GFSK





Date : 2017-06-05 Page 35 of 101 No. : DM17050549


RF Radiated Emissions (Lowest)- π/4-DQPSK





Date : 2017-06-05 Page 36 of 101 No. : DM17050549


RF Radiated Emissions (Highest)- π/4-DQPSK





Date : 2017-06-05 Page 37 of 101 No. : DM17050549


RF Radiated Emissions (Lowest)-8DPSK





Date : 2017-06-05 Page 38 of 101 No. : DM17050549

RF Radiated Emissions (Highest)-8DPSK





Date : 2017-06-05 Page 39 of 101 No. : DM17050549

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Frequency Range	Quasi-Peak Limits
[MHz]	[µV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results of Bluetooth Communication mode (GFSK 2402.0 MHz) (30MHz - 1GHz): Pass

Please refer to the following table for result details(The data is the worst cases)

Horizontal dBµV/m Limit 80 70 60 50 40 30 20 10 0 30.0 100.0 1000.0 MHz



Date : 2017-06-05 Page 40 of 101 No. : DM17050549

Result of Bluetooth Communication mode (GFSK 2402.0 MHz) (30MHz - 1GHz): Pass

Radiated Emissions					
		Quasi	-Peak		
Emission	E-Field	Level	Limit	Level	Limit
Frequency	Polarity	@3m	@3m	@3m	@3m
MHz		dBμV/m	dBμV/m	μV/m	μV/m
99.6	Horizontal	31.6	43.5	38.0	150
108.6	Horizontal	31.1	43.5	35.9	150
299.8	Horizontal	38.9	46.0	88.1	200



Date : 2017-06-05 Page 41 of 101 No. : DM17050549

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Frequency Range	Quasi-Peak Limits
[MHz]	$[\mu V/m]$
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results of Bluetooth Communication mode (GFSK 2402.0 MHz) (30MHz - 1GHz): Pass

Please refer to the following table for result details(The data is the worst cases)



Date : 2017-06-05 Page 42 of 101 No. : DM17050549

Result of Bluetooth Communication mode (GFSK 2402.0 MHz) (30MHz - 1GHz): Pass

Radiated Emissions					
	Quasi-Peak				
Emission	E-Field	Level	Limit	Level	Limit
Frequency	Polarity	@3m	@3m	@3m	@3m
MHz		dBμV/m	dBμV/m	μV/m	μV/m
99.9	Vertical	31.2	43.5	36.3	150
106.8	Vertical	28.7	43.5	27.2	150
299.8	Vertical	33.9	46.0	49.5	200

Remarks:

Calculated measurement uncertainty (30MHz - 1GHz): 4.6dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.



Date : 2017-06-05 Page 43 of 101

No. : DM17050549

3.1.3 AC Mains Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.207
Test Method: ANSI C63.10:2013

Test Date: 2017-05-10

Mode of Operation: Bluetooth Communication mode

Test Voltage: 120Va.c. 60Hz


Test Method:

The test was performed in accordance with ANSI ANSI C63.10:2013, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Receiver Setting:

Bandw. = 9 kHz, Meas. Time= 10.0 ms, Step Width = 5.0kHz Detector = MaxPeak and CISPR AV

Test Setup:





Date : 2017-06-05 Page 44 of 101 No. : DM17050549

Limits for Conducted Emissions (FCC 47 CFR 15.207):


Frequency Range	Quasi-Peak Limits	Average
[MHz]	[dBµV]	[dBµV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

^{*} Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of Bluetooth Communication mode (L): PASS

Please refer to the following diagram for individual results.



		Quasi-peak		Ave	rage
Conductor	Frequency	Level	Limit	Level	Limit
Live or Neutral	MHz	dΒμV	dΒμV	dΒμV	dΒμV
Live	0.180	37.7	65.0	_*_	_*_
Live	0.900	30.2	56.0	_*_	_*_
Live	25.060	31.8	60.0	_*_	_*_
Live	0.900	_*_	_*_	29.3	46.0
Live	1.640	_*_	_*_	27.3	46.0
Live	2.005	_*_	_*_	27.5	46.0



Date : 2017-06-05 Page 45 of 101 No. : DM17050549


Frequency Range	Quasi-Peak Limits	Average
[MHz]	[dBµV]	[dBµV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

^{*} Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of Bluetooth Communication mode (N): PASS

Please refer to the following diagram for individual results.



		Quasi-peak		Ave	rage
Conductor	Frequency	Level	Limit	Level	Limit
Live or Neutral	MHz	dΒμV	dΒμV	dΒμV	dΒμV
Neutral	0.180	36.4	65.0	_*_	_*_
Neutral	0.900	29.8	56.0	_*_	_*_
Neutral	25.060	32.2	60.0	_*_	_*_
Neutral	0.900	_*_	_*_	28.9	46.0
Neutral	2.640	_*_	_*_	24.4	46.0
Neutral	25.060	_*_	_*_	31.2	50.0

Remarks:

Calculated measurement uncertainty (0.15MHz - 30MHz): 3.2dB

^{-*-} Emission(s) that is far below the corresponding limit line.



Date : 2017-06-05 Page 46 of 101 No. : DM17050549

3.1.4 Number of Hopping Frequency

Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

Test Method:

The RF output of the EUT was connected to the spectrum analyzer by a low loss cable.

Spectrum Analyzer Setting:


RBW = 300kHz, VBW \geq RBW, Sweep = Auto, Span = the frequency band of operation Detector = Peak, Trace = Max. hold

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Measurement Data:

GFSK: 79 of 79 Channel






Date : 2017-06-05 Page 47 of 101

No. : DM17050549


π/4-DQPSK: 79 of 79 Channel





Date : 2017-06-05 Page 48 of 101 No. : DM17050549

8DPSK: 79 of 79 Channel





Date : 2017-06-05 Page 49 of 101

No. : DM17050549

3.1.5 20dB Bandwidth

Test Requirement: FCC 47CFR 15.247(a)(1)
Test Method: ANSI C63.10:2013

Test Date: 2017-05-27 Mode of Operation: Tx mode

Remark

The result has been done on all the possible configurations for searching the worst cases.

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Spectrum Analyzer Setting:

RBW = 30kHz, VBW \geq RBW, Sweep = Auto, Span = two times and five times the OBW Detector = Peak, Trace = Max. hold

Test Setup:


As Test Setup of clause 3.1.1 in this test report.



Date : 2017-06-05 Page 50 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2402	1.02	Within 2400-2483.5








Date : 2017-06-05 Page 51 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2441	1.015	Within 2400-2483.5

(Middle Operating Frequency) - (GFSK)






Date : 2017-06-05 Page 52 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2480	1.025	Within 2400-2483.5

(Highest Operating Frequency) - (GFSK)






Date : 2017-06-05 Page 53 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2402	1.08	Within 2400-2483.5

(Lowest Operating Frequency) - $(\pi/4 \text{ DQPSK})$






Date : 2017-06-05 Page 54 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2441	1.08	Within 2400-2483.5

(Middle Operating Frequency) - $(\pi/4 \text{ DQPSK})$






Date : 2017-06-05 Page 55 of 101 No. : DM17050549

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.08	Within 2400-2483.5

(Highest Operating Frequency) - $(\pi/4 \text{ DQPSK})$






Date : 2017-06-05 Page 56 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2402	1.15	Within 2400-2483.5

(Lowest Operating Frequency) - (8DPSK)






Date : 2017-06-05 Page 57 of 101 No. : DM17050549

Fundamental Frequency	20dB Bandwidth	FCC Limits
[MHz]	[MHz]	[MHz]
2441	1.15	Within 2400-2483.5

(Middle Operating Frequency) - (8DPSK)






Date : 2017-06-05 Page 58 of 101 No. : DM17050549

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.155	Within 2400-2483.5

(Highest Operating Frequency) - (8DPSK)





Date : 2017-06-05 Page 59 of 101 No. : DM17050549

3.1.6 Hopping Channel Separation

Requirements:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Analyzer Setting:

RBW = 300kHz, VBW ≥ RBW, Sweep = Auto, Span = Wide enough to captur the peaks of two adjacent channels Detector = Peak, Trace = Max. hold

Limit:


The measured maximum bandwidth* 2/3 = 1.025MHz* 2/3 = 683kHz (GFSK)

The measured maximum bandwidth * 2/3 = 1.155MHz * 2/3 = 770kHz ($\pi/4$ DQPSK, 8DPSK)



Date : 2017-06-05 Page 60 of 101 No. : DM17050549


Channel separation = 1MHz (>683kHz) (Lowest) (GFSK)





Date : 2017-06-05 Page 61 of 101 No. : DM17050549


Channel separation = 1MHz (>683kHz) (Mid) (GFSK)





Date : 2017-06-05 Page 62 of 101 No. : DM17050549


Channel separation = 1MHz (>683kHz) (Highest) (GFSK)





Date : 2017-06-05 Page 63 of 101 No. : DM17050549


Channel separation = 1MHz (>770kHz) (Lowest) $(\pi/4 \text{ DQPSK})$





Date : 2017-06-05 Page 64 of 101 No. : DM17050549


Channel separation = 1MHz (>770kHz) (Mid) ($\pi/4$ DQPSK)





Date : 2017-06-05 Page 65 of 101 No. : DM17050549


Channel separation = 1MHz (>770kHz) (Highest) ($\pi/4$ DQPSK)





Date : 2017-06-05 Page 66 of 101 No. : DM17050549


Channel separation = 1MHz (>770kHz) (Lowest) (8DPSK)





Date : 2017-06-05 Page 67 of 101 No. : DM17050549


Channel separation = 1MHz (>770kHz) (Mid) (8DPSK)





Date : 2017-06-05 Page 68 of 101 No. : DM17050549

Channel separation = 1MHz (>770kHz) (Highest) (8DPSK)





Date : 2017-06-05 Page 69 of 101 No. : DM17050549

3.1.7 Band-edge Compliance of RF Conducted Emissions Measurement:

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

According to the test method DA 00-705.

Spectrum Analyzer Setting:

RBW = 100kHz, VBW= 300kHz, Sweep = Coupled,

Span = Wide enough to captur the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Detector = Peak, Trace = Max. hold

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report




Date : 2017-06-05 Page 70 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
2400 – Lowest Fundamental (2402)	36.67

Band-edge Compliance of RF Emissions – Lowest (GFSK) (Hopping on)






Date : 2017-06-05 Page 71 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
2400 – Lowest Fundamental (2402)	36.16

Band-edge Compliance of RF Emissions – Lowest (GFSK) (Hopping off)






Date : 2017-06-05 Page 72 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
2483.5 - Highest Fundamental (2480)	42.01

Band-edge Compliance of RF Emissions - Highest (GFSK) (Hopping on)






Date : 2017-06-05 Page 73 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2483.5 - Highest Fundamental (2480)	41.75		

Band-edge Compliance of RF Emissions - Highest (GFSK) (Hopping off)






Date : 2017-06-05 Page 74 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental		
[MHz]	[dB]		
2400 – Lowest Fundamental (2402)	27.09		

Band-edge Compliance of RF Emissions – Lowest (π/4 DQPSK) (Hopping on)






Date : 2017-06-05 Page 75 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2400 – Lowest Fundamental (2402)	27.09		

Band-edge Compliance of RF Emissions – Lowest (π/4 DQPSK) (Hopping off)






Date : 2017-06-05 Page 76 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2483.5 - Highest Fundamental (2480)	32.32		

Band-edge Compliance of RF Emissions – Highest (π/4 DQPSK) (Hopping on)






Date : 2017-06-05 Page 77 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2483.5 - Highest Fundamental (2480)	32.36		

Band-edge Compliance of RF Emissions – Highest (π/4 DQPSK) (Hopping off)






Date : 2017-06-05 Page 78 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental		
[MHz]	[dB]		
2400 – Lowest Fundamental (2402)	27.57		

Band-edge Compliance of RF Emissions - Lowest (8DPSK) (Hopping on)






Date : 2017-06-05 Page 79 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental			
[MHz]	[dB]			
2400 – Lowest Fundamental (2402)	25.28			

Band-edge Compliance of RF Emissions - Lowest (8DPSK) (Hopping off)






Date : 2017-06-05 Page 80 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2483.5 - Highest Fundamental (2480)	32.35		

Band-edge Compliance of RF Emissions - Highest (8DPSK) (Hopping on)






Date : 2017-06-05 Page 81 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range	Radiated Emission Attenuated below the Fundamental [dB]		
[MHz]			
2483.5 - Highest Fundamental (2480)	32.46		

Band-edge Compliance of RF Emissions - Highest (8DPSK) (Hopping off)






Date : 2017-06-05 Page 82 of 101 No. : DM17050549

Band-edge Compliance of RF Conducted Emissions Measurement:

Limit :

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report





Date : 2017-06-05 Page 83 of 101 No. : DM17050549

Band-edge Compliance of RF Emissions – (π/4-DQPSK 2402MHz) RBW 100 kHz RF Att 30 dB Ref Lvl VBW 300 kHz 9 dBm SWT 6.6 s Unit dBm ▼1 [T1] -3.32 dBm 2.40298397 GHz ∇₂ [T1] -36.26 dBm 4.76601202 GHz -10 -20 IN1 1MAX 1165 -40-80

2.597 GHz/

Stop 26 GHz

Start 30 MHz



Date : 2017-06-05 Page 84 of 101 No. : DM17050549

Band-edge Compliance of RF Emissions – (8DPSK 2402MHz) RBW 100 kHz RF Att 30 dB Ref Lvl VBW 300 kHz 6.6 s 9 dBm dBm SWT Unit **▼**1 [T1] -2.02 dBm 2.40248397 GHz ∇₂ [T1] -38.91 dBr 4.76601202 GHz -10-20 1371 11474 1MAX -30 -40-50 -70-80 Start 30 MHz 2.597 GHz/ Stop 26 GHz



Date : 2017-06-05 Page 85 of 101 No. : DM17050549

3.1.8 Time of Occupancy (Dwell Time)

Requirements:

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channel employed.

No requirements for Digital Transmission System.

Spectrum Analyzer Setting:

 $RBW = 300kHz, VBW \ge RBW,$

Sweep = A longer sweep time to show two successive hops on a channel,


Span = Zero, Detector = Peak, Trace = Max. hold

Dwell Time = Pulse Duration * hop rate / number of channel * observation duration

Observed duration: $0.4s \times 79 = 31.6s$

Measurement Data:

Channel Occupied in 8DPSK: 79 of 79 Channel






Date : 2017-06-05 Page 86 of 101 No. : DM17050549

DH5 Packet:

DH5 Packet permit maximum 1600/79/6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds


Fig. A [Pulse duration of Lowest Channel]





Date : 2017-06-05 Page 87 of 101 No. : DM17050549


Fig. B [Pulse duration of Middle Channel]





Date : 2017-06-05 Page 88 of 101 No. : DM17050549

Fig. C
[Pulse duration of Highest Channel]






Date : 2017-06-05 Page 89 of 101 No. : DM17050549

DH3 Packet:

DH3 Packet permit maximum 1600/79/4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds


Fig. D
[Pulse duration of Lowest Channel]





Date : 2017-06-05 Page 90 of 101 No. : DM17050549


Fig. E [Pulse duration of Middle Channel]





Date : 2017-06-05 Page 91 of 101 No. : DM17050549

Fig. F
[Pulse duration of Highest Channel]






Date : 2017-06-05 Page 92 of 101 No. : DM17050549

DH1 Packet:

DH1 Packet permit maximum 1600/79/2 = 10.12 hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds


Fig. G
[Pulse duration of Lowest Channel]





Date : 2017-06-05 Page 93 of 101 No. : DM17050549


Fig. H
[Pulse duration of Middle Channel]





Date : 2017-06-05 Page 94 of 101 No. : DM17050549

Fig. I [Pulse duration of Highest Channel]



Time of occupancy (Dwell Time).

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Results
DH5	2402	3.02	0.322	0.400	Complies
DH5	2441	3.02	0.322	0.400	Complies
DH5	2480	3.02	0.322	0.400	Complies
DH3	2402	1.76	0.281	0.400	Complies
DH3	2441	1.76	0.281	0.400	Complies
DH3	2480	1.650	0.281	0.400	Complies
DH1	2402	0.50	0.160	0.400	Complies
DH1	2441	0.50	0.160	0.400	Complies
DH1	2480	0.50	0.160	0.400	Complies



Date : 2017-06-05 Page 95 of 101

No. : DM17050549

3.1.9 Channel Centre Frequency

Requirements:

Frequency hopping system in the 2400-2483.5MHz band shall use at least 79 (Channel 1 to 79) non-overlapping channels.

The EUT operates in according with the Bluetooth system specification within the 2400 - 2483.5 MHz frequency band.

RF channels for Bluetooth systems are spaced 1 MHz and are ordered in channel number k. In order to comply with out-of-band regulations, a lower frequency guard band of 2.0 MHz and a higher frequency guard band of 3.5MHz is used.

The operating frequencies of each channel are as follows:

First RF channel start from 2400MHz + 2MHz guard band = 2402MHz Frequency of RF Channel = 2402+k MHz, k = 1,...,79 (Channel separation = 1MHz)



Date : 2017-06-05 Page 96 of 101 No. : DM17050549

3.1.10 Pseudorandom Hopping Algorithm

Requirements:

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally by the transmitter.

EUT Pseudorandom Hopping Algorithm

The EUT is a Bluetooth device, the Pseudo-random hopping pattern; hopping characteristics and algorithm are based on the Bluetooth specification.



Date : 2017-06-05 Page 97 of 101 No. : DM17050549

3.1.11 Antenna Requirement

Test Requirements: § 15.203

Test Specification:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Results:

This is PCB antenna. There is no external antenna, the antenna gain = 1.2dBi. User is unable to remove or changed the Antenna.



Date : 2017-06-05 Page 98 of 101 No. : DM17050549

Appendix A

List of Measurement Equipment

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EMD004	LISN	ROHDE & SCHWARZ	ESH3-Z5	100102	2016.3.29	2018.3.29
EMD022	EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	100314	2016.3.29	2018.3.29
EMD035	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100441	2016.3.29	2018.3.29
EMD036	EMI Test Receiver	ROHDE & SCHWARZ	ESIB 26	100388	2016.3.29	2018.3.29
EMD041	TWO-LINE V- NETWORK	ROHDE & SCHWARZ	ENV216	100261	2016.3.29	2018.3.29
EMD061	Biconilog Antenna	ETS.LINDGREN	3142C	00060439	2016.12.30	2018.12.30
EMD062	Double-Ridged Waveguide (1GHz – 18GHz)	ETS.LINDGREN	3117	00075933	2014.11.15	2017.11.15
EMD084	MULTI-DVICE CONTROLLER	ETS.LINDGREN	2090	00060107	N/A	N/A
EMD088	Video Contol Unit	ETS.LINDGREN	Y21953A	2601073	N/A	N/A
EMD093	Monitor	ViewSonic	VA9036	Q8X064201876	N/A	N/A
EMD102	Intelligent Frequency	Ainuo Instrument Co., Ltd	AN97005SS	79707454	N/A	N/A
EMD103	Intelligent Frequency	Ainuo Instrument Co., Ltd	AN97005SS	79707455	N/A	N/A
EMD105	FACT-3 EMC Chamber	ETS.LINDGREN	FACT-3	3803	N/A	N/A
EMD106	Shielding Room #1	ETS.LINDGREN	RFD-100	3802	N/A	N/A
EMD111	Power meter	ROHDE & SCHWARZ	NRVD	102051	2016.3.29	2018.3.29
	100V Insertion Unit	ROHDE & SCHWARZ	URV5-Z4	100464	2016.3.29	2018.3.29
EMD113	Pre-Amplifier	ROHDE & SCHWARZ	N/A	1129588	2016.3.29	2018.3.29
EMD124	Loop Antenna	ETS-Lindgren	6502	00104905	2016.05.23	2018.05.23
EMD131	Standard Gain Horn Antenna (18GHz – 26.5GHz)	Chengdu AINFO lnc.	JXTXLB-42- 15-C-KF	J2021100721001	2015.06.27	2017.06.27
RE01	RF cable	N/A	N/A	N/A	2016-9-28	2018-9-27
RE02	RF cable	N/A	N/A	N/A	2016-9-28	2018-9-27

Remarks:-

N/A Not Applicable or Not Available



Date : 2017-06-05 Page 99 of 101 No. : DM17050549

Appendix B

Photographs of EUT

Front View of the product



Inside View of the product




Inner Circuit Bottom View








Inner Circuit Top View






Date : 2017-06-05 Page 100 of 101 No. : DM17050549

Photographs of EUT







Date : 2017-06-05 Page 101 of 101 No. : DM17050549

Photographs of EUT

Measurement of Radiated Emission Test Set Up



***** End of Test Report *****

Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by The STC (Dongguan) Company Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders
- 4. The Report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
- 5. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 6. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 7. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
- 10. Issuance records of the Report are available on the internet at dgstc@dgstc.org. Further enquiry of validity or verification of the Reports should be addressed to the Company.