

Toshiba Corporation
FCC ID: CJ6UPA3362WL
Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with Metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided),	The modular transmitter has buffered modulation/data inputs. All inputs to the modules are buffered through the radio circuitry.
3	Have it own power supply regulation	The modular transmitter has its own power supply regulator. Refer to Block diagram
4	Meet the antenna requirements of Section 15.203	The modular transmitter has an antenna that complies with section 15.203 and 15.204(c) of the FCC rules. It has a UFL type of connector at the transmitter end and is soldered to the antenna (depending on OEM configuration). Also the antenna will be internal in the OEM host equipment and inaccessible to the user. Refer to external photos
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested inside the laptop for limited modular approval. Refer to setup photos.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the	Two proposed FCC ID label format are included in the filing. One of label is to be placed on the module and the other

	enclosed module.	label is to be placed on the outside of system. Refer to FCC ID label format and location file.
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	Refer to “User’s Manual” Exhibit
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	SAR test was performed on the portable laptop, Portege M200