Test Report# TR_17875-24_FCC 15.247 DTS_ Revision: 2





Test Report - FCC Part 15.247/ DTS Applicant: ICOM Inc

ATIE.

Signature:	Into D. Pege	Sr. EMC Engineer
Name & Title:	Tim Royer, Lab Manager	
Date of Signature	01/31/2025	-
Signature:	Faunic Sund	
Signatare.	<u> </u>	
Name & Title:	Fouzia Syed, Senior Test enginee	r.

Date of Signature 01/31/2025

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615 (352) 472-5500 / testing@industrial-ia.com

Table of Contents

1.		APPLICANT INFORMATION	4
	1.1	Test Result Summary	4
2.		LOCATION OF TESTING	6
	2.1	1 Test Laboratory	
3.		TEST SAMPLE(S) (EUT/DUT)	6
	२ 1		7
	3.2	2 Configuration of EUT	
	3.3	3 Test Setup of EUT	8
4.		TEST METHODS & APPLICABLE REGULATORY LIMITS	9
	4.1	1 Test methods/Standards/Guidance:	
	4.2	2 Applied Limits and Regulatory Limits:	9
5.		MEASUREMENT UNCERTAINTY	9
6.		ENVIRONMENTAL CONDITIONS	9
	61		Q
-	0.1		
1.		LIST OF TEST EQUIPMENT AND TEST FACILITY	10
	7.1	I LIST OF TEST EQUIPMENT	10
8.		TEST RESULTS	11
	8.1	1 DTS conducted output power	12
		8.1.1 Conducted Output Power, 2402 MHz	13
		8.1.2 Conducted Output Power, 2442 MHz	
		8.1.3 Conducted Output Power, 2480 MHz	
	8.2	2 Occupied Bandwidth	
		8.2.1 99% Bandwidth Plot, 2402 MHz	
		8.2.2 99% Bandwidth Plot, 2442 MHz	
	0.2	8.2.3 99% Bandwlath Plot, 2480 MHz	
	8.3	3 6DB BANDWIDTH (DTS BW)	20 21
		0.5.1 OUD BUHUWIUITI (DTS DW), 2402 MHZ	۱∠۲ دد
		8.3.2 OUB DUHUWUUH (DTS BW), 2442 MHZ. 8.3.3 6dB Randwidth (DTS RW). 2480 MHZ	ےے۔ 22
	87	0.3.5 ОНВ ВИЛИЧИИЛ (ВТЗ ВУУ), 2400 ГЛП 2	25 21
	0	8 4 1 Power Spectral Density (PSD) 2402 MHz	
		8.4.2 Power Spectral Density (PSD), 2442 MHz	26
		8 4 3 Power Spectral Density (PSD), 2480 MHz	20 27
	8.5	5 Emissions in Nonrestricted Ereouency Bands (Out of Band)	
		8.5.1 Conducted Emissions Plot, 2402 MHz	
		8.5.2 Conducted Emissions Plot, 2442 MHz	
		8.5.3 Conducted Emissions Plot, 2480 MHz	
	8.6	5 Band-edge measurements	
		8.6.1 Lower Band Edge Plot	
		8.6.2 Upper Band Edge Plot	



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615 (352) 472-5500 / testing@industrial-ia.com

8.7	' Radiat	ted Emissions	.35
	8.7.1	Radiated Emissions, 2402 MHz	. 36
	8.7.2	Radiated Emissions, 2442 MHz	. 37
	8.7.3	Radiated Emissions, 2480 MHz	. 38
9.	ANNEX-E	3 – TEST SETUP PHOTOGRAPHS	. 39
10.	HISTORY	OF TEST REPORT CHANGES	. 39



1. Applicant Information

Applicant:ICOM IncAddress:1-1-32 Kamiminami Hirano-ku

Osaka Japan 547-0003

1.1 Test Result Summary

The following test procedure and guidance were used for measuring Digital Transmission System (DTS); FCC KDB 558074 D01 DTS Measurement Guidance and ANSI C63.10-2013. Full test results are available in this report.

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. Timco does not offer opinions and interpretations, only a pass/fail statement.



Applicable Clauses from Part 2 or KDB			
FCC Clauses	Description of the requirements	Result: (Pass, Fail, N/A)	
KDB 558074 D01	Duty Cycle	Reported	
KDB 558074 D01	99 % Bandwidth	Reported	
KDB 558074 D01	Band-edge measurements	Pass	

Applicable Clauses from Part 15.247				
FCC Clauses	Result: (Pass, Fail, N/A)			
15.247 (a) (1) – (1) (iii)	FHSS hopping requirements (1, i,ii,iii)	N/A		
15.247 (a) (1)	FHSS 20dB Bandwidth	N/A		
15.247 (a) (2)	DTS 6dB Bandwidth	Pass		
15.247 (b) (1) - (4)	Conducted output power	Pass		
15.247 (c) (1) – (2)	Operation with directional antenna gains > 6 dBi	N/A		
15.247 (d), 15.215 (b)	Conducted Emissions in Non-restricted bands	Pass		
15.247 (d), 15.215 (b)	Conducted Emissions at the Band-edge	Pass		
15.247 (e)	Power Spectral Density (PSD)	Pass		
15.247 (f)	Hybrid system hopping requirements	N/A		
15.247 (f)	Hybrid system Power Spectral Density	N/A		
15.247 (g)	FHSS System requirements	N/A		
15.247 (h)	FHSS spectrum sensing	N/A		

Applicable Clauses from Part 2 and Part 15 Subpart C				
FCC Clauses	Result: (Pass, Fail, N/A)			
15.203	Antenna requirements	Pass		
15.205	Restricted bands of operation	Pass		
15.207	AC Power Conducted Emissions	N/A		
15.209	Radiated Emissions in Restricted bands	Pass		
15.211	Tunnel Radio Systems	N/A		
15.212 (a)	Single Modular Transmitter	N/A		
15.212 (b)	Limited Modular Transmitter	N/A		
15.213	Cable Locating Equipment	N/A		



2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780 FCC Designation # US1070 FCC site registration is under A2LA certificate # 0955.01 ISED Canada test site registration # 2056A EU Notified Body # 1177 For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 12/13/2024

Dates of Testing: 01/02/2025 - 01/08/2025

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification		
FCC ID:	AFJ381510	
Certified Module FCC ID:	N/A	
Brief Description	Bluetooth module	
Model(s) #	UT-136B	
Firmware version	2.02	
Software version	N/A	
Serial Number	0000104	

Technical Characteristics			
Frequency Range	2400-2483.5 MHz		
RF O/P Power (Max.)	+7 dBm		
Modulation	FHSS GFSK, $\pi/4$ DQPSK, 8DPSK		
Bandwidth & Emission Class	N/A		
Number of Channels	78		
Duty Cycle	N/A		
Antenna Connector	N/A		
Voltage Rating (AC or Batt.)	DC3.3V, No battery included		

Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

3.2 Configuration of EUT

Band (MHz)	Mode	Number of Ant.
N/A	Transmit	1

Operating conditions during Testing:

No modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT).

Peripherals used during Testing:

A laptop provided by the manufacturer was used to program the EUT.

3.3 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.



4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

Test procedures and guidance for measuring Digital Transmission System (DTS) are provided in the FCC KDB 558074 D01 DTS Measurement Guidance and in Clause 11 of ANSI C63.10-2013.

- 1) ANSI C63.10-2013
- 2) FCC KDB 558074 D01

4.2 Applied Limits and Regulatory Limits:

3) FCC CFR 47 Part 15.247 (2020)

5. Measurement Uncertainty

Parameter	Uncertainty (dB)		
Conducted Emissions	± 3.14 dB		
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB		
Radiated Emissions (30 – 200 MHz)	± 2.16 dB		
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB		
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB		
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB		
Note: The uncertainties provided in this table represent an expanded uncertainty expressed at			

approximately the 95% confidence level using a coverage factor of K=2.

6. Environmental Conditions

6.1 Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric pressure	30.05 inHg

Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.



7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

7.1 List of Test Equipment

Test Equipment						
Туре	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna	<u>Biconical</u> <u>1057</u>	Eaton	94455-1	1057	09/01/2024	09/01/2027
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	09/01/2024	09/01/2027
Antenna	<u>Double-</u> <u>Ridged</u> <u>Horn/ETS</u> <u>Horn 1</u>	ETS-Lindgren	3117	00035923	5/31/23	5/30/2026
CHAMBER	<u>CHAMBER</u>	Panashield	3M	N/A	12/29/23	12/18/2025
Pre-amp	Pre-amp	RF-LAMBDA	RLNA00M45GA	NA	2/27/22	7/26/2025
Receiver	EMI Test Receiver R&S ESW44	Rohde & Schwarz	ESW44	103049	10/13/22	10/12/2025

Software									
Software	Author	Version	Validation on						
ESU Firmware	Rohde & Schwarz	4.43 SP3; BIOS v5.1-24-3	2018						
RSCommander	Rohde & Schwarz	1.6.4	2014						
ScopeExplorer	LeCroy	v2.25.0.0	2009						
Field Strength	Timco	v4.10.7.0	2016						



8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Unless noted otherwise in the referenced standard, the measurements of ac power-line conducted emissions and conducted power output will be reported in units of dBµV. Unless noted otherwise in the referenced standard, the measurements of radiated emissions will be reported in units of decibels, referenced to one microvolt per meter (dBµV/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of $dB\mu V$ if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.

Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dBµV	+ 10.36 dB/m	+0.40 dB	=30.36 dBµV/m @ 3m

EIRP = Pcond (dBm) + dBi



8.1 DTS conducted output power

Limits from FCC Part 15.247 (b) (3) and test procedure from ANSI C63.10-2013 section 11.9



Test Results, Mode 1								
Tuned Frequency (MHz)	Power Output (dBm)	Watts(W)						
2402	8.43	0.00697						
2442	8.50	0.00708						
2480	8.69	0.00740						

• MAXIMUM Conducted Output Power = 8.69 dBm



Conducted Output Power, Spectrum Plots



Conducted Output Power, 2402 MHz 8.1.1

Date: 6.JAN.2025 09:50:27



Conducted Output Power, 2442 MHz 8.1.2



Date: 6.JAN.2025 09:48:41



Conducted Output Power, 2480 MHz 8.1.3



Date: 6.JAN.2025 09:47:14



8.2 Occupied Bandwidth

Requirement from FCC KDB 558074 D01 and test procedure from ANSI C63.10-2013 section 6.9.3



99% BW Test Results

Tuned Frequency (MHz)	99% BW (MHz)
2402	0.706
2442	0.698
2480	0.709



99% Occupied Bandwidth Test Data / Spectrum Plots



8.2.1 99% Bandwidth Plot, 2402 MHz

Date: 6.JAN.2025 09:54:49





8.2.2 99% Bandwidth Plot, 2442 MHz

Date: 6.JAN.2025 09:57:12







Date: 6.JAN.2025 09:59:41



8.3 6dB Bandwidth (DTS BW)

Limits from FCC Part 15.247 (a) (2) and test procedure from ANSI C63.10-2013 section 11.8



Tuned Frequency (MHz)	6dB Bandwidth (DTS BW) (kHz)
2402	481.48
2442	483.48
2480	484.48

6dB BW Test Data / Spectrum Plots



8.3.1 6dB Bandwidth (DTS BW), 2402 MHz

Date: 6.JAN.2025 10:39:48





8.3.2 6dB Bandwidth (DTS BW), 2442 MHz

Date: 6.JAN.2025 10:34:49





8.3.3 6dB Bandwidth (DTS BW), 2480 MHz

Date: 6.JAN.2025 10:32:20



8.4 Power Spectral Density (PSD)

Limits from FCC Part 15.247 (e) and test procedure from ANSI C63.10-2013 section 11.10.



Tuned Frequency (MHz)	PSD Level (dBm)
2402	7.87
2442	7.92
2480	7.91





Power Spectral Density (PSD), 2402 MHz 8.4.1

Date: 6.JAN.2025 11:04:46





8.4.2 Power Spectral Density (PSD), 2442 MHz

Date: 6.JAN.2025 11:03:23





8.4.3 Power Spectral Density (PSD), 2480 MHz

Date: 6.JAN.2025 11:07:06



8.5 Emissions in Nonrestricted Frequency Bands (Out of Band)

Limits from FCC Part 15.247 (d) and 15.215 (b) and test procedure from ANSI C63.10-2013 section 7.8 or 11.11 as applicable.





Conducted Emissions in Non-Restricted Bands, Spectrum Plots





Date: 6.JAN.2025 11:26:56





8.5.2 Conducted Emissions Plot, 2442 MHz

Date: 6.JAN.2025 11:23:49





8.5.3 Conducted Emissions Plot, 2480 MHz

Date: 6.JAN.2025 11:28:40

.



8.6 Band-edge measurements

Requirement from FCC KDB 558074 D01 and test procedure from ANSI C63.10-2013 section 7.8 or 11.13 as applicable.







Band-edge Spectrum Plots



8.6.1 Lower Band Edge Plot

1 2.399832 GHz -75.49 dBm

Date: 6.JAN.2025 11:37:48



8.6.2 Upper Band Edge Plot



1 2.484899 GHz -77.94 dBm

Date: 6.JAN.2025 11:41:19



8.7 Radiated Emissions

Restricted Bands from FCC Part 15.205; Limits from FCC Part 15.209









Radiated Emissions in Restricted Bands, Tabular Data

Tuned Frequency (MHz)	Emission Frequency (MHz)	15.205 Restricted Band	15.205, 15.35, 15.247(d) Detector	Meter Reading (dBµV)	Antenna Polarity	Coax Loss (dB)	Duty Cycle Correction (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402.00	4804.00	x	PK	-0.40	н	7.10	0.00	34.19	3.00	40.88	73.98	33.10
2402.00	4804.00	x	PK	-1.00	V	7.10	0.00	34.19	3.00	40.28	73.98	33.70
2402.00	4804.00	x	AVG	-13.30	н	7.10	0.00	34.19	3.00	27.98	53.98	26.00
2402.00	4804.00	x	AVG	-14.90	V	7.10	0.00	34.19	3.00	26.38	53.98	27.60
2402.00	7206.00		PK	1.50	н	9.54	0.00	36.31	3.00	47.34	53.98	6.64
2402.00	7206.00		PK	1.40	V	9.54	0.00	36.31	3.00	47.24	53.98	6.74
2402.00	9608.00		PK	-0.40	н	10.70	0.00	36.81	3.00	47.11	53.98	6.87
2402.00	9608.00		PK	-0.50	V	10.70	0.00	36.81	3.00	47.01	53.98	6.97
2402.00	12010.00	X	PK	-1.30	н	12.40	0.00	38.79	3.00	49.89	73.98	24.09
2402.00	12010.00	×	PK	-2.40	V	12.40	0.00	38.79	3.00	48.79	73.98	25.19
2402.00	12010.00	×	AVG	-15.50	н	12.40	0.00	38.79	3.00	35.69	53.98	18.29
2402.00	12010.00	x	AVG	-15.70	V	12.40	0.00	38.79	3.00	35.49	53.98	18.49
2402.00	14412.00		PK	-3.00	н	13.35	0.00	39.72	3.00	50.07	53.98	3.91
2402.00	14412.00		PK	-3.20	V	13.35	0.00	39.72	3.00	49.87	53.98	4.11
2402.00	16814.00		AVG	-14.90	н	14.60	0.00	42.29	3.00	42.00	53.98	11.98
2402.00	16814.00		AVG	-15.00	V	14.60	0.00	42.29	3.00	41.90	53.98	12.08
2402.00	19216.00	×	PK	-0.50	н	16.00	0.00	16.00	3.00	31.50	73.98	42.48
2402.00	19216.00	x	PK	-1.20	V	16.00	0.00	16.00	3.00	30.80	73.98	43.18
2402.00	19216.00	X	AVG	-14.20	н	16.00	0.00	16.00	3.00	17.80	53.98	36.18
2402.00	19216.00	x	AVG	-14.20	V	16.00	0.00	16.00	3.00	17.80	53.98	36.18
2402.00	21618.00		PK	0.90	н	16.90	0.00	16.90	3.00	34.70	53.98	19.28
2402.00	21618.00		PK	1.30	V	16.90	0.00	16.90	3.00	35.10	53.98	18.88
2402.00	24020.00		PK	4.10	н	17.95	0.00	17.95	3.00	40.00	53.98	13.98
2402.00	24020.00		PK	4.10	V	17.95	0.00	17.95	3.00	40.00	53.98	13.98

Radiated Emissions, 2402 MHz 8.7.1

8.7.2 Radiated Emissions, 2442 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	15.205 Restricted Band	15.205, 15.35, 15.247(d) Detector	Meter Reading (dBµV)	Antenna Polarity	Coax Loss (dB)	Duty Cycle Correction (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2442.00	4884.00	x	РК	0.20	н	7.36	0.00	34.10	3.00	41.66	73.98	32.32
2442.00	4884.00	х	PK	0.50	v	7.36	0.00	34.10	3.00	41.96	73.98	32.02
2442.00	4884.00	х	AVG	-12.20	н	7.36	0.00	34.10	3.00	29.26	53.98	24.72
2442.00	4884.00	х	AVG	-13.30	v	7.36	0.00	34.10	3.00	28.16	53.98	25.82
2442.00	7326.00	х	РК	-1.30	н	9.59	0.00	36.41	3.00	44.70	73.98	29.28
2442.00	7326.00	х	PK	-0.40	V	9.59	0.00	36.41	3.00	45.60	73.98	28.38
2442.00	7326.00	х	AVG	-12.50	н	9.59	0.00	36.41	3.00	33.50	53.98	20.48
2442.00	7326.00	х	AVG	-11.30	V	9.59	0.00	36.41	3.00	34.70	53.98	19.28
2442.00	9768.00		PK	-0.80	н	11.01	0.00	37.03	3.00	47.24	53.98	6.74
2442.00	9768.00		PK	-1.40	V	11.01	0.00	37.03	3.00	46.64	53.98	7.34
2442.00	12210.00	x	PK	-2.60	н	12.50	0.00	39.05	3.00	48.94	73.98	25.04
2442.00	12210.00	х	PK	-2.50	v	12.50	0.00	39.05	3.00	49.04	73.98	24.94
2442.00	12210.00	х	AVG	-16.00	н	12.50	0.00	39.05	3.00	35.54	53.98	18.44
2442.00	12210.00	х	AVG	-15.90	v	12.50	0.00	39.05	3.00	35.64	53.98	18.34
2442.00	14652.00		PK	-4.10	н	13.61	0.00	39.87	3.00	49.37	53.98	4.61
2442.00	14652.00		PK	-4.20	V	13.61	0.00	39.87	3.00	49.27	53.98	4.71
2442.00	17094.00		AVG	-15.30	н	14.66	0.00	41.94	3.00	41.30	53.98	12.68
2442.00	17094.00		AVG	-15.30	v	14.66	0.00	41.94	3.00	41.30	53.98	12.68
2442.00	19536.00	х	PK	-0.30	н	15.61	0.00	15.61	3.00	30.92	73.98	43.06
2442.00	19536.00	х	PK	0.10	V	15.61	0.00	15.61	3.00	31.32	73.98	42.66
2442.00	19536.00	х	AVG	-13.90	н	15.61	0.00	15.61	3.00	17.32	53.98	36.66
2442.00	19536.00	х	AVG	-13.90	V	15.61	0.00	15.61	3.00	17.32	53.98	36.66
2442.00	21978.00		PK	3.20	н	16.97	0.00	16.97	3.00	37.15	53.98	16.83
2442.00	21978.00		PK	3.80	V	16.97	0.00	16.97	3.00	37.75	53.98	16.23
2442.00	24420.00		PK	5.20	н	18.29	0.00	18.29	3.00	41.77	53.98	12.21
2442.00	24420.00		PK	5.50	V	18.29	0.00	18.29	3.00	42.07	53.98	11.91

8.7.3 Radiated Emissions, 2480 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	15.205 Restricted Band	15.205, 15.35, 15.247(d) Detector	Meter Reading (dBµV)	Antenna Polarity	Coax Loss (dB)	Duty Cycle Correction (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2480.00	4960.00	x	PK	-0.01	н	7.72	0.00	33.99	3.00	41.70	73.98	32.28
2480.00	4960.00	х	PK	-0.80	V	7.72	0.00	33.99	3.00	40.91	73.98	33.07
2480.00	4960.00	X	AVG	-12.50	н	7.72	0.00	33.99	3.00	29.21	53.98	24.77
2480.00	4960.00	×	AVG	-12.40	V	7.72	0.00	33.99	3.00	29.31	53.98	24.67
2480.00	7440.00	×	PK	-1.70	н	9.56	0.00	36.21	3.00	44.07	73.98	29.91
2480.00	7440.00	×	PK	-1.40	V	9.56	0.00	36.21	3.00	44.37	73.98	29.61
2480.00	7440.00	x	AVG	-15.10	н	9.56	0.00	36.21	3.00	30.67	53.98	23.31
2480.00	7440.00	х	AVG	-13.40	V	9.56	0.00	36.21	3.00	32.37	53.98	21.61
2480.00	9920.00		PK	-2.60	н	11.15	0.00	37.07	3.00	45.62	53.98	8.36
2480.00	9920.00		PK	-1.60	V	11.15	0.00	37.07	3.00	46.62	53.98	7.36
2480.00	12400.00	×	PK	-2.30	н	12.54	0.00	39.26	3.00	49.50	73.98	24.48
2480.00	12400.00	×	PK	-2.00	V	12.54	0.00	39.26	3.00	49.80	73.98	24.18
2480.00	12400.00	×	AVG	-15.80	н	12.54	0.00	39.26	3.00	36.00	53.98	17.98
2480.00	12400.00	×	AVG	-15.80	V	12.54	0.00	39.26	3.00	36.00	53.98	17.98
2480.00	14880.00		PK	-3.60	н	13.44	0.00	40.09	3.00	49.94	53.98	4.04
2480.00	14880.00		PK	-3.10	V	13.44	0.00	40.09	3.00	50.44	53.98	3.54
2480.00	17360.00		AVG	-14.20	н	15.01	0.00	41.59	3.00	42.40	53.98	11.58
2480.00	17360.00		AVG	-14.20	V	15.01	0.00	41.59	3.00	42.40	53.98	11.58
2480.00	19840.00	×	PK	-1.10	н	16.21	0.00	16.21	3.00	31.33	73.98	42.65
2480.00	19840.00	×	PK	-0.60	V	16.21	0.00	16.21	3.00	31.83	73.98	42.15
2480.00	19840.00	x	AVG	-14.40	н	16.21	0.00	16.21	3.00	18.03	53.98	35.95
2480.00	19840.00	×	AVG	-14.40	V	16.21	0.00	16.21	3.00	18.03	53.98	35.95
2480.00	22320.00	×	PK	0.80	н	17.02	0.00	17.02	3.00	34.83	73.98	39.15
2480.00	22320.00	×	PK	1.00	V	17.02	0.00	17.02	3.00	35.03	73.98	38.95
2480.00	22320.00	x	AVG	-12.70	н	17.02	0.00	17.02	3.00	21.33	53.98	32.65
2480.00	22320.00	×	AVG	-12.70	V	17.02	0.00	17.02	3.00	21.33	53.98	32.65
2480.00	24800.00		PK	7.40	н	18.07	0.00	18.07	3.00	43.54	53.98	10.44
2480.00	24800.00		PK	8.10	V	18.07	0.00	18.07	3.00	44.24	53.98	9.74



9. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate supplementary ANNEX-B document.

10. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
	1	Initial release	01/21/2025
TR_17875-24_FCC 15.247 DTS_2	2	Change in page 1,4	01/31/2025



END OF TEST REPORT