



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shanghai Sunmi Technology Co.,Ltd.

Address: Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai, China

FCC ID: 2AH25D2SKT

Product Name: POS System

Model Number: L1583, L1553, L3553, L1581, L1582

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliance with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR22010036-00B

Date Of Issue: 2022-05-26

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	8
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 20 DB BANDWIDTH.....	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 CHANNEL SEPARATION	18
3.4.1 Applicable Standard.....	18
3.4.2 EUT Setup.....	18
3.4.3 Test Procedure	18
3.5 NUMBER OF HOPPING FREQUENCY	19
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.6 TIME OF OCCUPANCY(DWELL TIME).....	20
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure	20
3.7 PEAK OUTPUT POWER.....	21
3.7.1 Applicable Standard.....	21

3.7.2 EUT Setup.....	21
3.7.3 Test Procedure	21
3.8 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE.....	22
3.8.1 Applicable Standard.....	22
3.8.2 EUT Setup.....	22
3.8.3 Test Procedure	22
3.9 ANTENNA REQUIREMENT.....	23
3.9.1 Applicable Standard.....	23
3.9.2 Judgment.....	23
4. TEST DATA AND RESULTS	24
4.1 AC LINE CONDUCTED EMISSIONS.....	24
4.2 RADIATION SPURIOUS EMISSIONS.....	35
4.3 20 dB EMISSION BANDWIDTH:	49
4.4 CHANNEL SEPARATION:	53
4.5 NUMBER OF HOPPING FREQUENCY:.....	57
4.6 TIME OF OCCUPANCY(DWELL TIME):.....	59
4.7 PEAK CONDUCTED OUTPUT POWER:	63
4.8 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE:	64
5. RF EXPOSURE EVALUATION	71
5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)	71
5.1.1 APPLICABLE STANDARD.....	71
5.1.2 PROCEDURE.....	71
5.1.3 CALCULATED RESULT	71

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	POS System
EUT Models:	L1583
Multipel Model:	L1553, L3553, L1581, L1582
Operation Frequency:	2402-2480MHz
Maximum Peak Output Power (Conducted):	9.79 dBm
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Rated Input Voltage:	DC 24V from Adapter
Serial Number:	CR22010036-RF-S1(L1583 Type-1) CR22010036-RF-S1(L1553 Type-1) CR22010036-RF-S1(L3553 Type-1) CR22010036-RF-S1(L1581) CR22010036-RF-S1(L1582)
EUT Received Date:	2022.2.7
EUT Received Status:	Good
Note: The multiple models are electrically identical with Test model, please refer to the declaration letter for more detail, which was provided by manufacturer.	

Operation Frequency Detail:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
...	...	...	...
...	...	...	...
..	...	78	2480
39	2441	/	/

Per section 15.31(m), the lowest frequency, middle frequency, and highest frequency were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2402
Middle	2441
Highest	2480

Antenna Information Detail ▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
Shanghai Sunmi Technology Co.,Ltd.	FPC	50	1.86dBi/2.4~2.5GHz	Compliance
The Method of §15.203 Compliance:				
☒ Antenna must be permanently attached to the unit. ☐ Antenna must use a unique type of connector to attach to the EUT. ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
L3553 Adapter	jiangsu Chenyang Electron Co.,Ltd.	CYZS36-240150	Input: 100-240V~50/60Hz 1.5A Output: DC 24V 1.5A 36W
L1553&L1583 Adapter	jiangsu Chenyang Electron Co.,Ltd.	CYSE65-240250	Input: 100-240V~50/60Hz 1.7A Output: DC 24V 2.5A 60W

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:	No		
EUT Exercise Software:	test command		
The software " test command "was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲：			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
GFSK	Default	Default	Default
$\pi/4$ -DQPSK	Default	Default	Default
8DPSK	Default	Default	Default

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
SanDisk	USB Disk	16 GB	BL201026210Z
SanDisk	TF Card	16 GB	1183DRECV11N
PHILIPS	Keyboard	SPT6234	K234210510746
PHILIPS	Mouse	SPT6234	C234210506222
Kingston	USB Disk	DTI/2GB	CH 031308
TOTO LINK	Router	X5000R	X5000RK9T0560
Unknown	Load	Unknown	L01
Unknown	Load	Unknown	L02
Unknown	Earphone	Unknown	Ear01

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Keyboard Cable	No	No	1.2	Keyboard	USB Port of EUT
Earphone Cable	No	No	0.8	EUT	Earphone
Mouse Cable	No	No	1	USB port of EUT	Mouse
RJ45 Cable	No	No	3	EUT	Router
RJ11 Cable	No	No	3	EUT	Load
Cable	No	No	3	EUT	load

1.2.4 Block Diagram of Test Setup


AC line conducted emissions:



Spurious emissions:
Below 1GHz:



Above 1GHz:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC line conducted emissions	Compliance
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(1)	20 dB bandwidth	Compliance
FCC §15.247(a)(1)	Channel separation	Compliance
FCC §15.247(a)(1)(iii)	Number of hopping Frequency	Compliance
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliance
FCC §15.247(b)(1)	Peak output power measurement	Compliance
FCC §15.247(d)	Band edges	Compliance
FCC §15.203	Antenna requirement	Compliance
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 20 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

3.3.2 EUT Setup



3.3.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.


3.4 Channel Separation

3.4.1 Applicable Standard

FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.


3.5 Number Of Hopping Frequency

3.5.1 Applicable Standard

FCC §15.247 (a)(1)(iii)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize


It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

3.6 Time Of Occupancy(Dwell Time)

3.6.1 Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.6.2 EUT Setup



3.6.3 Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.


3.7 Peak Output Power

3.7.1 Applicable Standard

FCC §15.247 (b)(1)

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

3.7.2 EUT Setup



3.7.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
2. Add a correction factor to the display.


3.8 100 kHz Bandwidth of Frequency Band Edge

3.8.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.8.2 EUT Setup



3.8.3 Test Procedure

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	CR22010036-RF-S1(L1583 Type-1) CR22010036-RF-S1(L1553 Type-1) CR22010036-RF-S1(L3553 Type-1) CR22010036-RF-S1(L1581) CR22010036-RF-S1(L1582)	Test Date:	2022-02-09~2022-05-17
Test Site:	CE	Test Mode:	Transmitting(BDR middle channel was the worst)
Tester:	Nick Tang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24	Relative Humidity: (%)	71	ATM Pressure: (kPa)	100.8~101.5
----------------------	----	------------------------------	----	------------------------	-------------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2021-04-25	2022-04-24
R&S	LISN	ENV216	101134	2022-04-01	2023-03-31
R&S	EMI Test Receiver	ESR3	102726	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
Audix	Test Software	E3	190306 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Model: L1553 Type-1

Line:



No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.157	20.96	9.61	30.57	55.61	25.04	Average
2	0.157	40.02	9.61	49.63	65.61	15.98	QP
3	0.337	10.98	9.61	20.59	49.28	28.69	Average
4	0.337	22.32	9.61	31.93	59.28	27.35	QP
5	0.713	12.09	9.62	21.71	46.00	24.29	Average
6	0.713	18.22	9.62	27.84	56.00	28.16	QP
7	1.444	9.53	9.62	19.15	46.00	26.85	Average
8	1.444	15.91	9.62	25.53	56.00	30.47	QP
9	1.742	11.96	9.63	21.59	46.00	24.41	Average
10	1.742	19.20	9.63	28.83	56.00	27.17	QP
11	3.378	6.94	9.65	16.59	46.00	29.41	Average
12	3.378	17.11	9.65	26.76	56.00	29.24	QP


Neutral:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.156	23.52	9.61	33.13	55.66	22.53	Average
2	0.156	40.39	9.61	50.00	65.66	15.66	QP
3	0.315	14.29	9.61	23.90	49.85	25.95	Average
4	0.315	24.34	9.61	33.95	59.85	25.90	QP
5	0.710	19.74	9.62	29.36	46.00	16.64	Average
6	0.710	24.81	9.62	34.43	56.00	21.57	QP
7	1.734	13.23	9.63	22.86	46.00	23.14	Average
8	1.734	20.06	9.63	29.69	56.00	26.31	QP
9	2.723	11.97	9.64	21.61	46.00	24.39	Average
10	2.723	18.28	9.64	27.93	56.00	28.07	QP
11	3.380	12.54	9.65	22.19	46.00	23.81	Average
12	3.380	21.26	9.65	30.91	56.00	25.09	QP


Model: L1583 Type-1

Line:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	28.44	9.61	38.05	55.84	17.79	Average
2	0.153	43.54	9.61	53.15	65.84	12.69	QP
3	0.309	13.76	9.61	23.37	49.99	26.62	Average
4	0.309	24.79	9.61	34.40	59.99	25.59	QP
5	0.701	16.09	9.62	25.71	46.00	20.29	Average
6	0.701	23.01	9.62	32.63	56.00	23.37	QP
7	1.090	9.75	9.62	19.37	46.00	26.63	Average
8	1.090	16.35	9.62	25.98	56.00	30.02	QP
9	1.783	14.13	9.63	23.76	46.00	22.24	Average
10	1.783	22.56	9.63	32.19	56.00	23.81	QP
11	3.330	7.58	9.65	17.23	46.00	28.77	Average
12	3.330	17.17	9.65	26.82	56.00	29.18	QP


Neutral:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	30.04	9.61	39.65	55.78	16.13	Average
2	0.154	43.77	9.61	53.38	65.78	12.40	QP
3	0.184	25.59	9.61	35.20	54.28	19.08	Average
4	0.184	39.56	9.61	49.17	64.28	15.11	QP
5	0.725	19.14	9.62	28.76	46.00	17.24	Average
6	0.725	26.46	9.62	36.08	56.00	19.92	QP
7	1.697	13.02	9.63	22.65	46.00	23.35	Average
8	1.697	20.71	9.63	30.33	56.00	25.67	QP
9	3.286	11.74	9.65	21.39	46.00	24.61	Average
10	3.286	20.16	9.65	29.81	56.00	26.19	QP
11	3.599	12.72	9.65	22.37	46.00	23.63	Average
12	3.599	21.38	9.65	31.03	56.00	24.97	QP


Model: L3553 Type-1

Line:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	26.68	9.61	36.29	55.95	19.66	Average
2	0.151	45.46	9.61	55.07	65.95	10.88	QP
3	0.314	11.24	9.61	20.85	49.85	29.00	Average
4	0.314	25.98	9.61	35.59	59.85	24.26	QP
5	0.532	12.35	9.61	21.97	46.00	24.03	Average
6	0.532	24.11	9.61	33.72	56.00	22.28	QP
7	1.333	15.01	9.62	24.64	46.00	21.36	Average
8	1.333	23.11	9.62	32.73	56.00	23.27	QP
9	1.731	16.52	9.63	26.15	46.00	19.85	Average
10	1.731	24.89	9.63	34.52	56.00	21.48	QP
11	3.116	16.55	9.65	26.20	46.00	19.80	Average
12	3.116	28.45	9.65	38.10	56.00	17.90	QP


Neutral:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	27.00	9.61	36.61	55.99	19.38	Average
2	0.150	45.14	9.61	54.75	65.99	11.24	QP
3	0.248	15.10	9.61	24.71	51.82	27.11	Average
4	0.248	30.81	9.61	40.42	61.82	21.40	QP
5	0.528	18.69	9.61	28.30	46.00	17.70	Average
6	0.528	27.90	9.61	37.51	56.00	18.49	QP
7	1.220	19.89	9.62	29.51	46.00	16.49	Average
8	1.220	28.32	9.62	37.94	56.00	18.06	QP
9	1.697	19.97	9.63	29.60	46.00	16.40	Average
10	1.697	28.16	9.63	37.79	56.00	18.21	QP
11	3.135	17.98	9.65	27.63	46.00	18.37	Average
12	3.135	29.68	9.65	39.33	56.00	16.67	QP


Model: L1581

Line:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	37.50	9.61	47.11	65.58	18.47	QP
2	0.158	19.06	9.61	28.67	55.58	26.91	Average
3	0.207	30.96	9.61	40.57	63.32	22.75	QP
4	0.207	13.20	9.61	22.81	53.32	30.51	Average
5	0.589	18.70	9.62	28.32	56.00	27.68	QP
6	0.589	10.29	9.62	19.91	46.00	26.09	Average
7	1.264	16.93	9.62	26.55	56.00	29.45	QP
8	1.264	8.50	9.62	18.13	46.00	27.87	Average
9	1.745	26.92	9.63	36.54	56.00	19.46	QP
10	1.745	14.67	9.63	24.30	46.00	21.70	Average
11	2.540	14.74	9.64	24.38	56.00	31.62	QP
12	2.540	7.72	9.64	17.36	46.00	28.64	Average


Neutral:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.155	37.20	9.61	46.81	65.72	18.91	QP
2	0.155	19.41	9.61	29.02	55.72	26.70	Average
3	0.170	35.60	9.61	45.21	64.96	19.75	QP
4	0.170	17.84	9.61	27.45	54.96	27.51	Average
5	0.214	30.48	9.61	40.09	63.04	22.95	QP
6	0.214	15.00	9.61	24.61	53.04	28.43	Average
7	0.686	20.32	9.62	29.94	56.00	26.06	QP
8	0.686	13.39	9.62	23.01	46.00	22.99	Average
9	1.733	24.63	9.63	34.26	56.00	21.74	QP
10	1.733	13.20	9.63	22.83	46.00	23.17	Average
11	2.500	15.94	9.64	25.58	56.00	30.42	QP
12	2.500	7.84	9.64	17.48	46.00	28.52	Average


Model: L1582

Line:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	41.17	9.61	50.78	65.84	15.06	QP
2	0.153	21.70	9.61	31.31	55.84	24.53	Average
3	0.173	38.51	9.61	48.12	64.82	16.70	QP
4	0.173	18.56	9.61	28.17	54.82	26.65	Average
5	0.601	19.55	9.62	29.17	56.00	26.83	QP
6	0.601	11.67	9.62	21.29	46.00	24.71	Average
7	1.504	21.01	9.63	30.63	56.00	25.37	QP
8	1.504	9.81	9.63	19.44	46.00	26.56	Average
9	1.721	27.03	9.63	36.66	56.00	19.34	QP
10	1.721	14.06	9.63	23.68	46.00	22.32	Average
11	2.349	15.16	9.64	24.79	56.00	31.21	QP
12	2.349	8.45	9.64	18.09	46.00	27.91	Average

Neutral:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.156	39.72	9.61	49.33	65.68	16.35	QP
2	0.156	21.99	9.61	31.60	55.68	24.08	Average
3	0.169	38.77	9.61	48.38	65.00	16.62	QP
4	0.169	21.52	9.61	31.13	55.00	23.87	Average
5	0.612	19.11	9.62	28.73	56.00	27.27	QP
6	0.612	11.43	9.62	21.05	46.00	24.95	Average
7	0.718	19.47	9.62	29.09	56.00	26.91	QP
8	0.718	12.48	9.62	22.10	46.00	23.90	Average
9	1.731	24.88	9.63	34.51	56.00	21.49	QP
10	1.731	12.53	9.63	22.16	46.00	23.84	Average
11	2.871	18.49	9.65	28.14	56.00	27.86	QP
12	2.871	7.42	9.65	17.07	46.00	28.93	Average

4.2 Radiation Spurious Emissions

Serial Number:	CR22010036-RF-S1(L1583 Type-1) CR22010036-RF-S1(L1553 Type-1) CR22010036-RF-S1(L3553 Type-1) CR22010036-RF-S1(L1581) CR22010036-RF-S1(L1582)	Test Date:	2022-02-09~2022-05-17
Test Site:	966-2/966-1	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	18.1~24.2	Relative Humidity: (%)	52~67	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2024-02-04
AH	Preamplifier	PAM-1840VH	190	2021-11-19	2022-11-18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2021-08-08	2022-08-07
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Model: L1583 Type-1

1) 30MHz-1GHz(BDR Low channel was the worst)

Horizontal:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	76.512	46.73	-17.33	29.41	40.00	10.59	Peak
2	176.888	53.54	-13.62	39.93	43.50	3.57	QP
3	206.398	48.32	-12.55	35.78	43.50	7.72	Peak
4	265.676	53.71	-12.44	41.27	46.00	4.73	QP
5	311.087	48.50	-10.80	37.70	46.00	8.30	Peak
6	721.726	40.25	-3.49	36.77	46.00	9.23	Peak

Vertical:


No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.531	35.01	-4.20	30.81	40.00	9.19	Peak
2	38.888	41.58	-10.63	30.95	40.00	9.05	Peak
3	53.882	48.68	-17.48	31.20	40.00	8.80	Peak
4	88.652	50.85	-17.26	33.59	43.50	9.91	Peak
5	176.888	51.38	-13.62	37.76	43.50	5.74	QP
6	265.676	54.28	-12.44	41.84	46.00	4.16	QP

Model: L1553 Type-1

Horizontal:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	176.888	50.12	-13.62	36.50	43.50	7.00	Peak
2	201.393	49.94	-12.41	37.52	43.50	5.98	QP
3	293.084	48.04	-11.04	37.00	46.00	9.00	Peak
4	316.589	47.33	-10.81	36.52	46.00	9.48	Peak
5	495.934	46.83	-6.37	40.46	46.00	5.54	QP
6	620.710	44.06	-4.94	39.12	46.00	6.88	QP

Vertical:


No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	34.396	40.45	-7.18	33.27	40.00	6.73	Peak
2	88.342	48.58	-17.27	31.31	43.50	12.19	Peak
3	176.888	47.50	-13.62	33.89	43.50	9.61	Peak
4	372.005	45.62	-9.66	35.96	46.00	10.04	Peak
5	495.934	46.27	-6.37	39.90	46.00	6.10	Peak
6	620.710	41.93	-4.94	36.99	46.00	9.01	Peak

Model: L3553 Type-1

Horizontal:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	77.593	44.47	-17.46	27.01	40.00	12.99	Peak
2	175.037	45.64	-13.54	32.10	43.50	11.40	Peak
3	289.002	46.09	-11.28	34.81	46.00	11.19	Peak
4	495.934	46.47	-6.37	40.10	46.00	5.90	QP
5	704.226	41.38	-3.77	37.60	46.00	8.40	Peak
6	744.866	43.79	-3.11	40.68	46.00	5.32	QP


Vertical:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	33.211	39.57	-6.28	33.30	40.00	6.70	Peak
2	39.299	45.78	-10.96	34.82	40.00	5.18	QP
3	74.396	48.32	-17.16	31.16	40.00	8.84	Peak
4	159.225	43.92	-12.29	31.63	43.50	11.87	Peak
5	495.934	46.81	-6.37	40.44	46.00	5.56	QP
6	744.866	42.90	-3.11	39.79	46.00	6.21	Peak

Model: L1581


Horizontal:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	65.803	41.73	-17.11	24.62	40.00	15.38	Peak
2	125.007	36.23	-11.54	24.69	43.50	18.81	Peak
3	183.201	40.95	-13.74	27.21	43.50	16.29	Peak
4	209.313	39.75	-12.59	27.16	43.50	16.34	Peak
5	296.184	45.40	-10.91	34.49	46.00	11.51	Peak
6	361.714	44.45	-10.00	34.45	46.00	11.55	Peak


Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.416	35.10	-9.49	25.61	40.00	14.39	Peak
2	64.659	47.63	-17.20	30.43	40.00	9.57	Peak
3	132.221	40.32	-11.68	28.64	43.50	14.86	Peak
4	207.123	39.90	-12.56	27.34	43.50	16.16	Peak
5	298.268	42.95	-10.86	32.10	46.00	13.90	Peak
6	437.120	44.69	-7.53	37.17	46.00	8.83	Peak

Model: L1582

Horizontal:


No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	99.878	49.04	-14.62	34.42	43.50	9.08	Peak
2	135.506	48.50	-11.88	36.63	43.50	6.87	Peak
3	208.580	45.98	-12.58	33.40	43.50	10.10	Peak
4	266.609	50.38	-12.41	37.97	46.00	8.03	Peak
5	345.595	48.31	-10.25	38.06	46.00	7.94	Peak
6	601.427	44.40	-5.27	39.13	46.00	6.87	Peak


Vertical:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	63.983	44.08	-17.28	26.80	40.00	13.20	Peak
2	75.977	47.79	-17.27	30.52	40.00	9.48	Peak
3	99.878	48.71	-14.62	34.09	43.50	9.41	Peak
4	135.032	43.44	-11.85	31.59	43.50	11.91	Peak
5	174.424	47.50	-13.50	34.00	43.50	9.50	Peak
6	459.114	43.39	-6.97	36.42	46.00	9.58	Peak

2) 1-25GHz(L1583 Type-1 was the worst):*BDR Mode(GFSK) was the worst:*

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
2402.00	71.30	PK	H	31.51	102.81	N/A	N/A
2402.00	68.25	AV	H	31.51	99.76	N/A	N/A
2402.00	66.38	PK	V	31.51	97.89	N/A	N/A
2402.00	63.21	AV	V	31.51	94.72	N/A	N/A
2390.00	26.76	PK	H	31.46	58.22	74.00	15.78
2390.00	13.82	AV	H	31.46	45.28	54.00	8.72
4804.00	35.68	PK	H	10.91	46.59	74.00	27.41
4804.00	23.19	AV	H	10.91	34.10	54.00	19.90
7206.00	34.60	PK	H	14.22	48.82	74.00	25.18
7206.00	22.81	AV	H	14.22	37.03	54.00	16.97
Middle Channel: 2441 MHz							
2441.00	71.71	PK	H	31.61	103.32	N/A	N/A
2441.00	68.54	AV	H	31.61	100.15	N/A	N/A
2441.00	69.64	PK	V	31.61	101.25	N/A	N/A
2441.00	66.48	AV	V	31.61	98.09	N/A	N/A
4882.00	32.84	PK	H	11.07	43.91	74.00	30.09
4882.00	20.88	AV	H	11.07	31.95	54.00	22.05
7323.00	32.29	PK	H	14.80	47.09	74.00	26.91
7323.00	20.41	AV	H	14.80	35.21	54.00	18.79
High Channel: 2480 MHz							
2480.00	74.20	PK	H	31.64	105.84	N/A	N/A
2480.00	70.96	AV	H	31.64	102.60	N/A	N/A
2480.00	69.83	PK	V	31.64	101.47	N/A	N/A
2480.00	66.58	AV	V	31.64	98.22	N/A	N/A
2483.50	27.49	PK	H	31.64	59.13	74.00	14.87
2483.50	14.55	AV	H	31.64	46.19	54.00	7.81
4960.00	33.22	PK	H	11.23	44.45	74.00	29.55
4960.00	20.96	AV	H	11.23	32.19	54.00	21.81
7440.00	31.01	PK	H	15.26	46.27	74.00	27.73
7440.00	21.87	AV	H	15.26	37.13	54.00	16.87

Worst Test plots(BDR high channel was the worst)



4.3 20 dB Emission Bandwidth:

Serial Number:	CR22010036-RF-S1	Test Date:	2022/3/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Modes	Test Channel	Test Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Lowest	2402	1.038
	Middle	2441	1.038
	Highest	2480	1.038
EDR Mode ($\pi/4$ -DQPSK)	Lowest	2402	1.355
	Middle	2441	1.359
	Highest	2480	1.359
EDR Mode (8DPSK)	Lowest	2402	1.324
	Middle	2441	1.324
	Highest	2480	1.324





EDR Mode (8DPSK)


Lowest Channel



Middle Channel



Highest Channel



4.4 Channel Separation:

Serial Number:	CR22010036-RF-S1	Test Date:	2022/3/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Test Modes	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
BDR Mode (GFSK)	2402	0.999	0.692
	2441	0.999	0.692
	2480	1.003	0.692
EDR Mode ($\pi/4$ -DQPSK)	2402	0.999	0.903
	2441	1.003	0.906
	2480	0.999	0.906
EDR Mode (8DPSK)	2402	0.999	0.883
	2441	0.999	0.883
	2480	1.003	0.883






EDR Mode (8DPSK)

Lowest Channel




Date: 25 MAR 2022 16:37:21

Middle Channel



Date: 25 MAR 2022 16:39:23

Highest Channel



Date: 25 MAR 2022 16:40:53

4.5 Number Of Hopping Frequency:

Serial Number:	CR22010036-RF-S1	Test Date:	2022/3/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Modes	Frequency Range (MHz)	Number of Hopping Channel	Limits
GFSK	2400-2483.5	79	≥ 15
$\pi/4$ -DQPSK	2400-2483.5	79	≥ 15
8DPSK	2400-2483.5	79	≥ 15

Number of Hopping Channel

BDR Mode (GFSK)




Date: 25 MAR 2022 16:27:16

EDR Mode ($\pi/4$ -DQPSK)

Date: 25 MAR 2022 16:30:37

EDR Mode (8DPSK)



Date: 25 MAR 2022 16:34:19

4.6 Time Of Occupancy(Dwell Time):

Serial Number:	CR22010036-RF-S1	Test Date:	2022-03-30
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.4	Relative Humidity: (%)	65	ATM Pressure: (kPa)	101.0
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Modes	Packet Type	Test Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
BDR Mode (GFSK)	DH1	2441	0.435	0.139	0.400
	DH3	2441	1.693	0.271	0.400
	DH5	2441	2.951	0.315	0.400
EDR Mode ($\pi/4$ -DQPSK)	2DH1	2441	0.438	0.140	0.400
	2DH3	2441	1.841	0.295	0.400
	2DH5	2441	2.968	0.317	0.400
EDR Mode (8DPSK)	3DH1	2441	0.433	0.139	0.400
	3DH3	2441	1.704	0.273	0.400
	3DH5	2441	2.947	0.314	0.400

Note:


DH1:Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s

DH3:Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s


DH5:Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s

BDR Mode (GFSK)**DH1:**


Date: 30 MAR 2022 09:54:17


DH3:

Date: 30 MAR 2022 09:43:13


DH5:

Date: 30 MAR 2022 10:01:46




EDR Mode (8DPSK)**3DH1:**

Date: 30 MAR 2022 11:16:04

3DH3:

Date: 30 MAR 2022 11:27:51

3DH5:

Date: 30 MAR 2022 11:33:21

4.7 Peak Conducted Output Power:

Serial Number:	CR22010036-RF-S1	Test Date:	2022-03-25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
BDR Mode (GFSK)	2402	9.30	21
	2441	9.79	21
	2480	9.73	21
EDR Mode ($\pi/4$ -DQPSK)	2402	8.58	21
	2441	7.85	21
	2480	7.89	21
EDR Mode (8DPSK)	2402	8.59	21
	2441	7.89	21
	2480	7.81	21

4.8 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	CR22010036-RF-S1	Test Date:	2022-03-25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Mark Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07
HuiXunDa	DC Block	SMA-JK 18G	DCB181108042	2022-01-21	2023-01-20


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Please refer to the following Plots.


BDR Mode (GFSK)**Band Edge,
Left Side**


Date: 25 MAR 2022 15:24:58

**Band Edge,
Right Side**


Date: 25 MAR 2022 15:26:24




EDR Mode (8DPSK)**Band Edge,
Left Side****Band Edge,
Right Side**

Hopping Mode, BDR Mode (GFSK)**Band Edge,
Left Side**


Date: 25 MAR 2022 16:57:09

**Band Edge,
Right Side**


Date: 25 MAR 2022 16:59:34

Hopping Mode, EDR Mode ($\pi/4$ -DQPSK)**Band Edge,
Left Side**


Date: 25 MAR 2022 17:07:57

**Band Edge,
Right Side**

Date: 25 MAR 2022 17:01:41

Hopping Mode, EDR Mode (8DPSK)**Band Edge,
Left Side**

Date: 25 MAR 2022 17:06:19

**Band Edge,
Right Side**

Date: 25 MAR 2022 17:04:09

5. RF EXPOSURE EVALUATION

5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

5.1.1 Applicable Standard

FCC §15.247 (i) & §1.1310 & §2.1091

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

5.1.2 Procedure

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

5.1.3 Calculated Result

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BDR/EDR	2402-2480	1.86	1.53	10	10.00	20	0.0030	1.0
BLE	2402-2480	1.86	1.53	8	6.31	20	0.0019	1.0
Wi-Fi	2412-2462	1.86	1.53	22	158.49	20	0.0482	1.0

Note: The Wi-Fi and Bluetooth can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance.

===== END OF REPORT =====