



**Project name: 2\_TDK\_0603\_TAS**

FCC  
Federal Communications Commission

*Peter de Wit*  
10. November 2003  
Phone +31 (0) 6 22 47 00 55  
Fax +31 (0) 46 442 2192

**RF exposure requirements - FCC ID: PI4TDKB2IPC**

Dear Application Examiner,

The maximum measured power output is 2,41mW (3.82 dBm), the maximum antenna gain is 2,0 dBi = numeric gain 1,58 (see also FCC test report)

The maximum permissible exposure is defined in 47 CFR 1.1310 with 1 mW/cm<sup>2</sup>. The distance from the EUT's transmitting antenna where the exposure level reaches the maximum permitted level is calculated using the general equation:

$$S = P \cdot G / 4\pi R^2$$

$S_{\max} = 1\text{mW/cm}^2$ ,  $P = 2,41\text{mW}$ , linear power gain relative to the isotropic radiator = 2,0 dBi = 1,58 (numeric gain),  $R$  = distance in cm

Solving for  $R$ , the 1mW/cm<sup>2</sup> limit is reached in a distance of 0,55 cm to the transmitting antenna.

After installation of TDK Bluetooth module "Blu2i PCMCIA Adaptor", the minimum distance of 0,55 cm must always be ensured. During normal use of this device it is impossible that the user gets closer to the transmitting antenna.

Please contact us if you have any additional questions.

Best Regards

7layers AG