



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AY0009725(1) Date : 18 Feb 2019

Application No. : LY002912 (3)

Applicant : KODA ELECTRONICS (HK) CO., LTD.  
2/F MANDARIN COMMERCIAL HOUSE,  
38 MORRISON HILL ROAD, WANCHAI,  
HONG KONG

Buyer / Brand name : NONSTOP

Sample Description : One(1) item of submitted sample stated to be

Sample description	Model No
Bluetooth Wireless Speaker Qi Fast Charging Pad	Station A- Jetway
Bluetooth Wireless Speaker Qi Fast Charging Pad	Station A- Wood/Fabric

Sample registration No.: RY047334-001, RY047334-002

Radio Frequency : 2402 – 2480MHz Bluetooth

Supply voltage : AC100-240 to DC9V adaptor (Model: OBL-0904000U)

No. of submitted sample : (Two) set(s)

Date Received : 24 Jan 2019.

Test Period : 24 Jan 2019 to 04 Feb 2019.

Test Requested : RF Exposure

Test standard : KDB 680106 D01 RF Exposure Wireless Charging App v03  
47 CFR Part 2 section 2.1091

Test Result : See attached sheet(s) from page 2 to 3.

Conclusion : The submitted sample complies with RF Exposure requirements.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_ Page 1 of 3

Mr. WONG Lap-pong, Andrew  
Manager

FCC ID: 2ADLI-NSA-BK-WF

Document name: FCC MPE - Document Ref No: RT-EL-EMC-045- Issue Date: 03 Sep 2018 - Edition: 1



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AY0009725(1)

Date : 18 Feb 2019

Remark : All two models are the same in circuitry and components and construction, and therefore model **Station A-Wood/Fabric** was chosen to be the representative of the test sample. The difference(s) between the tested model and the declared model(s) is/are: Model no., Color and Decoration material.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-pong, Andrew  
Manager

Page 2 of 3

FCC ID: 2ADLI-NSA-BK-WF

Document name: FCC MPE - Document Ref No: RT-EL-EMC-045- Issue Date: 03 Sep 2018 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmateesting.org](http://www.cmateesting.org).  
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : [info@cmateesting.org](mailto:info@cmateesting.org) Web Site : <http://www.cmateesting.org>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AY0009725(1)

Date : 18 Feb 2019

### Simultaneous power

Not applicable

### RF Exposure Evaluation

According to KDB 447498 D01 clause 4.3.1 a), transmission from 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

### Calculation

-Frequency : 2.480GHz  
-Max. simultaneous power of channel , including tune-up tolerance : 0.033mW  
-Minimum test separation distances : <5mm

where

-f(GHz) is the RF channel transmit frequency in GHz.

-Power and distance are rounded to the nearest mW and mm before calculation.

-The result is rounded to one decimal place for comparison.

Substitute above reading for calculation.

$$[(\text{mW}) / (\text{mm})] \times \sqrt{\text{GHz}}$$

Result = 0.104

Requirements:  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

### Conclusion

The corresponding SAR test exclusion threshold was satisfied 4.3.1a) requirements. Measurement or numerical simulation is not required.

\*\*\*\*\* End of Evaluation \*\*\*\*\*