

Applic	cant/Grantee	Panasonic C	forporation of No	orth America	
FCC ID: ACJ9TGRI18D				**************************************	
	·			ılar Transmitters	
Reque	st for Modular		_	or Limited Modular Approval	
•		Requirement		EUT Conditions	Comply (Y/N)
		Singl	le Modular Appr	oval Requirements	
1	The radio elem transmitter mu The physical c may be located elements.	st have their carystal and tun	wn shielding.	The device does not have Metal shielding to cover RF section. Refer to External Photos.	N
2	The modular t modulation/da provided) to e comply with P conditions of e modulation.	nta inputs (if sunsure that the repair of the state of th	module will ments under	All inputs to the device are buffered through logic U1 inputs. Refer to Schematic Diagram.	Y
3	The modular transmitter must have its own power supply regulation.			There is no power supply in the module. 3.3V and 5.0V are fed by the final product.	N
4	The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.			The device is equipped with the unique antenna connector. Refer to External photos.	Y
5	stand-alone comust not be in testing for conrequirements. will be battery the AC line consection 15.20° data input/output module must rewill be market	onfiguration, <i>i</i> . side another description with I Unless the transfer powered, it monducted required. AC or DC poput lines connected with the metal with the metal side of the contain ferror of the contain for the contain	evice during Part 15 nsmitter module nust comply with rements found in ower lines and ected to the rites, unless they	The device was installed into the final product for testing. Refer to setup photos.	N



	shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)).		
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. (A) If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODELI" or "Contains FCC ID: XYZMODELI" Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. (B) If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization.	The proposed FCC ID label format is to be placed on the module. If FCC ID is not visible when the module is installed into the system, "Contains FCC ID: ACJ9TGRI18D" shall be placed on the outside of final host system.	Y



7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Refer to "User's Guide" Exhibit	Y
8	The modular transmitter must comply with any applicable RF exposure limits in Sections 1.1310 and 2.1093 in its final configuration.	The device complies with RF exposure compliance requirement	Y

A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Ben Botros

Project Manager

Buf h.

Panasonic Corporation of North America Product Safety & Compliance Department