



**MET Laboratories, Inc.** *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

13501 MCCALLEN PASS • AUSTIN, TEXAS 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

November 7, 2018

HID Global Corporation  
6533 Flying Cloud Drive  
Eden Prairie, MN 55344

Dear Robert Cresswell,

Enclosed is the EMC Wireless test report for compliance testing of the HID Global Corporation R10F as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15 Subpart C for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,  
MET LABORATORIES, INC.

Joel Huna  
Documentation Department

Reference: (\HID Global Corporation\EMCA99585-FCC247 Rev. 2)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.



*The Nation's First Licensed Nationally Recognized Testing Laboratory*



## **Electromagnetic Compatibility Criteria Test Report**

for the

**HID Global Corporation  
R10F**

**Tested under**  
the FCC Certification Rules  
contained in  
15.247 Subpart C for Intentional Radiators

**MET Report: EMCA99585-FCC247 Rev. 2**

November 7, 2018

**Prepared For:**

**HID Global Corporation  
6533 Flying Cloud Drive  
Eden Prairie, MN 55344**

**Prepared By:**  
**MET Laboratories, Inc.**  
13501 McCallen Pass  
Austin, TX 78753



## Electromagnetic Compatibility Criteria Test Report

for the

**HID Global Corporation  
R10F**

**Tested under**  
the FCC Certification Rules  
contained in  
15.247 Subpart C for Intentional Radiators



Giuliano Messina, Project Engineer  
Electromagnetic Compatibility Lab



Joel Huna  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



John Mason,  
Director, Electromagnetic Compatibility Lab



## Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	October 4, 2018	Initial Issue.
1	November 7, 2018	TCB Corrections.
2	November 9, 2018	TCB Corrections.



## Table of Contents

<b>I.</b>	<b>Executive Summary .....</b>	<b>1</b>
	A. Purpose of Test .....	2
	B. Executive Summary .....	2
<b>II.</b>	<b>Equipment Configuration .....</b>	<b>3</b>
	A. Overview.....	4
	B. References.....	5
	C. Test Site .....	5
	D. Measurement Uncertainty .....	5
	E. Description of Test Sample.....	6
	F. Equipment Configuration.....	6
	G. Support Equipment .....	6
	H. Mode of Operation.....	7
	I. Method of Monitoring EUT Operation .....	7
	J. Modifications .....	7
	a) Modifications to EUT .....	7
	b) Modifications to Test Standard.....	7
	K. Disposition of EUT .....	7
<b>III.</b>	<b>Electromagnetic Compatibility Criteria for Intentional Radiators .....</b>	<b>8</b>
	§ 15.203 Antenna Requirement .....	9
	§ 15.207(a) Conducted Emissions Limits .....	10
	§ 15.247(a)(a) 6 dB and 99% Bandwidth .....	13
	§ 15.247(b) Peak Power Output .....	15
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge.....	17
	§ 15.247 Operation Within the Bands .....	23
	§ 15.247(c) Spurious Emissions in Non-restricted Bands .....	26
	§ 15.247(e) Peak Power Spectral Density .....	30
	§ 2.1093 Maximum Permissible Exposure .....	32
<b>IV.</b>	<b>Test Equipment .....</b>	<b>33</b>
<b>V.</b>	<b>Certification &amp; User's Manual Information .....</b>	<b>35</b>
	A. Certification Information .....	36
	B. Label and User's Manual Information .....	40



## List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing .....	2
Table 2. EUT Summary Table.....	4
Table 3. References .....	5
Table 4. Uncertainty Calculations Summary .....	5
Table 5. Equipment Configuration .....	6
Table 6. Support Equipment.....	6
Table 7. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a) .....	10
Table 8. Conducted Emissions, 15.207(a), Test Results .....	11
Table 9. Output Power Requirements from §15.247(b) .....	15
Table 10. Restricted Bands of Operation.....	17
Table 11. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a) .....	18
Table 12. Test Equipment List .....	34

## List of Plots

Plot 1. Conducted Emissions, 15.207(a), DC+ .....	12
Plot 2. Conducted Emissions, 15.207(a), DC- .....	12
Plot 3. 6 dB Occupied Bandwidth, 2402 .....	14
Plot 4. 6 dB Occupied Bandwidth, 2442 .....	14
Plot 5. 6 dB Occupied Bandwidth, 2480 .....	14
Plot 6. Peak Power Output, 2402.....	16
Plot 7. Peak Power Output, 2442.....	16
Plot 8. Peak Power Output, 2480.....	16
Plot 9. Radiated Emissions, 30 MHz – 1 GHz, Horizontal .....	19
Plot 10. Radiated Emissions, 30 MHz – 1 GHz, Vertical.....	19
Plot 11. Radiated Emissions, 1 GHz – 7 GHz, Horizontal, Average.....	19
Plot 12. Radiated Emissions, 1 GHz – 7 GHz, Horizontal, Peak .....	20
Plot 13. Radiated Emissions, 1 GHz – 7 GHz, Vertical, Average.....	20
Plot 14. Radiated Emissions, 1 GHz – 7 GHz, Vertical, Peak.....	20
Plot 15. Radiated Emissions, 7 GHz – 18 GHz, Horizontal, Average.....	21
Plot 16. Radiated Emissions, 7 GHz – 18 GHz, Horizontal, Peak .....	21
Plot 17. Radiated Emissions, 7 GHz – 18 GHz, Vertical, Average .....	21
Plot 18. Radiated Emissions, 7 GHz – 18 GHz, Vertical, Peak.....	22
Plot 19. Radiated Restricted Bandedge, 2402, Horizontal, Average .....	23
Plot 20. Radiated Restricted Bandedge, 2402, Horizontal, Peak.....	23
Plot 21. Radiated Restricted Bandedge, 2402, Vertical, Average .....	24
Plot 22. Radiated Restricted Bandedge, 2402, Vertical, Peak .....	24
Plot 23. Radiated Restricted Bandedge, 2480, Horizontal, Average .....	24
Plot 24. Radiated Restricted Bandedge, 2480, Horizontal, Peak.....	25
Plot 25. Radiated Restricted Bandedge, 2480, Vertical, Average .....	25
Plot 26. Radiated Restricted Bandedge, 2480, Vertical, Peak .....	25
Plot 27. Conducted Spurious Emissions, 2402, 1 – 26.5 GHz .....	27
Plot 28. Conducted Spurious Emissions, 2402, 30 MHz – 1 GHz .....	27
Plot 29. Conducted Spurious Emissions, 2442, 1 – 26.5 GHz .....	27
Plot 30. Conducted Spurious Emissions, 2442, 30 MHz – 1 GHz .....	28
Plot 31. Conducted Spurious Emissions, 2480, 1 – 26.5 GHz .....	28
Plot 32. Conducted Spurious Emissions, 2480, 30 MHz – 1 GHz .....	28
Plot 33. Conducted Spurious Emissions, 2402, Bandedge .....	29
Plot 34. Conducted Spurious Emissions, 2480, Bandedge .....	29
Plot 35. Power Density, 2402 .....	31



Plot 36. Power Density, 2442 .....	31
Plot 37. Power Density, 2480 .....	31

## List of Figures

Figure 1. Block Diagram of Test Configuration.....	6
Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	13



## List of Terms and Abbreviations

<b>AC</b>	<b>Alternating Current</b>
<b>ACF</b>	<b>Antenna Correction Factor</b>
<b>Cal</b>	<b>Calibration</b>
<b><i>d</i></b>	<b>Measurement Distance</b>
<b>dB</b>	<b>Decibels</b>
<b>dB<sub>μ</sub>A</b>	<b>Decibels above one microamp</b>
<b>dB<sub>μ</sub>V</b>	<b>Decibels above one microvolt</b>
<b>dB<sub>μ</sub>A/m</b>	<b>Decibels above one microamp per meter</b>
<b>dB<sub>μ</sub>V/m</b>	<b>Decibels above one microvolt per meter</b>
<b>DC</b>	<b>Direct Current</b>
<b>E</b>	<b>Electric Field</b>
<b>DSL</b>	<b>Digital Subscriber Line</b>
<b>ESD</b>	<b>Electrostatic Discharge</b>
<b>EUT</b>	<b>Equipment Under Test</b>
<b><i>f</i></b>	<b>Frequency</b>
<b>FCC</b>	<b>Federal Communications Commission</b>
<b>GRP</b>	<b>Ground Reference Plane</b>
<b>H</b>	<b>Magnetic Field</b>
<b>HCP</b>	<b>Horizontal Coupling Plane</b>
<b>Hz</b>	<b>Hertz</b>
<b>IEC</b>	<b>International Electrotechnical Commission</b>
<b>kHz</b>	<b>kilohertz</b>
<b>kPa</b>	<b>kilopascal</b>
<b>kV</b>	<b>kilovolt</b>
<b>LISN</b>	<b>Line Impedance Stabilization Network</b>
<b>MHz</b>	<b>Megahertz</b>
<b>μH</b>	<b>microhenry</b>
<b>μ</b>	<b>microfarad</b>
<b>μs</b>	<b>microseconds</b>
<b>NEBS</b>	<b>Network Equipment-Building System</b>
<b>PRF</b>	<b>Pulse Repetition Frequency</b>
<b>RF</b>	<b>Radio Frequency</b>
<b>RMS</b>	<b>Root-Mean-Square</b>
<b>TWT</b>	<b>Traveling Wave Tube</b>
<b>V/m</b>	<b>Volts per meter</b>
<b>VCP</b>	<b>Vertical Coupling Plane</b>



# **I. Executive Summary**



## A. Purpose of Test

An EMC evaluation was performed to determine compliance of the HID Global Corporation R10F, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the R10F. HID Global Corporation should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the R10F, has been **permanently** discontinued.

## B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with HID Global Corporation, purchase order number 1110960546. All tests were conducted using measurement procedures ANSI C63.4-2014 and ANSI C63.10-2013.

FCC Reference 47 CFR Part 15.247:2005	Description	Compliance
Title 47 of the CFR, Part 15 §15.203	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	Conducted Emission Limits	Compliant
Title 47 of the CFR, Part 15 §15.247	Operation within the bands	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(2)	6dB Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(c)	Spurious Emissions in Non-restricted Bands	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	Radiated Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	Peak Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §2.1093	Maximum Permissible Exposure (MPE)	Compliant

**Table 1. Executive Summary of EMC Part 15.247 Compliance Testing**



## **II. Equipment Configuration**



## A. Overview

MET Laboratories, Inc. was contracted by HID Global Corporation to perform testing on the R10F, under HID Global Corporation's purchase order number 1110960546.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the HID Global Corporation, R10F.

The results obtained relate only to the item(s) tested.

<b>Model(s) Tested:</b>	R10F		
<b>Model(s) Covered:</b>	R10F		
<b>EUT Specifications:</b>	Primary Power: 12 VDC		
	FCC ID: JQ6-ICLASSR10F		
	Type of Modulations:	GFSK	
	Equipment Code:	DTS	
	Peak RF Output Power:	4.47 dBm	
	EUT Frequency Ranges:	2402 – 2480 MHz	
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.		
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C		
	Relative Humidity: 30-60%		
	Barometric Pressure: 860-1060 mbar		
<b>Evaluated by:</b>	Giuliano Messina		
<b>Report Date(s):</b>	November 7, 2018		

**Table 2. EUT Summary Table**



## B. References

<b>CFR 47, Part 15, Subpart C</b>	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
<b>ANSI C63.4:2014</b>	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>ISO/IEC 17025:2005</b>	General Requirements for the Competence of Testing and Calibration Laboratories
<b>ANSI C63.10:2013</b>	American National Standard for Testing Unlicensed Wireless Devices
<b>KDB 558074 v05</b>	Guidance For Performing Compliance Measurements On Digital Transmission Systems (DTS) Operating Under Section 15.247

**Table 3. References**

## C. Test Site

All testing was performed at MET Laboratories, Inc., 13501 McCallen Pass, Austin, TX 78753. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

## D. Measurement Uncertainty


Test Method	Typical Expanded Uncertainty	K	Confidence Level
<b>RF Frequencies</b>	±4.52 Hz	2	95%
<b>RF Power Conducted Emissions</b>	±2.97 dB	2	95%
<b>RF Power Radiated Emissions</b>	±3.54 dB	2	95%

**Table 4. Uncertainty Calculations Summary**



## E. Description of Test Sample

The HID Global Corporation R10F, Equipment Under Test (EUT), is a wall-mountable HF card reader that can connect via Bluetooth.



**Figure 1. Block Diagram of Test Configuration**

## F. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Slot #	Name / Description	Model Number	Part Number (White / Light Almond)	Serial Number	Rev. #
NA	NA	R10F	R10F	NA	NA	NA

**Table 5. Equipment Configuration**

## G. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number	*Customer Supplied Calibration Data
NA	12VDC Source	Duracell	DURA12-7F2	NA
NA	Contact Card	HID	NA	NA

The 'Customer Supplied Calibration Data' column will be marked as either not applicable, not available, or will contain the calibration date supplied by the customer.

**Table 6. Support Equipment**



## **H. Mode of Operation**

The EUT was turned on and configured to transmit consistently, with a computer interface used to control Bluetooth parameters.

## **I. Method of Monitoring EUT Operation**

The transmitter was monitored through a spectrum analyzer throughout testing.

## **J. Modifications**

### **a) Modifications to EUT**

No modifications were made to the EUT.

### **b) Modifications to Test Standard**

No modifications were made to the test standard.

## **K. Disposition of EUT**

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to HID Global Corporation upon completion of testing.



### **III. Electromagnetic Compatibility Criteria for Intentional Radiators**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.203      Antenna Requirement

**Test Requirement:**      **§ 15.203:** An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Results:**      The EUT as tested is compliant the criteria of §15.203. The EUT contains an integrated antenna.

**Test Engineer(s):**      Giuliano Messina

**Test Date(s):**      June 21, 2018



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.207(a) Conducted Emissions Limits

**Test Requirement(s):** § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50  $\Omega$  line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15- 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

**Table 7. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)**

**Test Procedure:** The EUT was placed on a 0.8 m-high wooden table above a ground plane. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50  $\Omega$ /50  $\mu$ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.10-2013*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50  $\Omega$ /50  $\mu$ H LISN as the input transducer to an EMI receiver. For the purpose of this testing, the transmitter was turned on.

**Test Results:** The EUT was compliant with this requirement. Measured emissions were within applicable limits.

**Test Engineer(s):** Giuliano Messina

**Test Date(s):** June 21, 2018




## 15.207(a) Conducted Emissions Test Results

Line	Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
DC+	0.242	31	62.038	-31.038	Pass	19.4	52.038	-32.638	Pass
DC+	1.442	29.3	56	-26.7	Pass	26.2	46	-19.8	Pass
DC+	12.81	22.9	60	-37.1	Pass	5.4	50	-44.6	Pass
DC+	13.214	38.9	60	-21.1	Pass	8.6	50	-41.4	Pass
DC+	14.346	20.8	60	-39.2	Pass	5.6	50	-44.4	Pass
DC+	27.122	32.4	60	-27.6	Pass	18.5	50	-31.5	Pass
DC-	0.242	58.9	62.038	-3.138	Pass	46.4	52.038	-5.638	Pass
*DC-	1.438	44.1	56	-11.9	Pass	44.1	46	-1.9	Pass
DC-	0.178	40.5	64.582	-24.082	Pass	39.1	54.582	-15.482	Pass
DC-	2.878	34.6	56	-21.4	Pass	33.9	46	-12.1	Pass
DC-	13.23	49.4	60	-10.6	Pass	15.5	50	-34.5	Pass
DC-	14.33	34	60	-26	Pass	8.9	50	-41.1	Pass


**Table 8. Conducted Emissions, 15.207(a), Test Results**

Note 1: \* - At this frequency, the measured electric-field strength exhibits a margin of compliance that is less than 3 dB below the specification limit. We recommend that every emission measured, have at least a 3 dB margin to allow for deviations in the emission characteristics that may occur during the production process.





Plot 1. Conducted Emissions, 15.207(a), DC+



Plot 2. Conducted Emissions, 15.207(a), DC-



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(a)(2) 6 dB Bandwidth

**Test Requirements:** § 15.247(a)(2): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.


**Test Procedure:** The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

**Test Results** The EUT was compliant with § 15.247 (a)(2).

The 6 dB Bandwidth was determined from the plots on the following pages.

**Test Engineer(s):** Giuliano Messina


**Test Date(s):** June 22, 2018




**Figure 2. Block Diagram, Occupied Bandwidth Test Setup**




## Occupied Bandwidth Test Results



**Plot 3. 6 dB Occupied Bandwidth, 2402**



**Plot 4. 6 dB Occupied Bandwidth, 2442**



**Plot 5. 6 dB Occupied Bandwidth, 2480**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) Peak Power Output

**Test Requirements:** §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
2400–2483.5	1.000

**Table 9. Output Power Requirements from §15.247(b)**

**Test Procedure:** The EUT was measured at the low, mid and high channels of each band at the maximum power level. Measurements were performed on a conducted setup, with the output of the EUT antenna connected directly to a spectrum analyzer.


**Test Results:** The EUT was compliant with the Peak Power Output limits of §15.247(b).

**Test Engineer(s):** Giuliano Messina


**Test Date(s):** June 22, 2018




## Peak Power Output Test Results



**Plot 6. Peak Power Output, 2402**



**Plot 7. Peak Power Output, 2442**



**Plot 8. Peak Power Output, 2480**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.209 Radiated Spurious Emissions Requirements and Band Edge

**Test Requirements:** §15.247(d); §15.205: Emissions outside the frequency band.

**§15.205(a):** Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
<sup>1</sup> 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	( <sup>2</sup> )

**Table 10. Restricted Bands of Operation**

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

<sup>2</sup> Above 38.6



**Test Requirement(s):** § 15.209 (a): Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 11.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dBμV) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

**Table 11. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)**

**Test Procedures:** The transmitter was turned on. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.


**Test Results:** The EUT was compliant with the Radiated Spurious Emission limits of § 15.247(d) and § 15.209. Measured emissions were within applicable limits.

**Test Engineer(s):** Giuliano Messina


**Test Date(s):** June 21, 2018




## Radiated Spurious Emissions, Test Results



**Plot 9. Radiated Emissions, 30 MHz – 1 GHz, Horizontal**




**Plot 10. Radiated Emissions, 30 MHz – 1 GHz, Vertical**




**Plot 11. Radiated Emissions, 1 GHz – 7 GHz, Horizontal, Average**






**Plot 12. Radiated Emissions, 1 GHz – 7 GHz, Horizontal, Peak**




**Plot 13. Radiated Emissions, 1 GHz – 7 GHz, Vertical, Average**




**Plot 14. Radiated Emissions, 1 GHz – 7 GHz, Vertical, Peak**






**Plot 15. Radiated Emissions, 7 GHz – 18 GHz, Horizontal, Average**




**Plot 16. Radiated Emissions, 7 GHz – 18 GHz, Horizontal, Peak**



**Plot 17. Radiated Emissions, 7 GHz – 18 GHz, Vertical, Average**





**Plot 18. Radiated Emissions, 7 GHz – 18 GHz, Vertical, Peak**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247 Operation Within the Bands


**Test Requirements:** §15.247: Operation within the Bands (Outlined in the previous section)

**Test Procedures:** The transmitter was turned on. Measurements were performed of the low and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line.


**Test Results:** The EUT was compliant with the requirements of this section.

**Test Engineer:** Giuliano Messina

**Test Date:** June 25,2018




**Plot 19. Radiated Restricted Bandedge, 2402, Horizontal, Average**




**Plot 20. Radiated Restricted Bandedge, 2402, Horizontal, Peak**






**Plot 21. Radiated Restricted Bandedge, 2402, Vertical, Average**




**Plot 22. Radiated Restricted Bandedge, 2402, Vertical, Peak**




**Plot 23. Radiated Restricted Bandedge, 2480, Horizontal, Average**






**Plot 24. Radiated Restricted Bandedge, 2480, Horizontal, Peak**



**Plot 25. Radiated Restricted Bandedge, 2480, Vertical, Average**



**Plot 26. Radiated Restricted Bandedge, 2480, Vertical, Peak**




## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Spurious Emissions in Non-restricted Bands


<b>Test Requirement:</b>	<b>15.247(d)</b> In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
<b>Test Procedure:</b>	For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10 <sup>th</sup> harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
<b>Test Results:</b>	The EUT was compliant with the Spurious Emission limits of <b>§15.247(d)</b> . Measured emissions were within applicable limits.
<b>Test Engineer(s):</b>	Giuliano Messina
<b>Test Date(s):</b>	June 22, 2018




## Spurious Emissions in Non-restricted Bands, Test Results



Plot 27. Conducted Spurious Emissions, 2402, 1 – 26.5 GHz




Plot 28. Conducted Spurious Emissions, 2402, 30 MHz – 1 GHz




Plot 29. Conducted Spurious Emissions, 2442, 1 – 26.5 GHz






**Plot 30. Conducted Spurious Emissions, 2442, 30 MHz – 1 GHz**




**Plot 31. Conducted Spurious Emissions, 2480, 1 – 26.5 GHz**




**Plot 32. Conducted Spurious Emissions, 2480, 30 MHz – 1 GHz**





Plot 33. Conducted Spurious Emissions, 2402, Bandedge



Plot 34. Conducted Spurious Emissions, 2480, Bandedge



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(e) Peak Power Spectral Density

**Test Requirements:** §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

**Test Procedure:** The transmitter was connected directly to a Spectrum Analyzer. The power level was set to the maximum level. The RBW was set to 30 kHz and a VBW set to 100 kHz. The spectrum analyzer was set to an auto sweep time and a peak detector was used. Measurements were carried out at the low, mid and high channels.


**Test Results:** The EUT was compliant with the peak power spectral density limits of § 15.247 (e).  
The peak power spectral density was determined from plots on the following page(s).

**Test Engineer:** Giuliano Messina


**Test Date:** June 22, 2018




## Peak Power Spectral Density



**Plot 35. Power Density, 2402**



**Plot 36. Power Density, 2442**



**Plot 37. Power Density, 2480**



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 2.1093 Maximum Permissible Mobile Exposure

#### RF Exposure Requirements:

(2) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

#### Test Results:

#### Bluetooth (2.4 GHz)

Per KDB 447498, Section 4.3.1 (a), applicable for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm:

$$\frac{\text{max. power of channel, including tuneup tolerance [mW]}}{\text{min. test separation distance [mm]}} * \sqrt{f \text{ [GHz]}} \leq 3.0 \text{ (1 - g SAR Limit)}$$

$$\frac{2.899 \text{ mW}}{5 \text{ mm}} * \sqrt{2.480} = 0.913 \leq 3.0 \text{ (1 - g SAR)}$$

FCC										
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Total Pwr. (mW)	Calculated SAR Threshold	1.0-g SAR Limit	Margin	Separation Distance Declared (mm)	Result
2480	4.47	2.799	-10	0.1	2.899	0.913	3.0	2.08693	5	Pass



## IV. Test Equipment



## Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

MET Asset #	Nomenclature	Manufacturer	Model	Last Cal Date	Cal Due Date
1A1184	Spectrum Analyzer	Agilent	E4407B	4/20/2018	4/20/2019
1A1083	EMI Test Receiver	Rohde & Schwarz	ESU40	9/12/2017	10/12/2018
1A1106	10m Chamber (FCC)	ETS	Semi-Anechoic	See Note	
1A1147	Bilog Antenna (30MHz to 1GHz)	Sunol Sciences Corp	JB3	3/9/2017	10/9/2018
1A1047	Horn Antenna	ETS	3117	2/23/2017	8/23/2018
1A1099	Generator	COM-Power Corp	CGO-51000	See Note	
1A1088	Pre-Amp	Rohde & Schwarz	TS-PR1	See Note	
1A1044	Generator	COM-Power Corp	CG-520	See Note	
1A1073	Multi Device Controller	ETS EMCO	2090	See Note	
1A1074	System Controller	Panasonic	WV-CU101	See Note	
1A1080	Multi Device Controller	ETS EMCO	2090	See Note	

**Table 12. Test Equipment List**

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.



## **V. Certification & User's Manual Information**



## Certification & User's Manual Information

### A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

#### **§ 2.801 Radio-frequency device defined.**

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

#### **§ 2.803 Marketing of radio frequency devices prior to equipment authorization.**

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
  - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
  - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.



- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing*;
  - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
  - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.



## Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

### § 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.<sup>1</sup> *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

### § 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

---

<sup>1</sup> In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.



## Certification & User's Manual Information

### § 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
  - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
    - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
    - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
  - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.



## Certification & User's Manual Information

### 1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

#### § 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

#### § 15.21 Information to user.

The user's manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



## Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

### § 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



# End of Report