



FCC CO-LOCATION RADIO TEST REPORT

FCC ID : A4RG013A
Equipment : Phone
Model Name : G013A
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was completed on Jun. 14, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency and Channel.....	7
2.2 Test Mode	7
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup.....	8
3 Test Result.....	9
3.1 Unwanted Emissions Measurement.....	9
3.2 Antenna Requirements	13
4 List of Measuring Equipment.....	14
5 Uncertainty of Evaluation.....	15
Appendix A. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR820225-02G	01	Initial issue of report	Jun. 29, 2018



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.407(b)	Unwanted Emissions	Pass	Under limit 3.87 dB at 30.270 MHz
3.2	15.203 15.407(a)	Antenna Requirement	Pass	-

Reviewed by: Joseph Lin

Report Producer: Wii Chang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	G013A
FCC ID	A4RG013A
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC/ GNSS/WPC WLAN 11b/g/n HT20/VHT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

EUT Information List	
No.	S/N
#1	84PX006ND

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency and Channel

2400-2483.5 MHz 802.11b		5150-5250 MHz Band 1 (U-NII-1)	
Channel	Freq. (MHz)	Channel	Freq. (MHz)
06	2437	44	5220

5250-5350 MHz Band 2 (U-NII-2A)		5470-5725 MHz Band 3 (U-NII-2C)	
Channel	Freq. (MHz)	Channel	Freq. (MHz)
60	5300	116	5580

5750-5825 MHz Band 4 (U-NII-3)	
Channel	Freq. (MHz)
157	5785

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


<Co-Location>

Modulation	Data Rate
802.11b + 802.11 a	1 Mbps + 6Mbps

Remark: For Radiated Test Cases, the tests were performed with Adapter 1.

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



2.4 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Unwanted Emissions Measurement

3.1.1 Limit of Unwanted Emissions

(1) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(2) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.


3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.


6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.1.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.1.6 Duty Cycle

Please refer to Appendix B.

3.1.7 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix A.



3.2 Antenna Requirements

3.2.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.2.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Jun. 6, 2018 ~ Jun. 14, 2018	Jul. 17, 2018	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Jan. 16, 2018	Jun. 06, 2018 ~ Jun. 14, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6- 06	35414&AT- N0602	30MHz~1GHz	Oct. 14, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 6	1GHz ~ 18GHz	Oct. 16, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Oct. 15, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Nov. 22, 2018	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 10, 2016	Jun. 06, 2018 ~ Jun. 14, 2018	Nov. 09, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Oct. 18, 2018	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 06, 2018 ~ Jun. 14, 2018	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1~4m	N/A	Jun. 06, 2018 ~ Jun. 14, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jun. 06, 2018 ~ Jun. 14, 2018	N/A	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 27, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55- 303K	17100018 00054002	1GHz~18GHz	Apr. 17, 2018	Jun. 06, 2018 ~ Jun. 14, 2018	Apr. 16, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4	9K-30M	Mar. 20, 2018	Jun. 06, 2018 ~ Jun. 14, 2018	Mar. 19, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4	30M-18G	Mar. 15, 2018	Jun. 06, 2018 ~ Jun. 14, 2018	Mar. 14, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2589/2	30M-18G	Mar. 15, 2018	Jun. 06, 2018 ~ Jun. 14, 2018	Mar. 14, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX8-587 2.5-6750-18 000-40ST	SN3	6.75GHz High Pass	Sep. 18, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000- 1530-8000-4 0SS	SN11	1G Low Pass	Sep. 18, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-00104 2	N/A	N/A	Jun. 06, 2018 ~ Jun. 14, 2018	N/A	Radiation (03CH11-HY)
Hygrometer	TECEPIL	DTN-303B	TP140325	N/A	Oct. 12, 2017	Jun. 06, 2018 ~ Jun. 14, 2018	Oct. 11, 2018	Radiation (03CH11-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Appendix A. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, Ken Wu and Chuan Zhu	Temperature :	22~25°C
		Relative Humidity :	50~55%

802.11b + 802.11a

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch44 Ant. 2

Horizontal

Vertical

Peak

Site : 03CH11-HY
Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL
Detector : Peak
Project : R00Z25-02
Setting : 18.5/18.5
: 11b_Tx_Ch06+11a_Tx_Ch44



Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark
MHz	dBuV/m	Limit	Line	Level Factor	Loss Factor	cm	deg
1 4874.00	57.16	-16.84	74.00	49.84	31.38	9.01	233 Peak
2 4874.00	48.61	-5.39	54.00	41.29	31.38	9.01	233 Average
3 7311.00	45.81	-28.19	74.00	53.55	36.28	11.31	0 Peak
4 10440.00	43.55	-30.45	74.00	49.10	39.61	14.68	0 Peak
5 15660.00	42.92	-31.08	74.00	44.72	37.67	18.06	0 Peak

Site : 03CH11-HY
Condition : PEAK_74 3m HORN 9120D-HF VERTICAL
Detector : Peak
Project : R00Z25-02
Setting : 18.5/18.5
: 11b_Tx_Ch06+11a_Tx_Ch44

Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark
MHz	dBuV/m	Limit	Line	Level Factor	Loss Factor	cm	deg
1 4874.00	51.12	-22.88	74.00	43.80	31.38	9.01	0 Peak
2 4874.00	40.89	-33.11	54.00	33.57	31.38	9.01	0 Average
3 7311.00	45.26	-28.74	74.00	53.00	36.28	11.31	0 Peak
4 10440.00	43.74	-30.26	74.00	49.29	39.61	14.68	0 Peak
5 15660.00	43.92	-30.08	74.00	45.72	37.67	18.06	0 Peak





802.11b + 802.11a_LF

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch44 Ant. 2_LF																																																																																																																																																																																																					
	Horizontal					Vertical																																																																																																																																																																																															
QP / Peak																																																																																																																																																																																																					
	Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>119.91</td><td>24.51</td><td>-18.99</td><td>43.50</td><td>38.21</td><td>17.33</td><td>1.39</td><td>32.46</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>170.13</td><td>28.46</td><td>-15.04</td><td>43.50</td><td>43.80</td><td>15.37</td><td>1.61</td><td>32.42</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>213.06</td><td>25.59</td><td>-17.91</td><td>43.50</td><td>41.18</td><td>15.02</td><td>1.72</td><td>32.39</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>302.10</td><td>26.70</td><td>-19.30</td><td>46.00</td><td>37.65</td><td>19.10</td><td>2.22</td><td>32.37</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>635.30</td><td>27.13</td><td>-18.87</td><td>46.00</td><td>30.18</td><td>26.16</td><td>3.15</td><td>32.46</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>941.90</td><td>33.39</td><td>-12.61</td><td>46.00</td><td>30.52</td><td>30.15</td><td>3.82</td><td>31.27</td><td>100</td><td>0</td><td>Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	119.91	24.51	-18.99	43.50	38.21	17.33	1.39	32.46	---	---	Peak	2	170.13	28.46	-15.04	43.50	43.80	15.37	1.61	32.42	---	---	Peak	3	213.06	25.59	-17.91	43.50	41.18	15.02	1.72	32.39	---	---	Peak	4	302.10	26.70	-19.30	46.00	37.65	19.10	2.22	32.37	---	---	Peak	5	635.30	27.13	-18.87	46.00	30.18	26.16	3.15	32.46	---	---	Peak	6	941.90	33.39	-12.61	46.00	30.52	30.15	3.82	31.27	100	0	Peak	Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC VERTICAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.54</td><td>33.20</td><td>-6.80</td><td>40.00</td><td>41.16</td><td>23.70</td><td>0.82</td><td>32.50</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>49.17</td><td>34.23</td><td>-5.77</td><td>40.00</td><td>51.21</td><td>14.48</td><td>1.02</td><td>32.49</td><td>100</td><td>145</td><td>Peak</td></tr><tr><td>3</td><td>63.48</td><td>32.32</td><td>-7.68</td><td>40.00</td><td>52.09</td><td>11.69</td><td>1.02</td><td>32.49</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>300.00</td><td>22.50</td><td>-23.50</td><td>46.00</td><td>33.47</td><td>19.08</td><td>2.22</td><td>32.37</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>563.20</td><td>26.45</td><td>-19.55</td><td>46.00</td><td>29.81</td><td>25.95</td><td>3.03</td><td>32.43</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>940.50</td><td>34.28</td><td>-11.72</td><td>46.00</td><td>31.48</td><td>30.10</td><td>3.82</td><td>31.29</td><td>---</td><td>---</td><td>Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	30.54	33.20	-6.80	40.00	41.16	23.70	0.82	32.50	---	---	Peak	2	49.17	34.23	-5.77	40.00	51.21	14.48	1.02	32.49	100	145	Peak	3	63.48	32.32	-7.68	40.00	52.09	11.69	1.02	32.49	---	---	Peak	4	300.00	22.50	-23.50	46.00	33.47	19.08	2.22	32.37	---	---	Peak	5	563.20	26.45	-19.55	46.00	29.81	25.95	3.03	32.43	---	---	Peak	6	940.50	34.28	-11.72	46.00	31.48	30.10	3.82	31.29	---	---
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																											
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																											
1	119.91	24.51	-18.99	43.50	38.21	17.33	1.39	32.46	---	---	Peak																																																																																																																																																																																										
2	170.13	28.46	-15.04	43.50	43.80	15.37	1.61	32.42	---	---	Peak																																																																																																																																																																																										
3	213.06	25.59	-17.91	43.50	41.18	15.02	1.72	32.39	---	---	Peak																																																																																																																																																																																										
4	302.10	26.70	-19.30	46.00	37.65	19.10	2.22	32.37	---	---	Peak																																																																																																																																																																																										
5	635.30	27.13	-18.87	46.00	30.18	26.16	3.15	32.46	---	---	Peak																																																																																																																																																																																										
6	941.90	33.39	-12.61	46.00	30.52	30.15	3.82	31.27	100	0	Peak																																																																																																																																																																																										
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																											
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																											
1	30.54	33.20	-6.80	40.00	41.16	23.70	0.82	32.50	---	---	Peak																																																																																																																																																																																										
2	49.17	34.23	-5.77	40.00	51.21	14.48	1.02	32.49	100	145	Peak																																																																																																																																																																																										
3	63.48	32.32	-7.68	40.00	52.09	11.69	1.02	32.49	---	---	Peak																																																																																																																																																																																										
4	300.00	22.50	-23.50	46.00	33.47	19.08	2.22	32.37	---	---	Peak																																																																																																																																																																																										
5	563.20	26.45	-19.55	46.00	29.81	25.95	3.03	32.43	---	---	Peak																																																																																																																																																																																										
6	940.50	34.28	-11.72	46.00	31.48	30.10	3.82	31.29	---	---	Peak																																																																																																																																																																																										





802.11b + 802.11a

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch60 Ant. 2																																																																																																																																																																				
	Horizontal					Vertical																																																																																																																																																														
Peak																																																																																																																																																																				
	Site : 03CH11-HV					Site : 03CH11-HV																																																																																																																																																														
	Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL					Condition : PEAK_74 3m HORN 91200-HF VERTICAL																																																																																																																																																														
	Detector : Peak					Detector : Peak																																																																																																																																																														
	Project : 820225-02					Project : 820225-02																																																																																																																																																														
	Setting : 18.5/18.5					Setting : 18.5/18.5																																																																																																																																																														
	: 11b_Tx_Ch06+11a_Tx_Ch60					: 11b_Tx_Ch06+11a_Tx_Ch60																																																																																																																																																														
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>56.39</td><td>-17.61</td><td>74.00</td><td>49.87</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>233 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>48.52</td><td>-5.48</td><td>54.00</td><td>41.20</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>233 Average</td></tr><tr><td>3</td><td>7311.00</td><td>45.75</td><td>-28.25</td><td>74.00</td><td>53.49</td><td>36.28</td><td>11.31</td><td>56.23</td><td>100</td><td>0 Peak</td></tr><tr><td>4</td><td>10600.00</td><td>42.54</td><td>-31.46</td><td>74.00</td><td>48.28</td><td>39.78</td><td>14.89</td><td>68.55</td><td>100</td><td>0 Peak</td></tr><tr><td>5</td><td>15900.00</td><td>42.48</td><td>-31.52</td><td>74.00</td><td>44.58</td><td>36.99</td><td>18.25</td><td>57.54</td><td>100</td><td>0 Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	4874.00	56.39	-17.61	74.00	49.87	31.38	9.01	33.07	100	233 Peak	2	4874.00	48.52	-5.48	54.00	41.20	31.38	9.01	33.07	100	233 Average	3	7311.00	45.75	-28.25	74.00	53.49	36.28	11.31	56.23	100	0 Peak	4	10600.00	42.54	-31.46	74.00	48.28	39.78	14.89	68.55	100	0 Peak	5	15900.00	42.48	-31.52	74.00	44.58	36.99	18.25	57.54	100	0 Peak	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>51.78</td><td>-22.22</td><td>74.00</td><td>44.46</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>48.95</td><td>-13.05</td><td>54.00</td><td>33.63</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Average</td></tr><tr><td>3</td><td>7311.00</td><td>46.68</td><td>-27.32</td><td>74.00</td><td>54.42</td><td>36.28</td><td>11.31</td><td>56.23</td><td>100</td><td>0 Peak</td></tr><tr><td>4</td><td>10600.00</td><td>42.62</td><td>-31.38</td><td>74.00</td><td>48.28</td><td>39.78</td><td>14.89</td><td>68.55</td><td>100</td><td>0 Peak</td></tr><tr><td>5</td><td>15900.00</td><td>42.89</td><td>-31.11</td><td>74.00</td><td>44.11</td><td>36.99</td><td>18.25</td><td>57.54</td><td>100</td><td>0 Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	4874.00	51.78	-22.22	74.00	44.46	31.38	9.01	33.07	100	0 Peak	2	4874.00	48.95	-13.05	54.00	33.63	31.38	9.01	33.07	100	0 Average	3	7311.00	46.68	-27.32	74.00	54.42	36.28	11.31	56.23	100	0 Peak	4	10600.00	42.62	-31.38	74.00	48.28	39.78	14.89	68.55	100	0 Peak	5	15900.00	42.89	-31.11	74.00	44.11	36.99	18.25	57.54	100	0 Peak
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																									
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																										
1	4874.00	56.39	-17.61	74.00	49.87	31.38	9.01	33.07	100	233 Peak																																																																																																																																																										
2	4874.00	48.52	-5.48	54.00	41.20	31.38	9.01	33.07	100	233 Average																																																																																																																																																										
3	7311.00	45.75	-28.25	74.00	53.49	36.28	11.31	56.23	100	0 Peak																																																																																																																																																										
4	10600.00	42.54	-31.46	74.00	48.28	39.78	14.89	68.55	100	0 Peak																																																																																																																																																										
5	15900.00	42.48	-31.52	74.00	44.58	36.99	18.25	57.54	100	0 Peak																																																																																																																																																										
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																										
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																											
1	4874.00	51.78	-22.22	74.00	44.46	31.38	9.01	33.07	100	0 Peak																																																																																																																																																										
2	4874.00	48.95	-13.05	54.00	33.63	31.38	9.01	33.07	100	0 Average																																																																																																																																																										
3	7311.00	46.68	-27.32	74.00	54.42	36.28	11.31	56.23	100	0 Peak																																																																																																																																																										
4	10600.00	42.62	-31.38	74.00	48.28	39.78	14.89	68.55	100	0 Peak																																																																																																																																																										
5	15900.00	42.89	-31.11	74.00	44.11	36.99	18.25	57.54	100	0 Peak																																																																																																																																																										



802.11b + 802.11a _LF

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch60 Ant. 2_LF																																																																																																																																																																																									
	Horizontal					Vertical																																																																																																																																																																																			
QP / Peak																																																																																																																																																																																									
	Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>119.91</td><td>24.29</td><td>-19.21</td><td>43.50</td><td>37.99</td><td>17.33</td><td>1.39</td><td>32.46</td><td>---</td><td>--- Peak</td></tr><tr><td>2</td><td>161.76</td><td>27.13</td><td>-16.37</td><td>43.50</td><td>41.76</td><td>16.08</td><td>1.61</td><td>32.42</td><td>---</td><td>--- Peak</td></tr><tr><td>3</td><td>210.63</td><td>24.59</td><td>-18.51</td><td>43.50</td><td>40.61</td><td>14.99</td><td>1.72</td><td>32.39</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>304.20</td><td>26.83</td><td>-19.97</td><td>46.00</td><td>36.88</td><td>19.12</td><td>2.31</td><td>32.37</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>668.90</td><td>27.55</td><td>-18.45</td><td>46.00</td><td>30.37</td><td>26.26</td><td>3.27</td><td>32.47</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>947.50</td><td>33.17</td><td>-12.83</td><td>46.00</td><td>29.95</td><td>30.46</td><td>3.82</td><td>31.23</td><td>100</td><td>0 Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	119.91	24.29	-19.21	43.50	37.99	17.33	1.39	32.46	---	--- Peak	2	161.76	27.13	-16.37	43.50	41.76	16.08	1.61	32.42	---	--- Peak	3	210.63	24.59	-18.51	43.50	40.61	14.99	1.72	32.39	---	--- Peak	4	304.20	26.83	-19.97	46.00	36.88	19.12	2.31	32.37	---	--- Peak	5	668.90	27.55	-18.45	46.00	30.37	26.26	3.27	32.47	---	--- Peak	6	947.50	33.17	-12.83	46.00	29.95	30.46	3.82	31.23	100	0 Peak	Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC VERTICAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.27</td><td>34.11</td><td>-5.89</td><td>40.00</td><td>41.59</td><td>24.17</td><td>0.82</td><td>32.50</td><td>---</td><td>--- Peak</td></tr><tr><td>2</td><td>47.55</td><td>34.87</td><td>-5.13</td><td>40.00</td><td>51.03</td><td>15.31</td><td>1.02</td><td>32.49</td><td>100</td><td>151 Peak</td></tr><tr><td>3</td><td>62.94</td><td>32.42</td><td>-7.58</td><td>40.00</td><td>52.24</td><td>11.64</td><td>1.02</td><td>32.49</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>302.10</td><td>20.71</td><td>-25.29</td><td>46.00</td><td>31.66</td><td>19.10</td><td>2.22</td><td>32.37</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>658.40</td><td>28.11</td><td>-17.89</td><td>46.00</td><td>31.03</td><td>26.24</td><td>3.20</td><td>32.47</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>959.40</td><td>33.04</td><td>-12.96</td><td>46.00</td><td>29.01</td><td>31.07</td><td>3.90</td><td>31.12</td><td>---</td><td>--- Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	30.27	34.11	-5.89	40.00	41.59	24.17	0.82	32.50	---	--- Peak	2	47.55	34.87	-5.13	40.00	51.03	15.31	1.02	32.49	100	151 Peak	3	62.94	32.42	-7.58	40.00	52.24	11.64	1.02	32.49	---	--- Peak	4	302.10	20.71	-25.29	46.00	31.66	19.10	2.22	32.37	---	--- Peak	5	658.40	28.11	-17.89	46.00	31.03	26.24	3.20	32.47	---	--- Peak	6	959.40	33.04	-12.96	46.00	29.01	31.07	3.90	31.12	---
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																															
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																															
1	119.91	24.29	-19.21	43.50	37.99	17.33	1.39	32.46	---	--- Peak																																																																																																																																																																															
2	161.76	27.13	-16.37	43.50	41.76	16.08	1.61	32.42	---	--- Peak																																																																																																																																																																															
3	210.63	24.59	-18.51	43.50	40.61	14.99	1.72	32.39	---	--- Peak																																																																																																																																																																															
4	304.20	26.83	-19.97	46.00	36.88	19.12	2.31	32.37	---	--- Peak																																																																																																																																																																															
5	668.90	27.55	-18.45	46.00	30.37	26.26	3.27	32.47	---	--- Peak																																																																																																																																																																															
6	947.50	33.17	-12.83	46.00	29.95	30.46	3.82	31.23	100	0 Peak																																																																																																																																																																															
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																															
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																															
1	30.27	34.11	-5.89	40.00	41.59	24.17	0.82	32.50	---	--- Peak																																																																																																																																																																															
2	47.55	34.87	-5.13	40.00	51.03	15.31	1.02	32.49	100	151 Peak																																																																																																																																																																															
3	62.94	32.42	-7.58	40.00	52.24	11.64	1.02	32.49	---	--- Peak																																																																																																																																																																															
4	302.10	20.71	-25.29	46.00	31.66	19.10	2.22	32.37	---	--- Peak																																																																																																																																																																															
5	658.40	28.11	-17.89	46.00	31.03	26.24	3.20	32.47	---	--- Peak																																																																																																																																																																															
6	959.40	33.04	-12.96	46.00	29.01	31.07	3.90	31.12	---	--- Peak																																																																																																																																																																															

802.11b + 802.11a

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch116 Ant. 2

Horizontal

Date: 2018-06-14

Level (dBuV/m)

Frequency (MHz)

Site : 03CH11-HY
Condition : PEAK(UNB) 3m HORN 9120D-HF HORIZONTAL
Detector : Peak
Project : 820225-02
Setting : 18.5/18.5

: 11b_Tx_Ch06+11a_Tx_Ch116

Freq	Level	Limit	Over	ReadAntenna	Cable	Preamplifier	A/Pos	T/Pos	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1 4874.00	56.58	-17.42	74.00	49.26	31.38	9.01	33.07	100	233 Peak
2 4874.00	48.39	-5.61	54.00	41.07	31.38	9.01	33.07	100	233 Average
3 7311.00	46.62	-27.38	74.00	54.36	36.28	11.31	56.23	100	0 Peak
4 11160.00	48.39	-25.61	74.00	54.36	40.07	15.20	61.53	100	0 Peak
5 16740.00	44.30	-23.90	68.20	42.79	39.08	18.93	56.82	100	0 Peak

Vertical

Date: 2018-06-14

Level (dBuV/m)

Frequency (MHz)

Site : 03CH11-VY
Condition : PEAK(UNB) 3m HORN 9120D-HF VERTICAL
Detector : Peak
Project : 820225-02
Setting : 18.5/18.5

: 11b_Tx_Ch06+11a_Tx_Ch116

Freq	Level	Limit	Over	ReadAntenna	Cable	Preamplifier	A/Pos	T/Pos	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1 4874.00	50.66	-23.34	74.00	43.34	31.38	9.01	33.07	100	0 Peak
2 4874.00	40.99	-33.01	54.00	33.67	31.38	9.01	33.07	100	0 Average
3 7311.00	47.53	-26.47	74.00	55.27	36.28	11.31	56.23	100	0 Peak
4 11160.00	45.73	-28.27	74.00	51.70	40.07	15.20	61.53	100	0 Peak
5 16740.00	46.93	-21.27	68.20	45.42	39.08	18.93	56.82	100	0 Peak





802.11b + 802.11a _LF

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch116 Ant. 2_LF																																																																																																																																																																																																				
	Horizontal											Vertical																																																																																																																																																																																								
QP / Peak	Level (dBuV/m) Date: 2018-06-14 Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>119.91</td><td>23.87</td><td>-19.63</td><td>43.50</td><td>37.57</td><td>17.33</td><td>1.39</td><td>32.46</td><td>---</td><td>--- Peak</td></tr><tr><td>2</td><td>161.49</td><td>26.92</td><td>-16.58</td><td>43.50</td><td>41.56</td><td>16.08</td><td>1.61</td><td>32.43</td><td>---</td><td>--- Peak</td></tr><tr><td>3</td><td>212.52</td><td>24.17</td><td>-19.33</td><td>43.50</td><td>39.77</td><td>15.01</td><td>1.72</td><td>32.39</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>302.10</td><td>26.14</td><td>-19.86</td><td>46.00</td><td>37.09</td><td>19.10</td><td>2.22</td><td>32.37</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>654.90</td><td>27.82</td><td>-18.18</td><td>46.00</td><td>30.72</td><td>26.26</td><td>3.20</td><td>32.47</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>955.90</td><td>32.87</td><td>-13.13</td><td>46.00</td><td>29.02</td><td>30.92</td><td>3.90</td><td>31.14</td><td>100</td><td>0 Peak</td></tr></table>											Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	119.91	23.87	-19.63	43.50	37.57	17.33	1.39	32.46	---	--- Peak	2	161.49	26.92	-16.58	43.50	41.56	16.08	1.61	32.43	---	--- Peak	3	212.52	24.17	-19.33	43.50	39.77	15.01	1.72	32.39	---	--- Peak	4	302.10	26.14	-19.86	46.00	37.09	19.10	2.22	32.37	---	--- Peak	5	654.90	27.82	-18.18	46.00	30.72	26.26	3.20	32.47	---	--- Peak	6	955.90	32.87	-13.13	46.00	29.02	30.92	3.90	31.14	100	0 Peak	Level (dBuV/m) Date: 2018-06-14 Site : 03CH11-HY Condition : QP 3m BI-LO6 6111D-LF_ETC VERTICAL Detector : Peak Project : 820225-02 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.27</td><td>36.13</td><td>-3.87</td><td>40.00</td><td>43.61</td><td>24.17</td><td>0.82</td><td>32.50</td><td>100</td><td>0 Peak</td></tr><tr><td>2</td><td>48.09</td><td>34.86</td><td>-5.14</td><td>40.00</td><td>51.42</td><td>14.90</td><td>1.02</td><td>32.49</td><td>---</td><td>--- Peak</td></tr><tr><td>3</td><td>63.48</td><td>32.21</td><td>-7.79</td><td>40.00</td><td>51.90</td><td>11.69</td><td>1.02</td><td>32.49</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>303.50</td><td>20.63</td><td>-25.37</td><td>46.00</td><td>31.48</td><td>19.11</td><td>2.31</td><td>32.37</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>663.30</td><td>28.38</td><td>-17.62</td><td>46.00</td><td>31.29</td><td>26.24</td><td>3.20</td><td>32.47</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>952.40</td><td>33.63</td><td>-12.37</td><td>46.00</td><td>30.03</td><td>30.71</td><td>3.90</td><td>31.18</td><td>---</td><td>--- Peak</td></tr></table>											Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	30.27	36.13	-3.87	40.00	43.61	24.17	0.82	32.50	100	0 Peak	2	48.09	34.86	-5.14	40.00	51.42	14.90	1.02	32.49	---	--- Peak	3	63.48	32.21	-7.79	40.00	51.90	11.69	1.02	32.49	---	--- Peak	4	303.50	20.63	-25.37	46.00	31.48	19.11	2.31	32.37	---	--- Peak	5	663.30	28.38	-17.62	46.00	31.29	26.24	3.20	32.47	---	--- Peak	6	952.40	33.63	-12.37	46.00	30.03	30.71	3.90	31.18	---	--- Peak
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																									
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																										
1	119.91	23.87	-19.63	43.50	37.57	17.33	1.39	32.46	---	--- Peak																																																																																																																																																																																										
2	161.49	26.92	-16.58	43.50	41.56	16.08	1.61	32.43	---	--- Peak																																																																																																																																																																																										
3	212.52	24.17	-19.33	43.50	39.77	15.01	1.72	32.39	---	--- Peak																																																																																																																																																																																										
4	302.10	26.14	-19.86	46.00	37.09	19.10	2.22	32.37	---	--- Peak																																																																																																																																																																																										
5	654.90	27.82	-18.18	46.00	30.72	26.26	3.20	32.47	---	--- Peak																																																																																																																																																																																										
6	955.90	32.87	-13.13	46.00	29.02	30.92	3.90	31.14	100	0 Peak																																																																																																																																																																																										
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																										
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																										
1	30.27	36.13	-3.87	40.00	43.61	24.17	0.82	32.50	100	0 Peak																																																																																																																																																																																										
2	48.09	34.86	-5.14	40.00	51.42	14.90	1.02	32.49	---	--- Peak																																																																																																																																																																																										
3	63.48	32.21	-7.79	40.00	51.90	11.69	1.02	32.49	---	--- Peak																																																																																																																																																																																										
4	303.50	20.63	-25.37	46.00	31.48	19.11	2.31	32.37	---	--- Peak																																																																																																																																																																																										
5	663.30	28.38	-17.62	46.00	31.29	26.24	3.20	32.47	---	--- Peak																																																																																																																																																																																										
6	952.40	33.63	-12.37	46.00	30.03	30.71	3.90	31.18	---	--- Peak																																																																																																																																																																																										



802.11b + 802.11a

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch157 Ant. 2																																																																																																																																																																			
	Horizontal					Vertical																																																																																																																																																													
Peak																																																																																																																																																																			
	Site : 03CH11-HY Condition : PEAK(UNIT) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 820225-02 Setting : 18.5/18.5 : 11b_Tx_Ch06+11a_Tx_Ch157					Site : 03CH11-HY Condition : PEAK(UNIT) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 820225-02 Setting : 18.5/18.5 : 11b_Tx_Ch06+11a_Tx_Ch157																																																																																																																																																													
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>52.06</td><td>-21.94</td><td>74.00</td><td>44.74</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>41.69</td><td>-12.31</td><td>54.00</td><td>34.37</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Average</td></tr><tr><td>3</td><td>7311.00</td><td>47.45</td><td>-26.55</td><td>74.00</td><td>55.19</td><td>36.28</td><td>11.31</td><td>56.23</td><td>100</td><td>0 Peak</td></tr><tr><td>4</td><td>11570.00</td><td>49.83</td><td>-24.17</td><td>74.00</td><td>55.95</td><td>39.86</td><td>15.49</td><td>61.75</td><td>100</td><td>0 Peak</td></tr><tr><td>5</td><td>17355.00</td><td>46.94</td><td>-21.26</td><td>68.20</td><td>41.83</td><td>40.96</td><td>19.31</td><td>55.53</td><td>100</td><td>0 Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	52.06	-21.94	74.00	44.74	31.38	9.01	33.07	100	0 Peak	2	4874.00	41.69	-12.31	54.00	34.37	31.38	9.01	33.07	100	0 Average	3	7311.00	47.45	-26.55	74.00	55.19	36.28	11.31	56.23	100	0 Peak	4	11570.00	49.83	-24.17	74.00	55.95	39.86	15.49	61.75	100	0 Peak	5	17355.00	46.94	-21.26	68.20	41.83	40.96	19.31	55.53	100	0 Peak	<table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>55.19</td><td>-18.81</td><td>74.00</td><td>47.87</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>46.39</td><td>-7.61</td><td>54.00</td><td>39.07</td><td>31.38</td><td>9.01</td><td>33.07</td><td>100</td><td>0 Average</td></tr><tr><td>3</td><td>7311.00</td><td>47.23</td><td>-26.77</td><td>74.00</td><td>54.97</td><td>36.28</td><td>11.31</td><td>56.23</td><td>100</td><td>0 Peak</td></tr><tr><td>4</td><td>11570.00</td><td>46.28</td><td>-27.80</td><td>74.00</td><td>52.32</td><td>39.86</td><td>15.49</td><td>61.75</td><td>100</td><td>0 Peak</td></tr><tr><td>5</td><td>17355.00</td><td>45.19</td><td>-23.01</td><td>68.20</td><td>40.08</td><td>40.96</td><td>19.31</td><td>55.53</td><td>100</td><td>0 Peak</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	55.19	-18.81	74.00	47.87	31.38	9.01	33.07	100	0 Peak	2	4874.00	46.39	-7.61	54.00	39.07	31.38	9.01	33.07	100	0 Average	3	7311.00	47.23	-26.77	74.00	54.97	36.28	11.31	56.23	100	0 Peak	4	11570.00	46.28	-27.80	74.00	52.32	39.86	15.49	61.75	100	0 Peak	5	17355.00	45.19	-23.01	68.20	40.08	40.96	19.31	55.53	100
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																									
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																									
1	4874.00	52.06	-21.94	74.00	44.74	31.38	9.01	33.07	100	0 Peak																																																																																																																																																									
2	4874.00	41.69	-12.31	54.00	34.37	31.38	9.01	33.07	100	0 Average																																																																																																																																																									
3	7311.00	47.45	-26.55	74.00	55.19	36.28	11.31	56.23	100	0 Peak																																																																																																																																																									
4	11570.00	49.83	-24.17	74.00	55.95	39.86	15.49	61.75	100	0 Peak																																																																																																																																																									
5	17355.00	46.94	-21.26	68.20	41.83	40.96	19.31	55.53	100	0 Peak																																																																																																																																																									
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																									
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																									
1	4874.00	55.19	-18.81	74.00	47.87	31.38	9.01	33.07	100	0 Peak																																																																																																																																																									
2	4874.00	46.39	-7.61	54.00	39.07	31.38	9.01	33.07	100	0 Average																																																																																																																																																									
3	7311.00	47.23	-26.77	74.00	54.97	36.28	11.31	56.23	100	0 Peak																																																																																																																																																									
4	11570.00	46.28	-27.80	74.00	52.32	39.86	15.49	61.75	100	0 Peak																																																																																																																																																									
5	17355.00	45.19	-23.01	68.20	40.08	40.96	19.31	55.53	100	0 Peak																																																																																																																																																									

802.11b + 802.11a_LF

11b_Tx_Ch06 Ant. 1 + 11a_Tx_Ch157 Ant. 2_LF

Horizontal

Level (dBuV/m)

80

74.3

68.6

62.9

57.1

51.4

45.7

40.0

34.3

28.6

22.9

17.1

11.4

5.7

50

100

200

300

400

500

600

700

800

900

1000

Frequency (MHz)

QP

Site : 03CH11-HY
Condition : QP 3m BI-LOG 6111D-LF_ETC HORIZONTAL
Detector : Peak
Project : 820225-02

	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	dB	cm	deg	
1	119.91	24.13	-19.37	43.50	37.83	17.33	1.39	32.46	---	---	Peak
2	162.83	27.21	-16.29	43.50	41.84	16.08	1.61	32.42	---	---	Peak
3	212.79	25.69	-17.81	43.50	41.29	15.01	1.72	32.39	---	---	Peak
4	304.90	25.32	-20.68	46.00	36.17	19.12	2.31	32.37	---	---	Peak
5	678.70	28.74	-17.26	46.00	31.53	26.29	3.27	32.47	---	---	Peak
6	944.00	33.89	-12.11	46.00	30.91	30.25	3.82	31.26	100	0	Peak

Vertical

Level (dBuV/m)

80

74.3

68.6

62.9

57.1

51.4

45.7

40.0

34.3

28.6

22.9

17.1

11.4

5.7

50

100

200

300

400

500

600

700

800

900

1000

Frequency (MHz)

QP

Site : 03CH11-HY
Condition : QP 3m BI-LOG 6111D-LF_ETC VERTICAL
Detector : Peak
Project : 820225-02

	Freq	Level	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	dB	cm	deg	
1	30.00	34.80	-5.20	40.00	42.28	24.17	0.82	32.50	100	335	Peak
2	47.55	34.97	-5.03	40.00	51.13	15.31	1.02	32.49	---	---	Peak
3	63.48	32.18	-7.82	40.00	51.95	11.60	1.02	32.49	---	---	Peak
4	304.90	22.81	-23.19	46.00	33.66	19.12	2.31	32.37	---	---	Peak
5	638.10	28.17	-17.83	46.00	31.11	26.27	3.15	32.46	---	---	Peak
6	956.60	33.07	-12.93	46.00	29.22	30.92	3.90	31.14	---	---	Peak




Appendix B. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1	802.11b	100.00	-	-	10Hz	0.00
2	802.11a	98.08	-	-	10Hz	0.08



<Ant. 1>


802.11b



Date: 11.JUN.2018 19:35:27

<Ant. 2>

802.11a



Date: 5.JUN.2018 22:05:10

—THE END—