MPE CALCULATION FCC ID: I28-ZBRZQ3BT I28-RFIDM6EM I28MD-FXLAN11AC

RF Exposure Requirements: RF Radiation Exposure Limits: RF Radiation Exposure Guidelines:

EUT Frequency Band:

Limits for General Population/Uncontrolled Exposure in the band of: Power Density Limit:

S = PG / $4\pi R^2$ or R = \sqrt{PG} / $4\pi S$

47 CFR §1.1307(b) 47 CFR §1.1310 FCC OST/OET Bulletin Number 65

902.75-927.25 MHz; 2402-2480 MHz, 2412-2462 MHz; 5180-5825 MHz

300-1500MHz: Limit = f/1500 mW / cm² 1500-100,000MHz: Limit = 1 mW / cm²

Equation:

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

EUT: Thermal Printer, Model No.: ZC150, ZC300, and ZC350

Prediction distance 20cm

ZQ3BT Radio:

(Bluetooth BDR/EDR): Power = 7.42 dBm, Antenna Gain = 1.69 dBi, Power density = 0.00109 mW/cm²

(Bluetooth LE): Power = 4.72 dBm, Antenna Gain = 1.69 dBi, Power density = 0.00203 mW/cm²

Туре	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Directional Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/ Fail
BLE	2402	4.72	1.69	1.69	±1dB	5.72	20	0.00109	1	Pass
BT-EDR	2402	7.40	1.69	1.69	±1dB	8.40	20	0.00203	1	Pass

M6e-MicroTT:

UHF RFID: Power = 28.11 dBm, Antenna Gain = 3 dBi, Power density = 0.323 mW/cm²

Туре	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Directional Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/ Fail
RFID	902.75	28.11	3	3	±1dB	29.11	20	0.323	0.602	Pass

AC Radio:

(Bluetooth BDR/EDR): Power = 10.27 dBm, Antenna Gain = 3.66 dBi, Power density = 0.00619 mW/cm² (Bluetooth LE): Power = 8.43 dBm, Antenna Gain =3.66 dBi, Power density = 0.00405 mW/cm² (WLAN-2.4GHz): Power=16.77 dBm, Antenna Gain =3.66 dBi, Power density = 0.02766 mW/cm² (WLAN-5GHz): Power=14.76 dBm, Antenna Gain =3.19 dBi, Power density = 0.01562 mW/cm²

Туре	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Directional Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/ Fail
BLE	2402	8.43	3.66	3.66	±1dB	9.43	20	0.00405	1	Pass
BT-BDR	2402	10.27	3.66	3.66	±1dB	11.27	20	0.00619	1	Pass
WLAN- 2.4GHz	2412	16.77	3.66	3.66	±1dB	17.77	20	0.02766	1	Pass
WLAN- 5GHz	5550	14.76	3.19	3.19	±1dB	15.76	20	0.01562	1	Pass

UHF Co-location with ZQ3BT: PASS

BT-EDR = (0.00203/1) x 100 = 0.203% RFID = (0.323/0.601) x 100 = 53.74% Total MPE Percentage = (0.203+53.74) % = **53.943% < 100%**

ZQ3BT Co-location with AC WLAN Radio: PASS

WLAN-2.4GHz = (0.02766/1) x 100% =2.766% BT-EDR = (0.00203/1) x 100% = 0.203% Total MPE Percentage = (2.766+0.203) %= **2.969% < 100%**

ZQ3BT Co-location with AC WLAN Radio: PASS

WLAN-2.4GHz = (0.02766/1) x 100 =2.766% RFID = (0.323/0.601) x 100 = 53.74% Total MPE Percentage = (2.766+53.74) % = **56.506% < 100%**

*Note: 2.4GHz and 5GHz do not transmit simultaneously

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Shuo Zhang

SIEMIC, Inc

Shuo

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 02/27/2019