



TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr		Report No.: KR22-SRF0013-A Page (1) of (8)	
1. Client - Name : Fibocom Wireless Inc. - Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China - Date of Receipt : 2022-01-11			
2. Use of Report : Class II Permissive change			
3. Name of Product / Model : LTE module / L850-GL			
4. Manufacturer / Country of Origin : Fibocom Wireless Inc. / China			
5. Host Name of Product / Model : Notebook PC / XE345XDA			
6. FCC ID : ZMOL850GLD			
7. Date of Test : 2022-02-03 to 2022-02-06			
8. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing (Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)			
9. Test method used : FCC Part 1.1310			
10. Test Result : Refer to the test result in the test report			
Affirmation	Tested by Name : Kwonse Kim (Signature)		Technical Manager Name : Seungyong Kim (Signature)
			2022-02-11
KCTL Inc. As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.			

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0013-A Page (2) of (8)	
---	--	---

REPORT REVISION HISTORY

Date	Revision	Page No
2022-02-10	Originally issued	-
2022-02-11	Revised calculation result	8

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR22-SRF0013 is superseded by the report No. KR22-SRF0013-A.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

CONTENTS

1. General information4

2. Device information4

 2.1. Additional WLAN/Bluetooth Module information5

 2.2. Simultaneous Transmission Configurations5

3. RF Exposure.....6

4. Test Result.....8

 4.1 Calculation result of RF exposure8

 4.2 Simultaneous Transmission Analysis8



KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0013-A Page (4) of (8)	 
---	--	---

1. General information

Client : Fibocom Wireless Inc.
 Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China
 Manufacturer : Fibocom Wireless Inc.
 Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China
 Laboratory : KCTL Inc.
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
 CAB Identifier: KR0040
 ISED Number: 8035A
 KOLAS No.: KT231

2. Device information

Equipment under test : LTE module
 Model : L850-GL
 Host name of Product : Notebook PC
 Host Model : XE345XDA
 Modulation technique : LTE_QPSK, 16QAM
 WCDMA_QPSK
 Power source : DC 7.72 V
 Antenna specification : LTE/WCDMA_FPCB Antenna
 Frequency range :

LTE Band 2	: 1 850 MHz ~ 1 910 MHz
LTE Band 4	: 1 710 MHz ~ 1 755 MHz
LTE Band 5	: 824 MHz ~ 849 MHz
LTE Band 7	: 2 500 MHz ~ 2 570 MHz
LTE Band 12	: 699 MHz ~ 716 MHz
LTE Band 13	: 777 MHz ~ 787 MHz
LTE Band 38	: 2 570 MHz ~ 2 620 MHz
LTE Band 66	: 1 710 MHz ~ 1 780 MHz
WCDMA 850	: 824 MHz ~ 849 MHz
WCDMA 1900	: 1 850 MHz ~ 1 910 MHz

Software version : Chrome OS
 Hardware version : REV5
 Test device serial No. : 1JKN91ZR600022M, 1JKP91ZR600093W, 1JKN91ZR600017E

Note.

1. In this report is based on original report FCC ID: ZMOL850GLD, additional simultaneous transmission measurement with intel module AX201D2W which is also integrated into this host was investigated in test report.
 - SAR Report No.: KR21-SPF0049 (Intel Mobile Communications / AX201D2W / FCC ID: PD9AX201D2)

2.1. Additional WLAN/Bluetooth Module information

Manufacturer	:	Intel Mobile Communications		
Model	:	AX201D2W		
FCC ID	:	PD9AX201D2		
Modulation technique	:	DSSS, OFDM, OFDMA		
Frequency range	:	802.11b/g/n/ax	2.4 GHz Band (2 400.0 – 2 483.5 MHz)	
		802.11a/n/ac/ax	5.15 GHz Band (5 150.0 – 5 250.0 MHz)	
			5.25 GHz Band (5 250.0 – 5 350.0 MHz)	
			5.47 GHz Band (5 470.0 – 5 725.0 MHz)	
			5.725 GHz Band (5 725.0 – 5 850.0 MHz)	
		Bluetooth/Low Energy	2.4 GHz Band (2 400.0 – 2 483.5 MHz)	
Antenna Information	:	Chain A (Aux): WLAN 2.4 GHz & 5 GHz and Bluetooth		
		Chain B (Main): WLAN 2.4 GHz & 5 GHz		

2.2. Simultaneous Transmission Configurations

No	Scenario
1	Bluetooth (Aux) + WWAN

Note.

- WWAN does not work simultaneously with WIFI.
- For the simultaneous analysis the highest ratio among the channels and modes of cellular module L850-GL and SAR values of the unlicensed module AX201D2W was selected for the RF exposure.

3. RF Exposure

3.1 Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f ²	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *= plane-wave equivalent power density

3.2 MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2} \quad (\Rightarrow R = \sqrt{\frac{PG}{4\pi S}})$$


S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

3.3 Antenna Position



The antenna of this product, under normal use condition, is at least 20 cm away from bottom. So, this device is classified as Mobile device.

3.4 Simultaneous transmission

According to KDB 447498 D01v06, When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions.

- The $\sum$ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg + $\sum$ of MPE ratios is ≤ 1.0
- The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $\sum$ of MPE ratios is ≤ 1.0 .

Test exclusion condition a):

$$\frac{\sum \text{ of Highest Reported SAR(Bluetooth)}}{\text{Limit}} + \frac{\text{Highest Max.tune up of cellular band}}{\text{Limit}} = < 1.0$$

4. Test Result

4.1 Calculation result of RF exposure

Band	Frequency range [MHz]	Max. Tune-up Power [dBm]	Ant. Gain [dBi]	Distance [cm]	Power density [mW/cm ²]	Limit [mW/cm ²]
WCDMA Band 2	1 850 – 1 910	24.5	2.55	20	0.100 863	1.00
WCDMA Band 5	824 – 849	24.5	1.63	20	0.081 608	0.55
LTE Band 2	1 850 – 1 910	24	2.55	20	0.089 894	1.00
LTE Band 4	1 710 – 1 755	24	3.14	20	0.102 975	1.00
LTE Band 5	824 – 849	24	1.63	20	0.072 733	0.55
LTE Band 7	2 500 – 2 570	24	3.69	20	0.116 877	1.00
LTE Band 12	699 – 716	24	-0.96	20	0.040 062	0.47
LTE Band 13	777 – 787	24	1.75	20	0.074 770	0.52
LTE Band 38	2 570 – 2 620	24	1.83	20	0.076 161	1.00
LTE Band 66	1 710 – 1 780	24	3.14	20	0.102 975	1.00

Note.

1. The power density P_d at a distance of 20 cm calculated from the friis transmission.

4.2 Simultaneous Transmission Analysis

Mode	Exposure Condition / Position	Scaled 1g SAR (W/kg)	Power density (mW/cm ²)	Ratio
Bluetooth (DH5)	Body SAR / Rear	0.210	N/A	0.131
Cellular Band (WCDMA B5)	MPE		0.082	0.149
Summation (Bluetooth SAR Ratio + WCDMA B5 MPE Ratio)				0.280

Note.

1. When the sum of ratios of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the 1.0 the additional equipment approval is not required.
2. Ratio calculation
 - Bluetooth: $0.210 / 1.6 = 0.131$
 - WCDMA Band 5 : $0.082 / 0.55 = 0.149$
3. Simultaneous transmission of RF exposure.
 - $0.131 + 0.149 = 0.280$

End of test report