

EXHIBIT 11-MPE CALCULATION for CISCO MPI WLAN

FCC ID: KBCIX260MPIAC860

Applicant: ITRONIX, Corp.

Model: IX260 with co-located WLAN transmitter listed below.

1.) MPI350

Tx Freq: 2450 MHz

Max Peak Power @ antenna terminal input: 21.2 dBm

Antenna Gain: 4.5 dBi

Please Note: The AC860, WAN and MPI350, WLAN do NOT transmit at the same time therefore no summed multiple frequency exposure is applicable.

The MPE calculations are submitted for multiple frequency exposure criteria. The ratio of the field strength or power density to the applicable exposure limit at the exposure location was determined for the transmitter above and the ratio does not exceed the 1 mW/cm² limit for uncontrolled exposure / general population exposure limits detailed in CFR 47, Part 1.1310.

Multiple Frequency Exposure Requirements

Ratio 1	Limit
MPI350	<1.0
0.074/1.0	<1.0
= .074	<1.0

Tx Frequency:	2450.00	(MHz)
Maximum Peak Power at Antenna Input Terminal:	21.20	(dBm)
Antenna gain (typical)+9dB for 8- element array:	4.50	(dBi)

S= 1.00 (mW/cm²)
P= 131.8257 (mW)
G= 2.82 (numeric)

R
= **5.44** (cm)

S
(mw/cm²)
at 20cm

0.073834505