

# INTERTEK TESTING SERVICES

---

## Analysis Report

The equipment under test (EUT) is a transmitter for a R/C Crash N Bash Robo Fighters operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by two 1.5V AA batteries. For more detail information pls. refer to the user manual.

Antenna Type: integral antenna

Antenna Gain: 0dBi

Modulation Type: Pulse modulation

The nominal conducted output power specified: -21.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -23.15dBm (+/- 3dB)

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 75.4dBuV/m at 3m in the frequency 27.145MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -19.83dBm

The ERP = EIRP - 2.15 = -21.98 dBm

which is within the production variation.

The maximum conducted output power specified is -18.0dBm = 0.016mW

The source-based time-averaging conducted output power  
=  $0.016 \cdot \text{Duty Cycle}$  mW < 0.016mW (Duty Cycle < 100%)

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

=  $474 \cdot [1 + \log(100/f(\text{MHz}))]/2$

= 371.2 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

### Transmitter Duty Cycle Calculation

The duration of one cycle = 88.87ms

Effective period of the cycle =  $217.4\mu\text{s} \times 13 + 797.1\mu\text{s} = 3623.3\mu\text{s}$   
= 3.6233ms