

FCC &ISED Radio Test Report**FCC ID: X5B-049032T****IC:8814A-049032T****The report concerns: Original Grant**

Report Reference No.....: 23EFSB12018 00441
Date Sample(s) Received.....: 2023-12-23
Date of Tested.....: From 2023-12-23 to 2024-01-15
Date of issue.....: 2024-01-16
Testing Laboratory: DongGuanShuoXin Electronic Technology Co., Ltd.
Address: Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

Applicant's name: PERFORMANCE DESIGNED PRODUCTS, LLC
Address: 14144 Ventura Blvd, Suite 200 Sherman. Oaks CA
91423 United States Of America
Manufacturer.....: PERFORMANCE DESIGNED PRODUCTS, LLC

Equipment.....: Afterglow Wave Dongle for Xbox
Trade Mark: /
Model: 049-032T
Ratings: I/P: 5Vdc

Test Engineer:




Blue Qiu

Responsible Engineer :



Smile Wang

Authorized Signatory:



King Wang

Table of Contents	Page
1 TEST REPORT DECLARE	4
2 SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	9
3.3 PARAMETERS OF TEST SOFTWARE	9
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.5 SUPPORT UNITS	10
3.6 TEST ENVIRONMENT CONDITIONS	10
4 AC POWER LINE CONDUCTED EMISSIONS TEST	11
4.1 LIMIT	11
4.2 TEST PROCEDURE	11
4.3 MEASUREMENT INSTRUMENTS LIST	11
4.4 TEST SETUP	12
4.5 EUT OPERATING CONDITIONS	12
4.6 TEST RESULTS	13
5 RADIATED EMISSION TEST	15
5.1 LIMIT	15
5.2 TEST PROCEDURE	16
5.3 MEASUREMENT INSTRUMENTS LIST	17
5.4 TEST SETUP	17
5.5 EUT OPERATING CONDITIONS	18
5.6 TEST RESULT- 9KHZ TO 30MHZ	19
5.7 TEST RESULT- 30MHZ TO 1000MHZ	20
5.8 TEST RESULT- ABOVE 1000MHZ(BAND EDGE)	22
5.9 TEST RESULTS - ABOVE 1000MHZ(HARMONIC)	30
6 BANDWIDTH TEST	42
6.1 LIMIT	42
6.2 TEST PROCEDURE AND SETTING	42
6.3 MEASUREMENT INSTRUMENTS LIST	42
6.4 TEST SETUP	42
6.5 EUT OPERATION CONDITIONS	42
6.6 TEST RESULTS	43

Table of Contents	Page
7MAXIMUM OUTPUT POWER	45
7.1LIMIT	45
7.2TEST PROCEDURE	45
7.3MEASUREMENT INSTRUMENTS LIST	45
7.4TEST SETUP	45
7.5EUT OPERATION CONDITIONS	45
7.6TESTRESULTS	46
8CONDUCTED SPURIOUS EMISSION	48
8.1LIMIT	48
8.2TEST PROCEDURE	48
8.3MEASUREMENT INSTRUMENTS LIST	48
8.4TEST SETUP	48
8.5EUT OPERATION CONDITIONS	48
8.6 TEST RESULTS	49
9POWER SPECTRAL DENSITY TEST	53
9.1LIMIT	53
9.2TEST PROCEDURE	53
9.3MEASUREMENT INSTRUMENTS LIST	53
9.4TEST SETUP	53
9.5EUT OPERATION CONDITIONS	53
9.6 TEST RESULTS	54
10FREQUENCY STABILITY MEASUREMENT	56
10.1LIMIT	56
10.2TEST PROCEDURE	56
10.3MEASUREMENT INSTRUMENTS LIST	56
10.4TEST SETUP	56
10.5EUT OPERATION CONDITIONS	56
10.6 TEST RESULTS	57

1TEST REPORT DECLARE

Applicant	PERFORMANCE DESIGNED PRODUCTS, LLC
Address	14144 Ventura Blvd, Suite 200 Sherman. Oaks CA 91423 United States Of America
Manufacturer	PERFORMANCE DESIGNED PRODUCTS, LLC
Address	14144 Ventura Blvd, Suite 200 Sherman. Oaks CA 91423 United States Of America
Factory	PERFORMANCE DESIGNED PRODUCTS, LLC
Address	14144 Ventura Blvd, Suite 200 Sherman. Oaks CA 91423 United States Of America
Equipment	Afterglow Wave Dongle for Xbox
Model No.	049-032T
Trade Mark	/
Model Difference	/
Standard	FCC Part15, Subpart C (15.247) RSS-247 Issue 3, Aug. 2023 RSS-Gen Issue 5, Mar. 2019 ANSI C63.10-2013

We Declare:

The equipment described above is tested by DongGuanShuoXin Electronic Technology Co., Ltd(ATT). and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and DongGuanShuoXin Electronic Technology Co., Ltd.(ATT) is assumed of full responsibility for the accuracy and completeness of these tests.

ATT is not responsible for the sampling stage, so the results only apply to the sample as received.

ATT's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. ATT shall have no liability for any declarations, inferences or generalizations drawn by the client or others from ATT issued reports.

2SUMMARY OF TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below:

Standard(s) Section		Test Item	Judgment	Remark
FCC	ISED			
15.207	RSS-Gen8.8	AC Power Line Conducted Emissions	N/A	-----
15.247(d) 15.205(a) 15.209(a)	RSS-247 5.5 RSS-Gen8.9 RSS-Gen8.10	Radiated Emissions	PASS	-----
15.247(a)(2)	RSS-247 5.2 (a) RSS-Gen6.7	Bandwidth	PASS	-----
15.247(b)(3)	RSS-247 5.4 (d)	Maximum Output Power	PASS	-----
15.247(d)	RSS-247 5.5	ConductedSpurious Emission	PASS	-----
15.247(e)	RSS-247 5.2 (b)	Power Spectral Density	PASS	-----
-	RSS-Gen 6.11	Frequency Stability	PASS	-----
15.203	-	Antenna Requirement	PASS	Note(2)

Note:

- (1) "N/A" denotes test is not applicable to this device.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

2.1 MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Uncertainty for Conduction emission test (9kHz-150kHz)	3.7 dB
Uncertainty for Conduction emission test (150kHz-30MHz)	3.3 dB
Uncertainty for Radiation Emission test (30MHz-200MHz)	4.60 dB (Polarize: V)
	4.60 dB (Polarize: H)
Uncertainty for Radiation Emission test (200MHz-1GHz)	6.10 dB (Polarize: V)
	5.08 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz-6GHz)	5.01 dB (Polarize: V)
	5.01 dB (Polarize: H)
Uncertainty for Radiation Emission test (6GHz-18GHz)	5.26 dB (Polarize: V)
	5.26 dB (Polarize: H)
Uncertainty for Radiation Emission test (18GHz-40GHz)	5.06 dB (Polarize: V)
	5.06 dB (Polarize: H)
Uncertainty for radio frequency	$\pm 0.048\text{kHz}$
Uncertainty for conducted RF Power	$\pm 0.32\text{dB}$

Note:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Facility:

The Test site used by DongGuanShuoXin Electronic Technology Co., Ltd. to collect test data is located on the Zone A, 1F, No. 6, XinGang Road YuanGang Street, XinAn District, ChangAn Town, DongGuan City, GuangDong, China

The test facility is recognized, certified, or accredited by the following organizations:

Item	Registration No.	Expiration Date
CNAS	L3098	2024-08-27
A2LA	4893.01	2024-06-30
Innovation, Science and Economic Development Canada (ISED)	11033A CAB identifier: CN0083	2024-06-30
Federal Communications Commission (FCC)	171688 Designation No.: CN1235	2024-06-30

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Afterglow Wave Dongle for Xbox	
Brand Name	/	
Test Model	049-032T	
Series Model	Engineer Sample	
Model Difference(s)	N/A	
Hardware Version	V1.0	
Software Version	V1.0	
PowerSource	Supplied from DC.	
Power Rating	5Vdc	
Operation Frequency	2402 MHz ~ 2480 MHz	
Modulation Technology	GFSK	
Bit Rate of Transmitter	2Mbps	
Antenna Information	Antenna Type: Chip antenna	Maximum Peak Gain: -0.9dBi
Max. Output Power	3.524dBm(0.002251W) 1Mbps 3.507dBm(0.002242W)2Mbps	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode 1M PHYNOTE (1)
Mode 2	TX Mode 2M PHYNOTE (1)

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 1	TX Mode

Radiated emissions test - Above 1GHz	
Final Test Mode	Description
Mode 1	TX Mode 1M PHYNOTE (1)
Mode 2	TX Mode 2M PHYNOTE (1)

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode 1M PHYNOTE (1)
Mode 2	TX Mode 2M PHYNOTE (1)


Note:

(1) The measurements are performed at the high, middle, low available channels.

3.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of BT LE

Test Software	FCC Testing Software V1.0.0		
Frequency (MHz)	2402	2440	2480
Parameters-1Mbps	37	37	37

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**3.5 SUPPORT UNITS**

Item	Equipment	Brand	Model No.	Series No.
AE	Computer	ASUS	FL5700U	/

Item	Cable Type	Shielded Type	Ferrite Core	Length
C1	USB-C Cable	N	N	1m

3.6 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage
AC Power Line Conducted Emissions	23.5°C	61%	AC 120V 60Hz
Radiated Emissions-9K-30MHz	23.5°C	61%	5Vdc
Radiated Emissions-30 MHz to 1GHz	23.5°C	61%	5Vdc
Radiated Emissions-Above 1000 MHz	23.5°C	61%	5Vdc
Bandwidth	22.9°C	58%	5Vdc
Maximum Output Power	22.9°C	58%	5Vdc
Conducted Spurious Emission	22.9°C	58%	5Vdc
Power Spectral Density	22.9°C	58%	5Vdc

4AC POWER LINE CONDUCTED EMISSIONS TEST**4.1LIMIT**

Frequency of Emission (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56*	56 to 46*
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


4.2TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.

4.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Pulse Limiter	MTS-systemtechnik	MTS-IMP-136	261115-010-0024	12/04/2024
2	EMI Test Receiver	R&S	ESCI	101308	11/29/2024
3	LISN	AFJ	LS16	16011103219	08/11/2024
4	LISN	Schwarzbeck	NSLK 8127	8127-432	08/11/2024
5	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

4.4 TEST SETUP




4.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting data or hopping on mode.

4.6 TEST RESULTS

Test Mode: TX Mode




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	46.43	10.73	57.16	65.78	-8.62	QP
2	0.1539	27.81	10.73	38.54	55.78	-17.24	AVG
3	0.1700	44.88	10.75	55.63	64.96	-9.33	QP
4	0.1700	27.45	10.75	38.20	54.96	-16.76	AVG
5	0.2179	40.60	10.88	51.48	62.89	-11.41	QP
6	0.2179	26.24	10.88	37.12	52.89	-15.77	AVG
7	0.5658	30.19	10.79	40.98	56.00	-15.02	QP
8	0.5658	22.06	10.79	32.85	46.00	-13.15	AVG
9	2.7339	30.55	10.77	41.32	56.00	-14.68	QP
10	2.7339	20.27	10.77	31.04	46.00	-14.96	AVG
11	3.5419	27.99	10.75	38.74	56.00	-17.26	QP
12	3.5419	14.55	10.75	25.30	46.00	-20.70	AVG

Remarks:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode
------------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	42.53	10.73	53.26	65.78	-12.52	QP
2	0.1539	26.69	10.73	37.42	55.78	-18.36	AVG
3	0.1859	40.59	10.89	51.48	64.21	-12.73	QP
4	0.1859	25.52	10.89	36.41	54.21	-17.80	AVG
5	0.2220	35.73	10.86	46.59	62.74	-16.15	QP
6	0.2220	17.59	10.86	28.45	52.74	-24.29	AVG
7	0.2779	34.29	10.58	44.87	60.88	-16.01	QP
8	0.2779	19.07	10.58	29.65	50.88	-21.23	AVG
9	2.7459	27.88	10.77	38.65	56.00	-17.35	QP
10	2.7459	17.09	10.77	27.86	46.00	-18.14	AVG
11	3.7459	27.46	10.75	38.21	56.00	-17.79	QP
12	3.7459	16.66	10.75	27.41	46.00	-18.59	AVG

Remarks:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

5 RADIATED EMISSION TEST

5.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a) and RSS-Gen 8.10, then the 15.209(a) and RSS-Gen 8.9 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-30 MHz)

Frequency (MHz)	Magnetic field strength (H-Field) (μ A/m)	Measurement Distance (meters)
0.009-0.490	6.37/F(kHz)	300
0.490-1.705	6.37/F(kHz)	30
1.705-30.0	0.08	30

LIMITS OF RADIATED EMISSION MEASUREMENT (30 MHz-1000MHz)

Frequency (MHz)	Field Strength (μ V/m at 3m)
30-88	100
88-216	150
216-960	200
Above 960	500

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

- (1) The limit for radiated test was performed according to FCC PART 15C and RSS-247.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. (below 1GHz)
- b. The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. (above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. The test result is calculated as the following:
 - (1) Result = Reading + Correct Factor
 - (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
 - (3) Margin = Result - Limit

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	RBW 1MHz VBW 3MHz peak detector for Pk value RMS detector for AV value


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

5.3 MEASUREMENT INSTRUMENTS LIST


Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	101307	11/29/2024
2	Spectrum Analyzer	Agilent	E4407B	US40240708	11/06/2024
3	Loop antenna	SCHWARZBECK K	FMZB1519	1519-062	01/15/2024
4	Broadband antenna	SCHWARZBECK	VULB9168	VULB9168-192	07/02/2024
5	HORN ANTENNA	SCHWARZBECK	BBHA9120D	9120D 1065	04/09/2024
6	Preamplifier Amplifier	HP	8447F	3113A05680	12/04/2024
7	PRE-AMPLIFIER	EMEC	EM01G26G	060679	04/05/2024
8	RF Cable	R&S	Test Cable 4	4	12/04/2024
9	RF Cable	R&S	Test Cable 5	5	12/04/2024
10	RF Cable	R&S	Test Cable 9	8	04/18/2024
11	RF Cable	R&S	Test Cable 10	9	04/18/2024
12	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A


5.4 TEST SETUP

9 kHz-30 MHz



30 MHz to 1 GHz



Above 1 GHz**5.5 EUT OPERATING CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULT- 9kHz TO 30MHz

Test Mode:	TX Mode
------------	---------

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $20 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor

5.7 TEST RESULT- 30MHz TO 1000MHz

Test Mode : TX Mode

Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	
1	*	50.9420	35.13	-12.77	22.36	40.00	-17.64	QP	100	230
2		62.8708	30.23	-11.83	18.40	40.00	-21.60	QP	100	200
3		66.7325	31.26	-12.70	18.56	40.00	-21.44	QP	100	240
4		86.5027	33.57	-15.95	17.62	40.00	-22.38	QP	100	230
5		131.7577	33.82	-13.95	19.87	43.50	-23.63	QP	100	180
6		230.9068	29.50	-9.37	20.13	46.00	-25.87	QP	100	200

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode : TX Mode

Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	
1		119.8555	49.52	-15.59	33.93	43.50	-9.57	QP	200	26
2		199.9856	39.34	-10.88	28.46	43.50	-15.04	QP	100	341
3	*	239.9874	45.38	-7.22	38.16	46.00	-7.84	QP	100	261
4		278.0668	38.33	-6.35	31.98	46.00	-14.02	QP	200	123
5		360.4476	38.53	-8.85	29.68	46.00	-16.32	QP	300	169
6		480.5276	38.38	-6.92	31.46	46.00	-14.54	QP	100	211

*:Maximum data x:Over limit !:over margin

⟨Reference Only

5.8 TEST RESULT- ABOVE 1000MHz(BAND EDGE)

Test Mode: 1M TX 2402 MHz




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		2390.000	24.17	30.14	54.31	74.00	-19.69	peak	150	302
2		2390.000	10.03	30.14	40.17	54.00	-13.83	AVG	150	302
3	*	2401.950	56.98	30.16	87.14	54.00	33.14	AVG	150	302 No Limit
4	X	2402.200	67.10	30.16	97.26	74.00	23.26	peak	150	302 No Limit

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 1M TX 2402 MHz

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		2390.000	27.26	30.14	57.40	74.00	-16.60	peak	150	14
2		2390.000	10.96	30.14	41.10	54.00	-12.90	AVG	150	14
3	X	2401.750	71.95	30.16	102.11	74.00	28.11	peak	150	14 No Limit
4	*	2401.950	61.15	30.16	91.31	54.00	37.31	AVG	150	14 No Limit

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 1M TX 2480 MHz

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1	*	2479.950	54.05	30.34	84.39	54.00	30.39	AVG	150	281	No Limit
2	X	2480.200	63.72	30.34	94.06	74.00	20.06	peak	150	281	No Limit
3		2483.500	24.50	30.34	54.84	74.00	-19.16	peak	150	281	
4		2483.500	11.12	30.34	41.46	54.00	-12.54	AVG	150	281	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 1M TX 2480 MHz

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1	X	2479.700	68.39	30.34	98.73	74.00	24.73	peak	150	225	No Limit
2	*	2479.950	58.16	30.34	88.50	54.00	34.50	AVG	150	225	No Limit
3		2483.500	24.09	30.34	54.43	74.00	-19.57	peak	150	225	
4		2483.500	12.55	30.34	42.89	54.00	-11.11	AVG	150	225	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 2M TX 2402 MHz

Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	
1		2390.000	22.48	30.14	52.62	74.00	-21.38	peak	150	199
2		2390.000	12.00	30.14	42.14	54.00	-11.86	AVG	150	199
3	X	2401.450	64.60	30.16	94.76	74.00	20.76	peak	150	199 No Limit
4	*	2401.950	54.01	30.16	84.17	54.00	30.17	AVG	150	199 No Limit

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 2M TX 2402 MHz

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		2390.000	26.47	30.14	56.61	74.00	-17.39	peak	150	183
2		2390.000	11.54	30.14	41.68	54.00	-12.32	AVG	150	183
3	*	2401.950	60.14	30.16	90.30	54.00	36.30	AVG	150	183 No Limit
4	X	2402.500	71.69	30.17	101.86	74.00	27.86	peak	150	183 No Limit

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 2M TX 2480 MHz

Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
		MHz	Level	Factor	ment			Height	Degree		
			dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1	*	2479.950	49.94	30.34	80.28	54.00	26.28	AVG	150	291	No Limit
2	X	2480.000	60.00	30.34	90.34	74.00	16.34	peak	150	291	No Limit
3		2483.500	23.48	30.34	53.82	74.00	-20.18	peak	150	291	
4		2483.500	10.97	30.34	41.31	54.00	-12.69	AVG	150	291	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 2M TX 2480 MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1	*	2479.950	56.72	30.34	87.06	54.00	33.06	AVG	150	96	No Limit
2	X	2480.000	67.74	30.34	98.08	74.00	24.08	peak	150	96	No Limit
3		2483.500	26.01	30.34	56.35	74.00	-17.65	peak	150	96	
4		2483.500	13.32	30.34	43.66	54.00	-10.34	AVG	150	96	


*:Maximum data x:Over limit !:over margin

(Reference Only)

5.9TEST RESULTS - ABOVE 1000MHz(HARMONIC)

Test Mode: 1M TX 2402 MHz

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree
1		7206.000	54.46	-2.25	52.21	74.00	-21.79	peak	150	96
2	*	7206.000	42.61	-2.25	40.36	54.00	-13.64	AVG	150	105

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 1M TX 2402 MHz

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		7206.000	55.45	-2.25	53.20	74.00	-20.80	peak	150	98
2	*	7206.000	43.94	-2.25	41.69	54.00	-12.31	AVG	150	114

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 1M TX 2440 MHz

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4880.000	54.04	-7.03	47.01	74.00	-26.99	peak	150	102
2	*	4880.000	42.28	-7.03	35.25	54.00	-18.75	AVG	150	115

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 1M TX 2440 MHz

Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4880.000	53.79	-7.03	46.76	74.00	-27.24	peak	150	114
2	*	4880.000	40.61	-7.03	33.58	54.00	-20.42	AVG	150	139


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 1M TX 2480 MHz

Vertical

80.0 dBuV/m




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4960.000	51.14	-6.78	44.36	74.00	-29.64	peak	150	163
2	*	4960.000	38.37	-6.78	31.59	54.00	-22.41	AVG	150	189

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 1M TX 2480 MHz




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree
1		4960.000	49.06	-6.78	42.28	74.00	-31.72	peak	150	118
2	*	4960.000	37.65	-6.78	30.87	54.00	-23.13	AVG	150	135

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Mode: 2M TX 2402 MHz

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree
1		7206.000	50.64	-2.25	48.39	74.00	-25.61	peak	150	135
2	*	7206.000	38.83	-2.25	36.58	54.00	-17.42	AVG	150	178

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Mode: 2M TX 2402 MHz

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		7206.000	50.09	-2.25	47.84	74.00	-26.16	peak	150	118
2	*	7206.000	37.43	-2.25	35.18	54.00	-18.82	AVG	150	124

*:Maximum data x:Over limit !:over margin

⌂ Reference Only

Test Mode: 2M TX 2440 MHz

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4880.000	49.88	-7.03	42.85	74.00	-31.15	peak	150	98
2	*	4880.000	38.31	-7.03	31.28	54.00	-22.72	AVG	150	124

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 2M TX 2440 MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4880.000	51.30	-7.03	44.27	74.00	-29.73	peak	150	135
2	*	4880.000	39.18	-7.03	32.15	54.00	-21.85	AVG	150	159


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 2M TX 2480 MHz

Vertical

80.0 dBuV/m




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		4960.000	50.02	-6.78	43.24	74.00	-30.76	peak	150	102
2	*	4960.000	38.37	-6.78	31.59	54.00	-22.41	AVG	150	118

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Mode: 2M TX 2480 MHz

Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dB/m	dB	cm	degree	
1		4960.000	50.51	-6.78	43.73	74.00	-30.27	peak	150	102
2	*	4960.000	38.36	-6.78	31.58	54.00	-22.42	AVG	150	127

*:Maximum data x:Over limit !:over margin

(Reference Only)

6BANDWIDTH TEST

6.1LIMIT

FCC Part15, Subpart C (15.247)& RSS-Gen/ RSS-247		
Section	Test Item	Limit
15.247(a)(2) RSS-Gen6.7 RSS-247 5.2 (a)	Bandwidth	≥ 500 kHz (6dB bandwidth)

6.2TEST PROCEDURE AND SETTING

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting:
For 6dB Bandwidth RBW= 100 kHz, VBW=300 kHz, Sweep time =Auto.
For 99% Bandwidth RBW=30kHz, VBW=100kHz, Sweep time =Auto for 1Mbps.
RBW=100kHz, VBW=300kHz, Sweep time =Auto for 2Mbps.

6.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2024/05/23
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

6.4TEST SETUP



6.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	6 dB bandwidth (MHz)	99%OBW (MHz)	Result
CH00	2402	1.0919	1.0866	PASS
CH19	2440	1.0953	1.0870	PASS
CH39	2480	1.0726	1.0842	PASS



TX Mode 2Mbps				
Channel	Frequency (MHz)	6 dB bandwidth (MHz)	99%OBW (MHz)	Result
CH00	2402	2.0600	2.0705	PASS
CH19	2440	2.0592	2.0785	PASS
CH39	2480	2.0641	2.0853	PASS



7 MAXIMUM OUTPUT POWER**7.1 LIMIT**


FCC Part15, Subpart C (15.247)&RSS-247		
Section	Test Item	Limit
15.247(b)(3) RSS-2475.4 (d)	Maximum Output Power	1 watt or 30dBm

7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The maximum conducted output power was performed in accordance with method 11.9.1.3(for peak power)ofANSI C63.10-2013.

7.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2024/05/23
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

7.4 TEST SETUP**7.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Result
CH00	2402	3.524	0.002251	PASS
CH19	2440	3.083	0.002034	PASS
CH39	2480	2.695	0.001860	PASS
Limit	30dBm / 1W			



TX Mode_2Mbps				
Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Result
CH00	2402	3.507	0.002242	PASS
CH19	2440	3.063	0.002024	PASS
CH39	2480	2.690	0.001858	PASS
Limit	30dBm / 1W			



8 CONDUCTED SPURIOUS EMISSION

8.1 LIMIT

For FCC

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

For ISSED

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting : RBW= 100 kHz, VBW=300 kHz, Sweep time = Auto.

8.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2024/05/23
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

8.4 TEST SETUP




8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.


8.6 TEST RESULTS

TX Mode_1Mbps


Bandedge- CH00 (Lower)



Bandedge CH39 (Upper)




CH00 – 10th Harmonic of the fundamental frequency




TX Mode_2Mbps


Bandedge- CH00 (Lower)



Bandedge CH39 (Upper)



CH00 – 10th Harmonic of the fundamental frequency



9POWER SPECTRAL DENSITY TEST**9.1LIMIT**

FCC Part15, Subpart C (15.247)&RSS-247		
Section	Test Item	Limit
15.247(e) RSS-2475.2 (b)	Power Spectral Density	8 dBm (in any 3 kHz)

9.2TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW=3 kHz, VBW=10kHz, Sweep time = auto.

9.3MEASUREMENT INSTRUMENTS LIST


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2024/05/23
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

9.4TEST SETUP**9.5EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	Power SpectralDensity (dBm/3 kHz)	Limit: <dBm/3KHz	Result
CH00	2402	-12.681	8	PASS
CH19	2440	-12.519	8	PASS
CH39	2480	-13.503	8	PASS



TX Mode_2Mbps				
Channel	Frequency (MHz)	Power SpectralDensity (dBm/3 kHz)	Limit: <dBm/3KHz	Result
CH00	2402	-15.141	8	PASS
CH19	2440	-16.220	8	PASS
CH39	2480	-16.240	8	PASS



10 FREQUENCY STABILITY MEASUREMENT

10.1 LIMIT

RSS-Gen			
Section	Test Item	Limit	Frequency Range (MHz)
RSS-Gen 6.11	Frequency Stability	Specified in the user's manual	2402-2480

10.2 TEST PROCEDURE


- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting:

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10kHz
Sweep Time	Auto

10.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2024/05/23
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A
4	Temperature conditioning	Guan Jian.HTH1000	-20-130℃	GJ1000-10D001	N/A
5	DC Power Supply	G.KE	IPR-10010D	010931954	N/A

10.4 TEST SETUP



10.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

10.6 TEST RESULTS

	Temperature vs. Frequency Stability	
Voltage	Temperature	Measurement Frequency (MHz)
3.7V	(°C)	2402
	-20	2401.9960
	25	2401.9960
	50	2401.9960
2.3V	25	2401.9960
Max. Deviation (MHz)		-0.004
Max. Deviation (ppm)		-1.665

Note: 2.3V is the end point voltage, and products below 2.3V will cease working.

END OF TEST REPORT