

FCC REPORT (WIFI)

Applicant: SWAGTEK

Address of Applicant: 10205 NW 19th St. Suite 101, Miami, FL, 33172

Equipment Under Test (EUT)

Product Name: 4G LTE MIFI

Model No.: MB52, LINK, UM52

Trade mark: LOGIC, iSWAG, UNONU

FCC ID: O55004119

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 06 Nov., 2019

Date of Test: 07 Nov., to 21 Nov., 2019

Date of report issued: 22 Nov., 2019

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.


This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	22 Nov., 2019	Original

Tested by:



Date:

22 Nov., 2019

Test Engineer

Reviewed by:


Winner Zhang

Date:

22 Nov., 2019

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND TEST MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	6
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	7
5.9 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 ANTENNA REQUIREMENT	8
6.2 CONDUCTED EMISSION	10
6.3 CONDUCTED OUTPUT POWER	13
6.4 OCCUPY BANDWIDTH	18
6.5 POWER SPECTRAL DENSITY	27
6.6 BAND EDGE	32
6.6.1 Conducted Emission Method.....	32
6.6.2 Radiated Emission Method.....	36
6.7 SPURIOUS EMISSION	61
6.7.1 Conducted Emission Method.....	61
6.7.2 Radiated Emission Method.....	65
7 TEST SETUP PHOTO	75
8 EUT CONSTRUCTIONAL DETAILS	76

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247 (d)	Pass
Spurious Emission	15.205 & 15.209	Pass
Remark:		
1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).		
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	

5 General Information

5.1 Client Information

Applicant:	SWAGTEK
Address:	10205 NW 19th St. Suite 101, Miami, FL, 33172
Manufacturer/ Factory:	SWAGTEK
Address:	10205 NW 19th St. Suite 101, Miami, FL, 33172

5.2 General Description of E.U.T.

Product Name:	4G LTE MIFI
Model No.:	MB52, LINK, UM52
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)) 2422MHz~2452MHz (802.11n(H40))
Channel numbers:	11 for 802.11b/802.11g/802.11(H20) 7 for 802.11n(H40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	External Antenna
Antenna gain:	ANT1: 1.5 dBi ANT2: 1.5 dBi
Power supply:	Rechargeable Li-ion Battery DC3.8V, 2200mAh
Test Sample Condition:	The test samples were provided in good working order with no visible defects.
Remark:	The No: MB52, LINK, UM52, were identical inside, the electrical circuit design, layout, components used and internal wiring. MB52 model corresponds to the trademark LOGIC. LINK model correspond to the trademark iSWAG. UM52 model corresponds to the trademark UNONU.

Operation Frequency each of channel for 802.11b/g/n(H20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

- For 802.11n-HT40 mode, the channel number is from 3 to 9;
- Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel. Channel 3, 6 & 9 selected for 802.11n-HT40 as Lowest, Middle and Highest channel, Channel.

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
<p>The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p> <p>We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
Per-scan all kind of data rate, the follow list were the worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps
Remark: 802.11b/802.11g support SISO, 802.11n20/802.11n40 support MIMO	

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.9 Test Instruments list

Radiated Emission:						
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)	
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020	
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-18-2019	03-17-2020	
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020	
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020	
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020	
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019	
				11-21-2019	11-20-2020	
EMI Test Software	AUDIX	E3	Version: 6.110919b			
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020	
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020	
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020	
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019	
				11-21-2019	11-20-2020	
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020	
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020	
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020	
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020	
RF Switch Unit	MWRFTEST	MW200	N/A	N/A	N/A	
Test Software	MWRFTEST	MTS8200	Version: 2.0.0.0			

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-18-2019	03-17-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-18-2019	03-17-2020
LISN	CHASE	MN2050D	1447	03-18-2019	03-17-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2019
				07-21-2019	07-20-2020
Cable	HP	10503A	N/A	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
E.U.T Antenna:	The Wi-Fi antenna is an Internal antenna which cannot replace by end-user, the best case gain of the antenna is 3 dBi. 



6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
Test setup:	<p style="text-align: center;">Reference Plane</p> <p><i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Product name:	4G LTE MIFI	Product model:	MB52
Test by:	YT	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%

Level (dBuV)

FCC PART 15.247 QP

FCC PART 15.247 AV

Frequency (MHz)


Trace: 7

	Read Freq	Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	21.90	-0.45	10.78	32.23	65.78	-33.55	QP
2	0.154	8.95	-0.45	10.78	19.28	55.78	-36.50	Average
3	0.230	20.58	-0.40	10.75	30.93	62.44	-31.51	QP
4	0.277	11.32	-0.39	10.74	21.67	50.90	-29.23	Average
5	0.449	22.18	-0.38	10.74	32.54	56.89	-24.35	QP
6	0.555	27.69	-0.39	10.76	38.06	56.00	-17.94	QP
7	0.555	16.81	-0.39	10.76	27.18	46.00	-18.82	Average
8	0.759	11.51	-0.38	10.80	21.93	46.00	-24.07	Average
9	0.938	9.78	-0.38	10.85	20.25	46.00	-25.75	Average
10	1.032	20.61	-0.38	10.87	31.10	56.00	-24.90	QP
11	2.225	9.08	-0.42	10.95	19.61	46.00	-26.39	Average
12	2.622	18.31	-0.43	10.93	28.81	56.00	-27.19	QP

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	4G LTE MIFI	Product model:	MB52
Test by:	YT	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Over Limit dB	Remark
1	0.150	8.53	-0.68	10.78	18.63	56.00 -37.37 Average
2	0.154	24.25	-0.68	10.78	34.35	65.78 -31.43 QP
3	0.182	21.68	-0.69	10.77	31.76	64.42 -32.66 QP
4	0.253	9.95	-0.65	10.75	20.05	51.64 -31.59 Average
5	0.546	25.32	-0.65	10.76	35.43	56.00 -20.57 QP
6	0.546	15.10	-0.65	10.76	25.21	46.00 -20.79 Average
7	0.595	12.31	-0.64	10.77	22.44	46.00 -23.56 Average
8	0.675	23.12	-0.64	10.77	33.25	56.00 -22.75 QP
9	1.027	21.10	-0.63	10.87	31.34	56.00 -24.66 QP
10	1.689	6.63	-0.66	10.94	16.91	46.00 -29.09 Average
11	2.461	17.98	-0.67	10.94	28.25	56.00 -27.75 QP
12	2.765	6.80	-0.67	10.93	17.06	46.00 -28.94 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	 <p>The diagram shows a Spectrum Analyzer with a green waveform on its screen. A red line connects the analyzer to a grey rectangular box labeled 'E.U.T'. This 'E.U.T' box sits on a white rectangular table labeled 'Non-Conducted Table'. Below the table is a thick grey horizontal bar labeled 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Mode	Test CH	Ant. Port	Conducted Output power(dBm)	Total power (dBm)	Limit (dBm)	Result
802.11b	Lowest	TX1	15.38	/	30.0	Pass
		TX2	15.35	/		
	Middle	TX1	15.62	/	30.0	Pass
		TX2	15.60	/		
	Highest	TX1	15.77	/	30.0	Pass
		TX2	15.71	/		
802.11g	Lowest	TX1	13.32	/	30.0	Pass
		TX2	13.28	/		
	Middle	TX1	13.66	/	30.0	Pass
		TX2	12.66	/		
	Highest	TX1	13.91	/	30.0	Pass
		TX2	13.87	/		
802.11n20	Lowest	TX1	13.47	16.49	30.0	Pass
		TX2	13.48			
	Middle	TX1	13.63	16.65	30.0	Pass
		TX2	13.65			
	Highest	TX1	13.94	16.96	30.0	Pass
		TX2	13.95			
802.11n40	Lowest	TX1	12.47	15.44	30.0	Pass
		TX2	12.38			
	Middle	TX1	12.99	15.98	30.0	Pass
		TX2	12.94			
	Highest	TX1	12.94	16.04	30.0	Pass
		TX2	13.12			


Remark:

- Because If any transmit signals are correlated with each other , Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dB_i ,
So the Directional gain=10 log 2+1.5=4.51dB_i
- The directional Gain of antenna is not greater than 6 dB_i, so the limit of power is 30 dBm.

Test plot as follows:


Remark: ANT1






Remark: ANT2

802.11b




802.11g




Date: 12.NOV.2019 13:48:15

Lowest channel




Date: 12.NOV.2019 13:50:27

Lowest channel




Date: 12.NOV.2019 13:48:43

Middle channel



Date: 12.NOV.2019 13:50:58

Middle channel




Date: 12.NOV.2019 13:49:06


Highest channel

Date: 12.NOV.2019 13:51:36

Highest channel



6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	 <p>The diagram illustrates the test setup for measuring occupy bandwidth. A Spectrum Analyzer is connected to the Equipment Under Test (E.U.T) via a coaxial cable. The E.U.T is placed on a Non-Conducted Table. The entire assembly sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Remark: ANT1


Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	10.24	15.52	15.36	35.84	>500	Pass
Middle	10.24	15.28	15.28	35.84		
Highest	10.24	15.28	15.36	35.68		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	12.48	16.48	17.60	35.84	N/A	N/A
Middle	12.64	16.48	17.60	35.84		
Highest	12.56	16.48	17.60	35.84		


Remark: ANT2


Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	10.24	15.36	15.36	35.68	>500	Pass
Middle	10.24	15.28	15.28	35.52		
Highest	10.24	15.28	15.28	35.52		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	12.56	16.48	17.60	35.84	N/A	N/A
Middle	12.56	16.48	17.60	35.84		
Highest	12.56	16.48	17.60	35.84		


Test plot as follows:

Remark: ANT1











Remark: ANT2

802.11b

6dB EBW




99% OBW




Date: 12.NOV.2019 14:23:46

Lowest channel




Lowest channel




Date: 12.NOV.2019 14:26:14

Middle channel



Middle channel





Date: 12.NOV.2019 14:28:12


Highest channel

Date: 12.NOV.2019 14:16:00


Highest channel







6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm/3KHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Mode	Test CH	Ant. Port	PSD (dBm/KHz)	Total PSD (dBm/KHz)	Limit(dBm/KHz)	Result
802.11b	Lowest	TX1	-7.63	/	8.00	Pass
		TX2	-9.07	/		
	Middle	TX1	-7.52	/		Pass
		TX2	-7.62	/		
	Highest	TX1	-7.69	/	8.00	Pass
		TX2	-7.42	/		
802.11g	Lowest	TX1	-13.58	/	8.00	Pass
		TX2	-13.83	/		
	Middle	TX1	-12.75	/		Pass
		TX2	-12.81	/		
	Highest	TX1	-12.37	/	8.00	Pass
		TX2	-11.32	/		
802.11n20	Lowest	TX1	-13.81	-10.47	8.00	Pass
		TX2	-13.17			
	Middle	TX1	-13.21	-9.85	8.00	Pass
		TX2	-12.53			
	Highest	TX1	-13.51	-10.54	8.00	Pass
		TX2	-13.59			
802.11n40	Lowest	TX1	-17.59	-14.45	8.00	Pass
		TX2	-17.34			
	Middle	TX1	-17.46	-14.19	8.00	Pass
		TX2	-16.95			
	Highest	TX1	-17.10	-14..29	8.00	Pass
		TX2	-17.50			


Remark:


1 .Because If any transmit signals are *correlated* with each other , Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dB_i , So the Directional gain=10 log 2+1.5=4.51dB_i

3. The directional Gain of antenna is not greater than 6 dB_i, so the limit of power is 8 dBm/3KHz.



Test plot as follows:

Remark: ANT1







Remark: ANT2



Date: 12.NOV.2019 13:57:35

Date: 12.NOV.2019 14:05:04



Lowest channel



Date: 12.NOV.2019 14:02:56

Date: 12.NOV.2019 14:06:06

Middle channel




Date: 12.NOV.2019 14:04:08

Date: 12.NOV.2019 14:06:58


Highest channel

Highest channel




6.6 Band Edge

6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is positioned at the top left, displaying a green waveform on its screen. A red horizontal line extends from the output of the analyzer to a grey rectangular box labeled "E.U.T". This "E.U.T" box is resting on a white rectangular platform labeled "Non-Conducted Table". Below the table is a thick grey horizontal bar labeled "Ground Reference Plane". The entire assembly is set against a white background.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Test plot as follows:

Remark: ANT1




Remark: ANT2

802.11b



Date: 12.NOV.2019 14:47:42


Lowest channel



Date: 12.NOV.2019 12:04:03


Highest channel

802.11g




Date: 12.NOV.2019 11:57:06

Lowest channel



Date: 12.NOV.2019 12:05:35

Highest channel




6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205										
Test Frequency Range:	2.3GHz to 2.5GHz										
Test Distance:	3m										
Receiver setup:	Frequency	Detector	RBW	VBW	Remark						
	Above 1GHz	Peak	1MHz	3MHz	Peak Value						
Limit:	Frequency	Limit (dBuV/m @3m)		Remark							
	Above 1GHz	54.00		Average Value							
Test Procedure:		<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 									
Test setup:											
Test Instruments:	Refer to section 5.9 for details										
Test mode:	Refer to section 5.3 for details										
Test results:	Passed										

Remark: ANT1

802.11b mode:

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss Factor	Preamp Factor	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	20.46	27.07	4.69	0.00	53.90	74.00 -20.10 Peak
2	2390.000	9.85	27.07	4.69	0.00	43.29	54.00 -10.71 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	17.76	27.08	4.69	0.00	51.21	74.00	-22.79 Peak
2	2390.000	8.62	27.08	4.69	0.00	42.07	54.00	-11.93 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna		Cable Preamp		Limit	Over Line	Over Limit	Remark
	Level	Factor	Loss	Factor				
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	21.83	27.36	4.81	0.00	55.70	74.00	-18.30 Peak
2	2483.500	9.60	27.36	4.81	0.00	43.47	54.00	-10.53 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Level		
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.51	27.35	4.81	0.00	53.37	74.00	-20.63 Peak
2	2483.500	9.17	27.35	4.81	0.00	43.03	54.00	-10.97 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g mode:

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna	Cable	Preamp	Limit		Over	Remark	
	Level	Factor	Loss	Factor	Level	Line		
	MHz	dBuV	dB/n	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	17.86	27.08	4.69	0.00	51.31	74.00	-22.69 Peak
2	2390.000	8.35	27.08	4.69	0.00	41.80	54.00	-12.20 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Antenna Factor	Cable Preamp		Limit Line	Over Limit	Over Remark
			Loss	Factor	Level	dBuV/m	dBuV/m
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2390.000	15.81	27.08	4.69	0.00	49.26	74.00	-24.74 Peak
2 2390.000	8.95	27.08	4.69	0.00	42.40	54.00	-11.60 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level		Cable Preamp		Limit Line	Over Limit	Remark
	MHz	dBuV	Factor	Loss Factor			
					dB	dBuV/m	dBuV/m
					dB	dBuV/m	dB
1	2483.500	18.43	27.36	4.81	0.00	52.30	74.00 -21.70 Peak
2	2483.500	8.50	27.36	4.81	0.00	42.37	54.00 -11.63 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq	ReadAntenna Level	Cable Factor	Preamp Loss	Limit		Over Line Limit	Remark				
				MHz	dBuV	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.93	27.35	4.81	0.00	54.79	74.00	-19.21	Peak		
2	2483.500	9.86	27.35	4.81	0.00	43.72	54.00	-10.28	Average		


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Remark: ANT2

802.11b mode:

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Level		
MHz	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.20	27.07	4.69	0.00	54.64	74.00	-19.36 Peak
2	2390.000	10.46	27.07	4.69	0.00	43.90	54.00	-10.10 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	19.74	27.08	4.69	0.00	53.19	74.00	-20.81 Peak
2	2390.000	8.94	27.08	4.69	0.00	42.39	54.00	-11.61 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	18.24	27.36	4.81	0.00	52.11	74.00	-21.89 Peak
2	2483.500	9.44	27.36	4.81	0.00	43.31	54.00	-10.69 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.49	27.35	4.81	0.00	53.35	74.00	-20.65 Peak
2	2483.500	9.86	27.35	4.81	0.00	43.72	54.00	-10.28 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g mode:


Product Name:	4G LTE MIFI		Product Model:	MB52
Test By:	YT		Test mode:	802.11g Tx mode
Test Channel:	Lowest channel		Polarization:	Vertical
Test Voltage:	AC 120/60Hz		Environment:	Temp: 24°C Huni: 57%

ReadAntenna Freq	Cable Level	Preamp Factor	Loss Factor	Level dB	Limit dBuV/m	Over Line dBuV/m	Over Limit dB	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 2390.000	19.36	27.07	4.69	0.00	52.80	74.00	-21.20	Peak
2 2390.000	8.73	27.07	4.69	0.00	42.17	54.00	-11.83	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	17.86	27.08	4.69	0.00	51.31	74.00	-22.69
2	2390.000	8.35	27.08	4.69	0.00	41.80	54.00	-12.20


Peak

Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read Level MHz	Antenna Factor	Cable Loss dB	Preamp Factor	Limit Level dB	Over Line dB	Over Limit dB	Over Remark
------	----------------------	-------------------	---------------------	------------------	----------------------	--------------------	---------------------	----------------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	18.10	27.36	4.81	0.00	51.97	74.00	-22.03 Peak
2	2483.500	9.70	27.36	4.81	0.00	43.57	54.00	-10.43 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna		Cable Preamp		Limit Line	Over Limit	Remark
	Freq	Level	Antenna Factor	Cable Loss			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB
1	2483.500	20.92	27.35	4.81	0.00	54.78	74.00 -19.22 Peak
2	2483.500	9.64	27.35	4.81	0.00	43.50	54.00 -10.50 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT20)(MIMO):

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna		Cable Preamp		Limit Line	Over Limit	Remark
	Freq	Level Factor	Loss Factor	Level			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	19.53	27.07	4.69	0.00	52.97	74.00 -21.03 Peak
2	2390.000	9.77	27.07	4.69	0.00	43.21	54.00 -10.79 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss Factor dB	Preamp Level dB	Line dBuV/m	Limit dBuV/m	Over Line dB	Over Limit Remark
1 2390.000	18.32	27.08	4.69	0.00	51.77	74.00	-22.23	Peak
2 2390.000	9.85	27.08	4.69	0.00	43.30	54.00	-10.70	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	17.72	27.36	4.81	0.00	51.59	74.00	-22.41 Peak
2	2483.500	8.94	27.36	4.81	0.00	42.81	54.00	-11.19 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	25.79	27.35	4.81	0.00	59.65	74.00	-14.35 Peak
2	2483.500	13.68	27.35	4.81	0.00	47.54	54.00	-6.46 Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT40)(MIMO):

Product Name:	4G LTE MIFI		Product Model:	MB52																																								
Test By:	YT		Test mode:	802.11n(HT40) Tx mode																																								
Test Channel:	Lowest channel		Polarization:	Vertical																																								
Test Voltage:	AC 120/60Hz		Environment:	Temp: 24°C Huni: 57%																																								
<table border="1"> <thead> <tr> <th>Freq</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th>Limit</th> <th>Over</th> <th>Line</th> <th>Limit</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Level</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr> <td>1 2390.000</td> <td>25.14</td> <td>27.07</td> <td>4.69</td> <td>0.00</td> <td>58.58</td> <td>74.00</td> <td>-15.42</td> <td>Peak</td> <td></td> </tr> <tr> <td>2 2390.000</td> <td>13.64</td> <td>27.07</td> <td>4.69</td> <td>0.00</td> <td>47.08</td> <td>54.00</td> <td>-6.92</td> <td>Average</td> <td></td> </tr> </tbody> </table>					Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Remark	MHz	Level	Factor	Loss	Factor	Level	dBuV/m	dBuV/m	dB		1 2390.000	25.14	27.07	4.69	0.00	58.58	74.00	-15.42	Peak		2 2390.000	13.64	27.07	4.69	0.00	47.08	54.00	-6.92	Average	
Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Remark																																			
MHz	Level	Factor	Loss	Factor	Level	dBuV/m	dBuV/m	dB																																				
1 2390.000	25.14	27.07	4.69	0.00	58.58	74.00	-15.42	Peak																																				
2 2390.000	13.64	27.07	4.69	0.00	47.08	54.00	-6.92	Average																																				
<i>Remark:</i>																																												
1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.																																												
2. The emission levels of other frequencies are very lower than the limit and not show in test report.																																												

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2390.000	24.79	27.08	4.69	0.00	58.24	74.00	-15.76 Peak
2 2390.000	13.68	27.08	4.69	0.00	47.13	54.00	-6.87 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	ReadAntenna Freq	Cable Level	Preamp Factor	Limit Loss Factor	Line Level	Over Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.83	27.36	4.81	0.00	53.70	74.00	-20.30 Peak
2	2483.500	9.86	27.36	4.81	0.00	43.73	54.00	-10.27 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Over
	Freq	Level	Factor	Loss					
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB
1	2483.500	20.34	27.35	4.81	0.00	54.20	74.00	-19.80	Peak
2	2483.500	9.98	27.35	4.81	0.00	43.84	54.00	-10.16	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.7 Spurious Emission


6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows (For ANT 1):


Test mode: 802.11b

Lowest channel



Test mode: 802.11g


Lowest channel




Date: 12.NOV.2019 12:09:11

Date: 12.NOV.2019 12:19:12

Middle channel




Middle channel




Date: 12.NOV.2019 12:13:17

Date: 12.NOV.2019 12:22:58

Highest channel



Highest channel




Date: 12.NOV.2019 12:14:44

Date: 12.NOV.2019 12:25:19

Test plot as follows (For ANT 2):

Test mode: 802.11b


Lowest channel



Date: 12.NOV.2019 12:11:03


Test mode: 802.11g

Lowest channel




Date: 12.NOV.2019 12:22:02

Middle channel




Date: 12.NOV.2019 12:14:08

Middle channel




Date: 12.NOV.2019 12:23:37

Highest channel



Date: 12.NOV.2019 12:17:32

Highest channel




Date: 12.NOV.2019 12:27:10

Test plot as follows (For MIMO):

Test mode: 802.11n(H20)


Lowest channel



Date: 12.NOV.2019 12:28:57


Test mode: 802.11n(H40)

Lowest channel




Date: 12.NOV.2019 12:35:53

Middle channel




Date: 12.NOV.2019 12:31:46

Middle channel




Date: 12.NOV.2019 12:36:40

Highest channel



Date: 12.NOV.2019 12:32:55


Highest channel



Date: 12.NOV.2019 12:38:36

6.7.2 Radiated Emission Method


Test Requirement:	FCC Part 15 C Section 15.209 and 15.205								
Test Frequency Range:	9kHz to 25GHz								
Test Distance:	3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit:	RMS	1MHz	3MHz	Average	Value				
	Frequency	Limit (dBuV/m @3m)		Remark					
	30MHz-88MHz	40.0		Quasi-peak Value					
	88MHz-216MHz	43.5		Quasi-peak Value					
	216MHz-960MHz	46.0		Quasi-peak Value					
	960MHz-1GHz	54.0		Quasi-peak Value					
	Above 1GHz	54.0		Average Value					
		74.0		Peak Value					
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 								
Test setup:	<p>Below 1GHz</p> <p>Antenna Tower</p> <p>Search Antenna</p> <p>RF Test Receiver</p> <p>Ground Plane</p> <p>EUT</p> <p>Turn Table</p> <p>0.8m</p> <p>3m</p> <p>4m</p> <p>1m</p> <p>Ground Plane</p>								
	<p>Above 1GHz</p> <p>Antenna Tower</p> <p>Search Antenna</p> <p>RF Test Receiver</p> <p>Ground Plane</p> <p>EUT</p> <p>Turn Table</p> <p>1.5m</p> <p>3m</p> <p>4m</p> <p>1m</p> <p>Ground Plane</p>								



Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	<ol style="list-style-type: none">1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.2. 9 kHz to 30MHz is too low, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):**Below 1GHz:**

Product Name:	4G LTE MIFI		Product Model:	MB52	
Test By:	YT		Test mode:	Wi-Fi Tx mode	
Test Frequency:	30 MHz ~ 1 GHz		Polarization:	Vertical	
Test Voltage:	AC 120/60Hz		Environment:	Temp: 24°C Huni: 57%	




FCC PART 15.247

Freq	ReadAntenna		Cable Preamp		Limit	Over Line	Over Limit	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	119.856	43.22	10.89	2.17	29.39	26.89	43.50	-16.61 QP
2	131.758	44.89	10.06	2.30	29.32	27.93	43.50	-15.57 QP
3	287.990	40.07	13.41	2.91	28.47	27.92	46.00	-18.08 QP
4	360.448	46.98	14.75	3.10	28.61	36.22	46.00	-9.78 QP
5	480.528	43.96	17.52	3.46	28.92	36.02	46.00	-9.98 QP
6	672.845	36.59	20.05	4.00	28.73	31.91	46.00	-14.09 QP

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	4G LTE MIFI	Product Model:	MB52
Test By:	YT	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq MHz	Read Level dBuV	Antenna Factor	Cable Loss dB	Preamp Level dB	Limit dBuV/m	Over Line dBuV/m	Over Limit dB	Over Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 129.468	42.99	10.21	2.28	29.33	26.15	43.50	-17.35	QP
2 239.987	48.38	12.30	2.82	28.59	34.91	46.00	-11.09	QP
3 287.990	45.66	13.41	2.91	28.47	33.51	46.00	-12.49	QP
4 360.448	48.72	14.75	3.10	28.61	37.96	46.00	-8.04	QP
5 480.528	39.30	17.52	3.46	28.92	31.36	46.00	-14.64	QP
6 672.845	38.25	20.05	4.00	28.73	33.57	46.00	-12.43	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test plot as follows (For ANT 1):

802.11b								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	50.52	30.94	6.81	41.82	46.45	74.00	-27.55	Vertical
4824.00	49.26	30.94	6.81	41.82	45.19	74.00	-28.81	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	41.25	30.94	6.81	41.82	37.18	54.00	-16.82	Vertical
4824.00	42.98	30.94	6.81	41.82	38.91	54.00	-15.09	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	49.90	31.20	6.85	41.84	46.11	74.00	-27.89	Vertical
4874.00	50.32	31.20	6.85	41.84	46.53	74.00	-27.47	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	41.52	31.20	6.85	41.84	37.73	54.00	-16.27	Vertical
4874.00	39.98	31.20	6.85	41.84	36.19	54.00	-17.81	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	49.63	31.46	6.89	41.86	46.12	74.00	-27.88	Vertical
4924.00	50.58	31.46	6.89	41.86	47.07	74.00	-26.93	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	41.25	31.46	6.89	41.86	37.74	54.00	-16.26	Vertical
4924.00	40.95	31.46	6.89	41.86	37.44	54.00	-16.56	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	50.52	30.94	6.81	41.82	46.45	74.00	-27.55	Vertical
4824.00	51.39	30.94	6.81	41.82	47.32	74.00	-26.68	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	42.52	30.94	6.81	41.82	38.45	54.00	-15.55	Vertical
4824.00	43.51	30.94	6.81	41.82	39.44	54.00	-14.56	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	49.63	31.20	6.85	41.84	45.84	74.00	-28.16	Vertical
4874.00	50.29	31.20	6.85	41.84	46.50	74.00	-27.50	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	41.52	31.20	6.85	41.84	37.73	54.00	-16.27	Vertical
4874.00	42.39	31.20	6.85	41.84	38.60	54.00	-15.40	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	49.63	31.46	6.89	41.86	46.12	74.00	-27.88	Vertical
4924.00	50.26	31.46	6.89	41.86	46.75	74.00	-27.25	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	41.52	31.46	6.89	41.86	38.01	54.00	-15.99	Vertical
4924.00	41.74	31.46	6.89	41.86	38.23	54.00	-15.77	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Test plot as follows (For ANT 2):

802.11b								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	49.96	30.94	6.81	41.82	45.89	74.00	-28.11	Vertical
4824.00	50.33	30.94	6.81	41.82	46.26	74.00	-27.74	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	40.52	30.94	6.81	41.82	36.45	54.00	-17.55	Vertical
4824.00	39.98	30.94	6.81	41.82	35.91	54.00	-18.09	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	50.42	31.20	6.85	41.84	46.63	74.00	-27.37	Vertical
4874.00	51.95	31.20	6.85	41.84	48.16	74.00	-25.84	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	42.63	31.20	6.85	41.84	38.84	54.00	-15.16	Vertical
4874.00	41.85	31.20	6.85	41.84	38.06	54.00	-15.94	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	50.52	31.46	6.89	41.86	47.01	74.00	-26.99	Vertical
4924.00	49.76	31.46	6.89	41.86	46.25	74.00	-27.75	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	42.51	31.46	6.89	41.86	39.00	54.00	-15.00	Vertical
4924.00	41.73	31.46	6.89	41.86	38.22	54.00	-15.78	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	49.50	30.94	6.81	41.82	45.43	74.00	-28.57	Vertical
4824.00	50.32	30.94	6.81	41.82	46.25	74.00	-27.75	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	41.42	30.94	6.81	41.82	37.35	54.00	-16.65	Vertical
4824.00	40.69	30.94	6.81	41.82	36.62	54.00	-17.38	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	51.42	31.20	6.85	41.84	47.63	74.00	-26.37	Vertical
4874.00	50.39	31.20	6.85	41.84	46.60	74.00	-27.40	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	41.52	31.20	6.85	41.84	37.73	54.00	-16.27	Vertical
4874.00	39.78	31.20	6.85	41.84	35.99	54.00	-18.01	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	51.26	31.46	6.89	41.86	47.75	74.00	-26.25	Vertical
4924.00	50.39	31.46	6.89	41.86	46.88	74.00	-27.12	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	42.52	31.46	6.89	41.86	39.01	54.00	-14.99	Vertical
4924.00	41.75	31.46	6.89	41.86	38.24	54.00	-15.76	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test plot as follows (For MIMO):

802.11n(HT20)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	45.25	36.06	6.81	41.82	46.30	74.00	-27.70	Vertical
4824.00	46.01	36.06	6.81	41.82	47.06	74.00	-26.94	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	36.63	36.06	6.81	41.82	37.68	54.00	-16.32	Vertical
4824.00	37.12	36.06	6.81	41.82	38.17	54.00	-15.83	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	49.42	36.32	6.85	41.84	50.75	74.00	-23.25	Vertical
4874.00	49.27	36.32	6.85	41.84	50.60	74.00	-23.40	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	38.01	36.32	6.85	41.84	39.34	54.00	-14.66	Vertical
4874.00	39.22	36.32	6.85	41.84	40.55	54.00	-13.45	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.02	36.58	6.89	41.86	48.63	74.00	-25.37	Vertical
4924.00	46.31	36.58	6.89	41.86	47.92	74.00	-26.08	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	37.07	36.58	6.89	41.86	38.68	54.00	-15.32	Vertical
4924.00	37.52	36.58	6.89	41.86	39.13	54.00	-14.87	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT40)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	45.11	36.06	6.81	41.82	46.16	74.00	-27.84	Vertical
4844.00	45.50	36.06	6.81	41.82	46.55	74.00	-27.45	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	36.23	36.06	6.81	41.82	37.28	54.00	-16.72	Vertical
4844.00	36.69	36.06	6.81	41.82	37.74	54.00	-16.26	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	49.37	36.32	6.85	41.84	50.70	74.00	-23.30	Vertical
4874.00	49.01	36.32	6.85	41.84	50.34	74.00	-23.66	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	39.15	36.32	6.85	41.84	40.48	54.00	-13.52	Vertical
4874.00	40.01	36.32	6.85	41.84	41.34	54.00	-12.66	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	46.69	36.45	6.87	41.85	48.16	74.00	-25.84	Vertical
4904.00	47.01	36.45	6.87	41.85	48.48	74.00	-25.52	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	37.45	36.45	6.87	41.85	38.92	54.00	-15.08	Vertical
4904.00	37.21	36.45	6.87	41.85	38.68	54.00	-15.32	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.