

Prüfbericht-Nr.: Test report no.:	ULR-TC568821300000074F	Auftrags-Nr.: Order no.:	166145926 0010	Seite 1 von 66 Page 1 of 66
Kunden-Referenz-Nr.: Client reference no.:	NA	Auftragsdatum: Order date:	2019-06-13	
Auftraggeber: Client:	1. HONEYWELL INTERNATIONAL INC, Honeywell Safety and Productivity Solutions 9680 OLD BAILES RD, FORT MILL, SC 29707, USA 2. Metro (Suzhou) Technologies Co., Ltd No: 221, Xinghai street china-Singapore Suzhou Industrial Park.			
Prüfgegenstand: Test item:	LUZON - WIFI & BT Module	Product Type	Wi-Fi BT Module	
Bezeichnung: Identification:	SOMAT39			
Auftrags-Inhalt: Order content:	Testing and issue of Test Report and Grant Certificate			
Prüfgrundlage: Test specification:	FCC Part 15 Subpart C 15.247, 15.207 RSS 247 Issue 2 and RSS GEN Issue 5			
Wareneingangsdatum: Date of sample receipt:	2021-05-20			
Prüfmuster-Nr & Serien-Nr.: Test sample no & serial no.:	A000939665-002 A000939665-001 Engineering Sample			
Prüfzeitraum: Testing period:	2021-05-21 - 2021-06-08			
Ort der Prüfung: Place of testing:	Wireless laboratory, Bangalore			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (India) Pvt.Ltd., 27/B, 2nd Cross, Electronic City Phase1 Bangalore -560 100, India FCC Test site registration number: 496599 ISED Test site registration number: 3466E-1			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:		genehmigt von: authorized by:		
Datum: Date:	2021-05-21	Ausstellatum: Issue date:	2021-12-07	Mahammadgouse Kaladagi
Stellung / Position:	Engineer	Stellung / Position:	Assistant Manager	
Sonstiges / Other:	FCC ID: HD5-HWUSIA IC: 1693B-HWUSIA			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				



Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 2 von 66
Page 2 of 66

TEST SUMMARY

Test Item	Applicable Standard		Result
	FCC	ISED	
Maximum conducted (Peak) output power	FCC 15.247(b)(1)	RSS 247 Issue 2, Section 5.4 (b)	Pass
Maximum Power Spectral Density	FCC 15.247(e)	RSS 247 Issue 2, Section 5.2 (b)	NA
DTS Bandwidth	FCC 15.247(a)(iii)	RSS 247 Issue 2, Section 5.1 (b)	Pass
Channel Frequency Separation	15.247(a)(1)	RSS 247 Issue 2, Section 5.1 (b)	Pass
Number of Hopping Channels	15.247(a)(iii)	RSS 247 Issue 2, Section 5.1 (d)	Pass
Time of Occupancy(Dwell Time)	15.247(a)(iii)	RSS 247 Issue 2, Section 5.1 (d)	Pass
Emissions in non-restricted frequency bands	FCC 15.247(d)	RSS 247 Issue 2, Section 5.5	Pass
Spurious Radiated Emissions and Restricted Bands of Operation	FCC 15.209 / FCC 15.205	RSS-Gen Issue 5, Section 8.9 /8.10	Pass
Conducted Emissions on a.c power Lines	FCC 15.207	RSS-Gen Issue 5, Section 8.8	Pass

Product Category: Electronics Testing
Test Discipline: EMC Test Facility

Compliance statement for Part 15.203:

"THE ANTENNA TYPE IS PIFA ANTENNA & IS INTERNAL TO THE MODULE, WITH NO POSSIBILITY OF REPLACEMENT WITH A NON-APPROVED ANTENNA BY THE END-USER. THEREFORE, THE EUT IS CONSIDERED TO COMPLY WITH THIS PROVISION."

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 3 von 66

Page 3 of 66

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
ULR-TC568821300000074F	01	Initial issue of report	2021-11-30
ULR-TC568821300000074F	02	Reviewer comments updated	2021-12-07

Table of Contents

1	GENERAL REMARKS	5
1.1	Attachments	5
2	TEST SITES	6
2.1	Testing Facilities.....	6
2.2	List of Test and Measurement Instruments.....	6
3	GENERAL PRODUCT INFORMATION.....	7
3.1	Product Function and Intended Use.....	7
3.1	Ratings and System Details of Equipment under Test	7
3.2	Measurement Uncertainty:	8
4	TEST SET-UP AND OPERATION MODE.....	9
4.1	Principle of Configuration Selection	9
4.2	UUT Operation and Software	9
4.3	Special Accessories and Auxiliary Equipment	9
4.4	Simultaneous Transmission	9
4.5	Countermeasures to achieve EMC Compliance	9
4.6	List of frequencies	9
4.7	Report references.....	10
5	Operational Description	11
6	TEST METHODOLOGY	11
6.1	Conducted Spurious Emission Test on AC Power Line.....	11
6.1.1	Test Setup Configuration	12
6.2	Radiated Emission Test	12
6.2.1	Test Setup Configuration	13
7	TEST RESULTS	15
7.1	Maximum conducted (Peak) output power	15
7.2	20dB Bandwidth	22
7.3	Number of Hopping Channels.....	29
7.4	Carrier Frequency Separation.....	33
7.5	Time of Occupancy (Dwell Time)	37
7.6	Emissions in non-restricted frequency bands and Conducted Spurious Emission.....	39
7.6.1	Band edge and reference plots	40
7.6.2	Out-Of-Band Emissions.....	46
7.7	Spurious Radiated Emissions & Restricted Bands of Operation	53
8	Conducted Emission on AC Power Lines	62
9	LIST OF TABLES.....	66
10	Power level used for 1, 2, 3 Mbps.....	66

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 5 von 66

Page 5 of 66

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document

1. TEST SETUP PHOTOS
2. EUT EXTERNAL PHOTOS
3. EUT INTERNAL PHOTOS
4. FCC LABEL AND LABEL LOCATION
5. BLOCK DIAGRAM
6. SPECIFICATION OF EUT
7. SCHEMATIC DIAGRAMS
8. BILL OF MATERIAL
9. USER MANUAL
10. MAXIMUM PERMISSIBLE EXPOSURE INFORMATION

2 TEST SITES

2.1 Testing Facilities

1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India

2. TUV Rheinland (India) Pvt.Ltd.,
108 , Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100.
India

Radiated Measurement site type :
Fully anechoic chamber (used for above 1 GHz
measurements)

Radiated Measurement site type :
Semi anechoic chamber (used for below 1 GHz
measurements)

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESW 44	101732	4.73 SP5	27.01.2022	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	FMZB 1519 B	1519B-00111	-	28.02.2022	Yearly	
Balloon and Biconical Antenna	Schwarzbeck mess-elektronik	VHBB-9124 / BBA-9106	01028	-	02.09.2021	Yearly	
Log - Periodical Antenna	Schwarzbeck mess-elektronik	VUSLP-9111B	9111B-111	-	31.08.2021	Yearly	
Horn Antenna	Frankonia	HAX-18	802	-	01.03.2022	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	Antenna-Port Conducted test
Spectrum Analyser	Agilent Technologies	E4407B	US41192 772	A.14.06	10.08.2021	Yearly	
Signal Analyser	Rohde & Schwarz	FSV7	101644	FW 3.40	15.01.2022	Yearly	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100811	-	04.08.2021	Yearly	
LISN	Rohde & Schwarz	ENV216	100022	-	04.09.2021	Yearly	Conducted AC Power line Test

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in SAC	EMC 32	10.60.00
2	Radiated spurious emission measurement in FAC	EMC 32	10.60.00

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

LUZON - WIFI & BT Module is a single Modular. The module to be used inside the Honeywell Products. The Module has Dual Band WIFI (2.4GHz & 5GHz) and BLUETOOTH radio interface. This module communicates with external host using SDIO interface for WIFI and UART for BLUETOOTH.

This Module supports 802.11a/b/g/n/ac for WIFI and Supports BT (Basic , EDR & BLE) The module will act as Access Point / Master only in NON - DFS bands. In the DFS band, the Module acts as Slave /Station device which do not have Radar detection functionality.

Powered with QCA6174A, **LUZON - WIFI & BT Module** achieve the best possible connectivity and performance in RF Environment.

This Module will be used to provide the WIFI & BLUETOOTH wireless connectivity for Honeywell Products

3.1 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Radio Protocol	Bluetooth
Operating Frequency Range	2400MHz-2483.5MHz
No. of Channels	79
Channel Spacing	1MHz
Transmitting Power Level	Refer Clause 10
Maximum Measured e.i.r.p	12.76 dBm (1Mbps 2440MHz)
Modulation	GFSK, pi/4-DQPSK,8-DPSK
Data Rates	1Mbps,2Mbps,3Mbps
Number of antennas	1
Antenna Gain	4.27 dBi
Antenna Type	PIFA Antenna
Supply Voltage to Product	3.3VDC , ± 0.1V
Environmental conditions	-40degC to +125degC Relative Humidity <85%
	-20degC to +65degC Relative Humidity <85% (Non-condensing, relative humidity)
EUT Dimension(L x W)	15mm x 15 mm x 2.05mm (L x W X H)

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details

Note: Product LUZON - WIFI & BT Module has multiple protocols. All the supported wireless protocols and their respective test results are issued in separate test reports, refer clause 4.7 Report references

3.2 Measurement Uncertainty:

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$

Table 4: Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3 dB
Unwanted Emissions, conducted	±3 dB
All emissions, radiated	±6 dB
Temperature	±3 °C
Supply Voltages	±3 %
Time	±5 %

Note: The Listed Measurement Uncertainties are the worst-case uncertainty, for the respective test cases. Above Table is for reporting purpose only and not used in determining Final Pass/Fail verdict.

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle on low, mid and high channels

4.2 UUT Operation and Software

Hardware Version Identification number (HVIN) : SOMAT39
Software version : Version A.0 (QCMBR)

4.3 Special Accessories and Auxiliary Equipment

Test laptop (QRCT tool with Software Version : 3.0.296.0),
LAN cable

4.4 Simultaneous Transmission

This product does not supports Simultaneous transmission

4.5 Countermeasures to achieve EMC Compliance

- None

4.6 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2400 – 2483.5 BT(BDR+EDR)	0	2402
	1	2403
	2	2404
	3	2405
	:	:
	:	:
	:	:
	37	2439
	38	2440
	39	2441
	40	2442
	:	:
	:	:
	:	:
	74	2476
	75	2477
	:	:
	:	:
	78	2480

Table 5: List of Bluetooth center Frequencies

Channel used for Bluetooth testing

Channel low : 2402MHz

Channel mid : 2440MHz

Channel high : 2480MHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 10 von 66
Page 10 of 66

Note:

TUV Sample Identification number : A000939665-002 – Radiated test Sample
A000939665-001 – Conducted test Sample

4.7 Report references

Note: Product LUZON - WIFI & BT Module has multiple protocols. All the supported wireless protocols and their respective test results are issued in separate test reports, following table lists the report numbers.

Radio Protocol	Report Number
RF test report for Wi-Fi (2.4GHz) & BLE (2.4GHz)	ULR-TC568821300000073F
RF test report for Bluetooth (2.4GHz) – (This report)	ULR-TC568821300000074F
RF test report for Wi-Fi (5GHz)	ULR-TC568821300000075F

5 Operational Description

This LUZON - WIFI & BT Module is a WiFi/BT single modular which will be placed inside the Honeywell products like printers, barcode scanners, RFID readers etc. to enable wireless connectivity. This module includes MAC & physical layer of 802.11a/b/g/n/ac and the Bluetooth modem.

This module operates on 3.6V DC Power supply with internal on board regulation to generate 3.3v for powering ON all the circuits. The entire RF circuits is enclosed in RF shield of dimension 25mm X 25mm.

The module uses internal power amplifier and LNA for 2.4GHz frequency band and an external front end chip for 5GHz frequency band. All filters and diplexers are included in the module to ensure maximum power flatness and optimum VSWR. The module has one antenna chain for 1X1 output.

The module supports range of data rates from 1Mbps in 802.11b mode to MCS9 in 802.11ac mode. This chipset also supports concurrent operation of Bluetooth (Version 5.0) for wireless connectivity during browsing or other device applications. Along with both standard and high speed (HS) Bluetooth data rates, Bluetooth low energy modes are also supported. Hardware WAPI acceleration engine, AES, TKIP, WPA and WPA2 are supported to provide the latest security requirement on your network.

The Device communicates with HOST using SDIO interface for WIFI and UART interface for BLUETOOTH.


6 TEST METHODOLOGY

6.1 Conducted Spurious Emission Test on AC Power Line

Measured levels of ac power-line conducted emission across the 50Ω LISN port (to which the EUT is connected). All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer.

The device is placed on the test table, raised 80cm above the reference ground plane. The vertical conducting plane is located 40cm to the rear of the device. AC Conducted emission measurement is made over frequency range from 150kHz to 30MHz, this measurement was performed with EUT powered by 2 methods and both method are tested individually, one with an AC adaptor with 110V AC 60Hz supply and second with Wireless charger with supply 110V AC 60Hz.

6.1.1 Test Setup Configuration



6.2 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2013. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, The measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Balloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded

6.2.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz- 30 MHz




Figure 2: Frequency Range 30 MHz – 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 15 von 66
Page 15 of 66

7 TEST RESULTS


7.1 Maximum conducted (Peak) output power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(1) / RSS 247 Issue 2, Section 5.4 (b)
Test Method	Subclause 7.8.5 of ANSI C63.10
Measurement Bandwidth	1 MHz
Detector	Peak
Port of testing	Antenna port
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36 dBm)

Test Setup



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C Voltage = 3.3VDC Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 10 b (6) (i) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 16 von 66

Page 16 of 66


Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB) +
4. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 4.27 dBi
5. Maximum (e.i.r.p) = Maximum Peak output power (dBm) + antenna gain (4.27 dBi)

Data Rate: 1Mbps

Data rate (Mbps)	Channel Frequency (MHz)	Measured Peak Power (dBm)	Maximum e.i.r.p (dBm)	e.i.r.p Limit (dBm)	Margin (dB)
1	2402	8.02	12.29	36	-25.98
	2440	8.49	12.76	36	-25.84
	2480	8.43	12.7	36	-25.22





Channel Frequency: 2402MHz

Data rate: 1Mbps

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 17 von 66
Page 17 of 66



Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 18 von 66

Page 18 of 66

Data Rate: 2Mbps

Data rate (Mbps)	Channel Frequency (MHz)	Measured Peak Power (dBm)	Maximum e.i.r.p (dBm)	e.i.r.p Limit (dBm)	Margin (dB)
2	2402	6.58	10.85	36	-27.07
	2440	7.06	11.33	36	-26.59
	2480	6.82	11.09	36	-26.83



Channel Frequency 2402MHz


Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 19 von 66

Page 19 of 66



Channel Frequency 2440MHz



Channel Frequency 2480MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 20 von 66
Page 20 of 66

Data Rate: 3Mbps

Data rate (Mbps)	Channel Frequency (MHz)	Measured Peak Power (dBm)	Maximum e.i.r.p (dBm)	e.i.r.p Limit (dBm)	Margin (dB)
3	2402	7.00	11.27	36	-26.65
	2440	7.48	11.75	36	-26.17
	2480	7.26	11.53	36	-26.39




Channel Frequency 2402MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 21 von 66
Page 21 of 66



Channel Frequency 2440MHz



Channel Frequency 2480MHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 22 von 66
Page 22 of 66


7.2 20dB Bandwidth

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (a) (i) / RSS 247 Issue 2, Section 5.1 (b)
Test Method	Subclause 7.8.7 of ANSI C63.10
Measurement Bandwidth	30 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	The bandwidth of frequency hopping channel is the 20 dB emission bandwidth ,measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random , with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 9(b) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 23 von 66
Page 23 of 66


Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)
3. This product do not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 4.27 dBi.

Data Rate: 1Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	99% OBW (kHz)
1	2402	1.01	918.76
	2440	1.02	914.47
	2480	1.02	917.20




Channel Frequency: 2402MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 24 von 66
Page 24 of 66



Channel Frequency: 2440MHz



Channel Frequency: 2480MHz

Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 25 von 66

Page 25 of 66

Data Rate: 2Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	99% OBW (MHz)
2	2402	1.18	1.331
	2440	1.19	1.328
	2480	1.18	1.329




Channel Frequency 2402MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 26 von 66
Page 26 of 66



Channel Frequency 2440MHz



Channel Frequency 2480MHz

Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 27 von 66

Page 27 of 66

Data Rate: 3Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	99% OBW (MHz)
3	2402	1.19	1.351
	2440	1.19	1.342
	2480	1.19	1.340




Channel frequency 2402MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 28 von 66
Page 28 of 66



Channel frequency 2440MHz



Channel frequency 2480MHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 29 von 66
Page 29 of 66


7.3 Number of Hopping Channels

Result

Pass

Test Specification	FCC Part 15 Subpart C Section 15.247 (a) (i) / RSS 247 Issue 2, Section 5.1 (d)
Test Method	Subclause 7.8.3 of ANSI C63.10
Measurement Bandwidth	100 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	Frequency hopping systems operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 9(b) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 30 von 66


Page 30 of 66

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB).

Test Plots:



Start hopping Frequency Observed 2400MHz

Stop hopping Frequency Observed 2481MHz





Total Number of Hopping Channels Observed = 79

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 31 von 66
Page 31 of 66

Data Rate: 2Mbps



Start hopping Frequency Observed 2400MHz
Stop hopping Frequency Observed 2481MHz

Total Number of Hopping Channels Observed = 79

Prüfbericht - Nr.:


Test Report No.:

ULR-TC568821300000074F

Seite 32 von 66

Page 32 of 66

Data Rate: 3Mbps



Start hopping Frequency Observed 2400MHz

Stop hopping Frequency Observed 2481MHz

Total Number of Hopping Channels Observed = 79

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 33 von 66
Page 33 of 66


7.4 Carrier Frequency Separation

Result

Pass

Test Specification	FCC Part 15 Subpart C Section 15.247 (a) (1) / RSS 247 Issue 2, Section 5.1 (b)
Test Method	Clause 7.8.2 of ANSI C63.10
Measurement Bandwidth	300 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 9(b) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F


Seite 34 von 66

Page 34 of 66

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)
3. This product do not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 2.35 dBi.



Frequency (MHz)	Channel spacing Observed (MHz)	20 dB Band width (MHz)
2439	1	1.01
2440	1	1.02
2441	1	1.02

Prüfbericht - Nr.:


Test Report No.:

ULR-TC568821300000074F

Seite 35 von 66

Page 35 of 66

Data Rate: 2Mbps



Frequency (MHz)	Channel spacing Observed (MHz)	20 dB Band width (MHz)
2439	1	1.18
2440	1	1.19
2441	1	1.18

Prüfbericht - Nr.:


Test Report No.:

ULR-TC568821300000074F

Seite 36 von 66

Page 36 of 66

Data Rate: 3Mbps



Frequency (MHz)	Channel spacing Observed (MHz)	20 dB Band width (MHz)
2439	1	1.19
2440	1	1.19
2441	1	1.19

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 37 von 66
Page 37 of 66


7.5 Time of Occupancy (Dwell Time)

Result

Pass

Test Specification	FCC Part 15 Subpart C Section 15.247 (a) (i) / RSS 247 Issue 2, Section 5.1 (d)
Test Method	Clause 7.8.4 of ANSI C63.10
Measurement Bandwidth	300 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that a minimum of 15 hopping channels are used.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 9(b) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Test results:

Note:


1. All the losses are included during measurement and final values are mentioned in the test report
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)
3. Testing is performed for all the applicable data rates only worst case graphs are reported (3DH5)

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 38 von 66
Page 38 of 66

Data Rate: DH5



Dwell Time



Number of bins

Single Burst	2.8805	ms
Measured Span (Seconds)	7.5	sec
No. Of Bins/Bursts in Measured Span	32	No.
Observation Period (79 hop ch x0.4s) - Seconds	31.6	sec
Total Burst in 31.6sec	388.36	ms
Limit	400.00	ms

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 39 von 66

Page 39 of 66

7.6 Emissions in non-restricted frequency bands and Conducted Spurious Emission

Result

Pass

Test Specification

FCC part 15 Subpart C 15.247 (d) / RSS 247 Issue 2, Section 5.5

Test Method

Subclause 7.8.8 of ANSI C63.10

Measurement Bandwidth

100 kHz

Detector

Peak


Port of testing

Antenna port

Requirement

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 9(b) in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 40 von 66

Page 40 of 66


Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report
2. Final Value (dBm) = Measured Value (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)
3. This product do not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 4.27 dBi

7.6.1 Band edge and reference plots

Data Rate (Mbps)	Channel Frequency (MHz)	Reference Value (B) (dBm)	Band edge Frequency (MHz)	Value at Band edge (A) (dBm)	A-B (dBc)	Minimum Limit (dBc)
1	2402	7.18	2390	-49.65	-56.83	-20.00
	2480	7.75	2483.5	-49.54	-57.29	-20.00




Channel Frequency 2402MHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 41 von 66
Page 41 of 66



Channel Frequency 2480MHz

Data Rate: 2Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	Reference Value (B) (dBm)	Band edge Frequency (MHz)	Value at Band edge (A) (dBm)	A-B (dBc)	Minimum Limit (dBc)
2	2402	3.67	2390	-49.88	-53.55	-20.00
	2480	3.84	2483.5	-51.18	-55.02	-20.00


Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 42 von 66


Page 42 of 66




Channel Frequency 2402MHz



Channel Frequency 2480MHz



Channel Frequency 2402MHz



Channel Frequency 2440MHz


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 44 von 66
Page 44 of 66

Data Rate: 3Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	Reference Value (B) (dBm)	Band edge Frequency (MHz)	Value at Band edge (A) (dBm)	A-B (dBc)	Minimum Limit (dBc)
3	2402	3.44	2390	-49.81	-52.62	-20.00
	2480	4.11	2483.5	-50.19	-54.30	-20.00



Channel Frequency 2402MHz


Prüfbericht - Nr.:

Test Report No.:


ULR-TC568821300000074F

Seite 45 von 66


Page 45 of 66



Channel Frequency 2480MHz




Channel Frequency 2402MHz



Channel Frequency 2480MHz

7.6.2 Out-Of-Band Emissions




Channel Frequency 2402MHz

Frequency Range 9KHz – 150KHz

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 47 von 66
Page 47 of 66



Channel Frequency 2402MHz

Frequency Range 150KHz – 30MHz




Channel Frequency 2402MHz

Frequency Range 30MHz – 1GHz

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 48 von 66
Page 48 of 66



Channel Frequency 2402MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2440MHz

Frequency Range 9KHz – 150KHz

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 49 von 66
Page 49 of 66



Channel Frequency 2440MHz

Frequency Range 150KHz – 30MHz




Channel Frequency 2440MHz

Frequency Range 30MHz – 1GHz

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 50 von 66
Page 50 of 66



Channel Frequency 2440MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2480MHz

Frequency Range 9KHz – 150KHz

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000074F

Seite 51 von 66
Page 51 of 66



Channel Frequency 2480MHz

Frequency Range 150KHz – 30MHz



Channel Frequency 2480MHz

Frequency Range 30MHz – 1GHz


Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 52 von 66

Page 52 of 66



Channel Frequency 2480MHz

Frequency Range 1GHz – 26.5GHz

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 53 von 66
Page 53 of 66

7.7 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205) / IC RSS-GEN, Section 8.9 and 8.10
Test Method	ANSI C63.10
Measurement Location	Fully anechoic chamber
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer 6 TEST METHODOLOGY

Table 6: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.3VDC

Relative humidity: 62%

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 54 von 66

Page 54 of 66

Test results:


Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY For more details

Test results for frequency range 9kHz – 30MHz

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported


Test results for frequency range 30MHz – 1GHz

Antenna Polarization	Measured Frequency (MHz)	Measured value (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	80.02	27.24	40.00	-12.76
	119.97	28.78	43.50	-14.72
	139.46	29.50	43.50	-14.00
	177.53	30.40	43.50	-13.10
	290.57	27.91	46.00	-18.09
	341.14	25.70	46.00	-20.30
	495.08	40.38	46.00	-5.62
	540.28	29.01	46.00	-16.99
Horizontal	79.96	26.53	40.00	-13.47
	119.97	27.60	43.50	-15.90
	141.95	32.71	43.50	-10.79
	177.53	31.06	43.50	-12.44
	316.69	31.90	46.00	-14.10
	356.75	31.95	46.00	-14.05
	396.02	34.00	46.00	-12.00
	490.42	30.22	46.00	-15.78




Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal



Channel Frequency 200MHz – 1GHz

Polarization Vertical



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F

Seite 57 von 66

Page 57 of 66

Test results for the frequencies in the range 1 GHz to 26.5 GHz

Data Rate: 1Mbps


Channel Frequency (MHz)	Antenna Polarization	Frequency (MHz)	Emission level (dBμV/m)	Limit (dBm)	Margin (dB)
2402	Vertical	2402(Pk)	105.06	-	-
		2402(Av)	104.68	-	-
		2390(Pk)	38.60	74*	-35.40
		2390(Av)	26.19	54*	-27.81
		4804(Pk)	41.43	74	-32.57
		4804(Av)	30.41	54	-23.59
		7206(Pk)	47.05	74	-26.95
		7206(Av)	34.80	54	-19.20
	Horizontal	2402(Pk)	95.04	-	-
		2402(Av)	95.43	-	-
		2390(Pk)	36.40	74*	-37.60
		2390(Av)	23.40	54*	-30.60
		4804(Pk)	41.30	74	-32.70
		4804(Av)	28.89	54	-25.11
		7206(Pk)	46.52	74	-27.48
		7206(Av)	34.69	54	-19.31
2440	Vertical	2440(Pk)	105.72	-	-
		2440(Av)	105.33	-	-
		4880(Pk)	41.05	74	-32.95
		4880(Av)	29.19	54	-24.81
		7320(Pk)	47.39	74	-26.61
		7320(Av)	35.00	54	-19.00
	Horizontal	2440(Pk)	98.65	-	-
		2440(Av)	98.25	-	-
		4880(Pk)	40.83	74	-33.17
		4880(Av)	28.90	54	-25.10
		7320(Pk)	47.31	74	-26.69
		7320(Av)	34.87	54	-19.13
2480	Vertical	2483.5(Pk)	46.91	74*	-27.09
		2483.5(Av)	35.02	54*	-18.98
		2480(Pk)	106.76	-	-
		2480(Av)	106.34	-	-
		4960(Pk)	42.26	74	-31.74
		4960(Av)	30.30	54	-23.70
		7440(Pk)	46.88	74	-27.12
		7440(Av)	34.92	54	-19.08
	Horizontal	2483.5(Pk)	40.98	74*	-33.02
		2483.5(Av)	29.23	54*	-24.77
		2480(Pk)	100.05	-	-
		2480(Av)	99.61	-	-
		4960(Pk)	40.98	74	-33.02
		4960(Av)	28.91	54	-25.09
		7440(Pk)	47.48	74	-26.52
		7440(Av)	34.77	54	-19.23

* : Indicate restricted band of operation §15.205

Pk: Peak Detector; Av: Average Detector


Worst case emissions plots

Data Rate: 1Mbps
Channel Frequency 2480MHz




Channel Frequency: 2480MHz

Polarization: Vertical




Channel Frequency: 2480MHz

Polarization: Horizontal




Channel Frequency: 1 – 9.9 GHz

Polarization: Vertical




Channel Frequency: 9.9 – 18 GHz

Polarization: Vertical




Channel Frequency: 1 – 9.9 GHz

Polarization: Horizontal




Channel Frequency: 9.9 – 18 GHz

Polarization: Horizontal



Channel Frequency: 18 - 40 GHz

Polarization: Vertical



Channel Frequency: 18 - 40 GHz

Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 62 von 66
Page 62 of 66

8 Conducted Emission on AC Power Lines

Result

Pass

Test Specification : FCC Part 15 Section 15.207 / RSS Gen Issue 5 Section 8.8
Test Method : ANSI C 63.10-2013
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC,60Hz
Test Method : Refer TEST METHODOLOGY

***Note: The product has tested with AC to DC adapter**

Limits of section 15.207

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV/m)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency

Test Conditions:

Normal Temperature = +24°C Voltage (V norm) = 110V AC (Through AC to DC Adapter) Relative Humidity = 64%


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 63 von 66
Page 63 of 66

Test result:

Power: 110V 60HZ_LINE



Line Graph

Quasipeak (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas.Time	Comments	Correction (dB)
0.215	1	38.06	63.05	-24.99	Phase 1	1	9k	0.02	Pass	20.16
21.26465	1	34.62	60	-25.38	Phase 1	1	9k	0.02	Pass	20.14
0.1653	1	38.56	65.16	-26.6	Phase 1	1	9k	0.02	Pass	20.22
0.29535	1	31.3	60.41	-29.11	Phase 1	1	9k	0.02	Pass	20.06
0.3503	1	27.85	58.96	-31.11	Phase 1	1	9k	0.02	Pass	20.07
1.1863	1	23.61	56	-32.39	Phase 1	1	9k	0.02	Pass	20.43
0.4315	1	24.4	57.25	-32.85	Phase 1	1	9k	0.02	Pass	20.08
0.2715	1	28.12	61.12	-33	Phase 1	1	9k	0.02	Pass	20.09
0.33795	1	24.46	59.25	-34.79	Phase 1	1	9k	0.02	Pass	20.06
5.68075	1	24.6	60	-35.4	Phase 1	1	9k	0.02	Pass	20.54
5.3592	1	23	60	-37	Phase 1	1	9k	0.02	Pass	20.54

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000074F


Seite 64 von 66

Page 64 of 66

Average (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas.Time	Comments	Correction (dB)
0.1653	1	22.29	55.16	-32.87	Phase 1	1	9k	0.02	Pass	20.22
0.215	1	17.61	53.05	-35.44	Phase 1	1	9k	0.02	Pass	20.16
0.2715	1	13.51	51.12	-37.61	Phase 1	1	9k	0.02	Pass	20.09
0.29535	1	20.33	50.41	-30.08	Phase 1	1	9k	0.02	Pass	20.06
0.33795	1	15.19	49.25	-34.06	Phase 1	1	9k	0.02	Pass	20.06
0.3503	1	15.93	48.96	-33.03	Phase 1	1	9k	0.02	Pass	20.07
0.4315	1	13.57	47.25	-33.68	Phase 1	1	9k	0.02	Pass	20.08
1.1863	1	12.09	46	-33.91	Phase 1	1	9k	0.02	Pass	20.43
5.3592	1	17.01	50	-32.99	Phase 1	1	9k	0.02	Pass	20.54
5.68075	1	17.42	50	-32.58	Phase 1	1	9k	0.02	Pass	20.54
21.26465	1	27.9	50	-22.1	Phase 1	1	9k	0.02	Pass	20.14

Line Table

Power: 110V60HZ_NEUTRAL



Neutral Graph

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 65 von 66
Page 65 of 66

Quasipeak (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas. Time	Comments	Correction (dB)
0.29665	2	39.24	60.3	-21.06	Neutral	1	9k	0.02	Pass	19.96
0.15675	2	39.99	65.57	-25.58	Neutral	1	9k	0.02	Pass	20.3
0.16805	2	38.24	64.96	-26.72	Neutral	1	9k	0.02	Pass	20.27
0.1795	2	37.25	64.58	-27.33	Neutral	1	9k	0.02	Pass	20.24
0.1916	2	36.02	64.04	-28.01	Neutral	1	9k	0.02	Pass	20.21
0.3442	2	29.58	59.06	-29.47	Neutral	1	9k	0.02	Pass	20.01
21.4065	2	30.08	60	-29.92	Neutral	1	9k	0.02	Pass	20.43
0.2262	2	32.15	62.6	-30.45	Neutral	1	9k	0.02	Pass	20.13
0.41605	2	26.37	57.49	-31.12	Neutral	1	9k	0.02	Pass	20.12
0.39895	2	26.43	57.9	-31.47	Neutral	1	9k	0.02	Pass	20.09
1.15335	2	23.55	56	-32.45	Neutral	1	9k	0.02	Pass	20.51
6.4893	2	20.28	60	-39.72	Neutral	1	9k	0.02	Pass	20.69

Average (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas. Time	Comments	Correction (dB)
0.29665	2	26.41	50.3	-23.89	Neutral	1	9k	0.02	Pass	19.96
21.4065	2	23.85	50	-26.15	Neutral	1	9k	0.02	Pass	20.43
0.3442	2	19.24	49.06	-29.82	Neutral	1	9k	0.02	Pass	20.01
0.41605	2	16.58	47.49	-30.91	Neutral	1	9k	0.02	Pass	20.12
0.39895	2	16.71	47.9	-31.19	Neutral	1	9k	0.02	Pass	20.09
0.15675	2	22.95	55.57	-32.62	Neutral	1	9k	0.02	Pass	20.3
0.16805	2	21.18	54.96	-33.78	Neutral	1	9k	0.02	Pass	20.27
0.1795	2	20.11	54.58	-34.47	Neutral	1	9k	0.02	Pass	20.24
1.15335	2	11.44	46	-34.56	Neutral	1	9k	0.02	Pass	20.51
0.1916	2	19.27	54.04	-34.76	Neutral	1	9k	0.02	Pass	20.21
6.4893	2	14.7	50	-35.3	Neutral	1	9k	0.02	Pass	20.69
0.2262	2	16.31	52.6	-36.29	Neutral	1	9k	0.02	Pass	20.13

Neutral Table

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000074F

Seite 66 von 66
Page 66 of 66

9 LIST OF TABLES

Table 1: List of test and measurement instruments	6
Table 2: Instrument application Software versions	6
Table 3: Ratings and System Details as declared by Client*	7
Table 4: Measurement Uncertainty	8
Table 5: List of Bluetooth center Frequencies	9
Table 6: Transmitter limits for Radiated emission	53

10 Power level used for 1, 2, 3 Mbps

Channel Frequency (MHz)	Power level
2402	9
2440	9
2480	9

*****END OF TEST REPORT*****