

ASAP Technology (jiangxi) Co., Ltd

TEST REPORT

SCOPE OF WORK

SAR Assessment– 080-08-4962

REPORT NUMBER

240506052SZN-002

ISSUE DATE

25 June 2024

[REVISED DATE]

[-----]

PAGES

4

DOCUMENT CONTROL NUMBER

RF Exposure

© 2017 INTERTEK



Test Report

Applicant : ASAP Technology (jiangxi) Co., Ltd
Ji'an Industrial Park, Ji'an, Jiangxi 343100 China

Sample Description

Product : Wireless charger

Model No. : 080-08-4962

Brand Name : dealworthy

Electrical Rating : Input: DC 5V 3A,9V 2A, 12V 1.5A
Wireless Output: 10.0W Max

Date Received : 06 May 2024

Date Test Conducted : 06 May 2024 to 25 June 2024

Test Requested : Test for compliance with CFR 47 part 1

Test Method : Environmental evaluation and exposure limit according
to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310
KDB 680106 D01 RF Exposure Wireless Charging v04

Test Result : Pass

Conclusion : When determining of test conclusion, measurement
uncertainty of tests have been considered.

***** End of Page *****

Prepared and Checked By:

Approved By:

Tenet Cao
Assistant Engineer

Ryan Chen
Senior Project Engineer
Date: 25 June 2024

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch


101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

Test Report

Test Setup Configuration



Note

- The RF exposure test is performed in the shield room.
- The test distance is between the edge of the charger and the the measurement probe.
- There are two coils, which coil will work depends on the placement of the mobile phone (vertical or horizontal). Both cases are tested, and only the worst patterns are shown in the report.

Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Cal. Date	Due Date
SZ186-06	The Magnetic Amplitude and Gradient Probe System	SPEAG	MAGPy-8D3D+E3D	2024-03-07	2025-03-07

Support Equipment List

Description	Manufacturer	Detail
Mobile phone	Samsung (Provided by Intertek)	Model: Samsung (SM-G9300)
Adapter	Quick Wall Charger (Provided by Client)	Model: 080-08-4962 Input: 100-240Vac 50/60Hz 0.5A Output: 5Vdc 3A, 9Vdc 2A, 12Vdc 1.5A

Reference Limit:

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: * = Plane wave equivalent power density

Test Result: Pass
H-Field Strength at 20 cm surrounding the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Limits (A/m)
0.115-0.205	1% Battery Level	0.05	0.05	0.05	0.07	0.14	1.63
0.115-0.205	50% Battery Level	0.06	0.06	0.05	0.07	0.12	1.63
0.115-0.205	99% Battery Level	0.05	0.06	0.04	0.06	0.13	1.63
0.115-0.205	Stand-by	0.04	0.05	0.04	0.05	0.11	1.63

E-Field Strength at 20 cm surrounding the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Limits (V/m)
0.115-0.205	1% Battery Level	4.33	2.97	3.93	4.47	6.62	614
0.115-0.205	50% Battery Level	4.12	2.78	3.83	4.33	6.45	614
0.115-0.205	99% Battery Level	4.19	2.91	3.87	4.42	6.33	614
0.115-0.205	Stand-by	3.88	2.88	3.66	4.17	6.25	614

Configuration photo of the test:

Please refer to RF Exposure setup photos. pdf.

***** End of Report*****