

FCC RF Exposure Report

Report No.: SA200109E02

FCC ID: 2AQ68T99W175

Test Model: T99W175

Received Date: Jan. 10, 2020

Test Date: Feb. 13 ~ May 28, 2020

Issued Date: May 29, 2020

Applicant: Hon Lin Technology Co., Ltd.

Address: 11F, No. 32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
3.1 Limits for Maximum Permissible Exposure (MPE).....	5
3.2 MPE Calculation Formula	5
3.3 Classification	5
3 Calculation Result of Maximum Density Power	6

Release Control Record

Issue No.	Description	Date Issued
SA200109E02	Original release	May 28, 2020

1 Certificate of Conformity

Product: 5G WWAN Module

Brand: Foxconn

Test Model: T99W175

Sample Status: Engineering Sample

Applicant: Hon Lin Technology Co., Ltd.

Test Date: Feb. 13 ~ May 28, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** May 29, 2020
Pettie Chen / Senior Specialist

Approved by : Bruce Chen , **Date:** May 29, 2020
Bruce Chen / Senior Project Engineer

2 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Density Power

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	1850.7-1909.3	27.79	20	0.120	1
WCDMA Band 4	1710.7-1754.3	27.74	20	0.118	1
LTE Band 2	1850.7-1909.3	28.09	20	0.128	1
LTE Band 4	1710.7-1754.3	28.25	20	0.133	1
LTE Band 7	2502.5-2567.5	28.66	20	0.146	1
LTE Band 25	1850.7-1914.3	27.99	20	0.125	1
LTE Band 30	2307.5-2312.5	23.50	20	0.045	1
LTE Band 38	2572.5-2617.5	28.85	20	0.153	1
LTE Band 41	2547.5-2652.5	32.03	20	0.317	1
LTE Band 48 (Per 10M)	3552.5-3697.5	22.78	20	0.038	1
LTE Band 48 (Full Power)	3552.5-3697.5	22.92	20	0.039	1
LTE Band 42 (Per 10M)	3552.5-3597.5	22.56	20	0.036	1
LTE Band 42 (Full Power)	3552.5-3597.5	22.79	20	0.038	1
LTE Band 66	1710.7-1779.3	27.95	20	0.124	1
LTE Band 7C	2507.8-2560.0	28.71	20	0.148	1
LTE Band 38C	2580.0-2610.0	30.26	20	0.211	1
LTE Band 41C	2506.0-2680.0	30.23	20	0.210	1
LTE Band 48C (Per 10M)	3560.0-3690.0	22.53	20	0.036	1
LTE Band 48C (Full Power)	3560.0-3690.0	22.89	20	0.039	1
LTE Band 42C (Per 10M)	3552.5-3697.5	22.25	20	0.033	1
LTE Band 42C (Full Power)	3552.5-3697.5	22.68	20	0.037	1
LTE Band 66C	1720.0-1770.0	28.89	20	0.154	1
LTE Band 66B	1715.0-1775.0	28.63	20	0.145	1
5GNR (n38)	2580.0-2610.0	28.51	20	0.141	1

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 5	826.4-846.6	25.15	27.30	20	0.107	0.551
LTE Band 5	824.7-848.3	25.84	27.99	20	0.125	0.550
LTE Band 26 (Part 22)	824.7-848.3	25.64	27.79	20	0.120	0.550
LTE Band 12	699.7-715.3	26.35	28.50	20	0.141	0.466
LTE Band 13	779.5-784.5	26.41	28.56	20	0.143	0.520
LTE Band 14	790.5-795.5	26.41	28.56	20	0.143	0.527
LTE Band 17	706.5-713.5	26.27	28.42	20	0.138	0.471
LTE Band 26 (Part 90)	814.7-823.3	25.78	27.93	20	0.124	0.543
LTE Band 71	665.5-695.5	25.97	28.12	20	0.129	0.444
LTE Band 5B	829.0-844.0	25.79	27.94	20	0.124	0.553

Function		Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Co-located Ratio<1
ENDC n2		1852.5-1907.5	-	27.55	20	0.113	1	-
ENDC n2	LTE Band 5	824.7-848.3	25.04	27.19	20	0.104	0.550	0.303
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.466	0.359
	LTE Band 13	779.5-784.5	25.46	27.61	20	0.115	0.520	0.334
	LTE Band 30	2307.5-2312.5	-	23.30	20	0.043	1	0.156
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.71	20	0.037	1	0.150
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.71	20	0.037	1	0.150
	LTE Band 66	1710.7-1779.3		27.47	20	0.111	1	0.224
ENDC n5		826.5-846.5	24.96	27.11	20	0.102	0.551	-
ENDC n5	LTE Band 2	1850.7-1909.3	-	27.66	20	0.116	1	0.302
	LTE Band 7	2502.5-2567.5	-	28.49	20	0.141	1	0.326
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.466	0.431
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.71	20	0.037	1	0.223
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.69	20	0.037	1	0.223
	LTE Band 66	1710.7-1779.3	-	27.44	20	0.110	1	0.296
ENDC n7		2507.8-2560.0	-	28.51	20	0.141	1	-
ENDC n7	LTE Band 5	824.7-848.3	25.05	27.20	20	0.104	0.550	0.331
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.466	0.387
ENDC n12		699.7-715.3	25.56	27.71	20	0.193	0.466	-
ENDC n12	LTE Band 2	1850.7-1909.3	-	27.66	20	0.116	1	0.368
	LTE Band 66	1710.7-1779.3	-	27.47	20	0.111	1	0.363
ENDC n41 (HPUE)		2506.02-2679.99	-	31.21	20	0.263	1	-
ENDC n41		2506.02-2679.99	-	28.90	20	0.154	1	-
ENDC n41	LTE Band 2	1850.7-1909.3	-	27.47	20	0.111	1	0.374
	LTE Band 25	1850.7-1914.3	-	27.47	20	0.111	1	0.374
	LTE Band 26 (Part 22)	824.7-848.3	24.86	27.01	20	0.100	0.550	0.445
	LTE Band 26 (Part 90)	814.7-823.3	24.86	27.01	20	0.100	0.543	0.447
	LTE Band 41 (HPUE)	2498.5-2687.5	-	30.80	20	0.239	1	0.502
	LTE Band 41	2498.5-2687.5	-	28.21	20	0.132	1	0.395
	LTE Band 66	1710.7-1779.3	-	27.46	20	0.111	1	0.374

Function		Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Co-located Ratio<1
ENDC n66		1712.5-1777.9	-	27.67	20	0.116	1	-
ENDC n66	LTE Band 5	824.7-848.3	24.86	27.01	20	0.100	0.550	0.298
	LTE Band 12	699.7-715.3	25.46	27.61	20	0.115	0.466	0.363
	LTE Band 13	779.5-784.5	25.45	27.60	20	0.114	0.520	0.336
	LTE Band 71	665.5-695.5	25.46	27.61	20	0.115	0.444	0.375
	LTE Band 30	2307.5-2312.5	-	23.20	20	0.042	1	0.158
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.72	20	0.037	1	0.154
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.71	20	0.037	1	0.153
ENDC n71		665.5-695.5	25.45	27.60	20	0.114	0.444	-
ENDC n71	LTE Band 2	1850.7-1909.3	-	27.67	20	0.116	1	0.374
	LTE Band 7	2502.5-2567.5	-	28.46	20	0.140	1	0.397
	LTE Band 66	1710.7-1779.3	-	27.47	20	0.111	1	0.369

*EIRP = ERP + 2.15dB

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---