

## FCC 47 CFR MPE REPORT

MMD Hong Kong Holding Limited

Soundbar Speaker

Model Number: TAB5305/37

Additional Model: TAB5105/37, TAB5305/xx, TAB5105/xx  
(xx=00-99 for country code)

FCC ID: 2AR2STAB5305

Prepared for:	MMD Hong Kong Holding Limited
	Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street,
	Kwun Tong, Kowloon, Hong Kong
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2011011
Date of Test:	Oct. 10~31, 2020
Date of Report:	Nov. 02, 2020



## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
GFSK	2402	-1.24	0.752	$-1 \pm 1$	0	1
	2441	-1.10	0.776	$-1 \pm 1$	0	1
	2480	-0.40	0.912	$0 \pm 1$	0	1
8-DPSK	2402	2.52	1.786	$2 \pm 1$	0	1
	2441	2.77	1.892	$2 \pm 1$	0	1
	2480	2.76	1.888	$2 \pm 1$	0	1

## 3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
2.4G Band						
GFSK	1	0	1	0.00025	1	Compiles
8-DPSK	3	0	1	0.00040	1	Compiles

**End of Test Report**