FCC PART 15D

MEASUREMENT AND TEST REPORT

For

Meizhou Guo Wei Electronics Co., Ltd

AD1 Section, Economic Development Area, Dongsheng Industrial District, Meizhou, Guangdong, China

FCC ID: 2ARRB-G31X18BS

Report Type:	**Product Type:**
Original Report	Digital Cordless Telephone

Report Number:	RSZ190131007-00A
Report Date:	2019-05-10
Reviewed By:	Hill He RF Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*".
The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION 4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION 6
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS 6
EXTERNAL I/O CABLE 6
BLOCK DIAGRAM OF TEST SETUP 6
SUMMARY OF TEST RESULTS 7
TEST EQUIPMENT LIST 8
§1.1307 (B) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) 9
APPLICABLE STANDARD 9
MPE CALCULATION 9
FCC§15.317 & §15.203 - ANTENNA REQUIREMENT 10
APPLICABLE STANDARD 10
ANTENNA CONNECTOR CONSTRUCTION 10
FCC§15.315 & §15.207 - CONDUCTED EMISSIONS 11
APPLICABLE STANDARD 11
EUT SETUP 11
EMI TEST RECEIVER SETUP 11
TEST PROCEDURE 12
CORRECTED FACTOR & MARGIN CALCULATION 12
TEST RESULTS SUMMARY 12
TEST DATA 12
FCC§15.323 (A) - EMISSION BANDWIDTH 17
APPLICABLE STANDARD 17
TEST PROCEDURE 17
TEST DATA 17
FCC§15.319 (C) - PEAK TRANSMIT POWER 20
APPLICABLE STANDARD 20
TEST PROCEDURE 20
TEST DATA 20
FCC§15.319 (D) - POWER SPECTRAL DENSITY 23
APPLICABLE STANDARD 23
TEST PROCEDURE 23
TEST DATA 23
FCC§15.323 (D) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND 27
APPLICABLE STANDARD 27

TEST PROCEDURE 27
TEST DATA 27

FCC§15.323 (F) - FREQUENCY STABILITY 37

APPLICABLE STANDARD 37
TEST PROCEDURE 37
TEST DATA 37

FCC§15.323 (C) (E) & §15.319(F) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE 39

APPLICABLE STANDARD 39
TEST PROCEDURE 39
TEST DATA 39
1) AUTOMATIC DISCONTINUATION OF TRANSMISSION, FCC §15.319(F) 40
2) MONITORING TIME, FCC §15.323(C) (1) 40
3) LOWER MONITORING THRESHOLD, FCC §15.323(C) (2) 40
4) MAXIMUM TRANSMIT PERIOD, FCC §15.323(C) (3) 41
5) SYSTEM ACKNOWLEDGEMENT, FCC §15.323(C) (4) 41
6) LEAST INTERFERED CHANNEL (LIC), FCC §15.323(C) (5) 42
7) RANDOM WAITING, FCC §15.323(C) (6) 44
8) MONITORING BANDWIDTH AND REACTION TIME, FCC §15.323(C) (7) 44
9) MONITORING ANTENNA, FCC §15.323(C) (8) 45
10) MONITORING THRESHOLD RELAXATION, FCC §15.323(C) (9) 46
11) DUPLEX CONNECTIONS, FCC §15.323(C) (10) 46
12) ALTERNATIVE MONITORING INTERVAL, FCC §15.323(C) (11) 47
13) FAIR ACCESS, FCC §15.323(C) (12) 48
14) FRAME REPETITION STABILITY FRAME PERIOD AND JITTER, FCC§15.323 (E) 48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Digital Cordless Telephone
Tested Model	Motorola CD501-B
Frequency Range	1920-1930 MHz
Transmit Power	18.81 dBm (0.076W)
Modulation Technique	GFSK
Antenna Specification	0 dBi
Voltage Range	DC 6V from adapter
Date of Test	2019-03-04 ~ 2019-04-16
Sample serial number	190131007
Received date	2019-01-31
Sample/EUT Status	Good condition
Adapter information	Adapter 1 Model: BLJ05W060040P-UA Input: AC 100-240V~50/60Hz, 0.2A Output: DC 6.0V, 400 mA Adapter 2 Model: HJ-0600400A1-US Input: AC 100-240V~50/60Hz, 0.15A Max Output: DC 6.0V, 400 mA

Objective

This test report was based on the *Meizhou Guo Wei Electronics Co., Ltd* tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17-2013.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.207, 15.315, 15.317, 15.319 and 15.323 rules.

Related Submittal(s)/Grant(s)

Submitted with PUE Handset unit submission with FCC ID: 2ARRB-G31X18HS.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2013, American National Standard Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communications Services (UPCS) Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty
RF conducted test with spectrum	±1.6dB
Occupied Bandwidth	±5%
Temperature	±1℃
Humidity	±6%
Supply voltages	±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing mode which is provided by the manufacturer.

Equipment Modifications

No modification was made to the EUT tested.

Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Digital Radio Communication Test	CMD60	830861/029
Unknown	Load	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Un-detachable DC Power Cable	1.5	EUT	Adapter
Un-shielding Detachable RJ11 Cable	3.0	EUT	Load

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 15.319 (i)&2.1091	Maximum Permissible exposure (MPE)	Compliance
§ 15.317, § 15.203	Antenna Requirement	Compliance
§ 15.315, § 15.207	Conducted Emission	Compliance
§ 15.323 (a)	Emission Bandwidth	Compliance
§ 15.319 (c)	Peak Transmit Power	Compliance
§ 15.319 (d)	Power Spectral Density	Compliance
§ 15.323 (d)	Emission Inside and Outside the sub-band	Compliance
§ 15.319 (g)	Radiated Emission	Not Applicable
§ 15.323 (f)	Frequency Stability Handset	Compliance
§ 15.323 (c)(e) § 15.319 (f)	Specific Requirements for UPCS	Compliance

Not Applicable: EUT is compliance with 15.323 (d).
Note: Pre-scan with two antennas for conducted peak power, and antenna 1 for the max power one, which was selected to test conducted items.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-02
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Unknown	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
RF Conducted test					
Ducommun Technologies	RF Cable	RG-214	3	Each Time	
WEINSCHEL	3dB Attenuator	6231	666	Each Time	
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2019-03-02	2020-03-01
Unknown	Power Splitter	1620	129	Each Time	
Rohde & Schwarz	Digital Radio Communication Test	CMD60	830861/029	2018-06-23	2019-06-23
TDK	Chamber	Chamber B	1#	2018-09-20	2021-09-19
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2018-06-23	2019-06-23

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

§1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to FCC §15.319(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	842/f	2.19/f	*(180/f\2\)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm^2);
P = power input to the antenna (in appropriate units, e.g., mW);
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For worst case:

Frequency (MHz)	Antenna Gain		Maximum Tune-up power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
	(dBi)	(numeric)	(dBm)	(mW)			
1921.536 - 1928.448	0	1.0	19.0	79.4	20	0.016	1.0

Result: The device meets MPE limit at 20 cm distance.

FCC§15.317 & §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has two integral antennas, the antennas gain are 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC§15.315 & §15.207 - CONDUCTED EMISSIONS

Applicable Standard

FCC§15.315, an unlicensed PCS device that is designed to be connected to the public utility (AC) power line must meet the limits specified in §15.207.

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.315 and FCC 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding the Outlet Cable Loss, LISN Insertion Loss, Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = Outlet Cable Loss + LISN Insertion Loss + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-04-16.

Test mode: Transmitting

Adapter 1:

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.165500	45.6	19.9	65.2	19.6	QP
0.189500	43.1	19.8	64.1	21.0	QP
0.286500	38.4	19.7	60.6	22.2	QP
0.306530	40.4	19.7	60.1	19.7	QP
0.317230	39.6	19.8	59.8	20.2	QP
0.463010	41.9	19.8	56.6	14.7	QP
0.165500	27.0	19.9	55.2	28.2	Ave.
0.189500	28.3	19.8	54.1	25.8	Ave.
0.286500	32.3	19.7	50.6	18.3	Ave.
0.306530	33.4	19.7	50.1	16.7	Ave.
0.317230	33.6	19.8	49.8	16.2	Ave.
0.463010	32.2	19.8	46.6	14.4	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.154500	45.7	19.8	65.8	20.1	QP
0.181500	44.2	19.8	64.4	20.2	QP
0.193500	43.3	19.8	63.9	20.6	QP
0.217500	41.3	19.8	62.9	21.6	QP
0.297470	45.0	19.7	60.3	15.3	QP
0.463010	42.9	19.8	56.6	13.7	QP
0.154500	28.3	19.8	55.8	27.5	Ave.
0.181500	27.6	19.8	54.4	26.8	Ave.
0.193500	29.0	19.8	53.9	24.9	Ave.
0.217500	30.2	19.8	52.9	22.7	Ave.
0.297470	39.4	19.7	50.3	10.9	Ave.
0.463010	35.3	19.8	46.6	11.3	Ave.

Adapter 2:

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.293500	40.4	19.7	60.4	20.0	QP
0.325170	38.5	19.8	59.6	21.1	QP
8.472030	38.2	20.0	60.0	21.8	QP
9.267730	41.4	20.0	60.0	18.6	QP
9.493450	42.1	20.0	60.0	17.9	QP
10.313490	41.1	20.0	60.0	18.9	QP
0.293500	33.6	19.7	50.4	16.8	Ave.
0.325170	34.2	19.8	49.6	15.4	Ave.
8.472030	30.1	20.0	50.0	19.9	Ave.
9.267730	33.7	20.0	50.0	16.3	Ave.
9.493450	34.7	20.0	50.0	15.3	Ave.
10.313490	34.4	20.0	50.0	15.6	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.285500	44.4	19.7	60.7	16.3	QP
0.298500	47.4	19.7	60.3	12.9	QP
0.336990	42.7	19.8	59.3	16.6	QP
9.238290	41.5	19.9	60.0	18.5	QP
10.143430	42.7	20.0	60.0	17.3	QP
10.361070	41.3	20.0	60.0	18.7	QP
0.285500	39.2	19.7	50.7	11.5	Ave.
0.298500	40.0	19.7	50.3	10.3	Ave.
0.336990	35.7	19.8	49.3	13.6	Ave.
9.238290	34.1	19.9	50.0	15.9	Ave.
10.143430	35.8	20.0	50.0	14.2	Ave.
10.361070	34.5	20.0	50.0	15.5	Ave.

Note:
1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
2) Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC§15.323 (a) - EMISSION BANDWIDTH

Applicable Standard

Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:

Test Setup 1:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test mode: Transmitting

Channel	Center Frequency (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.47	50 kHz ~ 2.5 MHz
Middle	1924.992	1.47	50 kHz ~ 2.5 MHz
High	1928.448	1.47	50 kHz ~ 2.5 MHz

Test Result: Compliance. Please refer to the following plots.

Low Channel



Date: 4.MAR.2019 10:46:27

Middle Channel



Date: 4.MAR.2019 10:53:24

High Channel



Date: 4.MAR.2019 10:56:17

FCC§15.319 (c) - PEAK TRANSMIT POWER

Applicable Standard

The peak power output as measured over an interval of time equal to the frame rate or transmission burst of the device under all conditions of modulation. Usually this parameter is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used[47 CFR 15, subpart D, 15.303].

The peak transmit power is according to ANSI C63.17-2013 §6.1.2

Per FCC Part15.319 (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Per FCC Part15.319 (e), the peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Calculation of Peak Transmit Power Limit:
Peak Transmit Power Limit = $100\mu W \times (EBW)^{1/2}$
EBW is the transmit emission bandwidth in Hz determined in the other test item:

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	≥ Emission bandwidth
Video bandwidth	≥ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test Result: Compliance. Please refer to the following table and plots.

Note: Pre-scan with two antennas for conducted peak power, and antenna 1 for the max power one was recorded.

Test mode: Transmitting:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	Limit (dBm)
Low	1921.536	18.66	20.83
Middle	1924.992	18.76	20.83
High	1928.448	18.81	20.83
$EBW_{Low\ channel}$ = 1466346Hz, $EBW_{Middle\ channel}$ = 1466346 Hz, $EBW_{High\ channel}$ = 1466346 Hz Peak Transmit Power Limit = $100(EBW)^{1/2}$ μW			

Low Channel



Middle Channel



Date: 4.MAR.2019 10:28:30

High Channel



Date: 4.MAR.2019 10:29:35

FCC§15.319 (d) - POWER SPECTRAL DENSITY

Applicable Standard

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

The power spectral density is measured in accordance with ANSI C63.17.2013 Clause 6.1.5.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	≥ 3 × RBW
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 μs). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test Result: Compliance. Please refer to following table and plots

Test mode: Transmitting

Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)	Result
		(dBm/3kHz)	(mW/3kHz)		
Low	1921.536	-5.87	0.259	3	Pass
Middle	1924.992	-3.97	0.401	3	Pass
High	1928.448	-5.02	0.315	3	Pass

Low Channel



Date: 4.MAR.2019 11:16:09



Date: 4.MAR.2019 11:18:14

Middle Channel



Date: 4.MAR.2019 11:11:34



Date: 4.MAR.2019 11:13:14

High Channel



Date: 4.MAR.2019 11:05:09



Date: 4.MAR.2019 11:08:51

FCC§15.323 (d) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND

Applicable Standard

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

   Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mw (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

Test Procedure

According to ANSI C63.17-2013 Clause 6.1.6.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.6 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test mode: Transmitting

Test Result: Compliance. Please refer to following plots

Low Channel (Unwanted Emission inside the Sub-band)



Date: 4.MAR.2019 11:45:56

Middle Channel (Unwanted Emission inside the Sub-band)



Date: 4.MAR.2019 11:57:15

High Channel (Unwanted Emission inside the Sub-band)



Date: 4.MAR.2019 12:01:09

Low Channel (Unwanted Emission outside the Sub-band)



Date: 4.MAR.2019 11:50:23



Date: 4.MAR.2019 11:50:45



Date: 4.MAR.2019 11:51:09



Date: 4.MAR.2019 11:51:26



Date: 4.MAR.2019 11:52:06

Middle Channel (Unwanted Emission outside the Sub-band)



Date: 4.MAR.2019 11:53:50



Date: 4.MAR.2019 11:54:06



Date: 4.MAR.2019 11:54:22



Date: 4.MAR.2019 11:54:39



Date: 4.MAR.2019 11:53:20

High Channel (Unwanted Emission outside the Sub-band)



Date: 4.MAR.2019 12:01:37



Date: 4.MAR.2019 12:01:59



Date: 4.MAR.2019 12:02:20



Date: 4.MAR.2019 12:02:41



Date: 4.MAR.2019 12:03:20

FCC§15.323 (f) - FREQUENCY STABILITY

Applicable Standard

Per §15.323(f), the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ±10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of −20℃ to +50℃ at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20 ℃. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage

Test Procedure

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20℃	85-115% or new batteries
-20℃	Normal
+50℃	Normal

During test, the equipment shall be placed in the boxes and set the temperature to the specified requirement until the thermal balance has been reached.

Using the mean carrier frequency at 20℃ and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ±10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20℃) at the two extreme supply voltages.
This test does not apply to a EUT that is capable only of operating from a battery.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.6 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test Result: Compliance.

Test mode: Transmitting

Temperature (℃)	Voltage (V_{DC})	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	6	1924.992	3.2	1.66	±10
20	5.4	1924.992	3.1	1.61	±10
	6.6	1924.992	4.8	2.49	±10
50	6	1924.992	3.5	1.82	±10

FCC§15.323 (c) (e) & §15.319(f) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE

Applicable Standard

FCC§15.323(c)(e) & §15.319(f) Specific Requirements for UPCS device.
ANSI C63.17 2013 §6.2 Frequency and time stability and §7.Monitoring tests and §8.Time and spectrum window access procedure.

Test Procedure

Measurement method according to ANSI C63.17 -2013

Test configuration as below



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Moon Tan on 2019-03-04.

Test Result: Compliance, please see the below data

1) Automatic Discontinuation of Transmission, FCC §15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Test result:

The following tests were performed after a connection had been established with handset.

Test condition	Reaction of EUT	Pass/Fail
Adapter removed from EUT	Connection break down	Pass
The Handset power off	Connection break down	Pass

2) Monitoring Time, FCC §15.323(c) (1)

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

Test procedure:

Measurement method is in according to ANSI C63.17 2013 clause 7.3.3.
RF signal generators apply uniform CW interference on all system carriers except two carriers (designated f_1 and f_2), each at level $T_L + U_M$. EUT can only transmit on these two carriers.

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC).

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_L+U_M+20dB and no interference on f_2. Initiate transmission and verify the transmission only on f_2. Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level T_L+U_M+20dB and immediately remove all interference from *f*1. The EUT should immediately attempt transmission on *f*1 (but at least 20 ms after the interference on *f*2 is applied), verify the transmission only on f_1.	EUT transmission f_1	Pass

3) Lower Monitoring Threshold, FCC §15.323(c) (2)

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 7.3.1

Test result:

Not applicable because the EUT has more 40 defined duplex system access channels and meet the provision of the Least Interfered Channel (LIC) based on FCC §15.323(c) (5).

4) Maximum Transmit Period, FCC §15.323(c) (3)

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Test procedure:

Measurement method according to ANSI C63.17- 2013 clause 8.2.2
The test procedure is as follows:
a) Activate the EUT and initiate a communication channel with the companion device, and start a timer or frame counter.
b) The centre frequency of spectrum analyzer was set to the carrier frequency and SPAN was set to ZERO. The spectrum analyzer was used to monitor the time and spectrum window of the communication channel.
c) Stop the timer at the end of the EUT transmission on the current time and frequency window (measure the time until the EUT changes to a different slot).

Test result:

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	17680	28,800	Pass
Second	17566	28,800	Pass

5) System Acknowledgement, FCC §15.323(c) (4)

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease.
Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 8.2.1
During testing initial transmission without acknowledgement, the signal from the EUT to the companion device is blocked by the circulator.

The test of the transmission time after loss of acknowledgements is performed by cutting off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

Test result:

Test	Time taken (second)	Limit (second)	Result
Initial Connection acknowledgement	0.30	1	Pass
Change of access criteria for control information	N/A	30	N/A
Transmission cease time after loss of acknowledgement	4.32	30	Pass

Note: N/A=Not Applicable

6) Least Interfered Channel (LIC), FCC §15.323(c) (5)

If access to spectrum is not available as determined by the above, and a minimum of 20 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level may be accessed.

A device utilizing the provisions of this paragraph (5) must have monitored all access channels defined for its system within the last 10 seconds and must verify, within the 20 milliseconds (40 milliseconds for devices designed to use a 20 millisecond frame period) immediately preceding actual channel access, that the detected power of the selected time and spectrum windows is no higher than the previously detected value.
The power measurement resolution bandwidth for this comparison must be accurate to within 6 dB.
No device or group of cooperating devices located within 1 metre of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold: $T_L = -174+10Log_{10}B + M_L + P_{MAX}-P_{EUT}$ (dBm)
Where: B=Emission bandwidth (Hz)
M_L = dB the threshold may exceed thermal noise (30 for T_L)
$P_{MAX} = 5Log_{10}B-10$(dBm)
P_{EUT} = Transmitted power (dBm)

Calculated thresholds:

Monitor Threshold	B(MHz)	M_L(dB)	P_{MAX} (dBm)	P_{EUT} (dBm)	Threshold (dBm)
Lower threshold	1.466	30	20.83	18.68	-80.19

Note: 1. The upper threshold is applicable as the EUT utilizes more than 20 duplex system channels

Test procedure:

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3

C63.17 clause 7.3.2, LIC procedure test:

a) Allow EUT transmission on only two carrier frequencies, which will be designated *f*1 and *f*2.

b) Apply interference to the EUT on *f*1 at a level of *TL* + *UM* + 7 dB and on *f*2 at a level of *TL* + *UM*. Initiate transmission. The EUT should transmit on *f*2. Terminate the connection. Repeat five times. If the EUT transmits once on *f*1, the test failed.

c) Apply interference to the EUT on *f*1 at a level of *TL* + *UM* and on *f*2 at a level of *TL* + *UM* + 7 dB. Initiate transmission. The EUT should transmit on *f*1. Terminate the connection. Repeat five times. If the EUT transmits once on *f*2, the test failed.

d) Apply interference to the EUT on *f*1 at a level of *TL* + *UM* + 1 dB and on *f*2 at a level of *TL* + *UM* − 6 dB. Initiate transmission. If the EUT transmits on *f*2, terminate the connection. Repeat five times. If the EUT transmits once on *f*1, the test failed.

e) Apply interference to the EUT on *f*1 at a level of *TL* + *UM* − 6 dB and on *f*2 at a level of *TL* + *UM* + 1 dB. Initiate transmission. If the EUT transmits on *f*1, terminate the connection. Repeat five times. If the EUT transmits once on *f*2, the test failed.

C63.17 clause 7.3.3, Selected channel confirmation:

a) Allow EUT transmission on only two carrier frequencies, which will be designated f1 and f2. This limitation to carriers f1 and f2 is performed preferably by administration commands for the EUT, or alternatively by applying by a multicarrier interference generator uniform interference on all system carriers except f1 and f2, at a level of TL + UM + 20 dB in-band per carrier. Set the interference level to the EUT on f1 to a level of TL + UM + 20dB, and let there be no interference applied on f2.

b) Initiate transmission and verify that the EUT transmits on f2. If a connection was made, terminate it.

c) Apply interference on f2 at a level of TL + UM + 20 dB in-band, and immediately remove all interference from f1 and immediately (but not sooner than 20 ms after the interference on f2 is applied) cause the EUT to attempt transmission. The EUT should now transmit on f1, if it transmits.

d) If the EUT transmits on f2, it fails.

Test result:

1) LIC procedure test:

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_L+U_M+7dB and the interference on f_2 at level T_L+U_M. Initiate transmission and verify the transmission only on f_2. Repeat 5 times.	EUT transmits on f_2	Pass
b) Apply the interference on f_1 at level T_L+U_M and the interference on f_2 at level T_L+U_M+7dB. Initiate transmission and verify the transmission only on f_1. Repeat 5 times.	EUT transmits on f_1	Pass
c) Apply the interference on f_1 at level T_L+U_M+1dB the interference on f_2 at level T_L+U_M-6dB. Initiate transmission and verify the transmission only on f_2. Repeat 5 times.	EUT transmits on f_2	Pass
d) Apply the interference on f_1 at level T_L+U_M-6dB and the interference on f_2 at level T_L+U_M+1dB. Initiate transmission and verify the transmission only on f_1. Repeat 5 times.	EUT transmits on f_1	Pass

2) Selected channel confirmation:

Interference (Refer to ANSI C63.17 clause 7.3.4)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_U+U_M and no interference on f_2. Initiate transmission and verify the transmission only on f_2. Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level T_L+U_M and immediately remove all interference from *f*1. The EUT should immediately attempt transmission on *f*1 (but at least 20 ms after the interference on *f*2 is applied), verify the transmission only on f_1.	EUT transmission f_1	Pass

7) Random waiting, FCC §15.323(c) (6)

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Test procedure:

This test is for EUTs that transmit control and signaling channels and that use the provisions of FCC §15.323(c)(6), thus to verify that the EUT (if in deferral) waits for a channel to go clear, then implements a 10 ms to 150 ms holdoff prior to using the channel. FCC §15.323(c)(6) is not restrictive for EUTs that use the LIC and offer 20 or more duplex communications channels, as a combined time and spectrum window cannot become unavailable as there is no threshold limit.Test method according to ANSI C63.17 2013 clause 8.1.3

a) Restrict operation of the EUT to a single carrier designated *f*1. For TDMA system, further restrict EUT transmission to a single timeslot of the usable timeslots available in the TDMA frame structure and synchronize the interference so as to occur centered within the timeslot.

b) Activate the EUT with no interference present. The EUT must transmit on *f*1. Then apply CW interference on *f*1. The interference level shall be at *TL* + *UM* as appropriate for EUTs that do or do not meet the requirements for using the upper threshold. The EUT must stop transmitting within 30 s.

c) Cancel the interference. Measure the time interval between the end of the interference transmission and the beginning of transmission by the EUT.

d) Repeat step b) and step c) 100 times. If the measured time intervals vary uniformly between 10 ms and 150 ms, the EUT passes the test.

Note:This is Not Applicable

8) Monitoring Bandwidth and Reaction Time, FCC §15.323(c) (7)

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than 50xSQRT (1.25/emission bandwidth in MHz) microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 7.5

a) Restrict the EUT to a single transmit carrier frequency *f*1, and verify that the EUT can establish a connection with no interference applied on *f*1.

b) Apply time-synchronized, pulsed interference on *f*1 at the pulsed level *TL* + *UM*, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 50 µs and $50\sqrt{1.25/B}$ µs, where *B* is the emission bandwidth of the EUT in megahertz.

c) With the channel interference level 6 dB above *TL* + *UM*, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 35 µs and $35\sqrt{1.25/B}$ µs, where *B* is the emission bandwidth of the EUT in megahertz.

Test Pulse width Equation (µs)	B(bandwidth) (MHz)	Pulse width (µs)	Limit (largest) (µs)
$50\ (1.25/B)^{1/2}$	1.466	46.17	50
$35\ (1.25/B)^{1/2}$	1.466	32.32	35

Test result:

1) Monitoring Bandwidth:

The antenna of the EUT used for monitoring is the same interior antenna that used for transmission, so the monitoring system bandwidth is equal to the emission bandwidth of the intended transmission

2) Reaction Time Test:

No.	Interference Pulse width (µs)	Reaction of EUT	Observing time (µs)	Result
1	50µs with level T_L+U_M	No transmission	25.77	Pass
2	35µs with level T_L+U_M+6dB	No transmission	18.56	Pass

9) Monitoring Antenna, FCC §15.323(c) (8)

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

Test procedure:

Measurement method according to ANSI C63.17 2013 paragraph 4

Test result:

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

10) Monitoring threshold relaxation, FCC §15.323(c) (9)

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Test procedure:

Measurement method according to ANSI C63.17 2013 paragraph 4

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC) based on FCC §15.323(c)(5).

11) Duplex Connections, FCC §15.323(c) (10)

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

Test procedure:

This test validates proper operation of an EUT that operates according to the provisions of FCC §15.323(c)(10) using a check of both transmit and receive channels on one end of the link to qualify both ends of the link for transmissions. Test method according to ANSI C63.17 clause 8.3.2 Validation of dual access criteria check for EUTs that implement the upper threshold

a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 40 dB above *TL* + *UM*.

b) Restrict the EUT and its companion device to operation at a single carrier *f*1 for TDMA systems and on *f*1 and *f*2 and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection on a time/spectrum window on the enabled carrier(s). Terminate the connection.

c) Apply interference to the EUT on the EUT's *transmit* time/spectrum windows at *TL* + *UM* per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below *TL*. Adjust the interference to the EUT on its *receive* time/spectrum windows such that a single time/spectrum window has interference at least 10 dB below *TL*, and the interference on the other time/spectrum windows is at *TL* + *UM* + 7 dB. The interference to the companion device should be at least 10 dB below *TL* on all active time/spectrum windows. The interference-free *receive* time/spectrum window must not be the duplex mate of the interference-free *transmit* time/spectrum window.

d) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *receive* time/spectrum window and its duplex mate. Otherwise, the EUT fails the test.

e) If a connection exists, terminate it. Reduce the interference on the EUT's *receive* time/spectrum windows to a level of *TL* + *UM* per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below *TL*. Raise the interference on the EUT's *transmit* time/spectrum windows to a level of *TL* + *UM* + 7 dB, maintaining one time/spectrum window with interference at least 10 dB below *TL*. The interference to the companion device should be at least 10 dB below *TL* on

all active time/spectrum windows. Again, the interference-free *transmit* and *receive* time/spectrum windows should not constitute a duplex pair if the system designates a specific duplex pairing for time/spectrum windows.

f) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *transmit* time/spectrum window and its duplex mate. Otherwise, the system fails the test.

Test result:

Interference (Refer to ANSI C63.17 § 8.3.2)	Reaction of EUT	Results
a) Only a single carrier f1 for EUT TDMA systems and on *f*1 and *f*2 and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) All Tx windows with level TL+UM except one & Rx windows with level TL+UM+7dB except one, which are not the duplex mate.	Connected on the target Rx window and its duplex mate.	Pass
c) All Tx windows with level TL+UM+7dB except one & Rx windows with level TL+UM except one, which are not duplex mate.	Connected on the target Tx window and its duplex mate.	Pass
d) All Tx & Rx windows with level TU+UM, except one for Tx window & one for Rx window, which are not duplex mate.	No connection possible	Pass

12) Alternative monitoring interval, FCC §15.323(c) (11)

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Test procedure:

This test validates the ability of the EUT to distinguish between same-system and other-system interference for purposes of satisfying the requirement of 47CFR15.323(c) (11). Test method according to ANSI C63.17 2013 clause 8.4

a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above *TL*.

b) Restrict the EUT and its companion device to operation at a single carrier *f*1 for TDMA systems and on *f*1 and *f*2 and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection.

c) Apply interference at *TL* + *UM* per carrier to the EUT on all *transmit* time/spectrum windows on the enabled carrier(s). The interference must use the same physical layer parameters (modulation, frame format, etc.) as the EUT transmissions, but with a system identifier different from that used by the EUT and the companion device. Ensure that the interference level at the companion device is at least 10 dB below *TL*. Apply no interference to the *receive* time/spectrum windows on the enabled carriers.

d) Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

Test result:

Interference (Refer to ANSI C63.17 § 8.4)	Reaction of EUT	Results
a) Only a single carrier f1 for EUT TDMA systems and on *f*1 and *f*2 and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) Apply interference with same parameters as EUT transmissions on all Tx windows with level TL+UM on the enabled carrier(s) and no interference on the Rx windows on the enabled carriers.	No connection is established	Pass

13) Fair Access, FCC §15.323(c) (12)

The provisions of FCC §15.323 (c) (10) or (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Test result:

The manufacturer declares that this device does not use any mechanisms as provided by FCC §15.323(c)(10) or (11) to extend the range of spectrum occupied over space or time for the purpose of denying fail access to spectrum to other device.

14) Frame Repetition Stability Frame Period and Jitter, FCC§15.323 (e)

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

Test procedure:

Measurement method according to ANSI C63.17- 2013 clause 6.2.2, 6.2.3

Test result:

Frame Period and Jitter:

Max. pos. Jitter (µs)	Max. neg. Jitter (µs)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (µs)
0.07	-0.07	10.01	20 or10/X	0.10

Note: X is a positive whole number.

******* END OF REPORT *******