



FCC TEST REPORT

FCC ID:2BETZ-I116

Report Number.....: ZKT-250214L2297E

Date of Test.....: Jan. 8, 2025 to Jan. 21, 2025

Date of issue.....: Feb. 28, 2025

Test Result: PASS

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: ShenZhen Aibo Technology Co., Ltd

Address: 3/F, A Bldg, RunFeng Industry Park, 4197 BaoAn Road, Gushu. XiXiang, BaoAn, Shenzhen

Manufacturer's name: ShenZhen Aibo Technology Co., Ltd

Address: 3/F, A Bldg, RunFeng Industry Park, 4197 BaoAn Road, Gushu. XiXiang, BaoAn, Shenzhen

Test specification:

Standard.....: FCC CFR Title 47 Part 15 Subpart C

Test procedure.....: /

Non-standard test method: N/A

Test Report Form No.....: TRF-EL-107_V0

Test Report Form(s) Originator.....: ZKT Testing

Master TRF: Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....: Power Combo Charging Tower

Trademark: /

Model/Type reference.....: i116Max
i116Pro, i116, PowerSync-105, RN105

Model difference.....: i116Max is tested model, other models are derivative models .The models are identical in circuit, only different on the model names and appearance colors. So the test data of i116 can represent the remaining models.

Ratings.....: Input: AC 100~240V, 50/60Hz, 2.5A
Total Output Power: 105W(Max)
Type-C1 Output:5V---3A, 9V---2.22A, 12V---1.67A, 20W(Max)
USB-A Output(Alone use):5V---3A,9V---2A,12V---1.5A, 18W(Max)
Type-C2 Cable Output: 5V --- 3A, 9V --- 3A, 12V --- 3A, 15V --- 3A, 20V---3.25A, 65W(Max)(Alone use)
PPS:3.3V-11V---3A, 3.3V-21V---3A
Lightning Cable Output(Optional):
5V---3A, 9V---2.22A, 20W(Max)(Alone use)
Type-C3 Cable Output:5V --- 3A, 9V --- 3A, 12V --- 3A, 15V --- 3A, 20V---3.25A, 65W(Max)(Alone use)
PPS:3.3V-11V---3A, 3.3V-21V---3A
USB-A+Type-C2 Cable Output:5V---3A, 15W(Max)
Type-C2 Cable+Type-C3 Cable Output:20W+45W
Type-C1+Type-C2 Cable+Type-C3 Cable Output:20W+20W+45W
Type-C1+USB-A+Type-C2 Cable+Type-C3 Cable Output: 20W+5V---3A(USB-A+Type-C2 Cable)+45W
Wireless Output for Phone:5W, 7.5W, 15W(Max)
Wireless Output for Earbuds: 3W, 5W(Max)



Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

**Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China**

Tested by (name + signature).....: Jim Liu

Jim Liu

Reviewer (name + signature).....: Jackson Fang

Jackson Fang

Approved (name + signature).....: Lake Xie

Lake Xie



TABLE OF CONTENTS

1. VERSION	4
2. TEST SUMMARY	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 Test mode	8
3.3 Block Diagram of EUT Configuration	9
3.4 Test Conditions	9
3.5 Description Of Support Units (Conducted Mode)	9
3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. CONDUCTED EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 Test Result	14
5. RADIATED EMISSION MEASUREMENT	16
5.1 Radiated Emission Limits	16
5.2 Anechoic Chamber Test Setup Diagram	17
5.3 Test Procedure	18
5.4 DEVIATION FROM TEST STANDARD	18
5.5 Test Result	19
6. BANDWIDTH TEST	24
7. ANTENNA REQUIREMENT	27
8. TEST SETUP PHOTO	28
9. EUT CONSTRUCTIONAL DETAILS	28



1. VERSION

Report No.	Version	Description	Approved
ZKT-250214L2297E	Rev.01	Initial issue of report	Feb. 28, 2025



2. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:
(1) "N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	AC Conducted Emission Test	$\pm 1.38\text{dB}$
2	3m chamber Radiated spurious emission(9KHz-30MHz)	$U=4.5\text{dB}$
3	3m chamber Radiated spurious emission(30MHz-1GHz)	$U=4.8\text{dB}$
4	3m chamber Radiated spurious emission(1GHz-18GHz)	$U=4.9\text{dB}$
5	3m chamber Radiated spurious emission(18GHz-40GHz)	$U=5.0\text{dB}$
6	Conducted Adjacent channel power	$U=1.38\text{dB}$
7	Conducted output power uncertainty Above 1G	$U=1.576\text{dB}$
8	Conducted output power uncertainty below 1G	$U=1.28\text{dB}$
9	humidity uncertainty	$U=5.3\%$
10	Temperature uncertainty	$U=0.59^{\circ}\text{C}$



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Power Combo Charging Tower
Test Model No.:	i116Max
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	Phone charging: 110.1-205 kHz Earbuds charging: 110.1-205 kHz
Modulation type:	MSK
Antenna Type:	Inductive loop coil Antenna
Antenna gain:	0dBi
Power supply:	Input: AC 100~240V, 50/60Hz, 2.5A Total Output Power: 105W(Max) Type-C1 Output:5V---3A, 9V---2.22A, 12V---1.67A, 20W(Max) USB-A Output(Alone use):5V---3A,9V---2A,12V---1.5A, 18W(Max) Type-C2 Cable Output: 5V --- 3A, 9V --- 3A, 12V --- 3A, 15V --- 3A, 20V---3.25A, 65W(Max)(Alone use) PPS:3.3V-11V---3A, 3.3V-21V---3A Lightning Cable Output(Optional): 5V---3A, 9V---2.22A, 20W(Max)(Alone use) Type-C3 Cable Output:5V --- 3A, 9V --- 3A, 12V --- 3A, 15V --- 3A, 20V---3.25A, 65W(Max)(Alone use) PPS:3.3V-11V---3A, 3.3V-21V---3A USB-A+Type-C2 Cable Output:5V---3A, 15W(Max) Type-C2 Cable+Type-C3 Cable Output:20W+45W Type-C1+Type-C2 Cable+Type-C3 Cable Output:20W+20W+45W Type-C1+USB-A+Type-C2 Cable+Type-C3 Cable Output: 20W+5V---3A(USB-A+Type-C2 Cable)+45W Wireless Output for Phone:5W, 7.5W, 15W(Max) Wireless Output for Earbuds: 3W, 5W(Max)




3.2 Test mode

Test Modes:	
Mode 1	AC Mains + Phone charging port(15W) + Earbuds charging port(Battery Status: $\leq 1\%$)
Mode 2	AC Mains + Phone charging port(15W) + Earbuds charging port(Battery Status:50%)
Mode 3	AC Mains + Phone charging port(15W) + Earbuds charging port(Battery Status: ≥ 98)
Mode 4	AC Mains + iPhone charging port(7.5W) + Earbuds charging port(Battery Status: $\leq 1\%$)
Mode 5	AC Mains + iPhone charging port(7.5W) + Earbuds charging port(Battery Status:50%)
Mode 6	AC Mains + iPhone charging port(7.5W) + Earbuds charging port(Battery Status: ≥ 98)
Mode 7	AC Mains + Phone charging port(5W) + Earbuds charging port(Battery Status: $\leq 1\%$)
Mode 8	AC Mains + Phone charging port(5W) + Earbuds charging port(Battery Status:50%)
Mode 9	AC Mains + Phone charging port(5W) + Earbuds charging port(Battery Status: ≥ 98)
Mode 10	AC Mains + Phone charging port(15W)
Mode 11	AC Mains + Phone charging port(7.5W)
Mode 12	AC Mains + Phone charging port(5W)
Mode 13	AC Mains + Earbuds charging port(Battery Status: $\leq 1\%$)
Mode 14	AC Mains + Earbuds charging port(Battery Status:50%)
Mode 15	AC Mains + Earbuds charging port(Battery Status: ≥ 98)
Mode 16	Standby
Note: All modes were tested, only the worst-case was recorded in the report. Mode 1 is the worst mode.	




3.3 Block Diagram of EUT Configuration

Conducted Emission



Radiated Emission



3.4 Test Conditions

Temperature: 23~26℃

Relative Humidity: 54~63 %

3.5 Description Of Support Units (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Wireless charging power parameters	Note
E-1	Power Combo Charging Tower	N/A	i116Max	N/A	N/A	EUT
E-2	Wireless charging load	N/A	EESON	N/A	5 W/ 7.5 W/ 10 W/ 15W	AE
E-3	AirPods	Apple	A2031	N/A	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation emissions& Radio Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Sep. 29, 2024	Sep. 28, 2025
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	00877	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Sep. 30, 2024	Sep. 29, 2025
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Sep. 30, 2024	Sep. 29, 2025
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Oct. 11, 2024	Oct. 10, 2025
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Sep. 29, 2024	Sep. 28, 2025
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Sep. 30, 2024	Sep. 29, 2025
11	Test Cable	N/A	R-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
12	Test Cable	N/A	R-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
13	Test Cable	N/A	R-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



Conducted emissions Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	RF-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	Test Cable	N/A	RF-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Test Cable	N/A	RF-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
6	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Sep. 29, 2024	Sep. 28, 2025
7	Signal Generator	Agilent	N5182A	N/A	A.01.87	Sep. 29, 2024	Sep. 28, 2025
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Van der Hoofden measuring head	Schwarzbeck Mess-elektronik	VDHH 9502	9502-039	N/A	Sep. 30, 2024	Sep. 29, 2025
10	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Sep. 30, 2024	Sep. 29, 2025
11	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
12	D.C. Power Supply	LongWei	TPR-6405 D	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
13	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\



4. CONDUCTED EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1814	47.98	9.90	57.88	64.42	-6.54	QP	P
2	0.1814	26.35	9.90	36.25	54.42	-18.17	AVG	P
3	0.2084	47.61	9.91	57.52	63.27	-5.75	QP	P
4	0.2084	23.61	9.91	33.52	53.27	-19.75	AVG	P
5	0.2535	45.90	9.93	55.83	61.64	-5.81	QP	P
6	0.2535	25.41	9.93	35.34	51.64	-16.30	AVG	P
7	0.3795	42.56	9.98	52.54	58.29	-5.75	QP	P
8	0.3795	27.83	9.98	37.81	48.29	-10.48	AVG	P
9 *	0.5955	40.56	10.03	50.59	56.00	-5.41	QP	P
10	0.5955	26.88	10.03	36.91	46.00	-9.09	AVG	P
11	0.8024	40.52	10.04	50.56	56.00	-5.44	QP	P
12	0.8024	19.84	10.04	29.88	46.00	-16.12	AVG	P

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1590	48.21	9.89	58.10	65.52	-7.42	QP	P
2	0.1590	31.81	9.89	41.70	55.52	-13.82	AVG	P
3	0.2172	47.73	9.92	57.65	62.93	-5.28	QP	P
4	0.2172	29.38	9.92	39.30	52.93	-13.63	AVG	P
5	0.2391	46.43	9.93	56.36	62.13	-5.77	QP	P
6	0.2391	30.67	9.93	40.60	52.13	-11.53	AVG	P
7	0.2802	45.06	9.94	55.00	60.81	-5.81	QP	P
8	0.2802	26.95	9.94	36.89	50.81	-13.92	AVG	P
9 *	0.5127	41.18	10.02	51.20	56.00	-4.80	QP	P
10	0.5127	25.20	10.02	35.22	46.00	-10.78	AVG	P
11	0.8160	40.76	10.05	50.81	56.00	-5.19	QP	P
12	0.8160	21.94	10.05	31.99	46.00	-14.01	AVG	P

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor



5. RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

5.1 Radiated Emission Limits

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value


Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value




5.2 Anechoic Chamber Test Setup Diagram

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



5.3 Test Procedure

Below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving loop antenna and in the center of a loop antenna, which was mounted on the top of a variable-height antenna tower.
- c. For each suspected emission, the EUT was arranged to its worst case, the height of interference-receiving loop antenna centre is 1 meter above the ground, and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- d. Both coaxial (loop plane perpendicular to the ground plane and to the measurement axis) and coplanar (loop plane perpendicular to the ground plane and coplanar with the measurement axis) polarizations of the antenna are set to make the measurement.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

30MHz-1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

5.4 DEVIATION FROM TEST STANDARD

No deviation




5.5 Test Result

Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80
Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.117	68.04	0.16	68.20	106.24	-38.04	Peak
2	0.141	67.48	0.16	67.64	104.68	-37.04	Peak
3	0.287	51.22	0.71	51.93	98.45	-46.52	Peak
4	0.668	43.94	1.44	45.38	71.11	-25.73	QP
5	1.087	41.64	2.29	43.93	66.88	-22.95	QP
6 *	1.540	39.73	3.22	42.95	63.85	-20.90	QP




Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 10





Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 13



Remarks:

Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Emission Level = Meter Reading - Factor


Margin = Emission Level- Limit.

The amplitude of emissions which are attenuated by more than 20db below the permissible value has no need to be reported.




30MHz-1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1





Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.



6. BANDWIDTH TEST

1. Set RBW = 1%-5%OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP






Temperature:	25.7 °C	Relative Humidity:	55%
Pressure:	101kPa		


	Frequency (KHz)	20dB bandwidth (KHz)	Result
Phone charging coil	141	0.199	Pass
Earbuds charging coil	117.3	0.054	Pass

Phone charging coil





Earbuds charging coil





7. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	
	The antenna is Coil Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details



8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****