

Annex 1: Measurement diagrams 20-1-0094901T09a-A1

Number of pages:	13	Date of Report:	2021-Sep-06
Testing company:	CETECOM GmbH Im Teelbruch 116 45219 Essen Germany Tel. + 49 (0) 20 54 / 95 19-0 Fax: + 49 (0) 20 54 / 95 19-150	Applicant:	Prodrive Technologies B.V.
Product: Model:	RFID Reader RFID Reader		
FCC ID:	Y2IRFIDR	IC:	9389A-RFIDR
Testing has been carried out in accordance with:	Title 47 CFR, Chapter I FCC Regulations, Subchapter A Part 15, Subpart C: §15.209 RSS-Gen, Issue 5 + Amendment 1 General Requirements for Compliance of Radio Apparatus FCC 15.209 Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		



Table of Contents

1 Measurement diagrams.....3

 Occupied bandwidth tests.....13

1 Measurement diagrams

2.01_H_Field_TX_standing


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TX 125 kHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



2.02_H_Field_TX_lying


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TX 125 kHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



2.03_H_Field_TXRX_lying


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TXRX 125 kHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



2.04_H_Field_TXRX_lying


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TXRX 125 kHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



2.05_RSE_TX_standing


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TX 13,56 MHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



2.06_RSE_TXRX_standing


Common Information

Test Description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Chamber (SAC1) with 3 m measurement distance
Version of Testsoftware:	EMC32 V10.50.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used Filter:	bypass
Test Standard:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	SSanthakum
Operating Mode:	TXRX 125 kHz
Power during tests:	12 V DC 110 V/60 Hz, full loaded batteries
Comment 1:	Channel low/middle/high
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
EUT Setup:	1
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
-------------	-------------------

Full Spectrum



3.01_RSE_TX_standing


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.205&15.209 & RSS Gen. Issue 5
Antenna polarisation:	horizontal/vertical
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
Operating Mode:	TX
Comment:	Channel no. low/middle/high
Verdict:	Passed

EUT Information

PMT number: 20-1-00949S04_C02

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)
---	---	---	---	---	---		---	---	---	---	---

(continuation of the "Final_Result" table from column 19 ...)

Frequency (MHz)	Raw Rec (dBµV)	Comment
---	---	


3.02_RSE_TX_lying

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.205&15.209 & RSS Gen. Issue 5
Antenna polarisation:	horizontal/vertical
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
Operating Mode:	TX
Comment:	Channel no. low/middle/high
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
	Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---	---

(continuation of the "Final_Result" table from column 19 ...)

Frequency (MHz)	Raw Rec (dBµV)	Comment
---	---	---


3.03_RSE_TXRX_standing

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.205&15.209 & RSS Gen. Issue 5
Antenna polarisation:	horizontal/vertical
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
Operating Mode:	TXRX 125 kHz
Comment:	Channel no. low/middle/high
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
	Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---	---

(continuation of the "Final_Result" table from column 19 ...)

Frequency (MHz)	Raw Rec (dBµV)	Comment
---	---	---


3.04_RSE_TXRX_lying

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.205&15.209 & RSS Gen. Issue 5
Antenna polarisation:	horizontal/vertical
Environmental Conditions::	Humidity : 50% rH; Temperature: 20 °C
Operating Mode:	TXRX 125 kHz
Comment:	Channel no. low/middle/high
Verdict:	Passed

EUT Information

PMT number:	20-1-00949S04_C02
	Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB/m)
---	---	---	---	---	---	---	---	---	---	---	---

(continuation of the "Final_Result" table from column 19 ...)

Frequency (MHz)	Raw Rec (dBµV)	Comment
---	---	---


Occupied bandwidth tests

EUT TX mode (without RFID tag)



Date: 6.SEP.2021 08:23:52

EUT TXRX mode (with RFID tag)



Date: 6.SEP.2021 08:28:13

End Of Annex 1