



F2 Labs
16740 Peters Road
Middlefield, Ohio 44062
United States of America
www.f2labs.com

MPE REPORT

Manufacturer: Runwise, Inc.
104 West 27th Street, Floor 3
New York, New York 10001 USA

Applicant: Same as Above

Product Name: Gen2 Wireless Network Module

Product Description: Serial UART to RF network interface, 900 MHz Radio

Model: V4.0

FCC ID: 2AQX2-G2RWHPMOD

IC: 24232-G2RWHPMOD

Testing Commenced: 2024-01-11

Testing Ended: 2025-01-10

Test Results: In Compliance

The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.

Standards:

- KDB447498
- FCC 1.1310
- Safety Code 6
- RSS-102



Evaluation Conducted by:

Julius Chiller, Senior Wireless Project Engineer

Report Reviewed by:

Ken Littell, Vice President of Operations

F2 Labs
26501 Ridge Road
Damascus, MD 20872
Ph 301.253.4500

F2 Labs
16740 Peters Road
Middlefield, OH 44062
Ph 440.632.5541

F2 Labs
8583 Zionsville Road
Indianapolis, IN 46268
Ph 317.610.0611

This test report may be reproduced in full; partial reproduction only may be made with the written consent of F2 Labs. The results in this report apply only to the equipment tested.



TABLE OF CONTENTS

1	<u>ADMINISTRATIVE INFORMATION</u>
2	<u>SUMMARY OF TEST RESULTS/MODIFICATIONS</u>
3	<u>ENGINEERING STATEMENT</u>
4	<u>EUT INFORMATION AND DATA</u>
5	<u>RF EXPOSURE FOR DEVICE >20cm FROM HUMAN</u>
	➤ <u>FCC</u>
	➤ <u>IC</u>



1 ADMINISTRATIVE INFORMATION

1.1 Measurement Location:

F2 Labs in Middlefield, Ohio.

Site description and attenuation data are on file with the FCC's Sampling and Measurement Branch at the FCC Laboratory in Columbia, MD.

Site description and attenuation data are on file with the Certification and Engineering Bureau, Industry Canada, Site Number 4730B.

1.2 Measurement Procedure:

All measurements were performed according to:

- KDB558074
- FCC 15.247
- FCC 15.249
- RSS-247
- RSS-210

1.4 Document History

Document Number	Description	Issue Date	Approved By
F2P30751A-R1-05E	First Issue	2025-01-28	K. Littell



2 SUMMARY OF TEST RESULTS

Test Name	Standard(s)	Results
RF Exposure for Device >20cm from Human	KDB447498 FCC 1.1310 Safety Code 6 RSS-102	Complies

Modifications Made to the Equipment
None



3 **ENGINEERING STATEMENT**

This report has been prepared on behalf of Runwise, Inc. to provide documentation for the calculations described herein, based on the measurements taken in supporting Test Reports. This equipment has been tested and calculations were found to comply with KDB447498, FCC 1.1310, Safety Code 6 and RSS-102. The test results found in this test report relate only to the item(s) tested.



4 EUT INFORMATION AND DATA

4.1 Equipment Under Test:

Product: Gen2 Wireless Network Module - 900 MHz Radio

Model: V4.0

Serial No.: 412

Firmware: V4.0

Hardware: V1.0.3

FCC ID: 2AQX2-G2RWHPMOD

IC: 24232- G2RWHPMOD

4.2 Trade Name:

Runwise, Inc.

4.3 Power Supply:

Module is DC powered at 3.7VDC nominal

4.4 Applicable Rules:

- KDB447498
- FCC 1.1310
- Safety Code 6
- RSS-102

4.5 Equipment Category:

Radio Transmitter-FHSS

4.6 Antenna:

2.5dBi Dipole

6dBi Omni Antenna

8dBi Yagi Antenna

4.7 Accessories:

Device	Manufacturer	Model Number	Serial Number
Test Fixture	Texas Instruments	CC1350	Rev1.3.0
Accessory Software Version:		FW Rev:1.0	

4.8 Test Item Condition:

The equipment to be tested was received in good condition.

**5. RF EXPOSURE FOR DEVICE >20cm FROM HUMAN****5.1 Requirements: Distance used is 20cm**

FCC	
Limit:	2402 MHz = 1mW/cm ² 902.4 MHz = 0.602mW/cm ²
Formula Used for Result:	$\frac{E.I.R.P.}{4 \pi R^2}$
Results:	<p>E.I.R.P. = 0.03mW</p> <p>0.03mW at the 2402 MHz Low Channel (highest)</p> $P(dBm) = E(dBuV/m) + 20 \log(d) - G - 104.77$ $80 + 9.542425 + 0 - 104.77 = -15.23dBm$ $P(dBm) = -15.23 \text{ which is } 0.03mW$ $\frac{0.03mW}{4 \pi R^2} = \frac{0.03 mW}{5026.55} = 0.000006 mW/cm^2$ <p>0.000006 mW/cm² is below the 1mW/cm² limit</p>
	<p>900 MHz E.I.R.P. = 3499mW</p> <p>3499mW at the 902.4 MHz Low Channel with 8 dBi Yagi antenna. The transmission has a duty cycle range of 0.027% to 30.5% with the max duty cycle possible being 30.5%. The max time-averaged power is 1066mW.</p> $\frac{1066mW}{4 \pi R^2} = \frac{1066mW}{5026.55} = 0.212 mW/cm^2$ <p>0.212 mW/cm² is below the limit of 0.602mW/cm² for 20cm distance.</p>



IC	
Limit:	2402 MHz = 5.35W/m ² 902.4 MHz = 2.74W/m ²
Formula Used for Result:	$\frac{E.I.R.P.}{4 \pi R^2}$
Results:	<p>E.I.R.P. = 0.03mW</p> <p>0.03mW at the 2402 MHz Low Channel (highest)</p> $P(dBm) = E(dBuV/m) + 20 \log(d) - G - 104.77$ $80 + 9.542425 + 0 - 104.77 = -15.23dBm$ $P(dBm) = -15.23 \text{ which is } 0.03mW$ $\frac{0.03mW}{4 \pi R^2} = \frac{0.03 mW}{5026.55} = 0.00006 W/m^2$ <p>0.00006 W/m² is below the 5.35 W/m² limit</p>
	<p>900 MHz E.I.R.P. = 3499mW</p> <p>3499mW at the 902.4 MHz Low Channel with 8 dBi Yagi antenna. The transmission has a duty cycle range of 0.027% to 30.5% with the max duty cycle possible being 30.5%. The max time-averaged power is 1066mW.</p> $\frac{1066mW}{4 \pi R^2} = \frac{1066mW}{5026.55} = 2.12 W/m^2$ <p>2.12 W/m² is below the limit of 2.74W/m² for 20cm distance.</p>