


RF TEST REPORT

Applicant iRay Technology Co., Ltd.
FCC ID 2ACHK-02113698
Product Digital Wireless Intraoral X-Ray Sensor
Brand iRayTechnology
Model Pluto0002XW
Report No. R2202A0183-R1V1
Issue Date April 19, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2022)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.



Prepared by: Xu Ying



Approved by: Xu Kai

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the Test Report	5
1.2. Test Facility	5
1.3. Testing Location	5
2. General Description of Equipment Under Test	6
2.1. Applicant and Manufacturer Information	6
2.2. General Information	6
3. Applied Standards	7
4. Test Configuration	8
5. Test Case Results	9
5.1. Unwanted Emission	9
5.2. Conducted Emission	35
6. Main Test Instruments	38
ANNEX A: The EUT Appearance	39
ANNEX B: Test Setup Photos	40

Version	Revision description	Issue Date
Rev.0	Initial issue of report.	April 10, 2023
Rev.1	Update description.	April 19, 2023
Note: This revised report (Report No.: R2202A0183-R1V1) supersedes and replaces the previously issued report (Report No.: R2202A0183-R1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of Measurement Results

Number	Test Case	Clause in FCC rules	Verdict
1	Unwanted Emissions	15.247(d),15.205,15.209	PASS
2	Conducted Emissions	15.207	PASS
Date of Testing: August 29, 2022 ~ February 16, 2023			
Date of Sample Received: February 28, 2022			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

There is only test Unwanted Emissions and Conducted Emissions for Pluto0002XW in this report. Other test items refer to the module report (Report No.: RF160104C01).

1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment Under Test

2.1. Applicant and Manufacturer Information

Applicant	iRay Technology Co., Ltd.
Applicant address	RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China
Manufacturer	iRay Technology Co., Ltd.
Manufacturer address	RM 202, Building 7, No. 590, Ruiqing RD., Pudong, Shanghai, China

2.2. General Information

EUT Description	
Model	Pluto0002XW
Lab internal SN	R2202A0183/S02
Hardware Version	MCU: 43907_V3.3.0.44 MCU: 54907_V3.3.0.44 FPGA: Ma179.0.1.4
Software Version	Dental_SDK_ReleasePackage_4.5.3.10417
Power Supply	Battery / AC adapter
Antenna Type	Stamping Antenna
Antenna Gain	4.80 dBi
Operating Frequency Range(s)	802.11b/g/n(HT20): 2412 ~ 2462 MHz
Modulation Type	802.11b: DSSS 802.11g/n(HT20): OFDM
EUT Accessory	
Adapter	Manufacturer: Dongguan Shilong Fuhua Electronic Co., LTD. Model: UES12LCP-050200SPA
Battery	Manufacturer: Zhengzhou BAK Battery Co., LTD. Model: N18650CL-29
Auxiliary test equipment	
PC	Manufacturer: DELL Model: Latitude 3400 (SN : 7VK5ZZ2)
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.	

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15C (2022) Radio Frequency Devices

ANSI C63.10-2013

Reference standard:

KDB 558074 D01 15.247 Meas Guidance v05r02

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the loop antenna is vertical, the others are vertical and horizontal. and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Test Mode	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

5. Test Case Results

5.1. Unwanted Emission

Ambient Condition

Temperature	Relative humidity
20°C ~25°C	45%~50%

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10.

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. Sweep the Restricted Band and the emissions less than 20 dB below the permissible value are reported.

The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

This method refer to ANSI C63.10.

The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:

Set the spectrum analyzer in the following:

9kHz~150 kHz

RBW=200Hz, VBW=1kHz/ Sweep=AUTO

150 kHz~30MHz

RBW=9KHz, VBW=30KHz,/ Sweep=AUTO

Below 1GHz

RBW=100kHz / VBW=300kHz / Sweep=AUTO

a) Peak emission levels are measured by setting the instrument as follows:

Above 1GHz

PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

b) Average emission levels are measured by setting the instrument as follows:

Above 1GHz

AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

c) Detector: The measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set

for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.


2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.


The test is in transmitting mode.

Test Setup


9KHz~ 30MHz



30MHz~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 15.247(d) specifies that “In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).”

Limit in restricted band

Frequency of emission (MHz)	Field strength($\mu\text{V/m}$)	Field strength($\text{dB}\mu\text{V/m}$)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30–88	100	40
88–216	150	43.5
216–960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Peak Limit=74 $\text{dB}\mu\text{V/m}$

Average Limit=54 $\text{dB}\mu\text{V/m}$

Spurious Radiated Emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.17 dB
200MHz-1GHz	4.84 dB
1-18GHz	4.35 dB
18-26.5GHz	5.90 dB
26.5GHz~40GHz	5.92 dB

Test Results:


A symbol ($\text{dB } \mu\text{V}/\text{m}$) in the test plot below means ($\text{dB}\mu\text{V}/\text{m}$)




802.11b-Channel 1 Peak+ Average




802.11b-Channel 11 Peak+ Average




802.11g-Channel 1 Peak+ Average



802.11g-Channel 11 Peak+ Average



802.11n HT20 -Channel 1 Peak+ Average



802.11n HT20 -Channel 11 Peak+ Average

Result of RE

Test result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the Emissions in the frequency band 9kHz-30MHz and 18GHz-26.5GHz are more than 20dB below the limit are not reported.


The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

Continuous TX mode:

Wi-Fi 2.4G

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11b, Channel 6 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

A symbol ($\text{dB } \mu\text{V/m}$) in the test plot below means (dB $\mu\text{V/m}$)




Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB $\mu\text{V/m}$)	Limit (dB $\mu\text{V/m}$)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
39.46	19.77	40.00	20.23	100.0	V	0.00	19
75.02	34.09	40.00	5.91	100.0	V	106.00	14
125.00	27.37	43.50	16.13	100.0	V	284.00	16
149.99	29.98	43.50	13.52	100.0	V	141.00	15
275.03	37.53	46.00	8.47	175.0	V	78.00	20
375.04	37.97	46.00	8.03	125.0	V	334.00	22


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit – Quasi-Peak

802.11b CH1



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1025.00	---	32.92	54.00	21.08	500.00	200.0	V	105.00	-8
1105.75	42.00	---	74.00	32.00	500.00	100.0	H	273.00	-8
1249.00	---	29.24	54.00	24.76	500.00	100.0	H	47.00	-7
1250.50	40.84	---	74.00	33.16	500.00	100.0	H	297.00	-7
1413.75	43.92	---	74.00	30.08	500.00	100.0	H	56.00	-6
1440.75	---	32.08	54.00	21.92	500.00	100.0	H	65.00	-6
1729.75	---	33.57	54.00	20.43	500.00	200.0	V	0.00	-4
1731.50	45.10	---	74.00	28.90	500.00	100.0	H	162.00	-4
1925.00	---	36.81	54.00	17.19	500.00	100.0	V	136.00	-3
2037.00	47.36	---	74.00	26.64	500.00	100.0	V	210.00	-2
2991.50	---	37.24	54.00	16.76	500.00	100.0	H	107.00	2
2993.00	48.74	---	74.00	25.26	500.00	100.0	H	0.00	2


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11b CH6



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1025.00	---	32.99	54.00	21.01	500.00	200.0	V	65.00	-8
1083.25	42.78	---	74.00	31.22	500.00	100.0	H	134.00	-8
1330.25	44.28	---	74.00	29.72	500.00	100.0	V	175.00	-6
1424.75	---	32.08	54.00	21.92	500.00	200.0	V	203.00	-6
1659.75	---	33.86	54.00	20.14	500.00	200.0	V	221.00	-4
1659.75	46.62	---	74.00	27.38	500.00	200.0	V	221.00	-4
1925.00	---	36.71	54.00	17.29	500.00	100.0	V	51.00	-3
1996.00	48.79	---	74.00	25.21	500.00	100.0	V	157.00	-2
2230.50	46.42	---	74.00	27.58	500.00	100.0	V	308.00	-1
2244.50	---	34.57	54.00	19.43	500.00	100.0	V	91.00	-1
2656.00	55.89	---	74.00	18.11	500.00	200.0	V	172.00	0
2656.00	---	39.38	54.00	14.62	500.00	200.0	V	172.00	0


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11b CH11



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1056.00	41.71	---	74.00	32.29	500.00	200.0	V	237.00	-8
1062.25	---	30.06	54.00	23.94	500.00	100.0	V	121.00	-8
1234.00	40.63	---	74.00	33.37	500.00	100.0	H	85.00	-7
1236.75	---	29.44	54.00	24.56	500.00	200.0	V	347.00	-7
1411.00	43.75	---	74.00	30.25	500.00	200.0	H	115.00	-6
1420.75	---	31.97	54.00	22.03	500.00	100.0	H	204.00	-6
1725.25	---	33.89	54.00	20.11	500.00	200.0	H	356.00	-4
1732.00	45.13	---	74.00	28.87	500.00	100.0	H	98.00	-4
1924.75	---	36.78	54.00	17.23	500.00	100.0	V	55.00	-3
2053.75	46.73	---	74.00	27.27	500.00	100.0	V	214.00	-2
2762.00	49.10	---	74.00	24.90	500.00	200.0	V	50.00	1
2762.75	---	36.51	54.00	17.49	500.00	100.0	H	7.00	1


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11g CH1



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1024.75	---	33.36	54.00	20.64	500.00	200.0	V	203.00	-8
1032.00	41.94	---	74.00	32.06	500.00	200.0	H	71.00	-8
1149.25	42.77	---	74.00	31.23	500.00	200.0	V	236.00	-8
1158.75	---	30.68	54.00	23.32	500.00	200.0	H	194.00	-7
1375.00	---	32.29	54.00	21.71	500.00	100.0	V	134.00	-6
1433.50	43.45	---	74.00	30.55	500.00	100.0	V	171.00	-6
1594.75	45.41	---	74.00	28.59	500.00	200.0	V	347.00	-5
1729.50	---	33.45	54.00	20.55	500.00	200.0	H	185.00	-4
1925.00	---	36.93	54.00	17.07	500.00	100.0	V	16.00	-3
2005.00	47.48	---	74.00	26.52	500.00	100.0	H	140.00	-2
2829.50	48.82	---	74.00	25.18	500.00	200.0	V	226.00	1
2947.75	---	37.46	54.00	16.54	500.00	100.0	H	318.00	2


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11g CH6



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1024.75	---	32.94	54.00	21.06	500.00	200.0	V	130.00	-8
1026.75	41.26	---	74.00	32.74	500.00	200.0	V	337.00	-8
1156.50	42.39	---	74.00	31.61	500.00	100.0	V	264.00	-8
1171.25	---	30.06	54.00	23.94	500.00	100.0	V	214.00	-7
1422.00	---	32.05	54.00	21.95	500.00	100.0	H	252.00	-6
1427.75	44.10	---	74.00	29.90	500.00	100.0	V	219.00	-6
1714.75	44.21	---	74.00	29.79	500.00	200.0	V	199.00	-4
1720.75	---	33.50	54.00	20.50	500.00	200.0	V	94.00	-4
1925.00	---	37.30	54.00	16.70	500.00	100.0	V	50.00	-3
2075.25	46.47	---	74.00	27.53	500.00	200.0	V	112.00	-2
2982.75	49.22	---	74.00	24.78	500.00	100.0	V	181.00	2
2995.00	---	37.26	54.00	16.74	500.00	200.0	V	190.00	2


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11g CH11



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1025.00	---	33.59	54.00	20.41	500.00	200.0	V	124.00	-8
1025.25	41.70	---	74.00	32.30	500.00	200.0	V	119.00	-8
1173.25	42.40	---	74.00	31.60	500.00	200.0	V	323.00	-7
1185.75	---	30.25	54.00	23.75	500.00	100.0	V	8.00	-7
1435.75	---	32.16	54.00	21.84	500.00	200.0	V	239.00	-6
1440.75	43.76	---	74.00	30.24	500.00	200.0	H	9.00	-6
1666.00	45.64	---	74.00	28.36	500.00	100.0	V	22.00	-4
1724.25	---	33.52	54.00	20.48	500.00	100.0	H	0.00	-4
1925.00	---	37.38	54.00	16.62	500.00	100.0	V	55.00	-3
2029.25	46.91	---	74.00	27.09	500.00	100.0	V	198.00	-2
2755.25	47.42	---	74.00	26.58	500.00	100.0	H	341.00	1
2772.75	---	36.55	54.00	17.45	500.00	100.0	H	115.00	1


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11n (HT20) CH1



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1056.00	41.80	---	74.00	32.20	500.00	200.0	V	287.00	-8
1074.75	---	31.67	54.00	22.33	500.00	100.0	V	121.00	-8
1211.50	42.38	---	74.00	31.62	500.00	100.0	V	236.00	-7
1213.50	---	31.15	54.00	22.85	500.00	100.0	V	17.00	-7
1420.50	---	32.22	54.00	21.78	500.00	100.0	H	107.00	-6
1424.25	43.84	---	74.00	30.16	500.00	100.0	V	157.00	-6
1669.25	45.60	---	74.00	28.40	500.00	200.0	V	12.00	-4
1728.25	---	33.68	54.00	20.32	500.00	100.0	H	222.00	-4
1925.00	---	36.10	54.00	17.90	500.00	200.0	V	187.00	-3
1996.50	46.89	---	74.00	27.11	500.00	100.0	V	185.00	-2
2817.25	---	37.32	54.00	16.68	500.00	100.0	H	241.00	1
2897.75	48.92	---	74.00	25.08	500.00	100.0	H	288.00	2


Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

802.11n (HT20) CH6



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1025.25	---	31.54	54.00	22.46	500.00	200.0	V	1.00	-8
1025.50	43.66	---	74.00	30.34	500.00	100.0	V	35.00	-8
1174.75	---	32.90	54.00	21.10	500.00	100.0	H	123.00	-7
1177.25	42.28	---	74.00	31.72	500.00	100.0	H	60.00	-7
1425.75	---	32.66	54.00	21.34	500.00	100.0	H	46.00	-6
1435.50	44.20	---	74.00	29.80	500.00	100.0	V	118.00	-6
1650.25	45.93	---	74.00	28.07	500.00	100.0	V	62.00	-4
1692.75	---	33.44	54.00	20.56	500.00	200.0	H	63.00	-4
1925.00	---	36.09	54.00	17.91	500.00	100.0	V	280.00	-3
2009.75	46.63	---	74.00	27.37	500.00	200.0	V	220.00	-2
2500.25	---	37.28	54.00	16.72	500.00	200.0	V	256.00	0
2666.50	48.93	---	74.00	25.07	500.00	100.0	V	208.00	1

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)


2. Margin = Limit –MAX Peak/ Average

802.11n (HT20) CH11



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz




Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1093.00	42.28	---	74.00	31.72	500.00	100.0	V	222.00	-8
1099.75	---	30.26	54.00	23.74	500.00	200.0	V	153.00	-8
1268.75	42.98	---	74.00	31.02	500.00	200.0	H	205.00	-7
1275.00	---	32.54	54.00	21.46	500.00	200.0	V	219.00	-7
1451.75	44.26	---	74.00	29.74	500.00	200.0	H	348.00	-6
1460.50	---	32.45	54.00	21.55	500.00	100.0	H	187.00	-6
1695.75	45.33	---	74.00	28.67	500.00	100.0	H	304.00	-4
1730.75	---	33.66	54.00	20.34	500.00	100.0	H	196.00	-4
1925.00	---	35.96	54.00	18.04	500.00	100.0	V	0.00	-3
2050.50	46.77	---	74.00	27.23	500.00	100.0	V	274.00	-2
2780.50	47.62	---	74.00	26.38	500.00	200.0	V	277.00	1
2784.75	---	36.76	54.00	17.24	500.00	200.0	V	75.00	1

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit –MAX Peak/ Average

During the test, the Radiates Emission from 18GHz to 26.5GHz was performed in all modes with all channels, 802.11b, Channel 6 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.



Radiates Emission from 18GHz to 26.5GHz

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
18416.50	---	40.38	54.00	13.62	500.00	100.0	H	0.00	-2
18431.38	52.02	---	74.00	21.98	500.00	200.0	H	300.00	-2
19418.44	---	40.74	54.00	13.26	500.00	100.0	H	118.00	-1
19435.44	51.73	---	74.00	22.27	500.00	100.0	V	0.00	-1
20593.56	---	39.05	54.00	14.95	500.00	200.0	H	256.00	0
20606.31	50.81	---	74.00	23.19	500.00	100.0	H	29.00	0
22701.56	---	37.78	54.00	16.22	500.00	100.0	V	196.00	3
22705.81	48.77	---	74.00	25.23	500.00	100.0	V	230.00	3
24163.56	---	37.41	54.00	16.59	500.00	100.0	H	280.00	3
24171.00	49.16	---	74.00	24.84	500.00	200.0	V	198.00	3
25902.88	46.75	---	74.00	27.25	500.00	100.0	H	0.00	5
25936.88	---	35.61	54.00	18.39	500.00	100.0	V	283.00	4

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)
2. Margin = Limit –MAX Peak/ Average

5.2. Conducted Emission

Ambient Condition

Temperature	Relative humidity
20°C ~25°C	45%~50%


Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz.

The measurement result should include both L line and N line.

The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50


*: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:


Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes with all channels, 802.11b, Channel 6 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.35	---	37.35	48.96	11.61	1000.00	9.000	L1	ON	21
0.36	45.37	---	58.80	13.43	1000.00	9.000	L1	ON	21
0.37	41.03	---	58.44	17.41	1000.00	9.000	L1	ON	21
0.48	---	31.93	46.33	14.40	1000.00	9.000	L1	ON	20
0.90	---	28.98	46.00	17.02	1000.00	9.000	L1	ON	20
0.91	34.13	---	56.00	21.87	1000.00	9.000	L1	ON	20
4.25	27.28	---	56.00	28.72	1000.00	9.000	L1	ON	19
4.28	---	20.42	46.00	25.58	1000.00	9.000	L1	ON	19
5.14	---	16.64	50.00	33.36	1000.00	9.000	L1	ON	19
5.27	19.65	---	60.00	40.35	1000.00	9.000	L1	ON	19
29.39	16.73	---	60.00	43.27	1000.00	9.000	L1	ON	20
29.94	---	15.70	50.00	34.30	1000.00	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.31	---	34.93	49.98	15.05	1000.00	9.000	N	ON	21
0.31	41.03	---	59.86	18.83	1000.00	9.000	N	ON	21
0.37	42.23	---	58.44	16.21	1000.00	9.000	N	ON	21
0.38	---	34.38	48.34	13.96	1000.00	9.000	N	ON	21
0.88	---	25.18	46.00	20.82	1000.00	9.000	N	ON	20
0.89	29.96	---	56.00	26.04	1000.00	9.000	N	ON	20
4.31	26.20	---	56.00	29.80	1000.00	9.000	N	ON	19
4.33	---	19.59	46.00	26.41	1000.00	9.000	N	ON	19
6.97	---	17.85	50.00	32.15	1000.00	9.000	N	ON	20
7.10	21.26	---	60.00	38.74	1000.00	9.000	N	ON	20
26.02	16.25	---	60.00	43.75	1000.00	9.000	N	ON	20
29.98	---	15.72	50.00	34.28	1000.00	9.000	N	ON	20

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 KHz to 30 MHz

6. Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	102389	2022-05-25	2023-05-24
Signal Analyzer	R&S	FSV40	100816	2022-05-14	2023-05-13
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2020-05-05	2023-05-04
Horn Antenna	R&S	HF907	102723	2021-07-24	2024-07-23
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2020-12-13	2022-12-12
				2022-12-13	2024-12-09
EMI Test Receiver	R&S	ESR	101667	2022-05-25	2023-05-24
Software	R&S	EMC32	10.35.10	/	/

*****END OF REPORT *****

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.