

Date / Time:	10/8/2003 3:38:14 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averagi ng:	6			
Batteries				

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

Two 3D SAR plots are shown. The left plot displays SAR distribution in a 3D volume with axes X (mm) from -100 to 100, Y (mm) from 0 to 30, and Z (mm) from -200 to 50. The right plot displays SAR distribution in a 3D volume with axes X (mm) from -100 to 100, Y (mm) from -100 to 100, and Z (mm) from -200 to -50. A color scale at the bottom indicates SAR (W/kg) from 0.0 to 1.6.

ZOOM SCAN RESULTS:

Spot SAR

(W/kg):

Start Scan

0.439

End Scan

0.437

**Change during
Scan (%)**

-0.24

Max E-field

(V/m):

37.93

Max SAR

(W/kg)

1g

1.191

10g

0.769

**Location of
Max (mm):**

X

75.1

Y

3.0

Z

-187.7

A 2D AREA SCAN plot showing SAR distribution in a 2D plane. The horizontal axis is labeled 'Y (mm)' and ranges from -100 to 100. The vertical axis is labeled 'Z (mm)' and ranges from 0 to -300. The plot shows a color-coded SAR distribution, with a color bar at the bottom indicating values from 0.1 to 0.9 W/kg. A yellow rectangular outline highlights a specific region of interest, and a smaller green rectangular outline highlights a sub-region within it. The SAR distribution is highest (red/orange) in the center of the highlighted region and decreases (blue) towards the edges.

AREA SCAN:

Scan Extent:

	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-200.0	-110.0	10.0

Date of Report: 04/26/2004



Appendix A Plots

Page 2 of 39

Date / Time:	10/8/2003 4:17:41 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular to phantom	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 3 of 39

Date / Time:	10/8/2003 5:10:20 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 4 of 39

Date / Time:	10/8/2003 4:44:57 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 5 of 39

Date / Time:	10/9/2003 9:46:13 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	824.2
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			



Liquid:	850
Type:	body
Conductivity:	0.977
Relative Permittivity:	56.2
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	4/6/2004 1:25:08 PM	Position:	Lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC83	Head Rotation:	0
Antenna:	parallel	Test Frequency:	848.8
Shape File:	broadcom381lap_newant.csv	Power Level:	max 2 timeslots TX

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	03/23/04			

Liquid:	850
Type:	Body
Conductivity:	0.987
Relative Permittivity:	55.36
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	10/9/2003 10:15:43 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	848.8
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	sv		

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.992
Relative Permittivity:	55.33
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

Two 3D SAR scan visualizations are shown. The left plot displays a color-coded SAR distribution over a grid of X (mm) from -5 to 25 and Y (mm) from -5 to 25, with Z (mm) from -195 to 50. The right plot shows a 3D grid of SAR values with a yellow box highlighting a region of interest. A color bar at the bottom indicates SAR values from 0.0 to 1.6 W/kg.

ZOOM SCAN RESULTS:

Spot SAR

(W/kg):

Start Scan

0.512

End Scan

0.518

**Change during
Scan (%)**

1.10

Max E-field

(V/m):

40.27

Max SAR

(W/kg)

1g

1.339

10g

0.879

Location of

Max (mm):

X

75.0

Y

-6.0

Z

-184.9

2D AREA SCAN plot showing a color-coded map of the phantom. The color scale ranges from 0.1 to 1.0 W/kg. The X-axis is labeled 'X (mm)' and ranges from -100 to 100. The Y-axis is labeled 'Y (mm)' and ranges from -300 to 0. A yellow rectangular box highlights the central region of the phantom, and a blue rectangular box highlights the central region of the color scale.

AREA SCAN:

Scan Extent:

	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-200.0	-110.0	10.0

Date of Report: 04/26/2004



Appendix A Plots

Page 8 of 39

Date / Time:	10/9/2003 11:08:03 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 9 of 39

Date / Time:	10/9/2003 11:33:09 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular to phantom	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	4/6/2004 9:58:15 AM	Position:	bystander 1cm
Filename:	inspiron600_vby661_3d.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC83	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	max 2 timeslots TX

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	03/23/04			

Liquid:	1900
Type:	Body
Conductivity:	1.549
Relative Permittivity:	52.65
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

A 3D surface plot showing the SAR distribution within a head phantom. The vertical axis is labeled 'Z (mm)' and ranges from -170 to 50. The horizontal axes are 'Y (mm)' ranging from -20 to 15 and 'X (mm)' ranging from -100 to 100. The plot shows a color-coded SAR distribution with a peak in the center of the head.

A 3D wireframe plot showing the SAR distribution within a head phantom. The vertical axis is labeled 'Z (mm)' and ranges from -170 to 50. The horizontal axes are 'Y (mm)' ranging from -100 to 100 and 'X (mm)' ranging from -100 to 100. The plot shows a color-coded SAR distribution with a peak in the center of the head.

A horizontal color scale bar for SAR (W/kg). The scale ranges from 0.0 (blue) to 1.0 (red), with intermediate values at 0.2, 0.4, 0.6, and 0.8. The label 'SAR (W/kg)' is centered below the bar.

ZOOM SCAN RESULTS:

Spot SAR

(W/kg):

Change during

Scan (%)

Max E-field

(V/m):

Max SAR

(W/kg)

Location of

Max (mm):

Start Scan

0.201

End Scan

0.201

0.00

25.44

1g

10g

0.802

0.436

X

Y

Z

75.1

-21.6

-159.5

The figure displays two plots related to SAR (Specific Absorption Rate) scans. The left plot is a 2D cross-section of a head phantom, showing a color-coded SAR distribution. The color scale ranges from 0.0 (black) to 1.0 (red), with intermediate values in yellow, green, and blue. The right plot is a 3D scan of a head phantom, showing a color-coded SAR distribution. The color scale ranges from 0.0 (black) to 1.0 (red), with intermediate values in yellow, green, and blue. The 3D plot includes a yellow rectangular region of interest on the side of the head, indicating the area of focus for the scan.

AREA SCAN:



	Min	Max	Steps
Y	-40.0	40.0	10.0
Z	-200.0	-120.0	10.0

Scan Extent:

Date / Time:	10/9/2003 11:59:59 AM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 12 of 39

Date / Time:	10/9/2003 12:25:03 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 13 of 39

Date / Time:	10/9/2003 12:58:01 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1850.2
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.539
Relative Permittivity:	53.42
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 14 of 39

Date / Time:	10/9/2003 1:25:31 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1909.8
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.551
Relative Permittivity:	53.02
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 15 of 39

Date / Time:	10/7/2003 1:49:51 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 16 of 39

Date / Time:	10/7/2003 2:16:14 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 17 of 39

Date / Time:	10/7/2003 3:09:28 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 18 of 39

Date / Time:	10/7/2003 2:43:13 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.983
Relative Permittivity:	55.62
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420




Date of Report: 04/26/2004

Appendix A Plots

Page 19 of 39


Date / Time:	10/7/2003 3:37:20 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel	Test Frequency:	824.02
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106	Liquid:	850
Cal File:	106_835_BODY_28	Type:	body
Cal Factors:		Conductivity:	0.974
		Relative Permittivity:	55.06
		Liquid Temp (deg C):	22.0
		Ambient Temp (deg C):	22.0
Amp Gain:	2	Ambient RH (%):	50
Averaging:	6	Density (kg/m3):	1000
Batteries Replaced:	10/03/2003	Software Version:	0.420



ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.532	0.532
Change during Scan (%)	0.12	
Max E-field (V/m):	35.55	
Max SAR (W/kg)	1g	10g
	1.104	0.787
Location of Max (mm):	X	Y
	75.0	-1.0
		Z
		-157.9



AREA SCAN:

Scan Extent:

	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-200.0	-110.0	10.0

Date of Report: 04/26/2004



Appendix A Plots

Page 20 of 39

Date / Time:	10/7/2003 4:07:17 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel	Test Frequency:	824.02
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.979
Relative Permittivity:	55.44
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 21 of 39

Date / Time:	10/8/2003 10:57:29 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 22 of 39

Date / Time:	10/8/2003 11:35:00 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 23 of 39

Date / Time:	10/8/2003 1:41:41 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 24 of 39

Date / Time:	10/8/2003 1:14:39 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.545
Relative Permittivity:	53.26
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 25 of 39

Date / Time:	10/8/2003 2:17:48 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1850.2
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.539
Relative Permittivity:	53.42
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 26 of 39

Date / Time:	10/8/2003 2:55:41 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1909.8
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.551
Relative Permittivity:	53.02
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 27 of 39

Date / Time:	10/10/2003 11:46:32 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 28 of 39

Date / Time:	10/10/2003 12:11:19 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular o phantom	Test Frequency:	835
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 29 of 39

Date / Time:	10/10/2003 12:44:28 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 30 of 39

Date / Time:	10/10/2003 1:09:53 PM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	835
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 31 of 39

Date / Time:	10/10/2003 1:44:45 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	824.02
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			



Liquid:	850
Type:	body
Conductivity:	0.977
Relative Permittivity:	56.2
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	10/10/2003 2:22:48 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	848.8
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_835_BODY_28			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.357	0.357	0.357
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	850
Type:	body
Conductivity:	0.992
Relative Permittivity:	55.33
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 33 of 39

Date / Time:	10/10/2003 3:00:14 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	parallel to phantom	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum
	SV		

Probe:	0106			
Cal File:	106_1900_HEAD_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.423	0.423	0.423
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.582
Relative Permittivity:	52.46
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 34 of 39

Date / Time:	10/10/2003 3:25:43 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	perpendicular to phantom	Test Frequency:	1880
Shape File:	broadcom381lap_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_HEAD_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.423	0.423	0.423
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			



Liquid:	1900
Type:	body
Conductivity:	1.582
Relative Permittivity:	52.46
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	4/6/2004 11:46:36 AM	Position:	bystander 1cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC83	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	max 2 timeslots TX

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	2			
Averaging:	6			
Batteries Replaced:	03/23/04			

Liquid:	1900
Type:	Body
Conductivity:	1.549
Relative Permittivity:	52.65
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date / Time:	10/13/2003 11:33:30 AM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.582
Relative Permittivity:	52.46
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

The figure displays two 3D SAR plots and a color bar. The left plot shows a color-coded SAR distribution on a grid, with the X-axis (mm) ranging from -25 to 15, the Y-axis (mm) ranging from -15 to 15, and the Z-axis (mm) ranging from -180 to -50. The right plot shows a 3D wireframe model of the head with SAR values, with the X-axis (mm) ranging from -100 to 100, the Y-axis (mm) ranging from -100 to 100, and the Z-axis (mm) ranging from -180 to -50. A color bar at the bottom indicates SAR values from 0.0 to 0.7 W/kg.

ZOOM SCAN RESULTS:

Spot SAR

(W/kg):

**Change during
Scan (%)**

Max E-field

(V/m):

Max SAR

(W/kg)

Location of

Max (mm):

Start Scan

0.160

End Scan

0.154

-3.16

21.19

1g

0.579

10g

0.333

X

75.1

Y

-16.0

Z

-175.9

Y (mm)

Z (mm)

SAR (W/kg)

AREA SCAN:

Scan Extent:

	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-200.0	-110.0	10.0

Date of Report: 04/26/2004



Appendix A Plots

Page 37 of 39

Date / Time:	10/10/2003 4:29:40 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	horizontal	Test Frequency:	1880
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_HEAD_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.423	0.423	0.423
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.582
Relative Permittivity:	52.46
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004



Appendix A Plots

Page 38 of 39

Date / Time:	10/13/2003 12:01:59 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1850.2
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.569
Relative Permittivity:	53.07
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420



Date of Report: 04/26/2004

Appendix A Plots

Page 39 of 39

Date / Time:	10/13/2003 12:29:37 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	GC82 card	Head Rotation:	0
Antenna:	vertical	Test Frequency:	1909.8
Shape File:	broadcom381side_newant.csv	Power Level:	maximum

Probe:	0106			
Cal File:	106_1900_BODY_28_GPRS			
Cal Factors:		X	Y	Z
	Air	415	805	371
	DCP	12.81	5.68	11.4
	Lin	0.477	0.477	0.477
Amp Gain:	1			
Averaging:	6			
Batteries Replaced:	10/03/2003			

Liquid:	1900
Type:	body
Conductivity:	1.588
Relative Permittivity:	52.78
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

