

# FCC Test Report

**Applicant** : **Anker Innovations Limited**

**Address** : **Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong**

**Product Name** : **Nano Receiver**

**Report Date** : **Dec. 11, 2023**



**Shenzhen Anbotek Compliance Laboratory Limited**



# Contents

|                                                 |    |
|-------------------------------------------------|----|
| 1. General Information .....                    | 5  |
| 1.1. Client Information .....                   | 5  |
| 1.2. Description of Device (EUT) .....          | 5  |
| 1.3. Auxiliary Equipment Used During Test ..... | 6  |
| 1.4. Description of Test Configuration .....    | 6  |
| 1.5. Description of Test Setup .....            | 7  |
| 1.6. Test Equipment List .....                  | 8  |
| 1.7. Measurement Uncertainty .....              | 9  |
| 1.8. Description of Test Facility .....         | 9  |
| 1.9. Disclaimer .....                           | 10 |
| 2. Summary of Test Results .....                | 11 |
| 3. Conducted Emission Test .....                | 12 |
| 3.1. Test Standard and Limit .....              | 12 |
| 3.2. Test Setup .....                           | 12 |
| 3.3. Test Procedure .....                       | 12 |
| 3.4. Test Data .....                            | 12 |
| 4. Radiated Emission and Band Edge .....        | 15 |
| 4.1. Test Standard and Limit .....              | 15 |
| 4.2. Test Setup .....                           | 16 |
| 4.3. Test Procedure .....                       | 17 |
| 4.4. Test Data .....                            | 18 |
| 5. 20dB Bandwidth Test .....                    | 25 |
| 5.1. Test Standard and Limit .....              | 25 |
| 5.2. Test Setup .....                           | 25 |
| 5.3. Test Procedure .....                       | 25 |
| 5.4. 5.4. Test Data .....                       | 25 |
| 6. Antenna Requirement .....                    | 28 |
| 6.1. Test Standard and Requirement .....        | 28 |
| 6.2. Antenna Connected Construction .....       | 28 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH .....       | 29 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH .....        | 29 |
| APPENDIX III -- INTERNAL PHOTOGRAPH .....       | 29 |



# TEST REPORT

Applicant : Anker Innovations Limited

Manufacturer : Anker Innovations Limited

Product Name : Nano Receiver

Test Model No. : A7850

Reference Model No. : N/A

Trade Mark : ANKER

Rating(s) : Input: DC 5V

Test Standard(s) : FCC Part15 Subpart C, Paragraph 15.249

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Nov. 14, 2023

Date of Test

Nov. 14 ~ 29, 2023

Prepared by

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Edward Pan

(Edward Pan)





## Revision History

| Report Version | Description     | Issued Date   |
|----------------|-----------------|---------------|
| R00            | Original Issue. | Dec. 11, 2023 |
|                |                 |               |
|                |                 |               |



## 1. General Information

### 1.1. Client Information

|              |   |                                                                             |
|--------------|---|-----------------------------------------------------------------------------|
| Applicant    | : | Anker Innovations Limited                                                   |
| Address      | : | Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong |
| Manufacturer | : | Anker Innovations Limited                                                   |
| Address      | : | Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong |

### 1.2. Description of Device (EUT)

|                                                                                                                                                                                              |   |                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------|
| Product Name                                                                                                                                                                                 | : | Nano Receiver                                              |
| Test Model No.                                                                                                                                                                               | : | A7850                                                      |
| Reference Model No.                                                                                                                                                                          | : | N/A                                                        |
| Trade Mark                                                                                                                                                                                   | : | ANKER                                                      |
| Test Power Supply                                                                                                                                                                            | : | DC 5V via PC from Adapter input AC 120V/60Hz/ DC 5V via PC |
| Test Sample No.                                                                                                                                                                              | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample)            |
| Adapter                                                                                                                                                                                      | : | N/A                                                        |
| <b>RF Specification</b>                                                                                                                                                                      |   |                                                            |
| Operation Frequency                                                                                                                                                                          | : | 2403~2479MHz                                               |
| Number of Channel                                                                                                                                                                            | : | 16 Channels                                                |
| Modulation Type                                                                                                                                                                              | : | GFSK                                                       |
| Antenna Type                                                                                                                                                                                 | : | PCB Antenna                                                |
| Antenna Gain(Peak)                                                                                                                                                                           | : | -2.12 dBi                                                  |
| <b>Remark:</b> 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. |   |                                                            |



### 1.3. Auxiliary Equipment Used During Test

| Description | Rating(s)                                                                                 |
|-------------|-------------------------------------------------------------------------------------------|
| MacBook Air | Model: A1466<br>Input: 14.85V/3.05A<br>CMIIT ID:C02HXB48DRVC                              |
| Adapter     | Input: AC 100-240V, 1A, 50-60Hz<br>Output: 14.85V/3.05A                                   |
| Mouse       | Manufacturer: Anker Innovations Limited<br>Model: A7852M<br>Input: DC 3V by AAA*2 battery |

### 1.4. Description of Test Configuration

| Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| 01      | 2403           | 05      | 2422           | 09      | 2441           | 13      | 2463           |
| 02      | 2407           | 06      | 2426           | 10      | 2445           | 14      | 2466           |
| 03      | 2414           | 07      | 2436           | 11      | 2453           | 15      | 2473           |
| 04      | 2419           | 08      | 2439           | 12      | 2459           | 16      | 2479           |


Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with Channel 01, 09 and 16.





## 1.5. Description of Test Setup



**1.6. Test Equipment List**

| Item | Equipment                                         | Manufacturer    | Model No.     | Serial No.   | Last Cal.     | Cal. Interval |
|------|---------------------------------------------------|-----------------|---------------|--------------|---------------|---------------|
| 1.   | L.I.S.N.<br>Artificial Mains<br>Network           | Rohde & Schwarz | ENV216        | 100055       | Oct. 12, 2023 | 1 Year        |
| 2.   | Three Phase<br>V-type Artificial<br>Power Network | CYBERTEK        | EM5040DT      | E215040DT001 | Jul. 05, 2023 | 1 Year        |
| 3.   | EMI Test Receiver                                 | Rohde & Schwarz | ESCI          | 100627       | Oct. 12, 2023 | 1 Year        |
| 4.   | EMI Test Receiver                                 | Rohde & Schwarz | ESR26         | 101481       | Oct. 12, 2023 | 1 Year        |
| 5.   | MXA Spectrum<br>Analysis                          | Agilent         | N9020A        | MY51170037   | Oct. 12, 2023 | 1 Year        |
| 6.   | EMI Preamplifier                                  | SKET Electronic | LNPA-0118G-45 | SKET-PA-002  | Oct. 12, 2023 | 1 Year        |
| 7.   | Double Ridged<br>Horn Antenna                     | SCHWARZBECK     | BBHA 9120D    | 02555        | Oct. 16, 2022 | 3 Year        |
| 8.   | Bilog Broadband<br>Antenna                        | Schwarzbeck     | VULB9163      | 345          | Oct. 23, 2022 | 3 Year        |
| 9.   | Loop Antenna                                      | Schwarzbeck     | FMZB1519B     | 00053        | Oct. 12, 2023 | 1 Year        |
| 10.  | Horn Antenna                                      | A-INFO          | LB-180400-KF  | J211060628   | Oct. 12, 2023 | 1 Year        |
| 11.  | Pre-amplifier                                     | SONOMA          | 310N          | 186860       | Oct. 12, 2023 | 1 Year        |
| 12.  | EMI Test Software<br>EZ-EMC                       | SHURPLE         | N/A           | N/A          | N/A           | N/A           |
| 13.  | MXA Spectrum<br>Analysis                          | KEYSIGHT        | N9020A        | MY53280032   | Oct. 12, 2023 | 1 Year        |
| 14.  | MXG RF Vector<br>Signal Generator                 | Agilent         | N5182A        | MY48180656   | Oct. 12, 2023 | 1 Year        |
| 15.  | Signal Generator                                  | Agilent         | E4421B        | MY41000743   | Oct. 12, 2023 | 1 Year        |
| 16.  | DC Power Supply                                   | IVYTECH         | IV3605        | 1804D360510  | Oct. 20, 2023 | 1 Year        |
| 17.  | Constant<br>Temperature<br>Humidity Chamber       | ZHONGJIAN       | ZJ-KHWS80B    | N/A          | Oct. 16, 2023 | 1 Year        |





### 1.7. Measurement Uncertainty

| Parameter                                                                                                                                                                                                                       | Uncertainty                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| Conducted emissions (AMN 150kHz~30MHz)                                                                                                                                                                                          | 3.8dB                                                     |
| Occupied Bandwidth                                                                                                                                                                                                              | 925Hz                                                     |
| Conducted Spurious Emission                                                                                                                                                                                                     | 1.24dB                                                    |
| Radiated spurious emissions (Below 30MHz)                                                                                                                                                                                       | 3.53dB                                                    |
| Radiated spurious emissions (30MHz~1GHz)                                                                                                                                                                                        | Horizontal: 3.92dB; Vertical: 4.52dB                      |
| Radiated spurious emissions (above 1GHz)                                                                                                                                                                                        | 1G-6GHz: 4.78dB;<br>6G-18GHz: 4.88dB<br>18G-40GHz: 5.68dB |
| The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032.<br>This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                                                           |

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.



**1.9. Disclaimer**

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



## 2. Summary of Test Results

| Standard Section                                            | Test Item           | Result |
|-------------------------------------------------------------|---------------------|--------|
| 15.203                                                      | Antenna Requirement | PASS   |
| 15.207                                                      | Conducted Emission  | PASS   |
| 15.205/15.209/15.249                                        | Radiated Emission   | PASS   |
| 15.249(d)                                                   | Band Edge           | PASS   |
| 15.215(c)                                                   | 20dB Bandwidth      | PASS   |
| <b>Remark:</b> "N/A" is an abbreviation for Not Applicable. |                     |        |






### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

| Test Standard                                                                                                                            | FCC Part15 Section 15.207 |                                |               |
|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------------|---------------|
| Test Limit                                                                                                                               | Frequency                 | Maximum RF Line Voltage (dBuV) |               |
|                                                                                                                                          |                           | Quasi-peak Level               | Average Level |
|                                                                                                                                          | 150kHz~500kHz             | 66 ~ 56 *                      | 56 ~ 46 *     |
|                                                                                                                                          | 500kHz~5MHz               | 56                             | 46            |
|                                                                                                                                          | 5MHz~30MHz                | 60                             | 50            |
| <b>Remark:</b> (1) *Decreasing linearly with logarithm of the frequency.<br>(2) The lower limit shall apply at the transition frequency. |                           |                                |               |

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data

During the test, pre-scan all modes, and found the Low CH (2403MHz) which is the worst case, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



**Conducted Emission Test Data**

Test Site: 1# Shielded Room  
Operating Condition: 2403MHz  
Test Specification: DC 5V via PC from Adapter input AC 120V/60Hz  
Comment: Live Line  
Temp.(°C)/Hum.(%RH): 23.5°C/65%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.4580      | 21.13          | 19.83       | 40.96         | 56.73        | -15.77          | QP       |        |
| 2   | 0.7780      | 12.55          | 19.86       | 32.41         | 46.00        | -13.59          | AVG      |        |
| 3   | 0.9500      | 22.92          | 19.85       | 42.77         | 56.00        | -13.23          | QP       |        |
| 4   | 1.0900      | 12.84          | 19.85       | 32.69         | 46.00        | -13.31          | AVG      |        |
| 5   | 1.3740      | 22.06          | 19.84       | 41.90         | 56.00        | -14.10          | QP       |        |
| 6   | 1.3980      | 12.94          | 19.84       | 32.78         | 46.00        | -13.22          | AVG      |        |
| 7   | 1.6780      | 18.56          | 19.84       | 38.40         | 56.00        | -17.60          | QP       |        |
| 8   | 1.7420      | 9.93           | 19.84       | 29.77         | 46.00        | -16.23          | AVG      |        |
| 9   | 2.0140      | 16.26          | 19.83       | 36.09         | 56.00        | -19.91          | QP       |        |
| 10  | 2.1099      | 7.62           | 19.83       | 27.45         | 46.00        | -18.55          | AVG      |        |
| 11  | 3.1099      | 1.98           | 19.84       | 21.82         | 46.00        | -24.18          | AVG      |        |
| 12  | 3.2139      | 11.47          | 19.84       | 31.31         | 56.00        | -24.69          | QP       |        |





**Conducted Emission Test Data**

Test Site: 1# Shielded Room  
Operating Condition: 2403MHz  
Test Specification: DC 5V via PC from Adapter input AC 120V/60Hz  
Comment: Neutral Line  
Temp.(°C)/Hum.(%RH): 23.5°C/65%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.4180      | 21.24          | 19.82       | 41.06         | 57.49        | -16.43          | QP       |        |
| 2   | 0.7780      | 12.59          | 19.86       | 32.45         | 46.00        | -13.55          | AVG      |        |
| 3   | 0.9740      | 23.14          | 19.85       | 42.99         | 56.00        | -13.01          | QP       |        |
| 4   | 1.2940      | 23.00          | 19.84       | 42.84         | 56.00        | -13.16          | QP       |        |
| 5   | 1.2940      | 13.22          | 19.84       | 33.06         | 46.00        | -12.94          | AVG      |        |
| 6   | 1.6420      | 10.22          | 19.84       | 30.06         | 46.00        | -15.94          | AVG      |        |
| 7   | 1.6580      | 20.45          | 19.84       | 40.29         | 56.00        | -15.71          | QP       |        |
| 8   | 1.9420      | 8.12           | 19.83       | 27.95         | 46.00        | -18.05          | AVG      |        |
| 9   | 1.9700      | 17.11          | 19.83       | 36.94         | 56.00        | -19.06          | QP       |        |
| 10  | 2.2780      | 15.60          | 19.83       | 35.43         | 56.00        | -20.57          | QP       |        |
| 11  | 2.2780      | 5.79           | 19.83       | 25.62         | 46.00        | -20.38          | AVG      |        |
| 12  | 3.3260      | 1.60           | 19.84       | 21.44         | 46.00        | -24.56          | AVG      |        |





## 4. Radiated Emission and Band Edge

### 4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 |                                  |                |            |                          |
|---------------|----------------------------------------|----------------------------------|----------------|------------|--------------------------|
| Test Limit    | Frequency (MHz)                        | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark     | Measurement distance (m) |
|               | 0.009MHz~0.490MHz                      | 2400/F(kHz)                      | -              | -          | 300                      |
|               | 0.490MHz-1.705MHz                      | 24000/F(kHz)                     | -              | -          | 30                       |
|               | 1.705MHz-30MHz                         | 30                               | -              | -          | 30                       |
|               | 30MHz~88MHz                            | 100                              | 40.0           | Quasi-peak | 3                        |
|               | 88MHz~216MHz                           | 150                              | 43.5           | Quasi-peak | 3                        |
|               | 216MHz~960MHz                          | 200                              | 46.0           | Quasi-peak | 3                        |
|               | 960MHz~1000MHz                         | 500                              | 54.0           | Quasi-peak | 3                        |
|               | Above 1000MHz                          | 500                              | 54.0           | Average    | 3                        |
|               |                                        | -                                | 74.0           | Peak       | 3                        |

**Remark:**

(1) The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

| Test Standard | FCC Part15 C Section 15.249 |                                                    |                                                |                |         |                          |
|---------------|-----------------------------|----------------------------------------------------|------------------------------------------------|----------------|---------|--------------------------|
| Test Limit    | Frequency (MHz)             | Field Strength of fundamental ((millivolts /meter) | Field Strength of Harmonics (microvolts/meter) | Limit (dBuV/m) | Remark  | Measurement distance (m) |
|               | 2400~2483.5                 | 50                                                 | -                                              | 114.0          | Peak    | 3                        |
|               | 2400~2483.5                 | 50                                                 | -                                              | 94.0           | Average | 3                        |
|               | 2400~2483.5                 | -                                                  | 500                                            | 74.0           | Peak    | 3                        |
|               | 2400~2483.5                 | -                                                  | 500                                            | 54.0           | Average | 3                        |

**Remark:**

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.



## 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz








Figure 3. Above 1 GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.





Report No.: 18220WC30240401

FCC ID: 2AOKB-A7850R1

Page 18 of 29

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

#### 4.4. Test Data

##### PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the Low CH (2403MHz) which is the worst case, only the worst case is recorded in the report.




Report No.: 18220WC30240401

FCC ID: 2AOKB-A7850R1

Page 19 of 29

**Test Results (30~1000MHz)**

Test Mode: 2403MHz  
Power Source: DC 5V via PC  
Polarization: Horizontal  
Temp.(°C)/Hum.(%RH): 21.0°C/56%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|-------------|--------------|--------|
| 1   | 31.9546     | 36.46          | -19.54        | 16.92           | 40.00          | -23.08          | QP       |             |              |        |
| 2   | 54.2610     | 31.13          | -17.35        | 13.78           | 40.00          | -26.22          | QP       |             |              |        |
| 3   | 112.9196    | 37.85          | -23.41        | 14.44           | 43.50          | -29.06          | QP       |             |              |        |
| 4   | 188.4125    | 42.63          | -22.82        | 19.81           | 43.50          | -23.69          | QP       |             |              |        |
| 5   | 385.2805    | 40.81          | -16.09        | 24.72           | 46.00          | -21.28          | QP       |             |              |        |
| 6   | 916.0687    | 33.16          | -6.04         | 27.12           | 46.00          | -18.88          | QP       |             |              |        |




Report No.: 18220WC30240401

FCC ID: 2AOKB-A7850R1

Page 20 of 29

**Test Results (30~1000MHz)**

Test Mode: 2403MHz  
Power Source: DC 5V via PC  
Polarization: Vertical  
Temp.(°C)/Hum.(%RH): 21.0°C/56%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|-------------|--------------|--------|
| 1   | 30.7455     | 33.46          | -17.84        | 15.62           | 40.00          | -24.38          | QP       |             |              |        |
| 2   | 45.5348     | 29.83          | -15.13        | 14.70           | 40.00          | -25.30          | QP       |             |              |        |
| 3   | 150.5378    | 38.41          | -22.07        | 16.34           | 43.50          | -27.16          | QP       |             |              |        |
| 4   | 289.0021    | 34.72          | -16.64        | 18.08           | 46.00          | -27.92          | QP       |             |              |        |
| 5   | 386.6338    | 39.57          | -14.59        | 24.98           | 46.00          | -21.02          | QP       |             |              |        |
| 6   | 801.7863    | 34.32          | -8.24         | 26.08           | 46.00          | -19.92          | QP       |             |              |        |





## Test Results (1GHz-25GHz)

Test channel: Lowest

## Peak value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| 2403.00         | 82.45          | 9.75          | 92.20           | 114.00         | -21.80          | Vertical     |
| 4806.00         | 29.13          | 15.27         | 44.40           | 74.00          | -29.60          | Vertical     |
| 7209.00         | 29.08          | 18.09         | 47.17           | 74.00          | -26.83          | Vertical     |
| 9612.00         | 30.16          | 23.76         | 53.92           | 74.00          | -20.08          | Vertical     |
| 12015.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 14418.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 2403.00         | 83.39          | 9.75          | 93.14           | 114.00         | -20.86          | Horizontal   |
| 4806.00         | 28.74          | 15.27         | 44.01           | 74.00          | -29.99          | Horizontal   |
| 7209.00         | 29.85          | 18.09         | 47.94           | 74.00          | -26.06          | Horizontal   |
| 9612.00         | 28.40          | 23.76         | 52.16           | 74.00          | -21.84          | Horizontal   |
| 12015.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| 14418.00        | *              |               |                 | 74.00          |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| 2403.00         | 72.38          | 9.75          | 82.13           | 94.00          | -11.87          | Vertical     |
| 4806.00         | 17.40          | 15.27         | 32.67           | 54.00          | -21.33          | Vertical     |
| 7209.00         | 18.13          | 18.09         | 36.22           | 54.00          | -17.78          | Vertical     |
| 9612.00         | 19.63          | 23.76         | 43.39           | 54.00          | -10.61          | Vertical     |
| 12015.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 14418.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 2403.00         | 73.62          | 9.75          | 83.37           | 94.00          | -10.63          | Horizontal   |
| 4806.00         | 17.07          | 15.27         | 32.34           | 54.00          | -21.66          | Horizontal   |
| 7209.00         | 18.88          | 18.09         | 36.97           | 54.00          | -17.03          | Horizontal   |
| 9612.00         | 17.91          | 23.76         | 41.67           | 54.00          | -12.33          | Horizontal   |
| 12015.00        | *              |               |                 | 54.00          |                 | Horizontal   |
| 14418.00        | *              |               |                 | 54.00          |                 | Horizontal   |

Remark:

- 1.Result =Reading + Factor
2. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



## Test Results (1GHz-25GHz)

Test channel: Middle

## Peak value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| 2441.00         | 86.01          | 9.75          | 95.76           | 114.00         | -18.24          | Vertical     |
| 4882.00         | 27.74          | 15.27         | 43.01           | 74.00          | -30.99          | Vertical     |
| 7323.00         | 33.21          | 18.09         | 51.30           | 74.00          | -22.70          | Vertical     |
| 9764.00         | 29.89          | 23.76         | 53.65           | 74.00          | -20.35          | Vertical     |
| 12205.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 14646.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 2441.00         | 81.41          | 9.75          | 91.16           | 114.00         | -22.84          | Horizontal   |
| 4882.00         | 27.29          | 15.27         | 42.56           | 74.00          | -31.44          | Horizontal   |
| 7323.00         | 33.76          | 18.09         | 51.85           | 74.00          | -22.15          | Horizontal   |
| 9764.00         | 32.00          | 23.76         | 55.76           | 74.00          | -18.24          | Horizontal   |
| 12205.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| 14646.00        | *              |               |                 | 74.00          |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| 2441.00         | 73.69          | 9.75          | 83.44           | 94.00          | -10.56          | Vertical     |
| 4882.00         | 18.90          | 15.27         | 34.17           | 54.00          | -19.83          | Vertical     |
| 7323.00         | 16.98          | 18.09         | 35.07           | 54.00          | -18.93          | Vertical     |
| 9764.00         | 18.46          | 23.76         | 42.22           | 54.00          | -11.78          | Vertical     |
| 12205.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 14646.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 2441.00         | 70.30          | 9.75          | 80.05           | 94.00          | -13.95          | Horizontal   |
| 4882.00         | 14.81          | 15.27         | 30.08           | 54.00          | -23.92          | Horizontal   |
| 7323.00         | 18.13          | 18.09         | 36.22           | 54.00          | -17.78          | Horizontal   |
| 9764.00         | 18.30          | 23.76         | 42.06           | 54.00          | -11.94          | Horizontal   |
| 12205.00        | *              |               |                 | 54.00          |                 | Horizontal   |
| 14646.00        | *              |               |                 | 54.00          |                 | Horizontal   |

Remark:

- 1.Result =Reading + Factor
2. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.





## Test Results (1GHz-25GHz)

| Test channel: Highest |                |               |                 |                |                 |              |
|-----------------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Peak value:           |                |               |                 |                |                 |              |
| Frequency (MHz)       | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 2479.00               | 83.72          | 9.75          | 93.47           | 114.00         | -20.53          | Vertical     |
| 4958.00               | 31.66          | 15.27         | 46.93           | 74.00          | -27.07          | Vertical     |
| 7437.00               | 28.96          | 18.09         | 47.05           | 74.00          | -26.95          | Vertical     |
| 9916.00               | 33.07          | 23.76         | 56.83           | 74.00          | -17.17          | Vertical     |
| 12395.00              | *              |               |                 | 74.00          |                 | Vertical     |
| 14874.00              | *              |               |                 | 74.00          |                 | Vertical     |
| 2479.00               | 84.44          | 9.75          | 94.19           | 114.00         | -19.81          | Horizontal   |
| 4958.00               | 27.76          | 15.27         | 43.03           | 74.00          | -30.97          | Horizontal   |
| 7437.00               | 33.06          | 18.09         | 51.15           | 74.00          | -22.85          | Horizontal   |
| 9916.00               | 28.55          | 23.76         | 52.31           | 74.00          | -21.69          | Horizontal   |
| 12395.00              | *              |               |                 | 74.00          |                 | Horizontal   |
| 14874.00              | *              |               |                 | 74.00          |                 | Horizontal   |
| Average value:        |                |               |                 |                |                 |              |
| Frequency (MHz)       | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 2479.00               | 75.28          | 9.75          | 85.03           | 94.00          | -8.97           | Vertical     |
| 4958.00               | 16.09          | 15.27         | 31.36           | 54.00          | -22.64          | Vertical     |
| 7437.00               | 19.40          | 18.09         | 37.49           | 54.00          | -16.51          | Vertical     |
| 9916.00               | 17.28          | 23.76         | 41.04           | 54.00          | -12.96          | Vertical     |
| 12395.00              | *              |               |                 | 54.00          |                 | Vertical     |
| 14874.00              | *              |               |                 | 54.00          |                 | Vertical     |
| 2479.00               | 72.81          | 9.75          | 82.56           | 94.00          | -11.44          | Horizontal   |
| 4958.00               | 15.19          | 15.27         | 30.46           | 54.00          | -23.54          | Horizontal   |
| 7437.00               | 22.38          | 18.09         | 40.47           | 54.00          | -13.53          | Horizontal   |
| 9916.00               | 20.05          | 23.76         | 43.81           | 54.00          | -10.19          | Horizontal   |
| 12395.00              | *              |               |                 | 54.00          |                 | Horizontal   |
| 14874.00              | *              |               |                 | 54.00          |                 | Horizontal   |

## Remark:

1.Result =Reading + Factor


2. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.






## Radiated Band Edge:

Test Mode: Lowest



Test Mode: Highest



Note: When the PK measure result value is less than the AVG limit value, the AV measure result values test not applicable.




## 5. 20dB Bandwidth Test

### 5.1. Test Standard and Limit

|               |                                |
|---------------|--------------------------------|
| Test Standard | FCC Part15 C Section 15.215(c) |
| Test Limit    | N/A                            |

### 5.2. Test Setup



### 5.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:  
RBW = 30kHz, VBW $\geq$ 3\*RBW = 100kHz,  
Detector= Average  
Trace mode= Max hold.  
Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

### 5.4. Test Data

|              |   |                |             |   |                  |
|--------------|---|----------------|-------------|---|------------------|
| Test Item    | : | 20dB Bandwidth | Test Mode   | : | CH Low ~ CH High |
| Test Voltage | : | DC 5V via PC   | Temperature | : | 25.7℃            |
| Test Result  | : | PASS           | Humidity    | : | 46%RH            |

| Channel | Bandwidth (kHz) | Result |
|---------|-----------------|--------|
| Low     | 3040            | PASS   |
| Middle  | 2760            | PASS   |
| High    | 2416            | PASS   |







Low Channel



Mid Channel







High Channel



## 6. Antenna Requirement

### 6.1. Test Standard and Requirement

| Test Standard | FCC Part15 Section 15.203                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Requirement   | 1) 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |

### 6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is -2.12 dBi. It complies with the standard requirement.



## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

