

## FCC 47 CFR MPE REPORT

INNOVATIVE TECHNOLOGY ELECTRONICS, LLC

MUSIC CENTER WITH BLUETOOTH

Model Number: VTA-204B

Additional Model: VTA-205B

FCC ID: 2AFHW-VTA-204BTO

Applicant:	INNOVATIVE TECHNOLOGY ELECTRONICS, LLC
Address:	3513 Brighton Blvd Suite 570, Denver, Colorado, 80216 United States
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2211049
Date of Test:	Oct. 18~Nov. 06, 2022
Date of Report:	Nov. 07, 2022

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	-2.18	0.6053
	2441	-3.47	0.4498
	2480	-4.24	0.3767
$\pi/4$ -DQPSK	2402	-0.05	0.9886
	2441	-1.25	0.7499
	2480	-2.07	0.6209
8-DPSK	2402	0.48	1.1169
	2441	-0.71	0.8492
	2480	-1.6	0.6918
BLE	2402	-2.55	0.5559
	2440	-3.67	0.4295
	2480	-4.54	0.3516

### 3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power ( dBm )	MAX Target power ( dBm )	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
				(dBi)	(Linear )			
2.4G Band								
GFSK	-2.18	-2±1	-1	-0.58	0.8750	0.0001	1	Complies
$\pi/4$ DQPSK	-0.05	0±1	1	-0.58	0.8750	0.0002	1	Complies
8-DPSK	0.48	0±1	1	-0.58	0.8750	0.0002	1	Complies
BLE	-2.55	-2±1	-1	-0.58	0.8750	0.0001	1	Complies

**End of Test Report**