

**RF Exposure Evaluation**

**Limit**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

**Evaluation Method**

Transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW,  $G$  = gain of antenna in linear scale;  $P_i = 3.1416$ ,  $R$  = distance between observation point and center of the radiator in cm

**Conducted Power Results & Manufacturing tolerance**

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance ±(dB)
2.4GWIFI	802.11b	11.90	11	1
	802.11g	14.89	14	1
	802.11n(HT20)	13.94	13	1
BLE	GFSK	6.29	5.5	1

**Evaluation Results**

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear scale	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
			dBm	mW				
2.4GWIFI	802.11b	20	12	15.85	1.12	0.004	1	PASS
	802.11g	20	15	31.62	1.12	0.007	1	PASS
	802.11n(HT20)	20	14	25.12	1.12	0.006	1	PASS
BLE	GFSK	20	6.5	4.47	1.12	0.001	1	PASS

Remark:

1. Output power including tune up tolerance;
2. The maximum 2.4G antenna gain is 0.5dBi
3. The exposure safety distance is 20cm.

**Simulation Transmission**

EUT can only work in 2.4GWIFI+BLE mode

The formula of calculated the Simulation Transmission MPE is:

$$CPD1/LPD1+CPD2/LPD2+.....etc.<1$$

CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+BLE mode	0.008	1	Pass

**Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.