# APPENDIX B PLOTS OF THE SAR MEASUREMENTS

Plots of the measured SAR distributions inside the phantom are given in this Appendix for all tested configurations.



# DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# **Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14** Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 824.2 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=824 MHz; $\sigma$ = 0.98 S/m; $\epsilon_r$ = 55.6; $\rho$ = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 128 Test/Area Scan (81x101x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.569 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 128 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.927 V/m; Power Drift = 0.01 dB Averaged SAR: SAR(1g) = 0.557 W/kg; SAR(10g) = 0.389 W/kg Maximum value of SAR (interpolated) = 0.703 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 836.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.5;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 190 Test/Area Scan 2 (81x101x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.551 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 190 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.451 V/m; Power Drift = 0.05 dB Averaged SAR: SAR(1g) = 0.535 W/kg; SAR(10g) = 0.374 W/kg Maximum value of SAR (interpolated) = 0.682 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 848.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.3;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

**Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 251 Test/Area Scan 2 (81x101x1):** Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.473 W/kg **Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 251 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.404 V/m; **Power Drift = -0.04 dB Averaged SAR: SAR(1g) = 0.462 W/kg; SAR(10g) = 0.323 W/kg** Maximum value of SAR (interpolated) = 0.579 W/kg

•B
<td

SAR Measurement Plot 3







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 824.2 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=824 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 55.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 128 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 1.000 W/kg Lap Held Antenna OUT 29-10-14/Channel 128 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 25.959 V/m; Power Drift = 0.07 dB Averaged SAR: SAR(1g) = 1.030 W/kg; SAR(10g) = 0.677 W/kg Maximum value of SAR (interpolated) = 1.400 W/kg











#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 836.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.5;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 190 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.980 W/kg Lap Held Antenna OUT 29-10-14/Channel 190 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 25.567 V/m; Power Drift = -0.02 dB Averaged SAR: SAR(1g) = 0.993 W/kg; SAR(10g) = 0.651 W/kg Maximum value of SAR (interpolated) = 1.340 W/kg











#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 848.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.3;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 251 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.850 W/kg Lap Held Antenna OUT 29-10-14/Channel 251 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 23.845 V/m; Power Drift = 0.00 dB Averaged SAR: SAR(1g) = 0.852 W/kg; SAR(10g) = 0.560 W/kg Maximum value of SAR (interpolated) = 1.160 W/kg











#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 824.2 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=824 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 55.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 128 Test 2 Variability/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 1.110 W/kg Lap Held Antenna OUT 29-10-14/Channel 128 Test 2 Variability/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 23.484 V/m; Power Drift = -0.21 dB Averaged SAR: SAR(1g) = 1.090 W/kg; SAR(10g) = 0.715 W/kg Maximum value of SAR (interpolated) = 1.420 W/kg











#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 824.2 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=824 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 55.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 128 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.339 W/kg Edge 2 Antenna IN 29-10-14/Channel 128 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 13.926 V/m; Power Drift = -0.18 dB Averaged SAR: SAR(1g) = 0.377 W/kg; SAR(10g) = 0.143 W/kg Maximum value of SAR (interpolated) = 1.330 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 836.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.5;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 190 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.276 W/kg Edge 2 Antenna IN 29-10-14/Channel 190 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.436 V/m; Power Drift = -0.19 dB Averaged SAR: SAR(1g) = 0.285 W/kg; SAR(10g) = 0.110 W/kg Maximum value of SAR (interpolated) = 0.994 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 848.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.3;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 251 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.232 W/kg Edge 2 Antenna IN 29-10-14/Channel 251 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.777 V/m; Power Drift = -0.14 dB Averaged SAR: SAR(1g) = 0.252 W/kg; SAR(10g) = 0.098 W/kg Maximum value of SAR (interpolated) = 0.873 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 824.2 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=824 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 55.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 128 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.165 W/kg Edge 3 Antenna OUT 29-10-14/Channel 128 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.635 V/m; Power Drift = -0.02 dB Averaged SAR: SAR(1g) = 0.168 W/kg; SAR(10g) = 0.113 W/kg Maximum value of SAR (interpolated) = 0.226 W/kg











#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 836.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.5;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 190 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.188 W/kg Edge 3 Antenna OUT 29-10-14/Channel 190 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.675 V/m; Power Drift = 0.06 dB Averaged SAR: SAR(1g) = 0.188 W/kg; SAR(10g) = 0.127 W/kg Maximum value of SAR (interpolated) = 0.255 W/kg



SAR Measurement Plot 12







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 850 MHz GSM; Frequency: 848.6 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.3;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

#### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 251 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.188 W/kg Edge 3 Antenna OUT 29-10-14/Channel 251 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.573 V/m; Power Drift = 0.02 dB Averaged SAR: SAR(1g) = 0.185 W/kg; SAR(10g) = 0.126 W/kg Maximum value of SAR (interpolated) = 0.253 W/kg



SAR Measurement Plot 13







# DUT Name: Dipole 900 MHz, Type: DV900V2, Serial: 047

# Configuration: System Check 29-10-14

Communication System: 0 - CW; Communication System Band: 900 MHz; Frequency: 900.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00 Medium Parameters used: f=900 MHz;  $\sigma$  = 1.06 S/m;  $\epsilon_r$  = 54.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 29-10-14/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.160 W/kg System Check 29-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 57.045 V/m; Power Drift = 0.00 dB Averaged SAR: SAR(1g) = 2.910 W/kg; SAR(10g) = 1.900 W/kg Maximum value of SAR (interpolated) = 4.170 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1850 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1850 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

**Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 512 Test/Area Scan (61x111x1):** Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.218 W/kg **Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 512 Test/Zoom Scan (21x21x36)/Cube 0:** Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.888 V/m; **Power Drift = 0.11 dB Averaged SAR: SAR(1g) = 0.209 W/kg; SAR(10g) = 0.127 W/kg** 

Maximum value of SAR (interpolated) = 0.323 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1880 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 51.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 661 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.203 W/kg Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 661 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.873 V/m; Power Drift = -0.13 dB Averaged SAR: SAR(1g) = 0.198 W/kg; SAR(10g) = 0.120 W/kg Maximum value of SAR (interpolated) = 0.311 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1910 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1910 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 51.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 810 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.225 W/kg Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 810 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.321 V/m; Power Drift = -0.10 dB Averaged SAR: SAR(1g) = 0.215 W/kg; SAR(10g) = 0.131 W/kg

Maximum value of SAR (interpolated) = 0.343 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Lap Held Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1850 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1850 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 25-11-14/Channel 512 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.401 W/kg Lap Held Antenna OUT 25-11-14/Channel 512 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.410 V/m; Power Drift = 0.01 dB Averaged SAR: SAR(1g) = 0.390 W/kg; SAR(10g) = 0.229 W/kg Maximum value of SAR (interpolated) = 0.615 W/kg



SAR Measurement Plot 18






### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1880 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 51.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 25-11-14/Channel 661 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.373 W/kg Lap Held Antenna OUT 25-11-14/Channel 661 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.257 V/m; Power Drift = -0.03 dB Averaged SAR: SAR(1g) = 0.357 W/kg; SAR(10g) = 0.212 W/kg Maximum value of SAR (interpolated) = 0.550 W/kg



SAR Measurement Plot 19







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1910 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1910 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 51.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 25-11-14/Channel 810 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.372 W/kg Lap Held Antenna OUT 25-11-14/Channel 810 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 12.468 V/m; Power Drift = -0.10 dB Averaged SAR: SAR(1g) = 0.363 W/kg; SAR(10g) = 0.214 W/kg Maximum value of SAR (interpolated) = 0.595 W/kg



SAR Measurement Plot 20







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1850 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1850 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 25-11-14/Channel 512 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.508 W/kg Edge 2 Antenna IN 25-11-14/Channel 512 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 10.839 V/m; Power Drift = 0.09 dB Averaged SAR: SAR(1g) = 0.525 W/kg; SAR(10g) = 0.194 W/kg Maximum value of SAR (interpolated) = 1.220 W/kg



SAR Measurement Plot 21







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1880 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 51.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 25-11-14/Channel 661 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.472 W/kg Edge 2 Antenna IN 25-11-14/Channel 661 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 13.451 V/m; Power Drift = 0.12 dB Averaged SAR: SAR(1g) = 0.512 W/kg; SAR(10g) = 0.195 W/kg Maximum value of SAR (interpolated) = 1.200 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1910 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1910 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 51.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 25-11-14/Channel 810 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.456 W/kg Edge 2 Antenna IN 25-11-14/Channel 810 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 13.260 V/m; Power Drift = -0.05 dB Averaged SAR: SAR(1g) = 0.518 W/kg; SAR(10g) = 0.193 W/kg Maximum value of SAR (interpolated) = 1.210 W/kg



SAR Measurement Plot 23





#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1850 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1850 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 25-11-14/Channel 512 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.406 W/kg Edge 3 Antenna OUT 25-11-14/Channel 512 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.306 V/m; Power Drift = -0.03 dB Averaged SAR: SAR(1g) = 0.343 W/kg; SAR(10g) = 0.203 W/kg Maximum value of SAR (interpolated) = 0.542 W/kg



SAR Measurement Plot 24







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1880 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 51.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 25-11-14/Channel 661 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.278 W/kg Edge 3 Antenna OUT 25-11-14/Channel 661 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.374 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 0.267 W/kg; SAR(10g) = 0.162 W/kg Maximum value of SAR (interpolated) = 0.457 W/kg



SAR Measurement Plot 25







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 3 Antenna OUT 25-11-14

Communication System: 0 - GPRS Class 10 (0); Communication System Band: 1900 MHz GSM; Frequency: 1910 MHz, Communication System PAR: 6.37 dB; PMF: 2.08; Duty Cycle: 1:4.33 Medium Parameters used: f=1910 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 51.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 25-11-14/Channel 810 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.341 W/kg Edge 3 Antenna OUT 25-11-14/Channel 810 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.668 V/m; Power Drift = -0.15 dB Averaged SAR: SAR(1g) = 0.284 W/kg; SAR(10g) = 0.167 W/kg Maximum value of SAR (interpolated) = 0.469 W/kg



SAR Measurement Plot 26







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 826.4 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=826.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4132 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.494 W/kg

Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4132 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.420 V/m; Power Drift = 0.05 dB Averaged SAR: SAR(1g) = 0.483 W/kg; SAR(10g) = 0.327 W/kg Maximum value of SAR (interpolated) = 0.624 W/kg

> d = 0d = 0.494 W/kg = -3.06 dBW/kg

> > SAR Measurement Plot 27







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Bystander 25mm Spacing Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 836.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4183 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.499 W/kg Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4183 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.392 V/m; Power Drift = 0.01 dB Averaged SAR: SAR(1g) = 0.479 W/kg; SAR(10g) = 0.324 W/kg

Maximum value of SAR (interpolated) = 0.627 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 846.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=846.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4233 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.473 W/kg Bystander 25mm Spacing Antenna OUT 28-10-14/Channel 4233 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.868 V/m; Power Drift = 0.02 dB Averaged SAR: SAR(1g) = 0.446 W/kg; SAR(10g) = 0.301 W/kg

Maximum value of SAR (interpolated) = 0.585 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 826.4 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=826.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 28-10-14/Channel 4132 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.469 W/kg Lap Held Antenna OUT 28-10-14/Channel 4132 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 18.310 V/m; Power Drift = 0.02 dB Averaged SAR: SAR(1g) = 0.481 W/kg; SAR(10g) = 0.319 W/kg Maximum value of SAR (interpolated) = 0.646 W/kg



SAR Measurement Plot 30







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 836.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 28-10-14/Channel 4183 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.479 W/kg Lap Held Antenna OUT 28-10-14/Channel 4183 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 18.599 V/m; Power Drift = -0.19 dB Averaged SAR: SAR(1g) = 0.476 W/kg; SAR(10g) = 0.315 W/kg Maximum value of SAR (interpolated) = 0.642 W/kg



SAR Measurement Plot 31







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 846.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=846.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 28-10-14/Channel 4233 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.454 W/kg Lap Held Antenna OUT 28-10-14/Channel 4233 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.657 V/m; Power Drift = 0.10 dB Averaged SAR: SAR(1g) = 0.451 W/kg; SAR(10g) = 0.296 W/kg Maximum value of SAR (interpolated) = 0.624 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 826.4 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=826.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 55.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 28-10-14/Channel 4132 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.201 W/kg Edge 2 Antenna IN 28-10-14/Channel 4132 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.388 V/m; Power Drift = 0.10 dB Averaged SAR: SAR(1g) = 0.191 W/kg; SAR(10g) = 0.071 W/kg Maximum value of SAR (interpolated) = 0.679 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 836.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 28-10-14/Channel 4183 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.218 W/kg Edge 2 Antenna IN 28-10-14/Channel 4183 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.905 V/m; Power Drift = -0.05 dB Averaged SAR: SAR(1g) = 0.199 W/kg; SAR(10g) = 0.074 W/kg Maximum value of SAR (interpolated) = 0.714 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 28-10-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 5 850 MHz; Frequency: 846.6 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=846.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 55.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 28-10-14/Channel 4233 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.230 W/kg Edge 2 Antenna IN 28-10-14/Channel 4233 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 10.240 V/m; Power Drift = -0.03 dB Averaged SAR: SAR(1g) = 0.207 W/kg; SAR(10g) = 0.078 W/kg Maximum value of SAR (interpolated) = 0.746 W/kg









## DUT Name: Dipole 900 MHz, Type: DV900V2, Serial: 047

## Configuration: System Check 28-10-14

Communication System: 0 - CW; Communication System Band: 900 MHz; Frequency: 900.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00 Medium Parameters used: f=900 MHz;  $\sigma$  = 1.07 S/m;  $\epsilon_r$  = 54.5;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 28-10-14/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.130 W/kg System Check 28-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 56.857 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 2.890 W/kg; SAR(10g) = 1.890 W/kg Maximum value of SAR (interpolated) = 4.130 W/kg








#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1712 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1712.5 MHz;  $\sigma$  = 1.49 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1312 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.142 W/kg Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1312 Test/Zoom Scan (21x21x36)/Cube 0:

Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 5.916 V/m; Power Drift = -0.13 dB Averaged SAR: SAR(1g) = 0.131 W/kg; SAR(10g) = 0.084 W/kg

Maximum value of SAR (interpolated) = 0.185 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1735 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1735.5 MHz;  $\sigma$  = 1.51 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1427 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.162 W/kg Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1427 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.499 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 0.151 W/kg; SAR(10g) = 0.095 W/kg

Maximum value of SAR (interpolated) = 0.216 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1753 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1752.5 MHz;  $\sigma$  = 1.52 S/m;  $\epsilon_r$  = 51.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1513 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.170 W/kg Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1513 Test/Zoom Scan (21x21x36)/Cube 0:

Bystander 25mm Spacing Antenna OUT 21-11-14/Channel 1513 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.785 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.162 W/kg; SAR(10g) = 0.101 W/kg Maximum value of SAR (interpolated) = 0.234 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Lap Held Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1712 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1712.5 MHz;  $\sigma$  = 1.49 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 21-11-14/Channel 1312 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.384 W/kg Lap Held Antenna OUT 21-11-14/Channel 1312 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.020 V/m; Power Drift = -0.00 dB Averaged SAR: SAR(1g) = 0.359 W/kg; SAR(10g) = 0.216 W/kg Maximum value of SAR (interpolated) = 0.534 W/kg











# DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1735 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1735.5 MHz;  $\sigma$  = 1.51 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 21-11-14/Channel 1427 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.412 W/kg Lap Held Antenna OUT 21-11-14/Channel 1427 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.725 V/m; Power Drift = -0.13 dB Averaged SAR: SAR(1g) = 0.388 W/kg; SAR(10g) = 0.232 W/kg Maximum value of SAR (interpolated) = 0.587 W/kg



SAR Measurement Plot 41







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1753 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1752.5 MHz;  $\sigma$  = 1.52 S/m;  $\epsilon_r$  = 51.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 21-11-14/Channel 1513 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.403 W/kg Lap Held Antenna OUT 21-11-14/Channel 1513 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.584 V/m; Power Drift = -0.07 dB Averaged SAR: SAR(1g) = 0.390 W/kg; SAR(10g) = 0.232 W/kg Maximum value of SAR (interpolated) = 0.597 W/kg





SAR Measurement Plot 42







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1712 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1712.5 MHz;  $\sigma$  = 1.49 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 21-11-14/Channel 1312 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.801 W/kg Edge 2 Antenna IN 21-11-14/Channel 1312 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 18.359 V/m; Power Drift = 0.06 dB Averaged SAR: SAR(1g) = 0.760 W/kg; SAR(10g) = 0.307 W/kg Maximum value of SAR (interpolated) = 1.640 W/kg



SAR Measurement Plot 43







# DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Edge 2 Antenna IN 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1735 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1735.5 MHz;  $\sigma$  = 1.51 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 21-11-14/Channel 1427 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.733 W/kg Edge 2 Antenna IN 21-11-14/Channel 1427 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.967 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 0.712 W/kg; SAR(10g) = 0.285 W/kg Maximum value of SAR (interpolated) = 1.550 W/kg



SAR Measurement Plot 44





# DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Edge 2 Antenna IN 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1753 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1752.5 MHz;  $\sigma$  = 1.52 S/m;  $\epsilon_r$  = 51.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 21-11-14/Channel 1513 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.711 W/kg Edge 2 Antenna IN 21-11-14/Channel 1513 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 17.582 V/m; Power Drift = -0.08 dB Averaged SAR: SAR(1g) = 0.698 W/kg; SAR(10g) = 0.278 W/kg Maximum value of SAR (interpolated) = 1.520 W/kg



SAR Measurement Plot 45







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 3 Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1712 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1712.5 MHz;  $\sigma$  = 1.49 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 21-11-14/Channel 1312 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.315 W/kg Edge 3 Antenna OUT 21-11-14/Channel 1312 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.455 V/m; Power Drift = -0.02 dB Averaged SAR: SAR(1g) = 0.305 W/kg; SAR(10g) = 0.194 W/kg Maximum value of SAR (interpolated) = 0.459 W/kg



SAR Measurement Plot 46







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1735 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1735.5 MHz;  $\sigma$  = 1.51 S/m;  $\epsilon_r$  = 51.1;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 21-11-14/Channel 1427 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.350 W/kg Edge 3 Antenna OUT 21-11-14/Channel 1427 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.853 V/m; Power Drift = -0.04 dB Averaged SAR: SAR(1g) = 0.343 W/kg; SAR(10g) = 0.215 W/kg Maximum value of SAR (interpolated) = 0.501 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 21-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 4 1735 MHz; Frequency: 1753 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1752.5 MHz;  $\sigma$  = 1.52 S/m;  $\epsilon_r$  = 51.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 21-11-14/Channel 1513 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.358 W/kg Edge 3 Antenna OUT 21-11-14/Channel 1513 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.983 V/m; Power Drift = -0.07 dB Averaged SAR: SAR(1g) = 0.357 W/kg; SAR(10g) = 0.222 W/kg Maximum value of SAR (interpolated) = 0.519 W/kg



SAR Measurement Plot 48







# DUT Name: Dipole 1800 MHz, Type: DV1800V2, Serial: 242

# Configuration: System Check 21-11-14

Communication System: 0 - CW (0); Communication System Band: 1800 MHz; Frequency: 1800 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1800 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 50.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 21-11-14/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 12.100 W/kg System Check 21-11-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 91.817 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 9.640 W/kg; SAR(10g) = 5.150 W/kg Maximum value of SAR (interpolated) = 16.000 W/kg



SAR Measurement Plot 49







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1852 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1852.5 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 53.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

**Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9262 Test/Area Scan (61x111x1):** Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.239 W/kg **Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9262 Test/Zoom Scan (21x21x36)/Cube 0:** 

Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.801 V/m; Power Drift = 0.06 dB Averaged SAR: SAR(1g) = 0.228 W/kg; SAR(10g) = 0.138 W/kg

Maximum value of SAR (interpolated) = 0.338 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1880 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.55 S/m;  $\epsilon_r$  = 53.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9400 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.244 W/kg Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9400 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.104 V/m; Power Drift = -0.10 dB Averaged SAR: SAR(1g) = 0.234 W/kg; SAR(10g) = 0.142 W/kg

Maximum value of SAR (interpolated) = 0.357 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Bystander 25mm Spacing Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1907.5 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 53.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9538 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.271 W/kg Bystander 25mm Spacing Antenna OUT 24-11-14/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.637 V/m; Power Drift = 0.03 dB Averaged SAR: SAR(1g) = 0.258 W/kg; SAR(10g) = 0.155 W/kg

Maximum value of SAR (interpolated) = 0.399 W/kg









#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1852 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1852.5 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 53.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 24-11-14/Channel 9262 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.378 W/kg Lap Held Antenna OUT 24-11-14/Channel 9262 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.889 V/m; Power Drift = -0.13 dB Averaged SAR: SAR(1g) = 0.370 W/kg; SAR(10g) = 0.218 W/kg Maximum value of SAR (interpolated) = 0.568 W/kg



SAR Measurement Plot 53







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Lap Held Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1880 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.55 S/m;  $\epsilon_r$  = 53.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 24-11-14/Channel 9400 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.369 W/kg Lap Held Antenna OUT 24-11-14/Channel 9400 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.921 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.366 W/kg; SAR(10g) = 0.217 W/kg Maximum value of SAR (interpolated) = 0.568 W/kg



SAR Measurement Plot 54






### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1907.5 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 53.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 24-11-14/Channel 9538 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.367 W/kg Lap Held Antenna OUT 24-11-14/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 8.072 V/m; Power Drift = -0.10 dB Averaged SAR: SAR(1g) = 0.360 W/kg; SAR(10g) = 0.212 W/kg Maximum value of SAR (interpolated) = 0.572 W/kg



SAR Measurement Plot 55







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1852 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1852.5 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 53.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 24-11-14/Channel 9262 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.602 W/kg Edge 2 Antenna IN 24-11-14/Channel 9262 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.342 V/m; Power Drift = -0.19 dB Averaged SAR: SAR(1g) = 0.675 W/kg; SAR(10g) = 0.254 W/kg Maximum value of SAR (interpolated) = 1.480 W/kg



SAR Measurement Plot 56







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1880 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.55 S/m;  $\epsilon_r$  = 53.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 24-11-14/Channel 9400 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.537 W/kg Edge 2 Antenna IN 24-11-14/Channel 9400 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 14.910 V/m; Power Drift = -0.21 dB Averaged SAR: SAR(1g) = 0.577 W/kg; SAR(10g) = 0.217 W/kg Maximum value of SAR (interpolated) = 1.300 W/kg







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1907.5 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 53.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 24-11-14/Channel 9538 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.561 W/kg Edge 2 Antenna IN 24-11-14/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 15.003 V/m; Power Drift = -0.03 dB Averaged SAR: SAR(1g) = 0.623 W/kg; SAR(10g) = 0.233 W/kg Maximum value of SAR (interpolated) = 1.420 W/kg



SAR Measurement Plot 58







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 3 Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1852 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1852.5 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 53.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 24-11-14/Channel 9262 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.328 W/kg Edge 3 Antenna OUT 24-11-14/Channel 9262 Test/Zoom Scan (21x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.783 V/m; Power Drift = 0.02 dB Averaged SAR: SAR(1g) = 0.328 W/kg; SAR(10g) = 0.192 W/kg Maximum value of SAR (interpolated) = 0.473 W/kg



SAR Measurement Plot 59







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 3 Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1880 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.55 S/m;  $\epsilon_r$  = 53.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 24-11-14/Channel 9400 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.297 W/kg Edge 3 Antenna OUT 24-11-14/Channel 9400 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.399 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 0.294 W/kg; SAR(10g) = 0.173 W/kg Maximum value of SAR (interpolated) = 0.424 W/kg



SAR Measurement Plot 60







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 3 Antenna OUT 24-11-14

Communication System: 0 - WCDMA - UMTS (0); Communication System Band: Band 2 1850 MHz; Frequency: 1908 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1907.5 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 53.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 24-11-14/Channel 9538 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.289 W/kg Edge 3 Antenna OUT 24-11-14/Channel 9538 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 7.358 V/m; Power Drift = -0.04 dB Averaged SAR: SAR(1g) = 0.279 W/kg; SAR(10g) = 0.165 W/kg Maximum value of SAR (interpolated) = 0.416 W/kg



SAR Measurement Plot 61







# DUT Name: Dipole 1950 MHz, Type: DV1950V3, Serial: 1113

### **Configuration: System Check 24-11-14**

Communication System: 0 - CW (0); Communication System Band: 1950 MHz; Frequency: 1950 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1950 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 53.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.67,4.67,4.67); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 24-11-14/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 12.800 W/kg System Check 24-11-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 89.895 V/m; Power Drift = 0.00 dB Averaged SAR: SAR(1g) = 10.100 W/kg; SAR(10g) = 5.210 W/kg Maximum value of SAR (interpolated) = 17.500 W/kg



SAR Measurement Plot 62







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 824.7 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=824.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

**Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 1013 Test/Area Scan (61x111x1):** Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.407 W/kg

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 1013 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.187 V/m; Power Drift = -0.04 dB Averaged SAR: SAR(1g) = 0.397 W/kg; SAR(10g) = 0.274 W/kg Maximum value of SAR (interpolated) = 0.495 W/kg

0 dB = 0.407 W/kg = -3.90 dBW/kg

SAR Measurement Plot 63







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 836.5 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 56.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 0384 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.408 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 0384 Test/Zoom Scan (21x21x36)/Cube 0:

Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 16.298 V/m; Power Drift = -0.02 dB Averaged SAR: SAR(1g) = 0.401 W/kg; SAR(10g) = 0.277 W/kg

Maximum value of SAR (interpolated) = 0.505 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 848.3 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 56.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 0777 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.365 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 0777 Test/Zoom Scan (21x21x36)/Cube 0:

Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 15.333 V/m; Power Drift = 0.00 dB Averaged SAR: SAR(1g) = 0.353 W/kg; SAR(10g) = 0.243 W/kg

Maximum value of SAR (interpolated) = 0.447 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 824.7 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=824.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 1013 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.584 W/kg Lap Held Antenna OUT 29-10-14/Channel 1013 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 24.223 V/m; Power Drift = -0.10 dB Averaged SAR: SAR(1g) = 0.578 W/kg; SAR(10g) = 0.380 W/kg Maximum value of SAR (interpolated) = 0.773 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 836.5 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 56.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 0384 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.598 W/kg Lap Held Antenna OUT 29-10-14/Channel 0384 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 24.428 V/m; Power Drift = -0.02 dB Averaged SAR: SAR(1g) = 0.588 W/kg; SAR(10g) = 0.387 W/kg Maximum value of SAR (interpolated) = 0.780 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 848.3 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 56.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 0777 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.532 W/kg Lap Held Antenna OUT 29-10-14/Channel 0777 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 23.023 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.524 W/kg; SAR(10g) = 0.345 W/kg Maximum value of SAR (interpolated) = 0.703 W/kg



SAR Measurement Plot 68







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 824.7 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=824.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 1013 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.145 W/kg Edge 2 Antenna IN 29-10-14/Channel 1013 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.041 V/m; Power Drift = -0.11 dB Averaged SAR: SAR(1g) = 0.178 W/kg; SAR(10g) = 0.066 W/kg Maximum value of SAR (interpolated) = 0.637 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 836.5 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 56.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 0384 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.156 W/kg Edge 2 Antenna IN 29-10-14/Channel 0384 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.491 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.186 W/kg; SAR(10g) = 0.071 W/kg Maximum value of SAR (interpolated) = 0.641 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 848.3 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 56.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 0777 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.149 W/kg Edge 2 Antenna IN 29-10-14/Channel 0777 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 11.081 V/m; Power Drift = 0.15 dB Averaged SAR: SAR(1g) = 0.178 W/kg; SAR(10g) = 0.068 W/kg Maximum value of SAR (interpolated) = 0.631 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 824.7 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=824.5 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 1013 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.097 W/kg Edge 3 Antenna OUT 29-10-14/Channel 1013 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 5.882 V/m; Power Drift = 0.00 dB Averaged SAR: SAR(1g) = 0.101 W/kg; SAR(10g) = 0.068 W/kg Maximum value of SAR (interpolated) = 0.136 W/kg



SAR Measurement Plot 72






### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 836.5 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=836.5 MHz;  $\sigma$  = 1.00 S/m;  $\epsilon_r$  = 56.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 0384 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.110 W/kg Edge 3 Antenna OUT 29-10-14/Channel 0384 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 5.999 V/m; Power Drift = 0.05 dB Averaged SAR: SAR(1g) = 0.114 W/kg; SAR(10g) = 0.077 W/kg Maximum value of SAR (interpolated) = 0.158 W/kg



SAR Measurement Plot 73







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 0 (836 MHz); Frequency: 848.3 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=848.5 MHz;  $\sigma$  = 1.01 S/m;  $\epsilon_r$  = 56.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 0777 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.105 W/kg Edge 3 Antenna OUT 29-10-14/Channel 0777 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 5.834 V/m; Power Drift = 0.02 dB Averaged SAR: SAR(1g) = 0.109 W/kg; SAR(10g) = 0.073 W/kg Maximum value of SAR (interpolated) = 0.151 W/kg



SAR Measurement Plot 74







#### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 817.9 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=818 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

### **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 476 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.409 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 476 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 15.512 V/m; Power Drift = -0.00 dB Averaged SAR: SAR(1g) = 0.408 W/kg; SAR(10g) = 0.283 W/kg

Maximum value of SAR (interpolated) = 0.506 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

# Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 820.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=820 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 560 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.411 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 560 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 15.528 V/m; Power Drift = 0.01 dB Averaged SAR: SAR(1g) = 0.411 W/kg; SAR(10g) = 0.284 W/kg

Maximum value of SAR (interpolated) = 0.515 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Bystander 25mm Spacing Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 823.1 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=823 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 684 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.409 W/kg Bystander 25mm Spacing Antenna OUT 29-10-14/Channel 684 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 15.344 V/m; Power Drift = 0.07 dB Averaged SAR: SAR(1g) = 0.404 W/kg; SAR(10g) = 0.279 W/kg

Maximum value of SAR (interpolated) = 0.508 W/kg











### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 817.9 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=818 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 476 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.638 W/kg Lap Held Antenna OUT 29-10-14/Channel 476 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 20.723 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.625 W/kg; SAR(10g) = 0.413 W/kg Maximum value of SAR (interpolated) = 0.841 W/kg



SAR Measurement Plot 78







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 820.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=820 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 560 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.639 W/kg Lap Held Antenna OUT 29-10-14/Channel 560 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 20.910 V/m; Power Drift = -0.06 dB Averaged SAR: SAR(1g) = 0.630 W/kg; SAR(10g) = 0.415 W/kg Maximum value of SAR (interpolated) = 0.837 W/kg



SAR Measurement Plot 79







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Lap Held Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 823.1 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=823 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 29-10-14/Channel 684 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.625 W/kg Lap Held Antenna OUT 29-10-14/Channel 684 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 20.851 V/m; Power Drift = -0.21 dB Averaged SAR: SAR(1g) = 0.615 W/kg; SAR(10g) = 0.408 W/kg Maximum value of SAR (interpolated) = 0.807 W/kg











# DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

### Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 817.9 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=818 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 476 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.164 W/kg Edge 2 Antenna IN 29-10-14/Channel 476 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.394 V/m; Power Drift = 0.19 dB

Averaged SAR: SAR(1g) = 0.147 W/kg; SAR(10g) = 0.058 W/kg Maximum value of SAR (interpolated) = 0.485 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 820.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=820 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 560 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.166 W/kg

Edge 2 Antenna IN 29-10-14/Channel 560 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.593 V/m; Power Drift = -0.01 dB Averaged SAR: SAR(1g) = 0.146 W/kg; SAR(10g) = 0.058 W/kg

Maximum value of SAR (interpolated) = 0.479 W/kg



SAR Measurement Plot 82







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 2 Antenna IN 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 823.1 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=823 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 Antenna IN 29-10-14/Channel 684 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.157 W/kg Edge 2 Antenna IN 29-10-14/Channel 684 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.448 V/m; Power Drift = -0.09 dB Averaged SAR: SAR(1g) = 0.138 W/kg; SAR(10g) = 0.055 W/kg Maximum value of SAR (interpolated) = 0.446 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 817.9 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=818 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 476 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.109 W/kg Edge 3 Antenna OUT 29-10-14/Channel 476 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.730 V/m; Power Drift = -0.04 dB Averaged SAR: SAR(1g) = 0.124 W/kg; SAR(10g) = 0.079 W/kg Maximum value of SAR (interpolated) = 0.185 W/kg



SAR Measurement Plot 84







## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 820.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=820 MHz;  $\sigma$  = 0.98 S/m;  $\epsilon_r$  = 57.0;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 560 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.113 W/kg Edge 3 Antenna OUT 29-10-14/Channel 560 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.812 V/m; Power Drift = -0.03 dB Averaged SAR: SAR(1g) = 0.126 W/kg; SAR(10g) = 0.082 W/kg Maximum value of SAR (interpolated) = 0.188 W/kg



SAR Measurement Plot 85







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Edge 3 Antenna OUT 29-10-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 10 (810 MHz); Frequency: 823.1 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=823 MHz;  $\sigma$  = 0.99 S/m;  $\epsilon_r$  = 56.9;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 3 Antenna OUT 29-10-14/Channel 684 Test/Area Scan (111x61x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.111 W/kg Edge 3 Antenna OUT 29-10-14/Channel 684 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 6.725 V/m; Power Drift = 0.12 dB Averaged SAR: SAR(1g) = 0.128 W/kg; SAR(10g) = 0.082 W/kg Maximum value of SAR (interpolated) = 0.193 W/kg



SAR Measurement Plot 86







# DUT Name: Dipole 900 MHz, Type: DV900V2, Serial: 047

## Configuration: System Check

Communication System: 0 - CW; Communication System Band: 900 MHz; Frequency: 900.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00 Medium Parameters used: f=900 MHz;  $\sigma$  = 1.07 S/m;  $\epsilon_r$  = 56.2;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (5.86,5.86,5.86); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.150 W/kg

System Check/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 57.162 V/m; Power Drift = -0.00 dB Averaged SAR: SAR(1g) = 2.930 W/kg; SAR(10g) = 1.910 W/kg Maximum value of SAR (interpolated) = 4.210 W/kg









### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

#### Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 1 (1880 MHz); Frequency: 1851 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1851 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 0025 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.206 W/kg

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 0025 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.004 V/m; Power Drift = -0.09 dB Averaged SAR: SAR(1g) = 0.196 W/kg; SAR(10g) = 0.121 W/kg Maximum value of SAR (interpolated) = 0.294 W/kg

0 0 dB = 0.206 W/kg = -6.86 dBW/kg

SAR Measurement Plot 88







### DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 1 (1880 MHz); Frequency: 1880 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1880 MHz;  $\sigma$  = 1.56 S/m;  $\epsilon_r$  = 51.7;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 0600 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.210 W/kg Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 0600 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.151 V/m; Power Drift = -0.11 dB Averaged SAR: SAR(1g) = 0.197 W/kg; SAR(10g) = 0.121 W/kg

Maximum value of SAR (interpolated) = 0.299 W/kg









## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Bystander 25mm Spacing Antenna OUT 25-11-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 1 (1880 MHz); Frequency: 1909 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1908.5 MHz;  $\sigma$  = 1.58 S/m;  $\epsilon_r$  = 51.6;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

# **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 1175 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.242 W/kg Bystander 25mm Spacing Antenna OUT 25-11-14/Channel 1175 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 9.907 V/m; Power Drift = -0.00 dB Averaged SAR: SAR(1g) = 0.226 W/kg; SAR(10g) = 0.140 W/kg

Maximum value of SAR (interpolated) = 0.351 W/kg








Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M141025 Tablet 1900 MHz EVDO FCC.da52:3

## DUT Name: Fujitsu Tablet Trust with Sierra WWAN, Type: EM7355, Serial: IMEI:356196050042429

## Configuration: Lap Held Antenna OUT 25-11-14

Communication System: 0 - CDMA2000 (1xEv-Do 153.6 kbps) (0); Communication System Band: Band Class 1 (1880 MHz); Frequency: 1851 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00 Medium Parameters used: f=1851 MHz;  $\sigma$  = 1.54 S/m;  $\epsilon_r$  = 51.8;  $\rho$  = 1000.0g/cm<sup>3</sup> Phantom section: Flat Section

## **DASY Configuration:**

Probe: ET3DV6 - SN1380; ConvF: (4.68,4.68,4.68); Calibrated: 13/12/2013; Sensor-Surface: 4 mm (Mechanical Surface Detection) Electronics: DAE3 Sn442; Calibrated: 10/12/2013 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held Antenna OUT 25-11-14/Channel 0025 Test/Area Scan (61x111x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 0.474 W/kg Lap Held Antenna OUT 25-11-14/Channel 0025 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 14.123 V/m; Power Drift = -0.18 dB Averaged SAR: SAR(1g) = 0.465 W/kg; SAR(10g) = 0.273 W/kg Maximum value of SAR (interpolated) = 0.721 W/kg



SAR Measurement Plot 91



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.





Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.