

South Industrial Estate Bowburn Co. Durham DH6 5AD United Kingdom Tel: +44 (0) 191 377 2000 Fax: +44 (0) 191 377 2020 email: sgsiea@sgs.com SGS United Kingdom Ltd. International Electrical Approvals

Electromagnetic Compatibility

Test of:	RF Card Entry System	
Model Number:	Refer to page 5	
Applicant:	PAC International Ltd	
Test Type:	Compliance	
Test Specification:	FCC CFR47, parts 15.107, 15.109, 15.207 and 15.209	
Test Result:	Complied	
SGS Serial Number:	DUR 24095.1/EMC/LS/02	
Date of Receipt:	10 th June 2002	
Date of Test(s):	10 th June 2002 – 20 th June 2002	
Date of Issue:	10 th January 2003	
Issue Number:	4	

This report refers only to the sample submitted for test.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

Test Engineer

Authorised Signatory

L.Steel

A. Reynard Technical Manager

Page 1 of 15



CONTENTS

Page Number

1.	Clie	ent Info	rmation	3
2.	Det	ails Of	Test Laboratory	3
3.	Equ	uipment	t Under Test (EUT)	4
	3.1	Identifica	ation Of EUT	4
4.	Tes	st Speci	fication, Methods and Procedures	5
	4.1	Test Spe	ecification(s)	5
	4.2	Purpose	Of Test	5
	4.3	Methods	s and Procedures	5
EU	Т Ѕу	vstem D	liagram	6
5.	Dev	viations	or Exclusions from the Test Specifications	7
6.	Ор	eration	of the EUT During Testing / Configuration and Peripherals	7
	6.1	Operatio	on of EUT during testing.	7
	6.2	Configura	ation and Peripherals	7
7.	Tes	st Resul	lts	8
	7.1	General	Comments	8
	7.2	Modifica	tions Made to the EUT	8
	7.3	Summai	ry of Test Results	8
		7.4	Conducted Emissions Test Results – 15.107/15.207	9
		7.5	Radiated Emissions Test Results – 15.1091	2
		7.6	Radiated Emissions Test Results – 15.2091	4

TEST REPORT Page 2 of 15



1. Client Information

Company Name:	PAC International Ltd
Address:	1 Park Gate Close, Bredbury, Stockport, SK6 2SZ.
Contact Person:	Shaun Byrne
Telephone:	0161 406 3400
Facsimile:	0161 430 8658

2. Details Of Test Laboratory

Company Name:	SGS International Electrical Approvals
UKAS Accreditation Number:	1116
Address:	South Industrial Estate, Bowburn, Co. Durham, DH6 5AD.
Contact Persons:	Mr Alan Reynard
Telephone:	0191 377 2000
Facsimile:	0191 377 2020



3. Equipment Under Test (EUT)

3.1 Identification Of EUT

Model Number:	Refer to page 5.	
Unique Identifier:	Refer to page 5	
Description of EUT:	RF Card Entry System	
Internal Clock Frequencies:	Refer to page 5.	
Supply Voltage:	12 or 15v dc via ac/dc adapter (see page 5)	
(To Controller)	NOTE: All other parts of the system obtain their power via the controller.	
Classification:	Refer to page 5.	
Accessories Supplied:	Refer to page 5.	



4. Test Specification, Methods and Procedures

4.1 Test Specification(s)

Specification(s)	Title
FCC CFR 47 : October 1999	Code Of Federal Regulations
Parts 15.107/15.207, 15.109 and 15.209	

4.2 Purpose Of Test

- 1) To test the whole system to clauses 15.107/15.207 and 15.109
- 2) To test the 20373 front panel card reader only, to the requirements of 15.209 (Upto 30 MHz only).

4.3 Methods and Procedures

The standard listed above refers to the following tests: -

CFR 47 Clause	Test
15.107/15.207	Conducted Emissions
	(Intentional and Unintentional Radiators)
15.109	Radiated Emissions
(30-1000 MHz)	(Intentional and Unintentional Radiators)
15.209	Radiated Emissions
(9 kHz to 30 MHz)	(Intentional Radiator)



EUT System Diagram



Page 6 of 15

*1=150 Ω /100nF networks as terminations.

- NOTE 1: All interconnecting cables 1m long. Interconnecting cables are signal/low voltage dc.
- NOTE 2: Power adapter is not supplied by PAC. It is a typical power supply, supplied in order to perform the conducted emissions test.
- NOTE 3: For testing to 15.107/15.207 a different ac/dc adapter was used to that shown above. The details of the adapter used for the Conducted Emissions are as follows:

Manufacturer: Ecopac Power UK Ltd, Model: SA60-12v, Voltage: 12 v dc

Component Model No.	Serial No.	Descsription	Intentional/ Unintentional Radiator?	Highest Frequency Generated/Used
20373	None	Controller	Unintentional	11 MHz
20373	None	Front Panel	Intentional and Unintentional	11 MHz
20381	1973717	Card Reader	Intentional and Unintentional	614 kHz
20382	1973947	Card Reader	Intentional and Unintentional	614 kHz



5. Deviations or Exclusions from the Test Specifications

There were no deviations from the test specifications.

6. Operation of the EUT During Testing / Configuration and Peripherals

6.1 Operation of EUT during testing.

Refer to individual test results sections for details of EUT operation during testing.

6.2 Configuration and Peripherals

Refer to page 5.



7. Test Results

7.1 General Comments

The test methods used are referred to in the individual test results sections of this test report.

7.2 Modifications Made to the EUT

No modifications were made to the EUT during the testing process.

7.3 Summary of Test Results

CFR 47 Clause	Test	Result
15.107/15.207	Conducted Emissions	Complied
	(Whole EUT system tested)	
15.109	Radiated Emissions	Complied
	(Whole EUT system tested)	
15.209	Radiated Emissions	Complied
	(PAC 20373 front panel card reader only)	

Result

- i) In the configuration tested, the whole system complies with the requirements of Clauses 15.107/15.207 and 15.109 of CFR 47 : October 1999.
- ii) In the configuration tested, the PAC 20373 front panel card reader complies with the requirements of Clause 15.209 of CFR 47 : October 1999, across the frequency range 9 kHz to 30 MHz.

Full details of all tests can be found in the test results section of this report.



Conducted Emissions Test Results - 15.107/15.207 7.4

CFR 47 Clause:	15.107/15.207
Limits:	CISPR 22, Class B
	(As specified in FCC document FCC 02-157 (ET Docket No. 98-80), adopted May 23 rd 2002).
Frequency Range	0.15 – 30 MHz.

Operating Mode

The compliance test was performed with authorised cards presented to the controller front panel reader, the 20381 reader and the 20382 reader.

NOTE: Measurements were performed at the AC mains of the controller:

Page 9 of 15

Test Method

As per ANSI 63.4 : 1992

Measurement detector details: Quasi-Peak, 9 kHz bandwidth

Test Results

NOTE: The test results shown have automatically been corrected to account for LISN attenuation and cable loss, via measurement software.



Live Terminal Worst Case Emissions

Frequency (MHz)	Quasi Peak Measurement (dBµV)	Quasi Peak Limit (dBµV)	Average Measurement (dBμV)	Average Limit (dBμV)
0.182	44.47	64.4	42.47	54.4
0.246	43.87	61.9	43.1	51.9
0.484	37.7	56.3	37.4	46.3
0.966	36.97	50.5	36.97	40.5
1	36.37	56	36.37	46
16.01	34.55	60	31.05	50

TEST REPORT

Page 10 of 15

Neutral Terminal Worst Case Emissions

Frequency (MHz)	Quasi Peak Measurement	Quasi Peak Limit	Average Measurement	Average Limit
~ /	(dBµV)	(dBµV)	(dBµV)	(dBµV)
0.184	46.07	64.3	44.27	54.3
0.241	45.37	62.1	44.57	52.1
0.484	40.5	56.3	40.5	46.3
0.970	37.17	56	37.17	46
1.29	28.97	56	28.97	46
16.15	31.85	60	27.85	50



Issue Date:10th January 2003 SGS Serial Number:DUR24095.1/EMC/LS/02 Issue Number: 4

Conducted Emissions Test Configuration



TEST REPORT

Page 11 of 15

Conducted Emissions Environmental Conditions

Power Supply (to controller)	120V, 60Hz
Temperature	19.5°C
Relative Humidity	43%
Barometric Pressure	994mb

Conducted Emissions Measurement Uncertainties

Frequency	\pm 200kHz
Amplitude	\pm 3.0dB

The uncertainties stated are calculated in accordance with the requirements of UKAS with a confidence level of 95%.

Test Equipment Used

Equipment Type	Model Number	Last Calibration Date
LISN (50Ω)	Thurlby Thandar TTi 1600	Jan 02
Chase Receiver	LHR7000	Sep 01
SGS Screened Room	-	-
Spectrum Analyser	HP8563E	Nov 00
Check Equip.	PLC 1C	_



7.5 Radiated Emissions Test Results - 15.109

CFR Clause	15.109
Limits	Class B
Frequency Range	30-1000 MHz

Page 12 of 15

Operating Mode

The compliance test was performed with authorised cards presented to the controller front panel reader, the 20381 reader and the 20382 reader.

Test Results

Worst Case Emissions

Frequency MHz	Peak Measurement	Quasi-Peak Limit	Antenna Polarity
	@3m	@3m	
	(dBµV/m)	(dBµV/m)	
33.21	25.0	40.0	Vertical
44.26	22.5	40.0	Vertical
100.46	30.2	43.5	Vertical
120.00	16.5	43.5	Vertical
266.03	15.4	46.0	Vertical
278.42	14.7	46.0	Vertical
288.35	16.5	46.0	Vertical
299.68	17.2	46.0	Vertical

NOTE 1: The test results shown have automatically been corrected to account for Antenna factors, preamplifier gain and cable losses, via measurement software.

NOTE 2: Vertical antenna polarity was worst case for all emissions, hence results for horizontal antenna polarity were not recorded.

Test Method

As per ANSI 63.4 : 1992

Measurements performed at a test distance of 3m.

Measurement detector details: Quasi-Peak, 120 kHz bandwidth



Radiated Emissions Test Configuration



TEST REPORT

Page 13 of 15

Radiated Emissions Environmental Conditions

Power Supply (to controller)	120V AC, 60 Hz
Temperature	14.5°C
Relative Humidity	46%
Barometric Pressure	992mb

Radiated Emissions Measurement Uncertainties

Frequency	± 200kHz
Amplitude	± 4.6dB

The uncertainties stated are calculated in accordance with the requirements of UKAS with a confidence level of 95%.

Test Equipment Used

Equipment Type	Model Number	Last Calibration Date
Receiver System	HP 8573B	Nov 01
Biconical Antenna	EMCO 3110	Nov 00
Log Periodic Antenna	EMCO 3146	Aug 01
Pre-amplifier	ZHL 1042J	Jan 02
Check Equip.	York CNE III	-
Software	Open Site HP85879	-



7.6 Radiated Emissions Test Results – 15.209

CFR Clause	15.209
Frequency Range	9 kHz to 30 MHz

Operating Mode

The compliance test was performed with an authorised card presented to the controller front panel reader.

Test Results

Peak Measurements

Frequency	Corrected Peak	Limit	Measurement
MHz	Measurement**	(dBµV/m)	Distance
	(dBµV/m)		(metres)
*0.154	-12.35	23.87	300
0.041	-40.05	35.34	300
0.125	-46.6	25.66	300
0.165	-48.97	23.25	300
0.308	-27.89	17.83	300
¹ 0.700	-14.08	30.70	30
¹ 0.850	-14.08	29.01	30
¹ 0.900	-14.08	28.51	30

*Indicates EUT carrier frequency. The supply voltage to the controller was varied between 85% and 115% to maximise the carrier level.

¹Indicates typical noise floor figures of test equipment.

Test Method

As per ANSI 63.4 : 1992

** Measurements performed at a test distance of 1m and extrapolated to correct distance of 300m and 30m respectively using a factor of 40 dB/decade. Hence a correction factor of – 99.08 for 300m and –59.08 for 30m was used. The corrected levels are shown above.

Measurement detector details: Peak Detector, 300 Hz bandwidth where F=<150kHz, 10 kHz bandwidth where F=>150 kHz



Issue Date:23rd December 2002 SGS Serial Number:DUR24095.1/EMC/LS/02 Issue Number: 2

Radiated Emissions Test Configuration



TEST REPORT

Page 15 of 15

Radiated Emissions Environmental Conditions

Power Supply (to controller)	120V AC, 60 Hz
Temperature	13°C
Relative Humidity	59%
Barometric Pressure	976mb

Radiated Emissions Measurement Uncertainties

Frequency	± 200kHz
Amplitude	± 4.6dB

The uncertainties stated are calculated in accordance with the requirements of UKAS with a confidence level of 95%.

Test Equipment Used

Equipment Type	Model Number	Last Calibration Date
Loop Antenna	EMCO 6502	Dec 00
Spectrum Analyser	HP8563E	Nov 00