## FCC ID: 2AALP-S3

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \*

 $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculated.

Maximum measured transmitter power:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1-g SAR
2.402	GFSK	2.256	2±1	3	0.618	3.00
2.441	GFSK	3.777	3±1	4	0.785	3.00
2.480	GFSK	2.105	2±1	3	0.628	3.00
2.402	π/4-DQPSK	0.026	0±1	1	0.390	3.00
2.441	π/4-DQPSK	2.102	2±1	3	0.623	3.00
2.480	π/4-DQPSK	0.255	0±1	1	0.397	3.00
2.402	8-DPSK	0.711	0±1	-1	0.246	3.00
2.441	8-DPSK	2.466	2±1	3	0.623	3.00
2.480	8-DPSK	0.623	0±1	1	0.397	3.00
2.402	GFSK	4.069	4±1	5	0.980	3.00
2.440	GFSK	4.625	4±1	5	0.988	3.00
2.480	GFSK	3.618	3±1	4	0.791	3.00

Conclusion:

For the max result 0.988 ≤ 3.0 for 1-g SAR extremity SAR, No SAR is required.

Sincerely,

Signature Company Name: Emtek (Shenzhen) Co., Ltd. Address: Bldg 69, Majialong Industry Zone, NanshanDistrict, Shenzhen, China. David Lee/ Manager