

	D	D					В		А			
						字号 /i 1 2	反本号 VO	描 初版发行	述	日期 2023.11.24		
											9	
	Structure Description	Instructions		Common	Fault Process							
	Screen Rear cover	Power on /off Run automatically after power on. Magnetic card Please put the card magnetic strip towards to track device inside when swipe the card, it can support both directions; Make sure to swipe the card stably and constantly. Note: The transaction may be fail if magnetic card's tripe is damaged or swipe way is wrong.		r one other questions of the below so other questions of the b	lutions can't solve the problems or l s, please contact the maintainer. ault Reason Soluti bonse in is the button. The terminal crashed Reboot the 1.A piece of of hard cardbo	on terminal					S	
	IC Card Reader	IC card IC card slot locate in the bottom of the keypad, keep the chip side up when insert card, and insert IC card to the end. The IC card should be inserted in the IC card slot during the transaction process. Note: The transaction probably fail if IC card chip contact point is damaged or oxidative.		"Ca Read rea card erro failure ple res	d is dirty or 2 Remove the	veral it and ections, pe away n the e dirt on ic card er, if the oblem change the issue on to the he irrection, sed of d should						
											4	
	 Attention Of Installation And Operation ▲ Operating Temperature: 0 to 50°C Storage Temperature: -20°C to 70°C Relative Humidity: 5% to 95% (Non-Condensing) Please follow the instruction strictly when install and connect the terminal. Do not damage the power line and power adaptor. It can't be used any more if the power line or power adaptor is damaged. Please check power supply socket whether complying 	Hazardous and noxious substances or elements Pb Hg Cd Cr(VI) PBB PBDE PCB O O O O O O Notes: Image: State Sta	1 Integrated PINPAD	the limits for a the FCC Rules reasonable pro- residential inst and can radiatu and used in ac harmful interfe there is no gua particular insta harmful interfe	t has been tested and found to com Class B digital device, pursuant to p . These limits are designed to provi otection against harmful interference allation. This equipment generates, e radio frequency energy and, if not cordance with the instructions, may rence to radio communications. Ho rrantee that interference will not occ Illation. If this equipment does caus rence to radio or television receptio	part 15 of ide e in a , uses t installed / cause wever, cur in a e on, which						
ade Park, en District,	 with terminal set voltage before insert the AC socket. Recommend to choose the fuse socket, and grounding well. Please leave the terminal away from liquid, and forbidden splash into any liquid or electric conduction material, otherwise it will cause a short-circuit or damage to the terminal. Please do not insert any foreign material into any ports, it will damage the terminal seriously. Please contact the professional POS maintainer When the terminal have fault, users or other non-qualified POS maintainer should not repair the terminal. Please do not touch the cutter knife in case of hurt when install the paper roll. Please use the standard print paper in case of paper jam or printer damage. Please do not use or place flammability spray, painting, etc. in case of fire. Forbid to disassemble or remake the terminal. Forbidden to use the terminal in illegal way, offenders will stand legal responsibility. 	 O means the content of this hazardous and noxious substance in all the homogeneous material of the component is below the requirement of SJ/T 11363-2006 standard X means the content of this hazardous and noxious substance at least in certain homogeneous material is higher than the requirements of SJ/T 11363-2006 standard; but the components marked by "X" in the above form are all due to the current industry technology develop level and cannot realize the substitution of the hazardous and noxious substances or elements Environmental protection indication: for the products which arrives or exceeds the use life, should be recycled used according to <the and="" electronic="" information="" management="" of="" product="">, cannot discard arbitrarily.</the> 	to modify this manual without prior notice and conti improve the accuracy, adequacy and completeness information contained in this manual. Shenzhen Xinguodu Technology Co.,Ltd does not a any legal responsibility for the adverse consequenc caused by-using this product not in accordance wit manual or using accessories which are not supplied Shenzhen Xinguodu Technology Co.,Ltd. This manual is copyrighted by @ Shenzhen Xinguod Technology Co.,Ltd.	and continuously the user is encouraged to try to correct the interfered one or more of the following measures: ess not accept equences noe with this supplied by —Reorient or relocate the receiving antenna. —Increase the separation between the equipment is receiver. —Connect the equipment into an outlet on a circuit different from that to which the receiver is connect							S	
I				i							2	
				第三视角	●投影		深均	1市新国都3	支付技术>	有限公司		
				图纸 A4 单位 mm 设 计 李艳华				G201操作号	手册-FCC认证			
				审核	XXXX	比	例	1:3	材料	105g铜版纠	£ –	
				批 准 	何杰锋 216 REV. A	料 	子 本号	XXXXXXXX V0	完成日期 第 1 页	2023.11.2 共 1	4 页	
	D		С			, 12 🔪	B					

	D		С				В			А		
						序号 /i 1 2	版本号 VO	描 初版发行	述	日期 2023.1		
												D
	Screen Keypad Keypad C Card Reader IC Card Reader IC Card Reader IC Card C Card Slot locate in t chip side up when ins	second, the showing as aggnetic strip towards to track device e card, it can support both directions; e card stably and constantly. may be fail if magnetic card's tripe is	ess card card close to the NFC area, and stay for one en remove card when you hear a "Di" voice, follow picture.	If the below solu	The terminal crashed response terminal crashed terminal c	tion						
)	RS232 port HO THE Card should dring the transaction Note: The transaction fail if IC card chip con is damaged or oxidation A should be the transaction Note: The transaction is damaged or oxidation A should be the transaction Note: The transaction Note: The transaction fail if IC card chip con is damaged or oxidation A should be the transaction Note: The transaction A should be transaction Note: The transaction Note: The transaction Note: The transaction Note: The transaction A should be transaction Note: The transaction Not	process. probably tact point		the c	ard" Card in a itself, try to bank. wrong way. 3.Pay attenti surface of magnetic d and the sp swiping ca be kept sta	o change the issue ion to the the direction, eed of rd should						†
. Trade Park, h f. gzhen District,	 Relative Humidity: 5% to 95% (Non-Condensing) Please follow the instruction strictly when install and connect the terminal. Do not damage the power line and power adaptor. It can't be used any more if the power line or power adaptor is damaged. Please check power supply socket whether complying with terminal set voltage before insert the AC socket. Recommend to choose the fuse socket, and grounding well. Please leave the terminal away from liquid, and forbidden splash into any liquid or electric conduction material, otherwise it will cause a short-circuit or damage to the terminal seriously. Please do not insert any foreign material into any ports, it will damage the terminal seriously. Please contact the professional POS maintainer When the terminal have fault, users or other non-qualified POS maintainer should not repair the terminal. Please use the standard print paper in case of paper jam 	At of this hazardous and noxious homogeneous material of the the requirement of SJ/T rd to f this hazardous and noxious n certain homogeneous material is uirements of SJ/T 11363-2006 mponents marked by "X" in the ue to the current industry technology annot realize the substitution of the	Item Quantity Integrated PINPAD 1 Operation Manual 1 Incement Xinguodu Technology Co.,Ltd reserves the right is manual without prior notice and continuously a accuracy, adequacy and completeness of the contained in this manual. Xinguodu Technology Co.,Ltd does not accept seponsibility for the adverse consequences using this product not in accordance with this using accessories which are not supplied by Xinguodu Technology Co.,Ltd. al is copyrighted by @ Shenzhen Xinguodu	the user is encouraged to try to correct the interference by							С 	
											C	7
第三视角投影									盲限公	司		
			图纸	图纸 A4 单位 mm 设 计 李艳华		G201操作手册-FCC认证						
			审	核	XXXX	比	例	1:3	材 料	105g钉	司版纸 -	
			批	准	何杰锋	料	号	XXXXXXXX	完成日期	2023.	11.24	
	FORM-R&D-216 REV. A 版本号 V0 第 1						第 1 页 	共 1 页				
	D C A							\searrow				