

EMF ASSESSMENT REPORT

Test Report No:	24-4791132400-9-1-2-RAD				
UL Project No:	4791132400				
Date of issue:	2024-12-23				
Total number of pages:	19				
Applicant:	SECO S.p.A.				
	Via Achille Grandi, 20				
	52100 Arezzo (AR) – Italy				
Contact's person:	Giacomo Martini (<u>giacomo.maritni@seco.com</u>)				
	Alessandro Savelli (<u>alessandro.savelli@seco.com)</u>				
Testing Laboratory:	UL International Italia S.r.I.				
	Via delle Industrie, 6				
	20061 Carugate (MI) – Italy				
lesting location:	UL International Italia S.r.I.				
	Via delle industrie, 6 20061 Carugato (MI) Italy				
Test specification:					
Regulations:	FCC				
Standards:	47 CFR Part 15				
Standards.	Parts 1.1307, 1.1310, 2.1091, 2.1093				
Non-standard test method:	N/A				
Scope of testing:	EMF Evaluation / MPE Calculation				
TRF No.:	TRF_EMF_rev 4				
est Report Form(s) Originator: UL International Italia S.r.I.					
Master TRF	2017-07				
Compiled by:	Andrea Giovanni Galbiati				
(name, function, signature)	Laboratory Engineer Fluchne Grovouri Golbioti				
	0 0				
Approved by:	Francesco Casati				
(name, function, signature)	Operations Leader Caral trancesco				
General disclaimer:					
The test results presented in this test report re	elate only to the object tested, not selected by UL International Italia S.r.l				
This report shall not be reproduced, except in	full, without the written approval of the issuing Testing Laboratory.				
I his document contains data (of information) using color and it printed, should be printed in color to retain legibility and the information represented by the color.					
Declination of responsibility:					
Data provided by the customer are clearly	identified with (*). UL International Italia S.r.I. cannot be considered				
responsible for this information, for any other document sent by the Applicant/Manufacturer and for any difference					
between the software version present in the tested sort	ested sample and that present in the object intended for final sale.				

not represent the software installed in the final version of the product.



Test Item Description:	KIOSK-HEAD 27"
Trade Mark: (*)	Теснло Gym
Manufacturer: (*)	Technogym S.p.A. Via Calcinaro, 2861 47521 Cesena (FC) – Italy
Model/Type reference: (*)	KIOSK-HEAD 27
Ratings: (*)	100-240 Vac; 1.0-0.5 A; 50/60 Hz
Testing:	
Date of receipt of test item:	2024-02-19
UL Sample Tag No.:	6773319
Status of sample upon receipt:	⊠ New and operational
	Reconditioned
	Damaged
Date(s) of performance of tests:	
Name and address of factory(ies): (*)	Technogym S.p.A. Via Calcinaro, 2861 47521 Cesena (FC) – Italy

General remarks:

A cross \square in a rectangular shape means that this option is applied.

Indicates that the listed condition, standard or equipment is applicable for this report.

□ Indicates that the listed condition, standard or equipment is not applicable for this report.

Throughout this report a □ comma / ⊠ point is used as decimal separator.

Where not otherwise specified or communicated in writing, statements of conformity (e.g. Pass/Fail) are established according to the following decision rule:

 considering that the applied test standards take measurement uncertainty into account, acceptance limit equals the tolerance limit (simple acceptance). This leads to a maximum 50% of false accept or false reject when the measured value equals the tolerance limit. See ILAC-G8:09/2019 for further details.

General product information: (*)

The Technogym Health represents an additional input point to further shape the Technogym personalized wellness journey.

It would allow to: collect additional users' health and fitness data needed to validate training program results, provide efficient and high-quality personalized training, increase Technogym's community, user motivation, health insights and retention. It would also represent a marketing tool to help the operator collecting new leads



Document history

Test Report No.	Reason for change	Date of issue
24-4791132400-9-1-0-RAD	Original release	2024-04-15
24-4791132400-9-1-1-RAD	 Deleting of marking plate section Deleting of IC ID below additional information of integrated radio module Deleting of section of photos of EUT Deleting of Attachment 1 Deleting of Attachment 2 Updating of power level and calculation 	2024-12-09
24-4791132400-9-1-2-RAD	Updating of power level and calculationUpdating of name of model	2024-12-23

NOTE: New test report issue cancels and replaces the previous one.



Table of Contents

1	Te	est Item Description	5
	1.1	Additional information of integrated radio module	7
2	Ve	erdict summary section	9
3	М	PE Assessment Requirements	10
	3.1	Exposure Limits	10
	3.2	Determination of exemption	11
	3.3	Radiofrequency radiation exposure evaluation: mobile devices	14
4	Μ	PE Calculation Method	15
	4.1	Single transmission evaluation results	16
	4.2	Multiple transmissions evaluation results	17
5	M	easurement Uncertainty	18
A	ttachr	nent 1: Opinions and Interpretations	19



1 Test Item Description

Serial number: (*)	E30	BR023080001						
Date of production: (*)	NIA							
Ports: (*)	Port		Cable					
			Spec lengt	tified Attache h(m) during te		ed est	Shielded	
	AC N	Mains	<	3				
	2 x l	JSB type-A 2.0	<	3				
	Seria	al Port	<	3				
	Ethe	rnet	>	3				
Supplementary information to the ports:								
Rated power supply: (*)		Voltage and frequency			Referen	се р	oles	
				N	L1	L	2 L3	
	\boxtimes	AC: 100-240 V; 50/60	Hz	Χ		Ľ		
		DC:						
Rated power: (*)								
Protection class: (*)	1							
Environment of intended use: (*)	X	Household / Residentia	al					
		Professional / Commer	rcial /	Light-i	industrial			
		Industrial						
		Professional healthcare	e facil	ity (on	ly for ME)		
		Home healthcare (only	for M	E)				
		Special (only for ME)						
		Road and Street						
Rated power: (*)								
Protection class: (*)		0						
	⊠							
		II (external PSU)						
		III (sensor)						
Environment of intended use: (*)	\boxtimes	Household / Residentia	al					
		Professional / Commer	cial /	Light-	industrial			
		Industrial						
		Professional healthcare	e facil	ity (on	ly for ME)		
		Home healthcare (only	for M	E)				
		Special (only for ME)						
		Road and Street						
		Automotive						



Working frequencies: (*)	32.768 kHz (RTC); 125 MHz (ETH Physical); 24MHz (USB); 74 MHz (LVDS spreaded) 2.4 GHz (Wi-Fi & BT) 5 GHz (Wi-Fi)						
Other parameters: (*)	NIA						
Firmware/Software version: (*)	40.1	5.2.5 + UnityTe	stApp_1.6				
Hardware version: (*)	NIA						
Dimensions in cm (W x H x D): (*)	58 x	179 x 62					
Modules/parts: (*)	Mod	ule/parts of test	item	Туре		Manufacturer	
Operating modes:	No. Operating mode o		de of test	le of test Ap Emissio		plied for testing	
		item				Immunity	
	1						
Supplemental information to the operating mode:							
Auxiliary equipment (AuxEq):	Desc	cription	Manufacturer		Туре		
Peripheral equipment that is part of the system under test							
Associated equipment (AE):	Description		Manufacturer		Туре		
Equipment that is not part of the system under test but needed to exercise and/or monitor the EUT							
Documents as provided by the applicant:	Description		File name		Issue date		
(*)							
Modifications to the test item during testing:	None						



1.1 Additional information of integrated radio module

Producer :	SECO (contains Murata module)
Module name	Murata LBEE5ZZ1XL
Frequency range :	2400 – 2483.5 MHz ; 5000 MHz (Wi-Fi 2.4 GHz b/g/n)
	5200 ; 5400 ; 5800 MHz (Wi-Fi 5GHz a)
	5000 MHz (Wi-Fi 5 GHz ac)
	2400 – 2483.5 MHz ; 5GHz (Wi-Fi 2.4 & 5 GHz ax)
	2400 – 2483.5 (Bluetooth 5.3)
FCC ID :	2ALZB-AS2DTGM
Antenna :	External antennas.



2 Key Features

- NXP 88W9098 inside
- Supports IEEE 802.11a/b/g/n/ac/ax specification: Dual band 2.4 GHz and 5 GHz
- MIMO with 20 MHz, 40 MHz, and 80 MHz channels
- Up to MCS11 data rates (1200 Mbps)
- Supports Bluetooth specification version 5.3
- For supported Bluetooth functions, refer to Bluetooth SIG site 1
- WLAN interface: PCIe 2.0 and SDIO 3.0
- Bluetooth interface: HCI UART and PCM
- Dimensions: 19.1 x 16.5 x 2.1 mm
- Weight: 1355 mg
- MSL: 3
- Surface-mount type
- RoHS compliant
- B10 life: 13 years, B1 life: 10 years
 (Wear-out failure with 20°C daily ambient room temperature change)
- Fit: 140.36 (Accidental failure)



Producer :	Elettronica GF S.r.I. & Dynastream innovations Inc.
Module name :	061F & D52M
Frequency range :	13.56 MHz (RFID) & 2402 MHz ÷ 2480 MHz (BLE)
FCC ID :	2ARDN0615D & O6R3153
Antenna :	Integrated antenna.
HUN Set of the set of	



2 Verdict summary section

Requirement – Test case	Reference standard	Accreditation	Verdict
Human exposure to electromagnetic fields	FCC 47 CFR Part 15 Parts 1.1307, 1.1310, 2.1091, 2.1093	None	Р
Supplementary information:			

Possible test case verdicts:
Test case not performed: N/P
Test case does not apply to test object: N/A
Test object does meet requirement: Pass (P)
Test object does not meet requirement: Fail (F)



3 MPE Assessment Requirements

3.1 Exposure Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
	(i) Li	mits for Occupational/Controlled Exposure		
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
	(ii) Limit	s for General Population/Uncontrolled Exposure		
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

Table 1 to § 1.1310(e)(1)-Limits for Maximum Permissible Exposure (MPE)



3.2 Determination of exemption

Single RF source

§1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

§1.1307(b)(3)(i)(B)

Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} (mW) = \begin{cases} ERP_{20 \ cm} (d/20 \ cm)^x & d \le 20 \ cm \\ ERP_{20 \ cm} & 20 \ cm < d \le 40 \ cm \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20} cm\sqrt{f}}\right)$$
 and *f* is in GHz

and

$$ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

d = the separation distance (cm);



§1.1307(b)(3)(i)(C)

Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C)—Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .



Multiple RF sources

§1.1307(b)(3)(ii)(A)

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

§1.1307(b)(3)(ii)(B)

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth, i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



3.3 Radiofrequency radiation exposure evaluation: mobile devices

§2.1091(a)

Requirements of this section are a consequence of Commission responsibilities under the National Environmental Policy Act to evaluate the environmental significance of its actions. See subpart I of part 1 of this chapter, in particular § 1.1307(b).

<u>§2.1091(b)</u>

For purposes of this section, the definitions in § 1.1307(b)(2) of this chapter shall apply. A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of **at least 20 centimeters** is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location while transmitting. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal desktop computer, are considered to be mobile devices **if they meet the 20-centimeter separation requirement**.

§2.1091(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP20cm in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the subscience from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$P_{th}(\text{mW}) = ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$

§2.1091(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

§2.1091(c)(3)

Unless otherwise specified in this chapter, any other single mobile or multiple mobile and portable RF source(s) associated with a device is exempt from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in § 1.1307(c) and (d) of this chapter



4 MPE Calculation Method

This model is applicable in the far-field region and over-estimates in the radiating near-field region. The farfield calculations are accurate when the distance, r, from an antenna of length D to a point of investigation is grater than

$$r = \frac{2D^2}{\lambda}$$

The Power density is

$$S = \frac{PG}{4\pi r^2}$$

Or equivalent:

$$S = \frac{EIRP}{4\pi r^2}$$

Where

P = Input power of the antenna

G = Antenna Gain relative to an isotropic antenna

r = distance from the antenna to the point of investigation

EIRP = Effective Isotropic Radiated Power

Conversion of output power:

 $dBm = 10 \times LOG_{10}(mW)$

 $mW = 10^{(dBm/10)}$

 $W = 10^{[(dBm-30)/10]}$

Conversion of Power Density:

 $1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$

1 W/m² = 0.1 mW/cm²



4.1 Single transmission evaluation results

Туре	Frequency (*) (MHz)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm²)	Limit (**) (mW/cm²)	Verdict
ВТ	2402	9.55	9.01	0.001793	1.0	Р
BLE	2442	9.52	8.95	0.001781	1.0	Р
Wi-Fi 2.4 GHz	2417	31.14	1300	0.258758	1.0	Р
Wi-Fi 5 GHz	5300	26.74	472	0.093962	1.0	Р

(*) As worst case, the lowest transmitting frequency of each band is used to determine the permissible minimum separation distance. (**) General population/Uncontrolled exposure, safety distance= 20 cm

NFC function (13.56 MHz) was not included because it has no influence on RF Exposure calculation. Electric Field @ 30m: < 0.5 mV/m



4.2 Multiple transmissions evaluation results

MAXIMUM PERMISSIBLE EXPOSURE (MPE)							
Evaluation Distance (m)	0.2						
Worst case simultaneous transmission	BT + BLE + Wi-Fi 2.4 GHz + Wi-Fi 5 GHz						
Туре	вт	BLE	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz			
S: Power Density at evaluation distance (mW/cm ²)	0.001793	0.001781	0.258758	0.093962			
S _{Lim} : Power Density Limit (mW/cm ²)	1.0	1.0	1.0	1.0			
Simultaneous Transmission Limit	$\sum_{i=1}^{n} \frac{S_i}{SLim_i} < 1$						
CALCULATION							
$\frac{0.001793}{1.0} + \frac{0.001781}{1.0} + \frac{0.258758}{1.0} + \frac{0.093962}{1.0} = 0.001783 + 0.001781 + 0.258758 + 0.093962 = 0.356 < 100000000000000000000000000000000000$							
VERDICT							
The Sum of the MPE Ratio is WITHIN THE LIMIT							



5 Measurement Uncertainty

Assessment is based on power levels and declared antenna gains detailed in this test report and were taken from the following RF module test report(s). EUT test information such as test equipment used, date of actual test, environmental conditions, measurement uncertainty and the person who performed the original tests are referenced in the listed test report/s.

Reference document	Provided by		
TGYM_Operational Description_FCC_IC v02	SECO S.p.A.		

< END OF TEST REPORT >



Attachment 1: Opinions and Interpretations

Not Applicable.

< END OF ATTACHMENT 1 >