

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Dongle with Bluetooth 5.3(Dual Mode) function operating in 2402-2480MHz and 5.2GHz function operating in 5155-5245MHz and 5.8GHz function operating in 5730-5848MHz. The EUT is powered by DC 5V/1.2A from adapter. For more detail information pls. refer to the user manual.

Modulation Type: GFSK, $\pi/4$ QPSK, and 8-DPSK

Bluetooth Version: 5.3 EDR

Antenna Type: Integral antenna

Antenna Gain: 2.25dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: -8dBm (Tolerance: +/- 3dB)

The nominal conducted output power specified: -10.25dBm (Tolerance: +/- 3dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 88.1 dB μ V/m at 3m in the frequency 2441MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -7.13 dBm

which is within the production variation.

The minimum peak radiated emission for the EUT is 84.8 dB μ V/m at 3m in the frequency 2402MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -10.43 dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -8dBm+3dB= -5dBm = 0.32mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

BLE:

Modulation Type: GFSK

Bluetooth Version: 5.3 BLE

Antenna Type: Integral antenna

Antenna Gain: 2.25dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: -8dBm (Tolerance: +/- 2dB)

The nominal conducted output power specified: -10.25dBm (Tolerance: +/- 2dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 88.5dBμV/m at 3m in the frequency 2440MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -6.73dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 86.6dBμV/m at 3m in the frequency 2480MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -8.63dBm
which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -8dBm+2dB= -6dBm = 0.25mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

5.8G:

Modulation Type: GFSK

Antenna Type: Integral antenna

Antenna 1 Gain: 3.67dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

Antenna 2 Gain: 3.84dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: -4dBm (Tolerance: +/- 2dB)

The nominal conducted output power specified: -7.67dBm (Tolerance: +/- 2dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 91.0dBμV/m at 3m in the frequency 5790MHz(ANT1)

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -4.23dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 89.9dBμV/m at 3m in the frequency 5730MHz(ANT1)

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -5.33dBm
which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -4dBm+2dB= -2dBm = 0.63mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 5.8GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

5.2G:

Modulation Type: GFSK

Antenna Type: Integral antenna

Antenna 1 Gain: 2.44dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

Antenna 2 Gain: 1.97dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal conducted output power specified: 4dBm (Tolerance: +/- 2dB)

The maximum conducted output power for the EUT is 5.95dBm in the frequency 5245MHz(ANT2) which is within the production variation.

The minimum conducted output power for the EUT is 3.11dBm in the frequency 5245MHz(ANT1) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting device is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 6dBm + 2.44dBi = 8.44dBm = 6.98mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 5.2GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

For Simultaneous transmitting of EDR and 5.8G and 5.2G, According to 865664D02 2.2 d) 1):
The sum of the ratios of the spatially averaged results to the applicable frequency
dependent ERP ratio = $0.32/3060 + 0.63/3060 + 6.98/3060 = 0.0030 < 1$

Since the sum of the ERP ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy ERP compliance for simultaneous transmission operations.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

FCC ID: 2BF6V-HT512DE