





RF TEST REPORT

Applicant Compal Electronics, Inc.

FCC ID GKREXCN1

Product 4G LCC Module

Brand COMPAL

Model EXC-N1

Report No. R2209A0845-R3V2

Issue Date October 20, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in FCC CFR47 Part 2 (2021)/ FCC CFR47 Part 27C (2021). The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

In Ying

Approved by: Xu Kai

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1	Tes	st Laboratory	5
	1.1	Notes of the Test Report	5
	1.2.	Test facility	5
	1.3	Testing Location	5
2	Gei	neral Description of Equipment under Test	6
	2.1	Applicant and Manufacturer Information	6
	2.2	General information	6
3	Apı	plied Standards	8
4	Tes	st Configuration	9
5	Tes	st Case	12
	5.1	RF Power Output and Effective Isotropic Radiated Power	12
	5.2	Occupied Bandwidth	14
	5.3	Band Edge	15
	5.4	Peak-to-Average Power Ratio (PAPR)	18
	5.5	Frequency Stability	19
	5.6	Spurious Emissions at Antenna Terminals	20
	5.7	Radiates Spurious Emission	22
6	Tes	st Results	26
	6.1	RF Power Output and Effective Isotropic Radiated Power	26
	6.2	Occupied Bandwidth	36
	6.3	Band Edge	59
	6.4	Peak-to-Average Power Ratio (PAPR)	93
	6.5	Frequency Stability	97
	6.6	Spurious Emissions at Antenna Terminals	101
	6.7	Radiates Spurious Emission	121
7	Mai	in Test Instruments	128
A	NNEX	A: The EUT Appearance and Change declaration letter	129
Α	NNEX	B: Test Setup Photos	130



Update information.

Update description.

Version

Rev.0

Rev.1

Rev.2

Revision descriptionIssue DateInitial issue of report.September 28, 2022

Report No.: R2209A0845-R3V2

October 19, 2022

October 20, 2022

Note: This revised report (Report No. R2209A0845-R3V2) supersedes and replaces the previously issued report (Report No. R2209A0845-R3V1). Please discard or destroy the previously issued report and dispose of it accordingly.



Summary of Measurement Results

Number	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Isotropic Radiated Power	2.1046 27.50(d)(4) /27.50(b)(10) /27.50(c)(10)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge	27.53(h) /27.53(g) /27.53(f) /27.53(c) /27.53(m)	PASS
4	Peak-to-Average Power Ratio	27.50(d)/KDB971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 27.54	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 /27.53(h) /27.53(g) /27.53(f) /27.53(c) /27.53(m)	PASS
7	Radiates Spurious Emission	2.1053 /27.53(h) /27.53(g) /27.53(m) /27.53(f) /27.53(c)	PASS

Date of Testing: September 3, 2019 ~ September 24, 2019 Date of Sample Received: (R2208A0783): August 25, 2022

Note: 1. PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

2. All test values duplicated from the report (Report No.: R2208A0783-R3).



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology** (shanghai) co., Ltd. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai,

Address: China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: http://www.ta-shanghai.com

E-mail: xukai@ta-shanghai.com



2 General Description of Equipment under Test

2.1 Applicant and Manufacturer Information

Applicant Compal Electronics, Inc.			
Applicant address No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei, (1			
Manufacturer	Compal Electronics, Inc.		
Manufacturer address	No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei, (114) Taiwan		

2.2 General information


EUT Description							
Model	EXC-N1						
IMEI	863879041726491						
Hardware Version	EXC-N1_MB_V1.01						
Software Version	EXC-N1_4.71.5_EQ10	1					
Power Supply	External Power Supply	,					
Antenna Type	The EUT don't have st	andard Antenna. The Antenna used for					
Antenna Type	testing in this report is	the after-market accessory.					
	WCDMA IV :2.5dBi						
	LTE Band 4:2.5dBi						
Antenna Gain	LTE Band 12:1.8dBi						
, misima Gam	LTE Band 13:1.8dBi						
	LTE Band 17:1.8dBi						
	LTE Band 41:3.9dBi						
Test Mode(s)	WCDMA Band IV;						
Test Wede(s)	LTE Band 4/12/13/17/41						
Test Modulation	(WCDMA) BPSK, QPS	K, (LTE)QPSK 16QAM;					
HSDPA UE Category	12						
HSUPA UE Category	8						
LTE Category	4						
	WCDMA Band IV:	25.47dBm					
	LTE Band 4:	25.20dBm					
Maximum E.I.R.P./ E.R.P.	LTE Band 12:	23.34dBm					
Maximum E.I.N.F./ E.N.F.	LTE Band 13:	22.96dBm					
	LTE Band 17	23.13dBm					
	LTE Band 41:	26.62dBm					
Rated Power Supply Voltage:	e: 3.8V						
Operating Voltage	Minimum: 3.3V Max	imum: 4.2V					
Operating Temperature	Lowest: -40°C High	nest: +85°C					



est Report Report No.: R2209A0845-R3V2

Testing Temperature	Lowest: -40°C Highe	est: +90°C	
	Mode	Tx (MHz)	Rx (MHz)
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
Operating Frequency Range(s)	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 17	704 ~716	734 ~746
	LTE Band 41	2496 ~ 2690	2496 ~ 2690

Note: The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.





3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 27C (2021)

FCC CFR47 Part 2 (2021)

Reference standard:

ANSI C63.26-2015

KDB 971168 D01 Power Meas License Digital Systems v03r01



4 Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated. Subsequently, only the worst case emissions are reported.

The following testing in WCDMA/LTE is set based on the maximum RF Output Power.

The following testing in different Bandwidth is set to detailin the following table:

Test modes are chosen to be reported as the worst case configuration below for WCDMA Band IV:

Test items	Modes/Modulation			
rest items	WCDMA Band IV			
	RMC			
RF power output	HSDPA/HSUPA			
	DC-HSDPA			
Effective Isotropic Radiated power	RMC			
Occupied Bandwidth	RMC			
Band Edge	RMC			
Peak-to-Average Power Ratio	RMC			
Frequency Stability	RMC			
Spurious Emissions at Antenna Terminals	RMC			
Radiates Spurious Emission	RMC			



Test modes are chosen to be reported as the worst case configuration below for LTE Band 4/12/13/17/41:

		Bandwidth (MHz)					Modulation		RB			Test			
Test items	Modes											Channel			
	1.75.4	1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	Н
	LTE 4	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RF power	LTE 12 LTE 13	0	0	0	0	-	-	0	0	0	0	0	0	0	0
output	LTE 17	-	-	0	0	-	-	0	0	0	0	0	0	0	0
	LTE 41	-	-	0	0	- 0	- 0	0	0	0	0	0	0	0	0
		-											0	1	
- c · ·	LTE 4	0	0	0	0	0	0	0	0	0	0	0		0	0
Effective Isotropic	LTE 12	0	0	0	0	-	-	0	0	0	0	0	0	0	0
Radiated	LTE 13	-	-	0	0	-	-	0	0	0	0	0	0	0	0
power	LTE 17	-	-	0	0	-	-	0	0	0	0	0	0	0	0
	LTE 41	-	-	0	0	0	0	0	0	0	0	0	0	0	0
	LTE 4	0	0	0	0	0	0	0	0	1	-	0	0	0	0
Occupied	LTE 12	0	0	0	0	-	ı	0	0	-	-	0	0	0	0
Bandwidth	LTE 13	-	-	0	0	-	-	0	0			0	0	0	0
Dandwidth	LTE 17	-	-	0	0	-	-	0	0	-	-	0	0	0	0
	LTE 41	-	-	0	0	0	0	0	0	-	-	0	0	0	0
	LTE 4	0	0	0	0	0	0	0	0	0	-	0	0	-	0
	LTE 12	0	0	0	0	-	-	0	0	0	-	0	0	-	0
Band Edge	LTE 13	-	-	0	0	-	-	0	0	0	-	0	0	-	0
	LTE 17	-	-	0	0	-	-	0	0	0	-	0	0	-	0
	LTE 41	-	-	0	0	0	0	0	0	0	-	0	0	-	0
	LTE 4	0	0	0	0	0	0	0	0	-	-	0	0	0	0
Peak-to-Aver	LTE 12	0	0	0	0	-	-	0	0	-	-	0	0	0	0
age Power	LTE 13	-	-	0	0	-	-	0	0	-	-	0	0	0	0
Ratio	LTE 17	-	-	0	0	-	-	0	0	-	-	0	0	0	0
	LTE 41	-	-	0	0	0	0	0	0	-	-	0	0	0	0
	LTE 4	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Frequency	LTE 12	0	0	0	0	-	-	0	0	0	0	0	0	0	0
Stability	LTE 13	-	-	0	0	-	-	0	0	0	0	0	0	0	0
	LTE 17	-	-	0	0	-	-	0	0	0	0	0	0	0	0
	LTE 41	-	-	0	0	0	0	0	0	0	0	0	0	0	0
Spurious	LTE 4	0	0	0	0	0	0	0	-	0	-	-	0	0	0
Emissions at	LTE 12	0	0	0	0	-	-	0	-	0	-	-	0	0	0
Antenna	LTE 13	-	-	0	0	-	-	0	-	0	-	-	0	0	0
Terminals	LTE 17			0	0	1	-	0	-	0	-	-	0	0	0

TA Technology (Shanghai) Co., Ltd.

TA-MB-05-003R

Page 10 of 130

TA .	RF Test Rep	ort								Report	No.: R220	9A0845-R	3V2		
	LTE 41	-	-	0	0	0	0	0	-	0	-	-	0	0	0
	LTE 4	0	-	0	-	-	0	0	-	0	-	-	0	0	0
Radiates	LTE 12	0	-	0	0	-	-	0	-	0	-	-	-	0	-
Spurious	LTE 13	-	-	0	0	-	-	0	-	0	-	-	-	0	-
Emission	LTE 17	-	-	0	0	-	-	0	-	0	-	-	-	0	-
LTE 41 O O - O - O						0	-								
Note	1. The m	1. The mark "O" means that this configuration is chosen for testing.													
Note	2. The m	nark "-	" mea	ns tha	t this	confia	uratior	n is not te	estina.						



5 Test Case

5.1 RF Power Output and Effective Isotropic Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement


During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.

ERP can then be calculated as follows:

EIRP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBi) where:dBd refers to gain relative to an ideal dipole.

EIRP (dBm) = ERP (dBm) + 2.15 (dB.)

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 27.50(b) (10) specifies that "Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP"

Rule Part 27.50(d) (4) specifies that "Fixed, mobile and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP"

Rule Part 27.50(h) (2) specifies that "Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power."



Test Report No.: R2209A0845-R3V2

Part 27.50(b)(10)	≤ 3 W (34.77 dBm)
Part 27.50(c)(10)	≤ 3 W (34.77 dBm)
Part 27.50(d)(4)	≤ 1 W (30 dBm)
Part 27.50(h)(2)	≤ 2 W (33 dBm)

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U=0.4 dB for RF power output, k = 2, U=0.4 dB for ERP/EIRP.

Test Results

Refer to the section 6.1 of this report for test data.



5.2 Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to ≥1%EBW, VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 624Hz.

Test Results

Refer to the section 6.2 of this report for test data.



F Test Report Report No.: R2209A0845-R3V2

5.3 Band Edge

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured.

The testing follows KDB 971168 D01 v03r01 Section 6.0

The EUT was connected to spectrum analyzer and system simulator via a power divider.

The band edges of low and high channels for the highest RF powers were measured.


For LTE Band 41 the middle channel, high channel set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge. Beyond the 1 MHz band from the band edge, RBW=1MHz was used; Low channel set RBW >= 2% EBW in the 1MHz band immediately outside and adjacent to the band edge. Beyond the 1 MHz band from the band edge, RBW=1MHz was used. RBW is set to ≥1%EBW, VBW is set to 3x RBW on spectrum analyzer.

Set spectrum analyzer with RMS detector.

The RF fundamental frequency should be excluded against the limit line in the operating frequency band

Checked that all the results comply with the emission limit line.

Test Setup



Limits

Rule Part 27.53(i) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz.

Rule Part 27.53(h) specifies that "for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P) dB$ "

Rule Part 27.53(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the TA Technology (Shanghai) Co., Ltd.

TA-MB-05-003R

Page 15 of 130



F Test Report No.: R2209A0845-R3V2

transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(m) (4)/ specifies that "for BRS and EBS stations. For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(4) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Example:

The limit line is derived from 43 + 10log (P) dB below the transmitter power P(Watts)

- = P(W) [43 + 10log(P)] (dB)
- = [30 + 10log(P)](dBm) [43 + 10log(P)](dB) = -13dBm.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Rule Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;



RF Test Report No.: R2209A0845-R3V2

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U=0.684dB.

Test Results

Refer to the section 6.3 of this report for test data.



5.4 Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure			
23°C ~25°C	45%~50%	101.5kPa			

Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (*e.g.*, dBm). Determine the PAPR from:

PAPR(dB) = PPk(dBm) - PAvg(dBm).

Test Setup



Limits

Rule Part 27.50(d)(5) Equipment employed must be authorized in accordance with the provisions of 24.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (d)(6) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for thenormal distribution is with the coverage factor k = 2, U = 0.4 dB.

Test Results

Refer to the section 6.4 of this report for test data.



5.5 Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size.

- (1)With all power removed, the temperature was decreased to -10°C and permitted to stabilize for three hours.
- (2)Measure the carrier frequency with the test equipment in a "call mode". These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.
- (3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried,

battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.2 V, with a nominal voltage of 3.8V.

Test setup



Limits

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor k = 3, U = 0.01ppm.

Test Results

Refer to the section 6.5 of this report for test data.



Test Report Report No.: R2209A0845-R3V2

5.6 Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure			
23°C ~25°C	45%~50%	101.5kPa			

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.


RBW is set to 100kHz, VBW is set to 300kHz for 30MHz~1GHz

RBW is set to 1MHz, VBW is set to 3MHz for above 1GHz, Sweep is set to ATUO.

Of those disturbances below (limit – 20 dB), the mark is not required for the EUT.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 27.53(h) specifies that "for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.."

Rule Part 27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically



F Test Report Report No.: R2209A0845-R3V2

radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Rule Part 27.53(m) $55 + 10 \log (P) dB$ on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(4) of this section.

Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

Part 27.53(a)/(h)/(g)	-13 dBm	
Dort 27 52/f) Limit	Limit out of the band 1559-1610 MHz	-13 dBm
Part 27.53(f) Limit	Limit in the band 1559-1610 MHz	-40 dBm
Part 27.53(m) Limit		-25 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor k = 1.96.

Frequency	Uncertainty			
9kHz-1GHz	0.684 dB			
1GHz-27GHz	1.407 dB			

Test Results

Refer to the section 6.6 of this report for test data.



F Test Report No.: R2209A0845-R3V2

5.7 Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

- 1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI C63.26-2015.
- 2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
- 3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz, VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, and the maximum value of the receiver should be recorded as (Pr).
- 5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (PcI) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
- 7. The measurement results are obtained as described below:

Power(EIRP)=PMea- PAg - Pcl + Ga

The measurement results are amend as described below:

Power(EIRP)=PMea- PcI + Ga


8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dB.

Report No.: R2209A0845-R3V2


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz~30MHz



30MHz~1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m



RF Test Report No.: R2209A0845-R3V2

Rule Part 27.53(h) specifies that "for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB."

Rule Part 27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f)For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Rule Part 27.53(m) 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(4) of this section.

Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;



Test Report No.: R2209A0845-R3V2

Part 27.53(a)/(h)/(g)	-13 dBm	
Dort 27 52/f) Limit	Limit out of the band 1559-1610 MHz	-13 dBm
Part 27.53(f) Limit	Limit in the band 1559-1610 MHz	-40 dBm
Part 27.53(m) Limit		-25 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = \pm 1.96$, $U = \pm 3.55$ dB.

Test Results

Refer to the section 6.7 of this report for test data.



6 Test Results

6.1 RF Power Output and Effective Isotropic Radiated Power

	Maximum	Output Po	wer (dBm)	EIRP (dBm)			
		Channel	Channel	Channel	Channel	Channel	Channel
WCDMA	Band IV	1312	1413	1513	1312	1413	1513
		1712.4	1732.6	1752.6	1712.4	1732.6	1752.6
		(MHz)	(MHz)	(MHz)	(MHz)	(MHz)	(MHz)
RM	IC	22.97	22.94	22.87	25.47	25.44	25.37
	Sub - Test 1	22.43	22.36	22.31	24.93	24.86	24.81
HSDPA	Sub - Test 2	22.42	22.38	22.28	24.92	24.88	24.78
ПЭДРА	Sub - Test 3	21.89	21.88	21.80	24.39	24.38	24.30
	Sub - Test 4	21.90	21.89	21.78	24.40	24.39	24.28
	Sub - Test 1	22.39	22.35	22.26	24.89	24.85	24.76
	Sub - Test 2	21.38	21.33	21.25	23.88	23.83	23.75
HSUPA	Sub - Test 3	21.85	21.81	21.74	24.35	24.31	24.24
	Sub - Test 4	21.31	21.30	21.22	23.81	23.80	23.72
	Sub - Test 5	22.32	22.28	22.20	24.82	24.78	24.70
	Sub - Test 1	22.31	22.30	22.21	24.81	24.80	24.71
DC HEDDA	Sub - Test 2	22.30	22.29	22.20	24.80	24.79	24.70
DC-HSDPA	Sub - Test 3	21.88	21.78	21.71	24.38	24.28	24.21
	Sub - Test 4	21.87	21.77	21.70	24.37	24.27	24.20



LTE Band 4			Maximum Output Power(dBm) EIRP (dBm)					n)	
		RB	RB	Channel/Frequency(MHz)					
BW	BW Modulation	size	offset	19957/	20175/	20393/	19957/	20175/	20393/
				1710.7	1732.5	1754.3	1710.7	1732.5	1754.3
		1	0	22.13	22.38	22.63	24.63	24.88	25.13
		1	2	22.34	22.20	22.65	24.84	24.70	25.15
		1	5	22.29	22.25	22.55	24.79	24.75	25.05
	QPSK	3	0	21.01	21.15	21.41	23.51	23.65	23.91
		3	2	21.06	21.19	21.35	23.56	23.69	23.85
		3	3	21.18	21.22	21.29	23.68	23.72	23.79
1.4MHz		6	0	21.14	21.25	21.36	23.64	23.75	23.86
1.4IVI⊓Z		1	0	21.10	21.96	21.94	23.60	24.46	24.44
		1	2	21.09	22.12	21.90	23.59	24.62	24.40
		1	5	20.99	22.00	21.63	23.49	24.50	24.13
	16QAM	3	0	20.12	20.05	20.26	22.62	22.55	22.76
		3	2	20.11	20.04	20.23	22.61	22.54	22.73
		3	3	20.17	20.04	20.09	22.67	22.54	22.59
		6	0	20.31	20.36	20.21	22.81	22.86	22.71
		RB	RB		Ch	annel/Free	quency(MI	Hz)	
BW	Modulation	size	offset	19965/	20175/	20385/	19965/	20175/	20385/
		0120	Oncot	1711.5	1732.5	1753.5	1711.5	1732.5	1753.5
		1	0	22.15	22.42	22.66	24.65	24.92	25.16
		1	7	22.37	22.25	22.69	24.87	24.75	25.19
		1	14	22.32	22.30	22.59	24.82	24.80	25.09
	QPSK	8	0	21.09	21.25	21.52	23.59	23.75	24.02
		8	4	21.16	21.27	21.45	23.66	23.77	23.95
		8	7	21.26	21.31	21.37	23.76	23.81	23.87
0.041.1-		15	0	21.17	21.29	21.39	23.67	23.79	23.89
3MHz		1	0	21.13	21.98	21.97	23.63	24.48	24.47
		1	7	21.12	22.17	21.94	23.62	24.67	24.44
		1	14	21.01	22.04	21.66	23.51	24.54	24.16
	16QAM	8	0	20.21	20.16	20.36	22.71	22.66	22.86
		8	4	20.20	20.15	20.33	22.70	22.65	22.83
		8	7	20.25	20.14	20.20	22.75	22.64	22.70
		15	0	20.34	20.40	20.24	22.84	22.90	22.74

7A RF TO	est Report						Report No	o.: R2209A08	45-R3V2
<u> </u>	- Streport				Ch	annel/Fre			40 1(012
BW Modulation	RB	RB	19975/	20175/	20375/	19975/	20175/	20375/	
		size	offset	1712.5	1732.5	1752.5	1712.5	1732.5	1752.5
		1	0	22.12	22.40	22.62	24.62	24.90	25.12
		1	13	22.35	22.21	22.66	24.85	24.71	25.16
		1	24	22.29	22.25	22.55	24.79	24.75	25.05
	QPSK	12	0	21.06	21.20	21.48	23.56	23.70	23.98
		12	6	21.14	21.23	21.40	23.64	23.73	23.90
		12	13	21.24	21.29	21.33	23.74	23.79	23.83
55411		25	0	21.15	21.28	21.37	23.65	23.78	23.87
5MHz		1	0	21.10	21.94	21.94	23.60	24.44	24.44
		1	13	21.09	22.15	21.91	23.59	24.65	24.41
		1	24	20.98	22.02	21.62	23.48	24.52	24.12
	16QAM	12	0	20.19	20.12	20.33	22.69	22.62	22.83
		12	6	20.17	20.10	20.29	22.67	22.60	22.79
		12	13	20.22	20.09	20.16	22.72	22.59	22.66
		25	0	20.32	20.36	20.19	22.82	22.86	22.69
		RB	RB	Channel/Frequency(MHz)					
BW	Modulation	size	offset	20000/	20175/	20350/	20000/	20175/	20350/
		0.20	Gilloct	1715	1732.5	1750	1715	1732.5	1750
		1	0	22.14	22.41	22.65	24.64	24.91	25.15
		1	25	22.38	22.26	22.70	24.88	24.76	25.20
		1	49	22.31	22.29	22.58	24.81	24.79	25.08
	QPSK	25	0	21.09	21.25	21.52	23.59	23.75	24.02
		25	13	21.17	21.28	21.44	23.67	23.78	23.94
		25	25	21.26	21.33	21.38	23.76	23.83	23.88
10MHz		50	0	21.23	21.30	21.41	23.73	23.80	23.91
1 OIVII 12		1	0	21.12	21.97	21.96	23.62	24.47	24.46
		1	25	21.12	22.19	21.94	23.62	24.69	24.44
		1	49	21.01	22.04	21.65	23.51	24.54	24.15
	16QAM	25	0	20.22	20.17	20.37	22.72	22.67	22.87
		25	13	20.19	20.14	20.32	22.69	22.64	22.82
		25	25	20.25	20.14	20.20	22.75	22.64	22.70
		50	0	20.35	20.41	20.23	22.85	22.91	22.73
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
DIA		1 (0							

Modulation

QPSK

BW

15MHz

20325/

1747.5

22.63

20175/

1732.5

22.37

Page 28 of 130

20325/

1747.5

25.13

20175/

1732.5

24.87

20025/

1717.5

24.63

20025/

1717.5

22.13

offset

0

size

1

RF Te	est Report						Report No	.: R2209A08	45-R3V2	
		1	38	22.36	22.25	22.67	24.86	24.75	25.17	
		1	74	22.28	22.24	22.54	24.78	24.74	25.04	
		36	0	21.07	21.21	21.49	23.57	23.71	23.99	
		36	18	21.14	21.23	21.40	23.64	23.73	23.90	
		36	39	21.23	21.30	21.34	23.73	23.80	23.84	
		75	0	21.21	21.26	21.36	23.71	23.76	23.86	
		1	0	21.07	21.95	21.94	23.57	24.45	24.44	
		1	38	21.10	22.16	21.92	23.60	24.66	24.42	
		1	74	20.98	22.00	21.62	23.48	24.50	24.12	
	16QAM	36	0	20.19	20.15	20.34	22.69	22.65	22.84	
		36	18	20.16	20.09	20.28	22.66	22.59	22.78	
		36	39	20.23	20.10	20.17	22.73	22.60	22.67	
		75	0	20.32	20.36	20.19	22.82	22.86	22.69	
		RB size	RB offset	Channel/Frequency(MHz)						
BW	Modulation			20050/	20175/	20300/	20050/	20175/	20300/	
				1720	1732.5	1745	1720	1732.5	1745	
		1	0	22.10	22.33	22.60	24.60	24.83	25.10	
		1	50	22.35	22.21	22.65	24.85	24.71	25.15	
		1	99	22.26	22.23	22.51	24.76	24.73	25.01	
	QPSK	50	0	21.04	21.16	21.45	23.54	23.66	23.95	
		50	25	21.12	21.19	21.37	23.62	23.69	23.87	
		50	50	21.20	21.25	21.30	23.70	23.75	23.8	
201411-		100	0	21.18	21.21	21.32	23.68	23.71	23.82	
20MHz		1	0	21.05	21.91	21.89	23.55	24.41	24.39	
		1	50	21.06	22.14	21.88	23.56	24.64	24.38	
		1	99	20.96	21.97	21.60	23.46	24.47	24.1	
	16QAM	50	0	20.16	20.11	20.31	22.66	22.61	22.81	
		50	25	20.13	20.07	20.25	22.63	22.57	22.75	
		50	50	20.20	20.05	20.13	22.70	22.55	22.63	
		100	0	20.30	20.32	20.16	22.80	22.82	22.66	

LTE Band 12				Maximum Output Power(dBm)			ERP (dBm)		
BW	Modulation	RB size	RB offset	23017/ 699.7	Ch 23095/ 707.5	annel/Fred 23173/ 715.3	quency(MI 23017/ 699.7	Hz) 23095/ 707.5	23173/ 715.3
1.4MHz	QPSK	1	0	23.37	23.27	23.06	23.02	22.92	22.71

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		1	2	23.24	23.22	23.65	22.89	22.87	23.30
		1	5	23.35	23.35	23.07	23.00	23.00	22.72
		3	0	22.39	22.19	22.32	22.04	21.84	21.97
		3	2	22.35	22.25	22.28	22.00	21.90	21.93
		3	3	22.24	22.40	22.27	21.89	22.05	21.92
		6	0	22.31	22.37	22.38	21.96	22.02	22.03
		1	0	22.53	22.86	21.76	22.18	22.51	21.41
		1	2	22.84	22.21	22.42	22.49	21.86	22.07
		1	5	22.40	22.92	21.84	22.05	22.57	21.49
	16QAM	3	0	21.47	21.46	21.56	21.12	21.11	21.21
		3	2	21.40	21.44	21.52	21.05	21.09	21.17
		3	3	21.31	21.41	21.49	20.96	21.06	21.14
		6	0	21.41	22.33	21.35	21.06	21.98	21.00
		RB	RB		Ch	annel/Free	quency(MI	Hz)	
BW	Modulation	size	offset	23025/	23095/	23165/	23025/	23095/	23165/
		0120	Onoot	700.5	707.5	714.5	700.5	707.5	714.5
		1	0	23.39	23.28	23.09	23.04	22.93	22.74
	QPSK	1	7	23.27	23.27	23.69	22.92	22.92	23.34
		1	14	23.37	23.39	23.10	23.02	23.04	22.75
		8	0	22.42	22.24	22.36	22.07	21.89	22.01
		8	4	22.38	22.30	22.32	22.03	21.95	21.97
		8	7	22.26	22.44	22.32	21.91	22.09	21.97
3MHz		15	0	22.39	22.39	22.42	22.04	22.04	22.07
SIVIFIZ		1	0	22.55	22.89	21.78	22.20	22.54	21.43
		1	7	22.87	22.25	22.45	22.52	21.90	22.10
		1	14	22.43	22.94	21.87	22.08	22.59	21.52
	16QAM	8	0	21.50	21.51	21.60	21.15	21.16	21.25
		8	4	21.42	21.48	21.55	21.07	21.13	21.20
		8	7	21.34	21.46	21.53	20.99	21.11	21.18
		15	0	21.44	22.38	21.39	21.09	22.03	21.04
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	23035/	23095/	23155/	23035/	23095/	23155/
				701.5	707.5	713.5	701.5	707.5	713.5
		1	0	23.38	23.24	23.07	23.03	22.89	22.72
5MHz	QPSK	1	13	23.25	23.26	23.66	22.90	22.91	23.31
JIVII IZ	QI OIL	1	24	23.34	23.34	23.06	22.99	22.99	22.71
		12	0	22.40	22.20	22.33	22.05	21.85	21.98

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		12	6	22.35	22.25	22.28	22.00	21.90	21.93
		12	13	22.23	22.41	22.28	21.88	22.06	21.93
		25	0	22.37	22.35	22.37	22.02	22.00	22.02
		1	0	22.50	22.87	21.76	22.15	22.52	21.41
		1	13	22.85	22.22	22.43	22.50	21.87	22.08
		1	24	22.40	22.90	21.84	22.05	22.55	21.49
	16QAM	12	0	21.47	21.49	21.57	21.12	21.14	21.22
		12	6	21.39	21.43	21.51	21.04	21.08	21.16
		12	13	21.32	21.42	21.50	20.97	21.07	21.15
		25	0	21.41	22.33	21.35	21.06	21.98	21.00
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	23060/	23095/	23130/	23060/	23095/	23130/
		0.20	0001	704	707.5	711	704	707.5	711
		1	0	23.35	23.20	23.04	23.00	22.85	22.69
		1	25	23.24	23.22	23.64	22.89	22.87	23.29
		1	49	23.32	23.33	23.03	22.97	22.98	22.68
	QPSK	25	0	22.37	22.15	22.29	22.02	21.80	21.94
		25	13	22.33	22.21	22.25	21.98	21.86	21.90
		25	25	22.20	22.36	22.24	21.85	22.01	21.89
10MHz		50	0	22.34	22.30	22.33	21.99	21.95	21.98
TOWINZ		1	0	22.48	22.83	21.71	22.13	22.48	21.36
		1	25	22.81	22.20	22.39	22.46	21.85	22.04
		1	49	22.38	22.87	21.82	22.03	22.52	21.47
	16QAM	25	0	21.44	21.45	21.54	21.09	21.10	21.19
		25	13	21.36	21.41	21.48	21.01	21.06	21.13
		25	25	21.29	21.37	21.46	20.94	21.02	21.11
		50	0	21.39	22.29	21.32	21.04	21.94	20.97

	LTE Band	Maximum Output Power(dBm)			ERP (dBm)				
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	23205/	23230/	23255/	23205/	23230/	23255/
		0120	Cilott	779.5	782	784.5	779.5	782	784.5
		1	0	22.95	23.13	23.22	22.60	22.78	22.87
ENAL I-	ODCK	1	13	23.01	23.11	23.11	22.66	22.76	22.76
5MHz	QPSK	1	24	23.18	23.21	23.31	22.83	22.86	22.96
		12	0	22.15	22.11	22.29	21.80	21.76	21.94

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		12	6	22.06	22.17	22.25	21.71	21.82	21.90
		12	13	22.07	22.31	22.29	21.72	21.96	21.94
		25	0	21.89	22.20	22.28	21.54	21.85	21.93
		1	0	22.35	21.57	21.81	22.00	21.22	21.46
		1	13	22.28	21.72	22.16	21.93	21.37	21.81
		1	24	22.49	21.61	21.66	22.14	21.26	21.31
	16QAM	12	0	21.11	21.14	21.19	20.76	20.79	20.84
		12	6	21.03	21.24	21.21	20.68	20.89	20.86
		12	13	20.92	21.31	21.28	20.57	20.96	20.93
		25	0	21.18	21.28	21.26	20.83	20.93	20.91
		RB	RB		Ch	annel/Fre	quency(MI	Hz)	
BW	Modulation	size	offset	1	23230/	/	/	23230/	/
				,	782	,	,	782	,
		1	0	1	23.17	1	/	22.82	/
		1	25	1	23.31	1	1	22.96	1
		1	49	1	23.11	1	1	22.76	/
	QPSK	25	0	/	22.08	/	/	21.73	/
		25	13	/	22.05	/	/	21.70	/
		25	25	/	22.04	/	/	21.69	/
10MHz		50	0	/	22.23	/	/	21.88	/
IUIVIMZ		1	0	/	21.62	/	/	21.27	/
		1	25	/	21.69	/	/	21.34	/
		1	49	/	21.70	/	/	21.35	/
	16QAM	25	0	/	21.17	/	/	20.82	/
		25	13	/	21.23	/	/	20.88	/
		25	25	/	21.32	/	/	20.97	/
		50	0	/	21.16	/	/	20.81	/

LTE Band 17				Maximum Output Power(dBm)			ERP (dBm)		
	RB		RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	23755/	23790/	23825/	23755/	23790/	23825/
	SIZE		Oliset	706.5	710	713.5	706.5	710	713.5
		1	0	23.38	23.40	23.29	23.03	23.05	22.94
		1	13	23.46	23.31	23.48	23.11	22.96	23.13
5MHz	QPSK	1	24	23.36	23.21	23.28	23.01	22.86	22.93
		12	0	22.44	22.39	22.36	22.09	22.04	22.01
		12	6	22.38	22.41	22.36	22.03	22.06	22.01

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		12	13	22.29	22.52	22.50	21.94	22.17	22.15
		25	0	22.45	22.34	22.49	22.10	21.99	22.14
		1	0	22.29	22.65	22.90	21.94	22.30	22.55
		1	13	22.17	23.14	22.95	21.82	22.79	22.60
		1	24	22.04	22.41	23.12	21.69	22.06	22.77
	16QAM	12	0	21.58	21.52	21.37	21.23	21.17	21.02
		12	6	21.30	21.45	21.40	20.95	21.10	21.05
		12	13	21.58	21.58	21.46	21.23	21.23	21.11
		25	0	21.45	21.59	21.50	21.10	21.24	21.15
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	23780/	23790/	23800/	23780/	23790/	23800/
		0.20	0001	709	710	711	709	710	711
		1	0	23.35	23.36	23.26	23.00	23.01	22.91
		1	25	23.45	23.27	23.46	23.10	22.92	23.11
		1	49	23.34	23.20	23.25	22.99	22.85	22.9
	QPSK	25	0	22.41	22.34	22.32	22.06	21.99	21.97
		25	13	22.36	22.37	22.33	22.01	22.02	21.98
		25	25	22.26	22.47	22.46	21.91	22.12	22.11
10MHz		50	0	22.42	22.29	22.45	22.07	21.94	22.10
TUIVITZ		1	0	22.27	22.61	22.85	21.92	22.26	22.50
		1	25	22.13	23.12	22.91	21.78	22.77	22.56
		1	49	22.02	22.38	23.10	21.67	22.03	22.75
	16QAM	25	0	21.55	21.48	21.34	21.20	21.13	20.99
		25	13	21.27	21.43	21.37	20.92	21.08	21.02
		25	25	21.55	21.53	21.42	21.20	21.18	21.07
		50	0	21.43	21.55	21.47	21.08	21.20	21.12

	LTE Band	Maximum Output Power(dBm)			EIRP (dBm)				
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	39675/	40620/	41565/	39675/	40620/	41565/
	S	SIZE	Oliset	2498.5	2593	2687.5	2498.5	2593	2687.5
		1	0	22.36	22.44	21.73	26.26	26.34	25.63
		1	13	22.69	22.43	22.19	26.59	26.33	26.09
5MHz	QPSK	1	24	22.23	22.28	21.98	26.13	26.18	25.88
		12	0	21.37	21.23	21.16	25.27	25.13	25.06
		12	6	21.35	21.26	21.19	25.25	25.16	25.09

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		12	13	21.36	21.35	21.24	25.26	25.25	25.14
		25	0	21.33	21.29	21.34	25.23	25.19	25.24
		1	0	21.05	21.65	21.59	24.95	25.55	25.49
		1	13	21.19	21.93	21.98	25.09	25.83	25.88
		1	24	20.74	21.54	21.52	24.64	25.44	25.42
	16QAM	12	0	20.53	20.12	20.33	24.43	24.02	24.23
		12	6	20.52	20.11	20.30	24.42	24.01	24.20
		12	13	20.46	20.17	20.25	24.36	24.07	24.15
		25	0	20.47	20.29	20.27	24.37	24.19	24.17
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	39700/	40620/	41540/	39700/	40620/	41540/
		0120	Oncot	2501	2593	2685	2501	2593	2685
		1	0	22.38	22.45	21.76	26.28	26.35	25.66
		1	25	22.72	22.48	22.23	26.62	26.38	26.13
		1	49	22.25	22.32	22.01	26.15	26.22	25.91
	QPSK	25	0	21.40	21.28	21.20	25.30	25.18	25.10
		25	13	21.38	21.31	21.23	25.28	25.21	25.13
		25	25	21.38	21.39	21.29	25.28	25.29	25.19
10MHz		50	0	21.41	21.31	21.38	25.31	25.21	25.28
TUIVITZ		1	0	21.07	21.68	21.61	24.97	25.58	25.51
		1	25	21.22	21.97	22.01	25.12	25.87	25.91
		1	49	20.77	21.56	21.55	24.67	25.46	25.45
	16QAM	25	0	20.56	20.17	20.37	24.46	24.07	24.27
		25	13	20.54	20.15	20.33	24.44	24.05	24.23
		25	25	20.49	20.22	20.29	24.39	24.12	24.19
		50	0	20.50	20.34	20.31	24.40	24.24	24.21
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	39725/	40620/	41515/	39725/	40620/	41515/
				2503.5	2593	2682.5	2503.5	2593	2682.5
		1	0	22.37	22.41	21.74	26.27	26.31	25.64
		1	38	22.70	22.47	22.20	26.60	26.37	26.10
		1	74	22.22	22.27	21.97	26.12	26.17	25.87
15MHz	QPSK	36	0	21.38	21.24	21.17	25.28	25.14	25.07
. 5 12		36	18	21.35	21.26	21.19	25.25	25.16	25.09
		36	39	21.35	21.36	21.25	25.25	25.26	25.15
		75	0	21.39	21.27	21.33	25.29	25.17	25.23
	16QAM	1	0	21.02	21.66	21.59	24.92	25.56	25.49

RF Te	est Report						Report No	.: R2209A08	45-R3V2
		1	38	21.20	21.94	21.99	25.10	25.84	25.89
		1	74	20.74	21.52	21.52	24.64	25.42	25.42
		36	0	20.53	20.15	20.34	24.43	24.05	24.24
		36	18	20.51	20.10	20.29	24.41	24.00	24.19
		36	39	20.47	20.18	20.26	24.37	24.08	24.16
		75	0	20.47	20.29	20.27	24.37	24.19	24.17
		RB	RB		Ch	annel/Fred	quency(MI	Hz)	
BW	Modulation	size	offset	39750/	40620/	41490/	39750/	40620/	41490/
		3120	Oliset	2506	2593	2680	2506	2593	2680
		1	0	22.34	22.37	21.71	26.24	26.27	25.61
	QPSK	1	50	22.69	22.43	22.18	26.59	26.33	26.08
		1	99	22.20	22.26	21.94	26.10	26.16	25.84
		50	0	21.35	21.19	21.13	25.25	25.09	25.03
		50	25	21.33	21.22	21.16	25.23	25.12	25.06
		50	50	21.32	21.31	21.21	25.22	25.21	25.11
20MHz		100	0	21.36	21.22	21.29	25.26	25.12	25.19
ZUIVITZ		1	0	21.00	21.62	21.54	24.90	25.52	25.44
		1	50	21.16	21.92	21.95	25.06	25.82	25.85
		1	99	20.72	21.49	21.50	24.62	25.39	25.40
	16QAM	50	0	20.50	20.11	20.31	24.40	24.01	24.21
		50	25	20.48	20.08	20.26	24.38	23.98	24.16
		50	50	20.44	20.13	20.22	24.34	24.03	24.12
		100	0	20.45	20.25	20.24	24.35	24.15	24.14



6.2 Occupied Bandwidth

Mode	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
WCDMA Band IV	1312	1712.4	4.1161	4.676
WCDMA Band IV	1413	1732.6	4.1231	4.688
(RMC)	1513	1752.6	4.1251	4.668

LTE Band 4 Pandwidth Frequency 99% Power 26dRc											
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)					
		(1411 12)	19957	1710.7	1.1217	1.350					
		1.4	20175	1732.5	1.1224	1.350					
			20393	1754.3	1.1218	1.330					
			19965	1711.5	2.7431	3.078					
		3	20175	1732.5	2.7522	3.071					
			20385	1753.5	2.7369	3.069					
			19975	1712.5	4.5377	5.034					
		5	20175	1732.5	4.5192	5.013					
	QPSK		20375	1752.5	4.5084	4.999					
			20000	1715	9.0159	10.020					
		10	20175	1732.5	9.014	9.962					
			20350	1750	9.0374	9.990					
			20025	1717.5	13.465	14.840					
100%		15	20175	1732.5	13.405	14.610					
			20325	1747.5	13.405	14.660					
			20050	1720	17.88	19.280					
		20	20175	1732.5	17.824	19.090					
			20300	1745	17.862	19.250					
			19957	1710.7	1.124	1.335					
		1.4	20175	1732.5	1.1231	1.318					
			20393	1754.3	1.1184	1.342					
			19965	1711.5	2.7471	3.061					
	16QAM	3	20175	1732.5	2.7359	3.055					
	. 5 42, 1111		20385	1753.5	2.7337	3.038					
			19975	1712.5	4.5201	4.976					
		5	20175	1732.5	4.5258	5.003					
			20375	1752.5	4.5315	4.971					

RF Test Report				Report No.: R2209A0845-R3V2	
		20000	1715	9.0049	9.973
	10	20175	1732.5	9.0265	10.020
		20350	1750	8.9865	9.899
		20025	1717.5	13.467	14.640
	15	20175	1732.5	13.417	13.700
		20325	1747.5	13.456	14.620
	20	20050	1720	17.846	19.230
		20175	1732.5	17.877	19.260
		20300	1745	17.863	19.200

LTE Band 12							
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)	
		(IVIII2)	23017	699.7	1.0977	1.321	
		4.4					
		1.4	23095	707.5	1.1205	1.302	
			23173	715.3	1.1097	1.326	
			23025	700.5	2.7417	3.068	
		3	23095	707.5	2.7441	3.052	
	QPSK		23165	714.5	2.743	3.056	
			23035	701.5	4.5229	4.987	
		5	23095	707.5	4.509	4.959	
			23155	713.5	4.5031	4.978	
		10	23060	704	9.0312	10.07	
			23095	707.5	9.021	10.01	
4000/			23130	711	9.0044	9.88	
100%	16QAM	1.4	23017	699.7	1.115	1.328	
			23095	707.5	1.1173	1.327	
			23173	715.3	1.1236	1.327	
		3	23025	700.5	2.7363	3.019	
			23095	707.5	2.7362	3.044	
			23165	714.5	2.7442	3.05	
		5	23035	701.5	4.5056	4.905	
			23095	707.5	4.5276	5.009	
			23155	713.5	4.5064	5.019	
		10	23060	704	8.9843	9.974	
			23095	707.5	9.0323	9.916	
			23130	711	8.9865	9.939	




LTE Band 13							
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)	
100%	QPSK	5	23205	779.5	4.5146	5.013	
			23230	782	4.5118	4.968	
			23255	784.5	4.5097	5.019	
		10	23230	782	9.028	10.09	
	16QAM	5	23205	779.5	4.5292	5.029	
			23230	782	4.5272	5.058	
			23255	784.5	4.5001	4.955	
		10	23230	782	9.0337	9.946	


LTE Band 17							
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)	
100%	QPSK	5	23755	706.5	4.507	5.017	
			23790	710	4.5013	4.979	
			23825	713.5	4.5253	4.975	
		10	23780	709	9.0302	10.08	
			23790	710	9.0221	9.964	
			23800	711	8.9966	10.06	
	16QAM	5	23755	706.5	4.5251	4.996	
			23790	710	4.5319	5.036	
			23825	713.5	4.4966	5.015	
		10	23780	709	9.0464	10.01	
			23790	710	9.0162	10.04	
			23800	711	9.0052	10.00	





LTE Band 41						
RB	Modulation	Bandwidth	Channel	Frequency	99% Power	-26dBc
		(MHz)		(MHz)	Bandwidth(MHz)	Bandwidth(MHz)
			39675	2498.5	4.5114	4.95
		5	40620	2593	4.4991	4.909
			41565	2687.5	4.5071	4.978
			39700	2501	9.0199	10.03
		10	40620	2593	9.0304	9.914
	QPSK		41540	2685	9.0344	10
		15	39725	2503.5	13.431	14.56
			40620	2593	13.444	15.05
			41515	2682.5	13.415	14.55
			39750	2506	17.867	19.03
		20	40620	2593	17.869	19.08
100%			41490	2680	17.836	19.1
100%	16QAM	5	39675	2498.5	4.5031	5.004
			40620	2593	4.495	5.005
			41565	2687.5	4.5047	4.968
		10	39700	2501	8.9819	9.938
			40620	2593	9.0224	9.88
			41540	2685	9.0292	9.929
		15	39725	2503.5	13.452	14.84
			40620	2593	13.417	14.54
			41515	2682.5	13.459	14.62
		20	39750	2506	17.881	19.16
			40620	2593	17.853	19.82
			41490	2680	17.821	19.24
















LTE Band 4 QPSK 1.4MHz CH-Low




LTE Band 4 QPSK 3MHz CH-Low




LTE Band 4 QPSK 1.4MHz CH-Middle




LTE Band 4 QPSK 3MHz CH-Middle




LTE Band 4 QPSK 1.4MHz CH-High




LTE Band 4 QPSK 3MHz CH-High








LTE Band 4 QPSK 5MHz CH-Low




LTE Band 4 QPSK 10MHz CH-Low



LTE Band 4 QPSK 5MHz CH-Middle




LTE Band 4 QPSK 10MHz CH-Middle




LTE Band 4 QPSK 5MHz CH-High




LTE Band 4 QPSK 10MHz CH-High









LTE Band 4 QPSK 15MHz CH-Low




LTE Band 4 QPSK 20MHz CH-Low




LTE Band 4 QPSK 15MHz CH-Middle




LTE Band 4 QPSK 20MHz CH-Middle




LTE Band 4 QPSK 15MHz CH-High




LTE Band 4 QPSK 20MHz CH-High









LTE Band 4 16QAM 1.4MHz CH-Low



LTE Band 4 16QAM 3MHz CH-Low




LTE Band 4 16QAM 1.4MHz CH-Middle




LTE Band 4 16QAM 3MHz CH-Middle




LTE Band 4 16QAM 1.4MHz CH-High



LTE Band 4 16QAM 3MHz CH-High







LTE Band 4 16QAM 5MHz CH-Low




LTE Band 4 16QAM 10MHz CH-Low




LTE Band 4 16QAM 5MHz CH-Middle



LTE Band 4 16QAM 10MHz CH-Middle




LTE Band 4 16QAM 5MHz CH-High




LTE Band 4 16QAM 10MHz CH-High









LTE Band 4 16QAM 15MHz CH-Low



LTE Band 4 16QAM 20MHz CH-Low




LTE Band 4 16QAM 15MHz CH-Middle




LTE Band 4 16QAM 20MHz CH-Middle




LTE Band 4 16QAM 15MHz CH-High



LTE Band 4 16QAM 20MHz CH-High








LTE Band 12 QPSK 1.4MHz CH-Low




LTE Band 12 QPSK 3MHz CH-Low




LTE Band 12 QPSK 1.4MHz CH-Middle




LTE Band 12 QPSK 3MHz CH-Middle




LTE Band 12 QPSK 1.4MHz CH-High




LTE Band 12 QPSK 3MHz CH-High








LTE Band 12 QPSK 5MHz CH-Low



LTE Band 12 QPSK 10MHz CH-Low



LTE Band 12 QPSK 5MHz CH-Middle




LTE Band 12 QPSK 10MHz CH-Middle




LTE Band 12 QPSK 5MHz CH-High




LTE Band 12 QPSK 10MHz CH-High









LTE Band 12 16QAM 1.4MHz CH-Low




LTE Band 12 16QAM 3MHz CH-Low




LTE Band 12 16QAM 1.4MHz CH-Middle




LTE Band 12 16QAM 3MHz CH-Middle




LTE Band 12 16QAM 1.4MHz CH-High



LTE Band 12 16QAM 3MHz CH-High









LTE Band 12 16QAM 5MHz CH-Low



LTE Band 12 16QAM 10MHz CH-Low




LTE Band 12 16QAM 5MHz CH-Middle



LTE Band 12 16QAM 10MHz CH-Middle



LTE Band 12 16QAM 5MHz CH-High




LTE Band 12 16QAM 10MHz CH-High





F Test Report Report No.: R2209A0845-R3V2


LTE Band 13 QPSK 5MHz CH-Low



LTE Band 13 QPSK 10MHz CH-Middle




LTE Band 13 QPSK 5MHz CH-Middle



LTE Band 13 QPSK 5MHz CH-High








LTE Band 13 16QAM 5MHz CH-Low




LTE Band 13 16QAM 10MHz CH-Middle




LTE Band 13 16QAM 5MHz CH-Middle



LTE Band 13 16QAM 5MHz CH-High








LTE Band 17 QPSK 5MHz CH-Low




LTE Band 17 QPSK 10MHz CH-Low



LTE Band 17 QPSK 5MHz CH-Middle




LTE Band 17 QPSK 10MHz CH-Middle



LTE Band 17 QPSK 5MHz CH-High




LTE Band 17 QPSK 10MHz CH-High





F Test Report No.: R2209A0845-R3V2


LTE Band 17 16QAM 5MHz CH-Low




LTE Band 17 16QAM 10MHz CH-Low




LTE Band 17 16QAM 5MHz CH-Middle



LTE Band 17 16QAM 10MHz CH-Middle




LTE Band 17 16QAM 5MHz CH-High




LTE Band 17 16QAM 10MHz CH-High













LTE Band 41 QPSK 10MHz CH-Low



LTE Band 41 QPSK 5MHz CH-Middle




LTE Band 41 QPSK 10MHz CH-Middle




LTE Band 41 QPSK 5MHz CH-High




LTE Band 41 QPSK 10MHz CH-High









LTE Band 41 QPSK 15MHz CH-Low




LTE Band 41 QPSK 20MHz CH-Low




LTE Band 41 QPSK 15MHz CH-Middle




LTE Band 41 QPSK 20MHz CH-Middle




LTE Band 41 QPSK 15MHz CH-High




LTE Band 41 QPSK 20MHz CH-High








LTE Band 41 16QAM 5MHz CH-Low




LTE Band 41 16QAM 10MHz CH-Low




LTE Band 41 16QAM 5MHz CH-Middle



LTE Band 41 16QAM 10MHz CH-Middle



LTE Band 41 16QAM 5MHz CH-High




LTE Band 41 16QAM 10MHz CH-High







LTE Band 41 16QAM 15MHz CH-Low




LTE Band 41 16QAM 20MHz CH-Low




LTE Band 41 16QAM 15MHz CH-Middle




LTE Band 41 16QAM 20MHz CH-Middle




LTE Band 41 16QAM 15MHz CH-High



LTE Band 41 16QAM 20MHz CH-High









6.3 Band Edge

All the test traces in the plots shows the test results clearly.








LTE Band 4 QPSK 1.4MHz CH-Low, 1 RB



LTE Band 4 QPSK 1.4MHz CH-High, 1 RB




LTE Band 4 QPSK 1.4MHz CH-Low, 100%RB



LTE Band 4 QPSK 1.4MHz CH-High, 100%RB




LTE Band 4 QPSK 3MHz CH-Low, 1 RB



LTE Band 4 QPSK 3MHz CH-High, 1 RB








LTE Band 4 QPSK 3MHz CH-Low, 100%RB




LTE Band 4 QPSK 3MHz CH-High, 100%RB



LTE Band 4 QPSK 5MHz CH-Low, 1 RB



LTE Band 4 QPSK 5MHz CH-High, 1 RB




LTE Band 4 QPSK 5MHz CH-Low, 100%RB




LTE Band 4 QPSK 5MHz CH-High, 100%RB








LTE Band 4 QPSK 10MHz CH-Low, 1 RB



LTE Band 4 QPSK 10MHz CH-High, 1 RB




LTE Band 4 QPSK 10MHz CH-Low, 100%RB



LTE Band 4 QPSK 10MHz CH-High, 100%RB




LTE Band 4 QPSK 15MHz CH-Low, 1 RB



LTE Band 4 QPSK 15MHz CH-High, 1 RB







LTE Band 4 QPSK 15MHz CH-Low, 100%RB




LTE Band 4 QPSK 15MHz CH-High, 100%RB



LTE Band 4 QPSK 20MHz CH-Low, 1 RB



LTE Band 4 QPSK 20MHz CH-High, 1 RB




LTE Band 4 QPSK 20MHz CH-Low, 100%RB




LTE Band 4 QPSK 20MHz CH-High, 100%RB








LTE Band 4 16QAM 1.4MHz CH-Low, 1 RB




LTE Band 4 16QAM 1.4MHz CH-High, 1 RB




LTE Band 4 16QAM 1.4MHz CH-Low, 100%RB



LTE Band 4 16QAM 1.4MHz CH-High, 100%RB



LTE Band 4 16QAM 3MHz CH-Low, 1 RB



LTE Band 4 16QAM 3MHz CH-High, 1 RB








LTE Band 4 16QAM 3MHz CH-Low, 100%RB




LTE Band 4 16QAM 3MHz CH-High, 100%RB



LTE Band 4 16QAM 5MHz CH-Low, 1 RB



LTE Band 4 16QAM 5MHz CH-High, 1 RB




LTE Band 4 16QAM 5MHz CH-Low, 100%RB




LTE Band 4 16QAM 5MHz CH-High, 100%RB









LTE Band 4 16QAM 10MHz CH-Low, 1 RB



LTE Band 4 16QAM 10MHz CH-High, 1 RB




LTE Band 4 16QAM 10MHz CH-Low, 100%RB



LTE Band 4 16QAM 10MHz CH-High, 100%RB




LTE Band 4 16QAM 15MHz CH-Low, 1 RB



LTE Band 4 16QAM 15MHz CH-High, 1 RB








LTE Band 4 16QAM 15MHz CH-Low, 100%RB



LTE Band 4 16QAM 15MHz CH-High, 100%RB



LTE Band 4 16QAM 20MHz CH-Low, 1 RB



LTE Band 4 16QAM 20MHz CH-High, 1 RB




LTE Band 4 16QAM 20MHz CH-Low, 100%RB




LTE Band 4 16QAM 20MHz CH-High, 100%RB









LTE Band 12 QPSK 1.4MHz CH-Low, 1 RB



LTE Band 12 QPSK 1.4MHz CH-High, 1 RB




LTE Band 12 QPSK 1.4MHz CH-Low, 100%RB




LTE Band 12 QPSK 1.4MHz CH-High, 100%RB



LTE Band 12 QPSK 3MHz CH-Low, 1 RB



LTE Band 12 QPSK 3MHz CH-High, 1 RB








LTE Band 12 QPSK 3MHz CH-Low, 100%RB




LTE Band 12 QPSK 3MHz CH-High, 100%RB



LTE Band 12 QPSK 5MHz CH-Low, 1 RB



LTE Band 12 QPSK 5MHz CH-High, 1 RB




LTE Band 12 QPSK 5MHz CH-Low, 100%RB




LTE Band 12 QPSK 5MHz CH-High, 100%RB








LTE Band 12 QPSK 10MHz CH-Low, 1 RB



LTE Band 12 QPSK 10MHz CH-High, 1 RB



LTE Band 12 QPSK 10MHz CH-Low, 100%RB



LTE Band 12 QPSK 10MHz CH-High, 100%RB




LTE Band 12 16QAM 1.4MHz CH-Low, 1 RB



LTE Band 12 16QAM 1.4MHz CH-High, 1 RB









LTE Band 12 16QAM 1.4MHz CH-Low, 100%RB



LTE Band 12 16QAM 1.4MHz CH-High, 100%RB



LTE Band 12 16QAM 3MHz CH-Low, 1 RB



LTE Band 12 16QAM 3MHz CH-High, 1 RB




LTE Band 12 16QAM 3MHz CH-Low, 100%RB




LTE Band 12 16QAM 3MHz CH-High, 100%RB







LTE Band 12 16QAM 5MHz CH-Low, 1 RB



LTE Band 12 16QAM 5MHz CH-High, 1 RB




LTE Band 12 16QAM 5MHz CH-Low, 100%RB



LTE Band 12 16QAM 5MHz CH-High, 100%RB




LTE Band 12 16QAM 10MHz CH-Low, 1 RB



LTE Band 12 16QAM 10MHz CH-High, 1 RB








LTE Band 12 16QAM 10MHz CH-Low, 100%RB




LTE Band 12 16QAM 10MHz CH-High, 100%RB



LTE Band 13 QPSK 5MHz CH-Low, 1 RB



LTE Band 13 QPSK 5MHz CH-High, 1 RB




LTE Band 13 QPSK 5MHz CH-Low, 100%RB




LTE Band 13 QPSK 5MHz CH-High, 100%RB








LTE Band 13 QPSK 10MHz CH-Low, 1 RB



LTE Band 13 QPSK 10MHz CH-High, 1 RB




LTE Band 13 QPSK 10MHz CH-Low, 100%RB




LTE Band 13 QPSK 10MHz CH-High, 100%RB




LTE Band 13 16QAM 5MHz CH-Low, 1 RB



LTE Band 13 16QAM 5MHz CH-High, 1 RB








LTE Band 13 16QAM 5MHz CH-Low, 100%RB




LTE Band 13 16QAM 5MHz CH-High, 100%RB



LTE Band 13 16QAM 10MHz CH-Low, 1 RB



LTE Band 13 16QAM 10MHz CH-High, 1 RB



LTE Band 13 16QAM 10MHz CH-Low, 100%RB



LTE Band 13 16QAM 10MHz CH-High, 100%RB






LTE Band 13 QPSK 5MHz CH-Low, 1 RB (763MHz ~775MHz)




LTE Band 13 QPSK 5MHz CH-Low, 1 RB (775MHz ~777MHz)




LTE Band 13 QPSK 5MHz CH-High, 1 RB (787MHz ~793MHz)



LTE Band 13 QPSK 5MHz CH-High, 1 RB (793MHz ~805MHz)





LTE Band 13 QPSK 5MHz CH-Low, 100%RB (763MHz ~775MHz)



LTE Band 13 QPSK 5MHz CH-Low, 100%RB (775MHz ~777MHz)



LTE Band 13 QPSK 5MHz CH-High, 100%RB (787MHz ~793MHz)



LTE Band 13 QPSK 5MHz CH-High, 100%RB (793MHz ~805MHz)







LTE Band 13 QPSK 10MHz CH-Low, 1 RB (763MHz ~775MHz)



LTE Band 13 QPSK 10MHz CH-Low, 1 RB (775MHz ~777MHz)



LTE Band 13 QPSK 10MHz CH-High, 1 RB (787MHz ~793MHz)



LTE Band 13 QPSK 10MHz CH-High, 1 RB (793MHz ~805MHz)






LTE Band 13 QPSK 10MHz CH-Low, 100%RB (763MHz ~775MHz)



LTE Band 13 QPSK 10MHz CH-Low, 100%RB (775MHz ~777MHz)



LTE Band 13 QPSK 10MHz CH-High, 100%RB (787MHz ~793MHz)




LTE Band 13 QPSK 10MHz CH-High, 100%RB (793MHz ~805MHz)







LTE Band 13 16QAM 5MHz CH-Low, 1 RB (763MHz ~775MHz)



LTE Band 13 16QAM 5MHz CH-Low, 1 RB (775MHz ~777MHz)



LTE Band 13 16QAM 5MHz CH-High, 1 RB (787MHz ~793MHz)



LTE Band 13 16QAM 5MHz CH-High, 1 RB (793MHz ~805MHz)





LTE Band 13 16QAM 5MHz CH-Low, 100%RB (763MHz ~775MHz)



LTE Band 13 16QAM 5MHz CH-Low, 100%RB (775MHz ~777MHz)



LTE Band 13 16QAM 5MHz CH-High, 100%RB (787MHz ~793MHz)



LTE Band 13 16QAM 5MHz CH-High, 100%RB (793MHz ~805MHz)





LTE Band 13 16QAM 10MHz CH-Low, 1 RB (763MHz ~775MHz)



LTE Band 13 16QAM 10MHz CH-Low, 1 RB (775MHz ~777MHz)



LTE Band 13 16QAM 10MHz CH-High, 1 RB (787MHz ~793MHz)



LTE Band 13 16QAM 10MHz CH-High, 1 RB (793MHz ~805MHz)





F Test Report Report No.: R2209A0845-R3V2

LTE Band 13 16QAM 10MHz CH-Low, 100%RB (763MHz ~775MHz)



LTE Band 13 16QAM 10MHz CH-Low, 100%RB (775MHz ~777MHz)




LTE Band 13 16QAM 10MHz CH-High, 100%RB (787MHz ~793MHz)




LTE Band 13 16QAM 10MHz CH-High, 100%RB (793MHz ~805MHz)








LTE Band 17 QPSK 5MHz CH-Low, 1 RB



LTE Band 17 QPSK 5MHz CH-High, 1 RB



LTE Band 17 QPSK 5MHz CH-Low, 100%RB




LTE Band 17 QPSK 5MHz CH-High, 100%RB




LTE Band 17 QPSK 10MHz CH-Low, 1 RB



LTE Band 17 QPSK 10MHz CH-High, 1 RB








LTE Band 17 QPSK 10MHz CH-Low, 100%RB



LTE Band 17 QPSK 10MHz CH-High, 100%RB



LTE Band 17 16QAM 5MHz CH-Low, 1 RB



LTE Band 17 16QAM 5MHz CH-High, 1 RB



LTE Band 17 16QAM 5MHz CH-Low, 100%RB




LTE Band 17 16QAM 5MHz CH-High, 100%RB





LTE Band 17 16QAM 10MHz CH-Low, 1 RB



LTE Band 17 16QAM 10MHz CH-High, 1 RB



LTE Band 17 16QAM 10MHz CH-Low, 100%RB



LTE Band 17 16QAM 10MHz CH-High, 100%RB



