



Report No: FCC 1703019-01 File reference No: 2017-03-08

Applicant: Huizhou Weide Electronics Co.,Ltd

Product: Bluetooth headphone

Model No: WD-5188, 8062720

Trademark: TURBOX

Test Standards: FCC Part 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for the

evaluation of electromagnetic compatibility

Approved By

# Jack Chung

Jack Chung

Manager

Dated: March 08, 2017

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1703019-01 Page 2 of 93

Date: 2017-03-08



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAS-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

### FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

Page 3 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



# **Test Report Conclusion**

### Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
5.1	Test Method and Test Procedure.	12
5.2	Configuration of the EUT	12
5.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
7.0	20dB and 99% Bandwidth	22
8.0	Maximum Output Power	46
9.0	Carrier Frequency Separation.	49
10.0	Number of Hopping Channel	53
11.0	Time of Occupancy (Dwell Time)	57
12.0	Out of Band Measurement	70
13.0	Antenna Requirement	83
14.0	FCC Label	84
15.0	Photo of Test Setup and FUT View	85

Report No.: FCC1703019-01

Date: 2017-03-08



Page 4 of 93

### 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian

District, Shenzhen, Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988 For 3m Anechoic Chamber

### 1.2 Applicant Details

Applicant: Huizhou Weide Electronics Co.,Ltd

Address: JIMADI INDUSTRIAL AREA, BOLUO, HUIZHOU, GUANGDONG, CHINA

Telephone: -Fax: --

### 1.3 Description of EUT

Product: Bluetooth headphone

Manufacturer: Huizhou Weide Electronics Co.,Ltd

Address: JIMADI INDUSTRIAL AREA, BOLUO, HUIZHOU, GUANGDONG, CHINA

Brand Name: TURBOX
Model Number: WD-5188
Additional Model Number: 8062720

Type of Modulation GFSK, 月/4DQPSK, 8DPSK for Bluetooth

Frequency range 2402-2480MHz for Bluetooth

Channel Spacing 1MHz for Bluetooth

Frequency Selection By software

Channel Number 79 channel for Bluetooth

Antenna: PCB Antenna and the maximum Gain of this antenna is 0dBi;

### 1.4 Submitted Sample: 2 Samples

### 1.5 Test Duration

2017-03-02 to 2017-03-07

### 1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703019-01 Page 5 of 93

Date: 2017-03-08



Test Engineer 1.7

The sample tested by

Print Name: Terry Tang

Page 6 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



2.0 Test Equipments					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2016-08-22	2017-08-21
TWO	R&S	E7112 75	100204	2017 00 22	2017 00 21
Line-V-NETW		EZH3-Z5	100294	2016-08-22	2017-08-21
TWO	R&S	EZH3-Z5	100253	2016-08-22	2017-08-21
Line-V-NETW		EZN3-Z3	100233	2010-08-22	2017-08-21
	R&S				
Ultra Broadband		HL562	100157	2016-08-23	2017-08-22
ANT					
	R&S	ESDV	100008	2016-08-22	2017-08-21
ESDV Test Receiver					
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2016-08-22	2017-08-21
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-
Loop Antenna	EMCO	6502	00042960	2016-08-23	2017-08-22
ESPI Test Receiver	R&S	ESI26	838786/013	2016-08-22	2017-08-23
3m OATS			N/A	2016-08-24	2017-08-23
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2016-08-24	2017-08-23
Horn Antenna	R&S	BBHA 9120D	9120D-631	2016-08-24	2017-08-23
Power meter	Anritsu	ML2487A	6K00003613	2016-08-22	2017-08-21
Power sensor	Anritsu	MA2491A	32263	2016-08-22	2017-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2016-08-23	2017-08-21
LISN	AFJ	LS16C	10010947251	2016-08-22	2017-08-21
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2016-08-23	2017-08-22
9*6*6 Anechoic			N/A	2016-08-24	2017-08-23
EMI Test Receiver	RS	ESCS30	100139	2016-08-22	2017-08-21
DE Cabla	SCHWARZBEC			2016-08-23	2017 00 22
RF Cable	K			2010-08-23	2017-08-22
Pre-Amplifier	HP	8447D	2727A05017	2016-08-05	2017-08-04
Pre-Amplifier	EM	EM30265		2016-08-05	2017-08-04

Page 7 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



#### 3.0 **Technical Details**

#### 3.1 **Summary of test results**

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and Restricted bands	15.247(d),15.205(a), 15.209 (a),15.109	PASS	Complies
<b>Conducted Emissions</b>	15.207(a), 15.107	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

#### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247 and RSS-247 Issue 1

#### 4.0 **EUT Modification**

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Page 8 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



#### 5. Power Line Conducted Emission Test

#### 5.1 Schematics of the test




EUT: Equipment Under Test

### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2014. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2014.

Test Voltage: 120V~60Hz Block diagram of Test setup



## 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2014. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Report No.: FCC1703019-01 Page 9 of 93

Date: 2017-03-08



#### A. EUT

Device	Manufacturer	Model	FCC	
Bluetooth headphone	Huizhou Weide Electronics	WD-5188, 8062720	2AGA95188C	
Bructooth headphone	Co.,Ltd	WD-3188, 8002720	2AUA93100C	

#### B. Internal Device

Device	Manufacturer	Model	Rating

#### C. Peripherals

Device	Manufacturer	Model	Rating
Power	DUNNS	JY05100	Input: 100-240V~, 50/60Hz, 0.2A;
Supply	Mobiles		Output: DC5V, 1A

### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2014.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

### 5.5 Power line conducted Emission Limit according to Paragraph 15.107,15.207

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No.: FCC1703019-01 Page 10 of 93

Date: 2017-03-08



### A: Conducted Emission on Live Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Charging and Keep Bluetooth Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



No. Mk	. Freq.	_	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.4952	19.00	10.27	29.27	56.08	-26.81	QP	
2	0.4952	8.40	10.27	18.67	46.08	-27.41	AVG	

Report No.: FCC1703019-01 Page 11 of 93

Date: 2017-03-08



#### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Humidity: 65%RH Atmospheric Pressure: 101 KPa Temperature: 26°C

**EUT set Condition: Charging and Keep Bluetooth Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level		Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.4951	22.40	10.27	32.67	56.08	-23.41	QP	
2 *	0.4951	17.60	10.27	27.87	46.08	-18.21	AVG	

Report No.: FCC1703019-01 Page 12 of 93


Date: 2017-03-08



#### 6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

### **Block diagram of Test setup**



- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1703019-01 Page 13 of 93

Date: 2017-03-08



#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

### Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. GFSK was the worse case because it has highest output power

Report No.: FCC1703019-01

Date: 2017-03-08



Page 14 of 93

#### Test result

### General Radiated Emission Data and Harmonics Radiated Emission Data

### Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

**EUT set Condition:** Keep Bluetooth Transmitting

**Results: Pass** 

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
133.680	30.56	Н	43.50
935.400	41.32	Н	46.00
308.440	33.32	Н	46.00
949.040	41.58	V	46.00


Page 15 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



### Test Figure:



Date: 6.MAR.2017 15:11:22

Page 16 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



Test Figure:

V



Date: 6.MAR.2017 15:08:18 Report No.: FCC1703019-01 Page 17 of 93

Date: 2017-03-08



### Operation Mode: Transmitting under Low Channel (2402MHz)

	8	,	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4804		Н	74(Peak)/ 54(AV)
4804		V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

## **Operation Mode: Transmitting g under Middle Channel (2441MHz)**

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4882	-	Н	74(Peak)/ 54(AV)
4882		V	74(Peak)/ 54(AV)
7323		H/V	74(Peak)/ 54(AV)
9764		H/V	74(Peak)/ 54(AV)
12205		H/V	74(Peak)/ 54(AV)
14646		H/V	74(Peak)/ 54(AV)
17087		H/V	74(Peak)/ 54(AV)
19528		H/V	74(Peak)/ 54(AV)
21969		H/V	74(Peak)/ 54(AV)
24410		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Page 18 of 93 Report No.: FCC1703019-01

Date: 2017-03-08



### Operation Mode: Transmitting under High Channel (2480MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4960		Н	74(Peak)/ 54(AV)
4960		V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

Report No.: FCC1703019-01


Date: 2017-03-08



Please refer to the following test plots for details:


### Low Channel: Horizontal





### Low Channel: Vertical

### 97.0 dBuV/m



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 20 of 93

Report No.: FCC1703019-01


Date: 2017-03-08



### **Middle Channel: Horizontal**



#### Middle Channel: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Page 21 of 93

Report No.: FCC1703019-01


Date: 2017-03-08



### **High Channel: Horizontal**



### **High Channel: Vertical**



# Note: for the radiated emissions above 18G, it is the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: FCC1703019-01

Date: 2017-03-08



Page 22 of 93

### 7.0 20dB and 99%Bandwidth Measurement

### 7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 7.2 Limits of 20dB Bandwidth Measurement

N/A

### 7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =3MHz, RBW =30 kHz, VBW=100 kHz, Sweep = auto Detector function = peak, Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

#### 7.4 Test Result

#### **Type of Modulation: GFSK**

Type of Modulation of SI				
EUT	Blue	Bluetooth headphone		WD-5188
Mode	Keep Transmitting		Input Voltage	DC3.7V
Temperat	re 24 deg. C,		Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass/ Fail
Low	2402	938		Pass
Middle	2441	944		Pass
High	2480	883		Pass

Page 23 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



### Test Figure:

### 1. Condition: Low Channel




Date: 6.MAR.2017 15:45:41 Page 24 of 93

Date: 2017-03-08



### 2. Condition: Middle Channel

Report No.: FCC1703019-01




6.MAR.2017 Date: 15:40:30 Report No.: FCC1703019-01 Page 25 of 93

Date: 2017-03-08



### 3. High Channel



7.MAR.2017 Date: 11:30:43 Report No.: FCC1703019-01

Date: 2017-03-08



Page 26 of 93

### **Test Result**

Type of Modulation:  $\sqrt{1/4}$ DQPSK

EUT	Blu	Bluetooth headphone		WD-5188
Mode	K	Keep Transmitting		DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1263		Pass
Middle	2441	1238		Pass
High	2480	1238		Pass


Report No.: FCC1703019-01 Page 27 of 93

Date: 2017-03-08



### Test Figure:

### 1. Condition: Low Channel




Date: 6.MAR.2017 15:31:41 Report No.: FCC1703019-01 Page 28 of 93

Date: 2017-03-08



### 2. Condition: Middle Channel




6.MAR.2017 Date: 15:33:00 Report No.: FCC1703019-01 Page 29 of 93

Date: 2017-03-08



### 3. High Channel



6.MAR.2017 Date: 15:36:28

Page 30 of 93 Report No.: FCC1703019-01

Date: 2017-03-08



### **Test Result**

**Type of Modulation: 8DPSK** 

EUT	Blu	Bluetooth headphone		WD-5188
Mode	K	Keep Transmitting		DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1281		Pass
Middle	2441	1275		Pass
High	2480	1275		Pass

Page 31 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



### Test Figure:

### 1. Condition: Low Channel




Date: 6.MAR.2017 15:27:48 Report No.: FCC1703019-01 Page 32 of 93

Date: 2017-03-08



### 2. Condition: Middle Channel




6.MAR.2017 Date: 15:23:55 Report No.: FCC1703019-01 Page 33 of 93

Date: 2017-03-08



### 3. High Channel



6.MAR.2017 Date: 15:20:31 Report No.: FCC1703019-01

Date: 2017-03-08



Page 34 of 93

**Type of Modulation: GFSK** 

Type of Middle and Office				
EUT	Blue	etooth headphone	Model	WD-5188
Mode	Ke	ep Transmitting	Input Voltage	DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)	Minimum Limit (kHz)	Pass/ Fail
Low	2402	848		Pass
Middle	2441	836		Pass
High	2480	842		Pass


Report No.: FCC1703019-01 Page 35 of 93

Date: 2017-03-08



### Test Figure:

### 1. Condition: Low Channel




Date: 6.MAR.2017 17:39:15 Report No.: FCC1703019-01 Page 36 of 93

Date: 2017-03-08



### 2. Condition: Middle Channel




6.MAR.2017 Date: 17:40:17 Report No.: FCC1703019-01 Page 37 of 93

Date: 2017-03-08



# 3. High Channel



6.MAR.2017 Date: 17:41:33

Date: 2017-03-08



Page 38 of 93

# **Test Result**

Type of Modulation:  $\sqrt{1/4}$ DQPSK

EUT	Blu	Bluetooth headphone		WD-5188
Mode	K	eep Transmitting	Input Voltage	DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	2402 1178		Pass
Middle	2441 1166			Pass
High	2480 1166			Pass

Page 39 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



# Test Figure:

# 1. Condition: Low Channel



Date: 6.MAR.2017 17:45:52


Page 40 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



### 2. Condition: Middle Channel




Date: 6.MAR.2017 17:44:27

Page 41 of 93 Report No.: FCC1703019-01

Date: 2017-03-08



# 2. High Channel



Date: 6.MAR.2017 17:42:58

Date: 2017-03-08



Page 42 of 93

### **Test Result**

**Type of Modulation: 8DPSK** 

EUT	Blu	Bluetooth headphone		WD-5188
Mode	Ko	eep Transmitting	Input Voltage	DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402 1160			Pass
Middle	2441 1154			Pass
High	2480	2480 1160		Pass

Page 43 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



# Test Figure:

# 1. Condition: Low Channel




17:47:31

Report No.: FCC1703019-01 Page 44 of 93

Date: 2017-03-08



### 2. Condition: Middle Channel




6.MAR.2017 Date: 17:49:41 Report No.: FCC1703019-01 Page 45 of 93

Date: 2017-03-08



# 3. High Channel



6.MAR.2017 Date: 17:51:07

Date: 2017-03-08



Page 46 of 93

# 8. Maximum Output Power

# 8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **8.2 Limits of Maximum Output Power**

The Maximum Output Power Measurement is 30dBm.

#### **8.3 Test Procedure**

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB bandwidth of the emission being measured; VBW = the 20 dB

RBW=3MHz; Sweep = 60s; Detector function = PK; Trace = max hold

- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Report No.: FCC1703019-01 Page 47 of 93

Date: 2017-03-08



#### **8.4Test Results**

# Type of Modulation: GFSK

EUT	Blu	etooth headphone Mod		el	WD-5188
Mode	K	eep Transmitting	Input Voltage		DC3.7V
Temperature	е	24 deg. C,	Humidity		56% RH
Channel	Channel Frequency (MHz)	Max. Power Output (dBm	Max. Power Output (dBm)  Peak		Pass/ Fail
		Peak			
Low	2402	3.20		30	Pass
Middle	2441	5.23		30	Pass
High	2480	5.35		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

# 

EUT	EUT Blueto		tooth headphone Mode		el	WD-5188	
Mode		Ke	ep Transmitting Inpu		Voltage	DC3.7V	
Temperature	e		24 deg. C,	Humidity		56% RH	
Channel	Cł	nannel Frequency (MHz)	Max. Power Output (dBm	)	Peak Power Limit (dBm)	Pass/ Fail	
Low		2402	1.01		30	Pass	
Middle		2441	3.58		30	Pass	
High		2480	3.58		30	Pass	

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Date: 2017-03-08



Page 48 of 93

# **Type of Modulation: 8DPSK**

EUT	Blue	Bluetooth headphone		Model	WD-5188
Mode	Ke	ep Transmitting	Input Voltage		DC3.7V
Temperature	e	24 deg. C,	Нι	umidity	56% RH
Channel	Channel Frequency (MHz)	Max. Power Output (dBm Peak	Max. Power Output (dBm)  Peak		Pass/ Fail
Low	2402	1.44		30	Pass
Middle	2441	3.87		30	Pass
High	2480	3.98		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

Date: 2017-03-08



Page 49 of 93

# 9. Carrier Frequency Separation

### 9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

# 9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

#### 9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span; Video (or Average) Bandwidth (VBW)  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 50 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




#### 9.4Test Result

# Type of Modulation: GFSK

EUT	Bluetooth headp	Model	,	WD-5188	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity		56% RH
Carrier I	Frequency Separation		Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2/3	of the 20 dB ban	dwidth	Pass

# **Test Plots**



6.MAR.2017 11:12:42 Date:

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 51 of 93

Report No.: FCC1703019-01


Date: 2017-03-08



# Type of Modulation: Л/4DQPSK

EUT	Bluetooth headp	Model	,	WD-5188	
Mode	Hopping On		Input Voltage		DC3.7V
Temperature	24 deg. C,		Humidity	56% RH	
Carrier I	Frequency Separation		Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2	2/3 of 20 dB bandy	width	Pass

### **Test Plots**



6.MAR.2017 11:43:17

Page 52 of 93 Report No.: FCC1703019-01


Date: 2017-03-08



# **Type of Modulation: 8DPSK**

EUT	Bluetooth headp	Model	,	WD-5188	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity		56% RH
Carrier I	Frequency Separation		Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2	2/3 of 20 dB bandy	width	Pass

# **Test Plots**



6.MAR.2017 14:08:02 Date:

Date: 2017-03-08



Page 53 of 93

# 10. Number of Hopping Channels

### 10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

## 10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

#### **10.3 Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW=300 kHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Record the number of hopping channels.

Page 54 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### **10.4Test Result**

# Type of Modulation: GFSK

EUT	Bluetooth headphone		Model		WD-5188
Mode		Hopping On	Input Voltage	DC3.7V	
Temperature		24 deg. C, Humidity			56% RH
Operating Frequency		Number of hopping channels		Limit	Pass/ Fail
2402-2480MHz		79		≥ 15	Pass

# **Test Plot**



Date: 6.MAR.2017 11:08:47

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 55 of 93

Report No.: FCC1703019-01


Date: 2017-03-08



# Type of Modulation: $\sqrt{J/4DQPSK}$

EUT	Bluetooth headphone		Model			WD-5188
Mode	Hopping On		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH
Operating Frequency		Number of hopp channels	oing	Liı	mit	Pass/ Fail
2402-2480MHz		79		≥ 15		Pass

### **Test Plot**



6.MAR.2017 11:51:04

Page 56 of 93

Report No.: FCC1703019-01


Date: 2017-03-08



# **Type of Modulation: 8DPSK**

EUT	Bluetooth headphone		Model			WD-5188	
Mode		Hopping On		oltage		DC3.7V	
Temperature		24 deg. C,	Humidi	ty		56% RH	
Operating Frequency		Number of hopp channels	oing	Liı	mit	Pass/ Fail	
2402-2480MHz		79		>	15	Pass	

### **Test Plot**



6.MAR.2017 12:00:28 Date:

Date: 2017-03-08



# Page 57 of 93

# 11. Time of Occupancy (Dwell Time)

# 11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

#### 11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Date: 2017-03-08



Page 58 of 93

#### 11.4 Test Result

# Type of Modulation: GFSK

EUT Bluetooth hea		headphone Model		V	VD-5188		
Mode	Keep Tra	ansmitting	Input Voltage	I	DC3.7V		
Temperatur	re 24 d	leg. C, Humidity		24 deg. C,		5	56% RH
Channel	Reading	Hopin	g Rate	Actual	Limit		
			DH5				
High	3.01ms	266.66	7 hop/s	0.321s	0.4s		
Middle	3.01ms	266.66	7 hop/s	0.321s	0.4s		
Low	2.99ms	266.66	7 hop/s	0.319s	0.4s		

Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period, Test period = 0.4 [seconds / channel]  $\times$  79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 $\mu$ s with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: DH5 was the worst case.

Page 59 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



Test Plots:

DH5




6.MAR.2017 16:12:50 Date:

Page 60 of 93

Report No.: FCC1703019-01

Date: 2017-03-08






Page 61 of 93

Report No.: FCC1703019-01

Date: 2017-03-08





Date:

Date: 2017-03-08



Page 62 of 93

#### **Test Result**

# Type of Modulation: $\sqrt{J/4DQPSK}$

EUT	Bluetooth headphone		Model	WD-5188		
Mode	Keep Tra	ansmitting	Input Voltage	DC3.7V		
Temperatur	re 24 d	deg. C, Humidity		5	56% RH	
Channel	Reading	Hoping Rate		Actual	Limit	
DH5						
High	2.99ms	266.667 hop/s		0.319s	0.4s	
Middle	3.01ms	266.667 hop/s		0.321s	0.4s	
Low	2.99ms	266.667 hop/s		0.319s	0.4s	

Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period, Test period = 0.4 [seconds / channel]  $\times$  79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 $\mu$ s with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 2DH5 was the worst case.


Page 63 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



#### Test Plots:




Date: 6.MAR.2017 16:12:09

Page 64 of 93

Report No.: FCC1703019-01

Date: 2017-03-08






Page 65 of 93

Report No.: FCC1703019-01

Date: 2017-03-08





6.MAR.2017 16:03:01 Date:

Report No.: FCC1703019-01 Page 66 of 93

Date: 2017-03-08



# Type of Modulation: 8DPSK

EUT	Bluetooth headphone		Model	WD-5188		
Mode	Keep Tra	Keep Transmitting		DC3.7V		
Temperatur	re 24 d	deg. C, Humidity		56% RH		
Channel	Reading	Hoping Rate Actual		Limit		
DH5						
High	3.01ms	266.667 hop/s		0.321s	0.4s	
Middle	3.03ms	266.667 hop/s		0.323s	0.4s	
Low	3.01ms	266.667 hop/s		0.321s	0.4s	

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of  $625\mu s$  with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 3DH5 was the worst case.


Page 67 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



Test Plots:




6.MAR.2017 15:55:05 Date:

Page 68 of 93

Report No.: FCC1703019-01

Date: 2017-03-08






Date: 6.MAR.2017 16:00:34

Page 69 of 93

Report No.: FCC1703019-01

Date: 2017-03-08






Date: 2017-03-08



Page 70 of 93

# 12 Out of Band Measurement

# 12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

#### 12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### **12.3 Test Procedure**

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100kHz, VBW=300 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 71 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# Type of Modulation: GFSK

#### Out of Band Test Result 12.4

Product:	Blue	Bluetooth headphone		Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	45.6		$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$		Limit	54(dBμV/m)
2390MHz				

# **Test Figure:**



6.MAR.2017 14:39:43 Date:

Page 72 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# Type of Modulation: GFSK

#### 12.4 Out of Band Test Result

Product:	Bluetooth headphone		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	42.9		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

# **Test Figure:**



Page 73 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### Type of Modulation: GFSK

### Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	43.5		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2390MHz				

# **Test Figure:**



Date: 6.MAR.2017 14:35:56

Page 74 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### Type of Modulation: GFSK

### Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	43.6		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

# **Test Figure:**



Date: 6.MAR.2017 14:33:38

Page 75 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# Type of Modulation: Л/4DQPSK

#### Out of Band Test Result 12.4

Product:	Blue	etooth headphone	Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 45.1			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

# **Test Figure:**



14:45:10

Page 76 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# Type of Modulation: Л/4DQPSK

#### Out of Band Test Result 12.4

Product:	Bluetooth headphone		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 42.6			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

### **Test Figure:**



Date: 6.MAR.2017 14:42:57

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 77 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# Type of Modulation: Л/4DQPSK

# Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 43.0			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

### **Test Figure:**



Date: 6.MAR.2017 14:49:21

Page 78 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### Type of Modulation: Л/4DQPSK

# Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 42.2			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

### **Test Figure:**



Date: 6.MAR.2017 14:31:35

Page 79 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	Bluetooth headphone		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 44.6			74(dBμV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

# **Test Figure:**



14:50:56

Page 80 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




### **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	Bluetooth headphone		Test Mode:	High Channel
Mode	Kee	ping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 43.3			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

### **Test Figure:**



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 81 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# **Type of Modulation: 8DPSK**

# Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 43.9			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

### **Test Figure:**



Date: 6.MAR.2017 14:22:11

Page 82 of 93

Report No.: FCC1703019-01

Date: 2017-03-08




# **Type of Modulation: 8DPSK**

### Out of Band Test Result

Product:	Blue	etooth headphone	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 42.1			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

### **Test Figure:**



Date: 6.MAR.2017 14:14:47 Report No.: FCC1703019-01

Date: 2017-03-08



# Page 83 of 93

# 13.0 Antenna Requirement

#### 13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 13.2 Antenna Connected constructions

PCB antenna used. The maximum Gain of the antennas is 0dBi.

Report No.: FCC1703019-01 Page 84 of 93

Date: 2017-03-08



#### 14.0 FCC Label

# **FCC ID: 2AGA95188C**

This device complies with part 15 of the FCC rules and Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Page 85 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



#### 15.0 **Photo of testing**

Conducted Emission Test Setup:



Report No.: FCC1703019-01

Date: 2017-03-08



#### Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703019-01

Date: 2017-03-08



# Photographs - EUT

Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 88 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703019-01 Page 89 of 93

Date: 2017-03-08



Outside view



Page 90 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 91 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 92 of 93

Report No.: FCC1703019-01

Date: 2017-03-08



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 93 of 93


Report No.: FCC1703019-01

Date: 2017-03-08



Inside view





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.