



MPE Calculation for FCC Uncontrolled Environment

Formula from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Source Based Time Averaged Duty Cycle is 100% in calculation below

Maximum peak output power at antenna input terminal:	<u>12.57</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>0.0181</u>	(W)
Maximum antenna gain:	<u>0.00</u>	(dBi)
Maximum antenna gain:	<u>1.000</u>	(numeric)
Prediction distance:	<u>20</u>	(cm)
Prediction frequency:	<u>915</u>	(MHz)
Time Averaged Duty Cycle	<u>100</u>	%
MPE limit for uncontrolled exposure at prediction frequency:	<u>6.10</u>	(W/m^2)
Power density at prediction frequency:	<u>0.0036</u>	(mW/cm^2)
Power density at prediction frequency:	<u>0.036</u>	(W/m^2)
Maximum allowable antenna gain:	<u>22.30</u>	(dBi)
Margin of Compliance:	<u>22.30</u>	(dB)