



REPORT No. : SZ18090145S01

RF EXPOSURE EVALUATION REPORT

APPLICANT : Shenzhen Jimi IOT Co., Ltd

PRODUCT NAME : Container GPS Tracker

MODEL NAME : CT10

BRAND NAME : N/A

FCC ID : 2AMLFCT10

STANDARD(S) : 47CFR 2.1091
KDB 447498

ISSUE DATE : 2018-10-16

Reviewed by: Gan Yueming
Gan yueming (Reviewer)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information.....	3
1.1 Applicant and Manufacturer Information.....	3
1.2 Equipment Under Test (EUT) Description.....	3
1.3 Photographs of the EUT.....	4
1.4 Applied Reference Documents.....	5
2. Device Category and RF Exposure Limit.....	6
3. Measurement of RF Output Power.....	7
4. RF Exposure Evaluation.....	9
Annex A General Information.....	10

Version No.	Date	Description
1.0	2018-10-16	Original

Tested By	
Test engineer:	Su Jinhai



1. Technical Information

Note: Provide by manufacturer.

1.1 Applicant and Manufacturer Information

Applicant:	Shenzhen Jimi IOT Co., Ltd
Applicant Address:	4/F, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Xin'an Street, Bao'an District, Shenzhen, China
Manufacturer:	Shenzhen Jimi IOT Co., Ltd
Manufacturer Address:	4/F, Building C, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Xin'an Street, Bao'an District, Shenzhen, China

1.2 Equipment Under Test (EUT) Description

EUT Type:	Container GPS Tracker
Hardware Version:	V2.0
Software Version:	NFC117_V0003_20180705
Frequency Bands:	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~1907.6 MHz WCDMA Band V: 826.4 MHz ~846.6 MHz
Modulation Mode:	GPRS: GMSK EDGE: 8PSK WCDMA: QPSK
Antenna Type:	Monopole Antenna
Antenna Gain:	824~960MHZ: 0.6dBi , 1710~2170MHZ: 0dBi

1.3 Photographs of the EUT

1. EUT front view



2. EUT rear view





1.3.1 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V2.0	NFC117_V0003_20180705

1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1091	Radio frequency Radiation Exposure Evaluation: mobile devices
2	KDB 447498 D01v06	General RF Exposure Guidance

2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

3. Measurement of RF Output Power

<GSM Conducted Power>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GPRS 1 Tx slot	31.86	31.92	31.98	32.50	22.86	22.92	22.98	23.50
GPRS 2 Tx slots	29.64	29.76	29.86	30.50	23.64	23.76	23.86	24.50
GPRS 3 Tx slots	27.54	27.72	27.86	28.50	23.28	23.46	23.60	24.24
GPRS 4 Tx slots	25.31	25.49	25.62	26.50	22.31	22.49	22.62	23.50
EDGE 1 Tx slot	25.43	25.66	25.81	26.50	16.43	16.66	16.81	17.50
EDGE 2 Tx slots	25.03	25.24	25.40	26.00	19.03	19.24	19.40	20.00
EDGE 3 Tx slots	23.46	23.41	23.53	24.00	19.20	19.15	19.27	19.74
EDGE 4 Tx slots	20.78	20.98	21.15	22.00	17.78	17.98	18.15	19.00

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GPRS 1 Tx slot	29.41	29.25	29.56	30.50	20.41	20.25	20.56	21.50
GPRS 2 Tx slots	27.39	27.18	26.93	28.00	21.39	21.18	20.93	22.00
GPRS 3 Tx slots	25.78	25.52	25.22	26.50	21.52	21.26	20.96	22.24
GPRS 4 Tx slots	23.66	23.41	23.17	24.50	20.66	20.41	20.17	21.50
EDGE 1 Tx slot	24.73	24.71	24.78	25.50	15.73	15.71	15.78	16.50
EDGE 2 Tx slots	24.39	24.41	24.51	25.50	18.39	18.41	18.51	19.50
EDGE 3 Tx slots	22.37	22.23	22.36	23.00	18.11	17.97	18.10	18.74
EDGE 4 Tx slots	19.47	19.37	19.57	20.50	16.47	16.37	16.57	17.50

<Time slot consignations>

No. of Slots	Slot 1	Slot 2	Slot 3	Slot 4
Slot Consignation	1Up4Down	2Up3Down	3Up2Down	4Up1Down
Duty Cycle	1:8.3	1:4.15	1:2.77	1:2.08
Correct Factor	-9.03dB	-6.02dB	-4.26dB	-3.01dB

Note: According to KDB 447498, maximum source-based time-average power will be used for calculating MPE, therefore GPRS 2TX slots of GSM850 and GPRS 3TX slots of GSM1900 are selected to be calculated.



<WCDMA Conducted Power>

Band		WCDMA Band II			Tune-up Limit (dBm)
TX Channel		9262	9400	9538	
Rx Channel		9662	9800	9938	
Frequency (MHz)		1852.4	1880	1907.6	
3GPP Rel 99	RMC 12.2Kbps	21.67	21.66	21.73	22.50

Band		WCDMA Band V			Tune-up Limit (dBm)
TX Channel		4132	4182	4233	
Rx Channel		4357	4407	4458	
Frequency (MHz)		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	21.56	21.59	21.53	22.50



4. RF Exposure Evaluation

Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Maximum Tune-up Limit (dBm)	Antenna Gain (dBi)	EIRP (mW)	Power density (mW/cm ²)	Limit for MPE (mW/cm ²)
GSM850	848.8	30.50	0.6	1288.25	0.256	0.566
GSM1900	1850.2	26.50	0	446.684	0.089	1.0
WCDMA Band II	1907.6	22.50	0	177.828	0.035	1.0
WCDMA Band V	836.4	22.50	0.6	204.174	0.041	0.558

Note:

MPE calculation method

$$\text{Power Density} = \text{EIRP} / 4\pi R^2$$

Where: EIRP = P+G

P = Average Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

_____ END OF REPORT _____