


EMC TEST REPORT



Report No.: 14070653-FCC-E1

Supersede Report No.: N/A

Applicant	SHENZHEN KINGSUN ENTERPRISES Co.,Ltd	
Product Name	Bluetooth Remote shutter speaker	
Model No.	DC-0553	
Test Standard	FCC Part 15 Subpart B Class B:2014, ANSI C63.4: 2009	
Test Date	December 11, 2014	
Issue Date	December 22, 2014	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
LiLi Xia Test Engineer	Alex Liu Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	14070653-FCC-E1
Page	3 of 24

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 AC POWER LINE CONDUCTED EMISSIONS	8
6.2 RADIATED EMISSIONS	12
ANNEX A. TEST INSTRUMENT	15
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	16
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	20
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	23
ANNEX E. DECLARATION OF SIMILARITY	24

1. Report Revision History

Report No.	Report Version	Description	Issue Date
14070653-FCC-E1	NONE	Original	December 22, 2014

2. Customer information

Applicant Name	SHENZHEN KINGSUN ENTERPRISES Co.,Ltd
Applicant Add	25/F, CEC Information Building, Xinwen Rd., Shenzhen, Guangdong, China
Manufacturer	Shenzhen E-Ran Technology Co.,Ltd.
Manufacturer Add	6 Floor, Block A Xiangjiang Industrial Park, Songbai Road, Shiyan Town, Baoan District, Shenzhen

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Remote shutter speaker
Main Model:	DC-0553
Serial Model:	ER-BT30
Date EUT received:	December 02, 2014
Test Date(s):	December 11, 2014
Equipment Category :	JBP
Antenna Gain:	Bluetooth: 0.9 dBi
Type of Modulation:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
RF Operating Frequency (ies):	Bluetooth: 2402-2480 MHz
Number of Channels:	Bluetooth: 79CH
Port:	USB Port
Input Power:	Battery: Model: 502026 Spec: 3.7V 180mAh USB Power Supply: 5V
Trade Name :	N/A
GPRS/EGPRS Multi-slot class	N/A
FCC ID:	2AAPKDC-0553

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2009	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2009	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB


6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	19°C
Relative Humidity	59%
Atmospheric Pressure	1009mbar
Test date :	December 11, 2014
Tested By :	LiLi Xia

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.107	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.															
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>	Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	
Frequency ranges (MHz)	Limit (dBµV)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.
-----------	---


Test Report	14070653-FCC-E1
Page	9 of 24

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
3.74	40.74	56.00	-15.26	30.40	46.00	-15.60	10.76
3.26	35.82	56.00	-20.18	25.23	46.00	-20.77	10.67
3.98	40.38	56.00	-15.62	30.37	46.00	-15.63	10.81
4.46	32.69	56.00	-23.31	22.42	46.00	-23.58	10.90
4.70	37.36	56.00	-18.64	26.72	46.00	-19.28	10.94
4.22	38.91	56.00	-17.09	27.37	46.00	-18.63	10.85

Test Mode:	Transmitting Mode
------------	-------------------



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
3.50	35.59	56.00	-20.41	24.68	46.00	-21.32	10.71
3.26	38.27	56.00	-17.73	26.24	46.00	-19.76	10.67
3.02	33.83	56.00	-22.17	22.49	46.00	-23.51	10.63
0.15	40.19	66.00	-25.81	20.89	56.00	-35.11	12.49
3.98	31.73	56.00	-24.27	21.22	46.00	-24.78	10.81
1.36	30.52	56.00	-25.48	19.70	46.00	-26.30	10.32

6.2 Radiated Emissions

Temperature	19°C
Relative Humidity	59%
Atmospheric Pressure	1009mbar
Test date :	December 11, 2014
Tested By :	LiLi Xia

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.107(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges		
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level
-----------	--

Test Report	14070653-FCC-E1
Page	13 of 24


	over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz. ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode:	Transmitting Mode
------------	-------------------

(Below 1GHz)



Test Data

Vertical & Horizontal Polarity Plot @3m

Frequency (MHz)	Quasi Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
276.98	42.15	0.00	H	120.00	-7.01	46.00	-3.85
268.09	39.01	339.00	H	122.00	-7.13	46.00	-6.99
283.01	40.09	359.00	H	145.00	-6.92	46.00	-5.91
243.69	35.57	140.00	H	135.00	-7.49	46.00	-10.43
241.51	33.57	3.00	H	154.00	-7.52	46.00	-12.43
256.08	34.33	37.00	H	100.00	-7.31	46.00	-11.67


Note: The above 1GHz frequency was pre-scanned and the result which was 20dB lower than the limit line per 15.109 was not recorded.


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/18/2014	09/17/2015	☒
Line Impedance Stabilization Network	LI-125A	191106	09/26/2014	09/25/2015	☒
Line Impedance Stabilization Network	LI-125A	191107	09/26/2014	09/25/2015	☒
LISN	ISN T800	34373	09/26/2014	09/25/2015	☒
Transient Limiter	LIT-153	531118	09/02/2014	09/01/2015	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☒
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	09/02/2014	09/01/2015	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☒
Double Ridge Horn Antenna	AH-118	71259	09/25/2014	09/24/2015	☒


Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo







EUT - Top View



EUT - Bottom View




EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo



Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Test Report	14070653-FCC-E1
Page	22 of 24

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
Lenovo	Lenovo Laptop	E40& 0579A52	N/A	N/A

Test Report	14070653-FCC-E1
Page	23 of 24

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see Attachment

Annex E. DECLARATION OF SIMILARITY

Shenzhen Kingsun Enterprises Co., Ltd.

To: SIEMIC , 775 Montague Expressway, Milpitas, CA 95035,USA

Declaration Letter

Dear Sir,

For our business issue and marketing requirement, we would like to list 2 model numbers on the **FCC** certificates and reports, as following:


Model No.: DC-0553/ ER-BT30

We declare that the difference of these is listed as below:

Main Model No	Serial Model No	Difference
<u>DC-0553</u>	<u>ER-BT30</u>	The only difference between the two models is the model number

Thank you!

Signature:



Printed name/title:

Tel: 0755-82947405

Fax: 0755-82947077

Address:

2014.12