





Description of equality

To whom it may concern,

We, the undersigned **BARTEC GmbH**, hereby declare that the devices BARTEC SP9EX1 Smartphone and BARTEC SP9EX2 Smartphone share the same hardware and software.

The same applies for the devices BARTEC SC9EX1 Smartscanner and BARTEC SC9EX2 Smartscanner.

The only difference are the hazardous area marking of the devices, see table for clarification:

BARTEC SP9EX1 Smartphone	BARTEC SP9EX2 Smartphone
BARTEC SP9EX1 Type: 17-S19P-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX 3153X II 1G Ex ia IIC T4 Ga II 2D Ex ia IIC T135°C Db IP64 IECEX UL 24.0004X Class I, Div 1, Groups A, B, C and D; Class II, Div 1, Groups E, F and G; Class III, T4 Zone 0, AEx ia IIC T4 Ga Zone 21, AEx ia IIC T135°C Db Zone 0, Ex ia IIC T4 Ga Zone 21, Ex ia IIC T135°C Db -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSS MFD: MONTHYY <i>reserved for logos of country approvals</i> USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: 17-S120-0020/**** Utiliser uniquement la batterie BARTEC GmbH type: 17-S120-0020/**** INTRINSICALLY SAFE/SECURITÉ INTRINSÈQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.	BARTEC SP9EX2 Type: B7-S29P-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX xxxxxx II 3G Ex ic IIC T4 Gc II 3D Ex ic IIC T135°C Dc IP64 IECEX UL 24.xxxxxx Class I, Div 2, Groups A, B, C and D; Class II, Div 2, Groups E, F and G; Class III, T4 Zone 2, AEx ic IIC T4 Gc Zone 22, AEx ic IIC T135°C Dc Zone 2, Ex ic IIC T4 Gc Zone 22, Ex ic IIC T135°C Dc -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSS MFD: MONTHYY <i>reserved for logos of country approvals</i> USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: B7-A220-0098/**** Utiliser uniquement la batterie BARTEC GmbH type: B7-A220-0098/**** INTRINSICALLY SAFE/SECURITÉ INTRINSÈQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.
BARTEC SC9EX1 Smartscanner	BARTEC SC9EX2 Smartscanner
BARTEC SC9EX1 Type: 17-S19C-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX 3153X II 1G Ex ia op is IIC T4 Ga II 2D Ex ia op is IIC T135°C Db IP64 IECEX UL 24.0004X Class I, Div 1, Groups A, B, C and D; Class II, Div 1, Groups E, F and G; Class III, T4 Zone 0, AEx ia op is IIC T4 Ga Zone 21, AEx ia op is IIC T135°C Db Zone 0, Ex ia op is IIC T4 Ga Zone 21, Ex ia op is IIC T135°C Db -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSS MFD: MONTHYY <i>reserved for logos of country approvals</i> USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: 17-S120-0020/**** Utiliser uniquement la batterie BARTEC GmbH type: 17-S120-0020/**** INTRINSICALLY SAFE/SECURITÉ INTRINSÈQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.	BARTEC SC9EX2 Type: B7-S29C-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX xxxxxx II 3G Ex ic op is IIC T4 Gc II 3D Ex ic op is IIC T135°C Dc IP64 IECEX UL 24.xxxxxx Class I, Div 2, Groups A, B, C and D; Class II, Div 2, Groups E, F and G; Class III, T4 Zone 2, AEx ic op is IIC T4 Gc Zone 22, AEx ic op is IIC T135°C Dc Zone 2, Ex ic op is IIC T4 Gc Zone 22, Ex ic op is IIC T135°C Dc -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSS MFD: MONTHYY <i>reserved for logos of country approvals</i> USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: B7-A220-0098/**** Utiliser uniquement la batterie BARTEC GmbH type: B7-A220-0098/**** INTRINSICALLY SAFE/SECURITÉ INTRINSÈQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.

If you have any question regarding the declaration, please don't hesitate to contact us.

Thank you!

Sincerely yours,

Dr. Martin U. Schefter
Managing Director
BARTEC GmbH

Sebastian Kuhn
BARTEC GmbH
Tel: +49 7931 597 Ext: 187
E-mail: sebastian.kuhn@bartec.com