

RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name	wireless earbuds
Model No.	EP-N6, EP-N6L
Test Mode	TX
FCC ID	2ATIH-EP-N6L

1.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

1.2 EUT RF EXPOSURE EVALUATION

Operational Mode: EDR						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power (dBm)	Maximum tune-up Power (mW)	Calculated value	Exclusion threshold
2402MHz	0.83	± 1	1.83	1.52	0.47	3
2442MHz	1.17	± 1	2.17	1.65	0.52	3
2480MHz	1.46	± 1	2.46	1.76	0.55	3
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						