

RADIO FREQUENCY EXPOSURE EVALATION

General Information

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
EUT Description : Direct Connect Full Color A21,
Direct Connect Reveal Full Color A21
Model No. : CLEDA2116CD@, CLEDA2116CDRV@
Radio Tech : BLE 5.0, IEEE 802.11 b/g/n.

Description of Test Facility

Name of Firm : Audix Technology (Shanghai) Co., Ltd.
Site Location : 3F, Building 34, No. 680 Guiping Rd.,
Caohejing, Hi-Tech Park, Shanghai 200233, China
NVLAP, Lab Code : 200371-0
FCC Designation Number : CN5027
Test Firm Registration Number: 954668

Evaluation Method

KDB 447498 D04 Interim General RF Exposure Guidance v01

Applicable Standard:

KDB 447498 D04 v01:

Section 2.1.3: SAR-Based Exemption.

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions. Accordingly, a RF source is considered an RF exempt device if its available maximum time-averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold. This exemption threshold was derived based on general population 1-g SAR requirements and is detailed in Appendix C.

FCC CFR 47 §1.1307(b)(3)(i)(B):

A single RF source is exempt if the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

RF Exposure evaluation:

Mode	Frequency	Max output power		Ant. Gain	Max E.I.R.P		P _{th}
	MHz	dBm	mW	dBi	dBm	mW	mW
BLE1M	2480	11.849	15.31	-0.2	11.649	14.618	3060
BLE2M	2402	11.686	14.74	-0.2	11.486	14.080	3060
802.11b	2462	16.83	48.19	-0.2	16.63	46.026	3060
802.11g	2462	14.44	27.80	-0.2	14.24	26.546	3060
802.11n20	2437	13.98	25.00	-0.2	13.78	23.878	3060
802.11n40	2437	12.49	17.74	-0.2	12.29	16.943	3060

Note1: For this EUT, and the separation distance is 20 cm. And the Bluetooth and WIFI can not transmit at the same time.

Note2: The Conducted output power and Maximum EIRP both no greater than the threshold P_{th}, that meets the exemption, the RF exposure evaluation is not required.

-END-