

# FCC RF EXPOSURE REPORT

## FCC ID: 2AG7C-BULLET5S

**Project No.** : 2008H002  
**Equipment** : IP CAMERA  
**Brand Name** : N/A  
**Test Model** : Bullet 5S  
**Series Model** : N/A  
**Applicant** : Hangzhou Meari Technology Co., Ltd.  
**Address** : Room 604-605, Building 1, No.768 Jianghong Road,  
Changhe street, Binjiang District, Hangzhou, Zhejiang, China  
**Manufacturer** : Hangzhou Meari Technology Co., Ltd.  
**Address** : Room 604-605, Building 1, No.768 Jianghong Road,  
Changhe street, Binjiang District, Hangzhou, Zhejiang, China  
**Factory** : Hangzhou Meari Technology Co., Ltd.  
**Address** : No. 91 Chutian Road, Xixing Street, Binjiang District,  
Hangzhou, Zhejiang, China  
**Date of Receipt** : Aug. 04, 2020  
**Date of Test** : Aug. 04, 2020~Aug. 18, 2020  
**Issued Date** : Aug. 28, 2020  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: SH2020080442, adapter: SH2020080442-3  
**Standard(s)** : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091  
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

*Allen Wei*

**Prepared by :** Allen Wei

*Ryan. Wang*

**Approved by :** Ryan Wang



Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China  
TEL: +86-021-61765666  
Web: www.newbtl.com

## REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Aug. 28, 2020

## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1	UB	UB02C115B3D1322A	dipole	RF Cable+Terminal	3	N/A

## 2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
3	1.9953	15	31.622777	0.0125525	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

**End of Test Report**