

FCC CERTIFICATION TEST REPORT

Applicant	:	BEIJING MADV TECHNOLOGY CO., LTD.	
Address of Applicant	-	No.80, Floor 4, Building 17, Yard 30, ShiXingDaJie, Shijingshan District, Beijing, China	
Manufacturer	:	BEIJING MADV TECHNOLOGY CO., LTD.	
Address of Manufacturer	-	No.80, Floor 4, Building 17, Yard 30, ShiXingDaJie, Shijingshan District, Beijing, China	
Equipment under Test	:	Birddy Smart Bird House Camera	
Model No.	•	FJ27HWXJ	
Trade Mark		RELI	
FCC ID		2AJ2LFJ27HWXJ	
Test Standard(s)		FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013,	
Report No.	•	DDT-RE23120425-2E01	
Issue Date	•	2024/02/29	
Issue By	•	Guangdong Dongdian Testing Service Co., Ltd.	
Address of Laboratory	-	Unit 2,Building 1,No.17,Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808	



Table of Contents

	Test report declares	4
1.	Summary of Test Results	5
2.	General Test Information	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT	6
2.3.	Assistant equipment used for test	7
2.4.	Block diagram of EUT configuration for test	7
2.5.	Deviations of test standard	7
2.6.	Test environment conditions	7
2.7.	Test laboratory	8
2.8.	Measurement uncertainty	8
3.	Equipment Used During Test	9
4.	Radiated Spurious Emissions	10
4.1.	Block diagram of test setup	10
4.2.	Limit	11
4.3.	Test procedure	12
4.4.	Test result	14
5.	Antenna Requirements	17
5.1.	Limit	17
5.2.	Result	17
6.	Test Setup Photograph	18
7.	Photos of the EUT	19

Test Report Declare

:	BEIJING MADV TECHNOLOGY CO., LTD.
:	No.80, Floor 4, Building 17, Yard 30, ShiXingDaJie, Shijingshan District, Beijing, China.
:	Birddy Smart Bird House Camera
:	FJ27HWXJ
)	RELI BO
:	BEIJING MADV TECHNOLOGY CO., LTD.
:	No.80, Floor 4, Building 17, Yard 30, ShiXingDaJie, Shijingshan District, Beijing, China

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C

Test procedure used: ANSI C63.10:2013,

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-RE23120425-2E01		
Date of Receipt:	2023/12/07	Date of Test:	2023/12/07 ~ 2024/02/29

Prepared By:

Johnson Huang

Johnson Huang/Engineer

Damon Mu

Approved By:

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
	Initial issue	2024/02/29	8



1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.			
Description of Test Item Standard Result		Results	
Radiated Spurious Emissions	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.247(d)	PASS	

Note1: This report is modified based on DDT-RE23101326-2E01 Note2: Changed components, test radiated spurious emissions below 1G, this is based on the judgment of the engineer.

2. General Test Information

2.1. Description of EUT

EUT Name	:	Birddy Smart Bird House Camera
Model Number	:	FJ27HWXJ
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 5V from External adapter or
Radio Technology	:	IEEE 802.11b/g/n
Operation frequency	:	IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz IEEE 802.11n HT40: 2422MHz-2452MHz
Modulation	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	:	IEEE 802.11b: up to 11 Mbps IEEE 802.11g: up to 54 Mbps IEEE 802.11n HT20: up to 72.2 Mbps IEEE 802.11n HT40: up to 150 Mbps
Antenna Type	:	Glue stick antenna, Maximum PK gain: 4.16 dBi
Sample Number	:	S23101326-04 for conductive S23101326-05 for radiation

Note 1: EUT is the abbreviation of equipment under test. Note 2: "⊠" means to be chosen or applicable; "□" means don't to be chosen or not applicable; This note applies to entire report.

Channel	information				
СН	Frequency (MHz)	СН	Frequency (MHz)	СН	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/ @

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
N/A	N/A	N/A	N/A	N/A

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
NoteBook	Dell	i7-1255U MX550	N/A	038C0A5A- F922-40B9- A219- 8D44E9D1
Adapter	SOLUM VINA COMPANY LIMITED	EP-TA200	Input:100-240V 50-60Hz, 0.5A Output:9V/1.67A or 5V/2A	R37N4ER2G0 1SE3

2.3. Assistant equipment used for test

2.4. Block diagram of EUT configuration for test



Test software: AmebaPRO mptool 1v8.3.exe

The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode,	channel, and data rat	e information		
Mada	Setting Tx Power	data rate (Mbps)	Channel	Frequency
wode	ANT1	(see Note)	Channel	(MHz)
	Default	1	LCH: CH1	2412
	Default	1	MCH: CH6	2437
802.110	Default	1	HCH: CH11	2462
	Default	6 (8)	LCH: CH1	2412
	Default	6	MCH: CH6	2437
802.11g	Default	6	HCH: CH11	2462
IEEE	Default	MCS 0	LCH: CH1	2412
802.11n	Default	MCS 0	MCH: CH6	2437
HT20	Default	MCS 0	HCH: CH11	2462
IEEE	Default	MCS 0	LCH: CH3	2422
802.11n	Default	MCS 0	MCH: CH6	2437
HT40	Default	MCS 0	HCH: CH9	2452
Note: Accordin	a exploratory test. El	IT will have maying up a	utput power in these	data rata aa

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

Temperature range:	+15℃ to +35 ℃	
Humidity range:	20% to 75%	
Pressure range:	86 kPa to106 kPa	

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2,Building 1,No.17,Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty			
Bandwidth	1.1%			
Deals Outrast Dower (Conducted) (Construm analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);			
Peak Output Power (Conducted) (Spectrum analyzer)	1.38 dB (3.6 GHz ≤ f < 8 GHz)			
Peak Output Power (Conducted) (Power Sensor)	0.74 dB			
Dower Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);			
Power Spectral Density	1.38 dB (3.6 GHz ≤ f < 8 GHz)			
	6.7 x 10 ⁻⁸ (Antenna couple method)			
Frequencies Stability	5.5 x 10 ⁻⁸ (Conducted method)			
	0.86 dB (10 MHz ≤ f < 3.6 GHz);			
Conducted spurious emissions	1.40 dB (3.6 GHz ≤ f < 8 GHz)			
	1.66 dB (8 GHz ≤ f < 26.5 GHz)			
Uncertainty for radio frequency (RBW < 20 kHz)	3×10 ⁻⁸ ®			
Temperature	0.4 °C			
Humidity	2 %			
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB			
Uncertainty for Radiation Emission test	4.70 dB (Antenna Polarize: V)			
(30 MHz - 1 GHz)	4.84 dB (Antenna Polarize: H)			
	4.10 dB (1 - 6 GHz)			
Uncertainty for Radiation Emission test	4.40 dB (6 GHz - 18 GHz)			
(1 GHz - 40 GHz)	3.54 dB (18 GHz - 26 GHz)			
	4.30 dB (26 GHz - 40 GHz)			
Uncertainty for Power line conduction omission test	3.34dB (150KHz-30MHz)			
	3.72dB (9KHz-150KHz)			
Note: This uncertainty represents an expanded uncerta 95% confidence level using a coverage factor of k=2.	inty expressed at approximately the			

3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	
⊠Radiation 3#chamber	•				
EMI TEST RECEIVER	R&S	ESU26	100472	2024/04/22	
PSA Series Spectrum Analyzer	Agilent	E4447A	MY50180031	2024/04/22	
Active Loop Antenna	Schwarzbeck	FMZB-1519	1519-038	2024/09/10	
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	2024/07/11	
Double Ridged Horn Antenna	Schwarzbeck	BBHA 9120 D	02468	2024/09/17	
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	2024/04/25	
Pre-amplifier ®	COM-POWER	PAM-118A	18040084	2024/07/14	
Pre-amplifier	COM-POWER	PAM-840A	461369 🧹	2024/04/26	
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1- X8+ JCT26S- NJ-NJ-1.5M	4.5M+8M+1.5M	M 2024/04/20	
RF Cable	Yuhu	JCTB810-NJ- NJ-9M+ ZT26S- SMAJ-SMAJ- 1M	21123964	2024/04/22	
Band Reject Filter(2400-2500 MHz)	REBES	BRM50702	G555	N/A	
Band Reject Filter(5150-5880 MHz)	REBES	BRM50716	G392	N/A	
High Pass Filter(8000-25000 MHz)	ХВ	XBLBQ-GTA67	210820-2-3	N/A	
High Pass Filter(500-2000 MHz)	REBES	HPM50102	004	N/A	
High Pass Filter(1200-18000	REBES	HPM50108	056	N/A	
Test Software	Tonscend	JS32-RE	V 5.0.0.1®	N/A	

TRF No.: RT-4-E-02-005 FCC ID Report 2.4GHz WiFi Ver.1.0

4. Radiated Spurious Emissions

4.1. Block diagram of test setup

In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

4.2. Limit

(1) FCC 15.205 Restricted frequency band:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505 (8)	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	0 108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225 🛒	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

Guangdong Dongdian Testing Service Co., Ltd.

(2) FCC	15.209	Limit.
---------	--------	--------

		1.85			
Freq	luency	(MHz)	Measurement distance (meters)	Field stre	ngth limit
				μV/m	dB(µV)/m
0.0	009 ~ 0	.490	300	2400/F(kHz)	67.6-20log(F)
0.4	190 ~ 1	.705	30	24000/F(kHz)	87.6-20log(F)
1.	705 ~ 3	30.0	30	30	29.54
30	~	88	3	100	40.0
88	~	216	3	150	43.5
216	~	960	3	200	46.0
960	~	1000	(2) 3	500 🛞	54.0
Above	e	1000 🍟	3	74.0 dB(μV)/m (Peak), 54	4.0 dB(μV)/m (Average)
Noto:					

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

 $\label{eq:limit_3m} \mbox{Limit}_{30m} (dBuV/m) \mbox{= Limit}_{30m} (dBuV/m) \mbox{= 40Log} (30m/3m) \mbox{(3) Limit for this EUT}$

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

4.3. Test procedure

(1) EUT height should be 0.8 m for below 1 GHz at a semi - anechoic chamber while EUT height should be 1.5 m for above 1 GHz at full chamber or semi - anechoic chamber ground with absorbers.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	3m	
18GHz-40GHz	Horn Antenna (18GHz-40GHz)	1m

(2) The antenna used as below table.

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0°to 360°on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or

Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1m above ground.)

- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

- (4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz, for emissions from 9 kHz-90 kHz,110 kHz-490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.
- (6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9 kHz-150 kHz	200 Hz
150 kHz-30 MHz	9 kHz 💿
30 MHz-1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; RMS detector RBW 1 MHz VBW 10 Hz for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

4.4. Test result

Pass. (See below detailed test result)

comply with AV limit, only recorded the worst case in this report.

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.

Note 1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

Note 2: 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is 802.11b mode) Note 3: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in 802.11b, Tx 2412 MHz mode. Note 4: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to

Radiated Emission test (below 1GHz) TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-12-14	Tested By:	Bairong
EUT:	Birddy Smart Bird House Camera	Model Number:	FJ27HWXJ
Test Mode:	2.4GWIFI TX	Power Supply:	Battery
Condition:	Temp:22.8°C;Humi:63.1%	Test Site:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23120425\FCC	BELOW 1G\20231	214-233349_H
Memo [.]	Left Side Sample Number S23120420-0	3 Power Setting N	Δ



Data L	.ist				Nº A					
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.15	40.77	10.31	4.47	-31.00	24.55	40.00	15.45	QP	Horizontal
2	57.30	39.37	12.31	4.75	-30.65	25.78	40.00	14.22	QP	Horizontal
3	62.77	31.27	12.49	4.77	-30.61	17.92	40.00	22.08	QP	Horizontal
4	143.89	42.11	9.28	5.29	-30.77	25.91	43.50	17.59	QP	Horizontal
5	577.11	23.83	18.65	7.24	-29.90	19.82	46.00	26.18	QP	Horizontal
6	995.80	22.88	22.44	8.68	-28.14	25.86	54.00	28.14	QP	Horizontal

Note:

- 1. Result Level = Reading + Cable loss + Antenna Factor + AMP
- 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-12-14	Tested By:	Bairong
EUT:	Birddy Smart Bird House Camera	Model Number:	FJ27HWXJ
Test Mode:	2.4GWIFI TX	Power Supply:	Battery
Condition:	Temp:22.8°C;Humi:63.1%	Test Site:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23120425\FCC	BELOW 1G\202312	214-233433_V
Memo:	Left Side Sample Number:S23120420-0	3 Power Setting:NA	A



Data L	.ist					U.			W	
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	40.22	39.44	12.09	4.60	-30.85	25.28	40.00	14.72	QP	Vertical
2	43.32	41.16	12.86	4.64	-30.80	27.86	40.00	12.14	QP	Vertical
3	58.03	41.48	12.78	4.75	-30.65	28.36	40.00	11.64	QP	Vertical
4	152.19	37.29	8.54	5.34	-30.74	20.43	43.50	23.07	QP	Vertical
5	666.79	22.45	19.43	7.62	-29.90	19.60	46.00	26.40	QP	Vertical
6	993.01	23.15	22.40	8.67	-28.16	26.06	54.00	27.94	QP	Vertical

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
 If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

5. Antenna Requirements

5.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2. Result

The device support 1T1R SISO, the antenna is used for this product are Glue stick antenna, and no antenna other than that furnished by the responsible party shall be used with the device, antenna gain is 4.16 dBi.

Guangdong Dongdian Testing Service Co., Ltd.

Report No.: DDT-RE23120425-2E01

7. Photos of the EUT

Please refer to DDT-Q23120425-1E appendix I.



