

Test Report Number: 5106021EMC08 Rev:0 Aegex Technologies, LLC/100IC Page: 1 of 6

RF Exposure Report

Project Number:	5106021	Quotation Number:	SUW-202301003949
Report Number:	5106021EMC08	Revision Leve	el: O
Client:	Aegex Technolog	jies, LLC	
Equipment Under Test:	Tablet		
Model Name:	Aegex100IC		
Model Number:	100IC		
FCC ID:	Contains 2AGVY	-100MWBXX01	

Applicable Standards: 47 CFR §§ 2.1091 (Mobile)

FCC KDB 447498 D01 General RF Exposure Guidance v06

FCC OET Bulletin 65

Report issued on: 27 August 2024

Result: Compliant



FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01 Report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:

Stephen C. Whalen, EMC/RF Lab Manager

tah (What

Reviewed by:

Daniel Alvarez, RF/EMC Sr. Staff Engineer

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com//en/Terms-and-Conditions.aspx. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.



TABLE OF CONTENTS

1	GE	NERAL INFORMATION	3
	1.1	CLIENT INFORMATION	3
	1.2	TEST LABORATORY	3
	1.3	GENERAL INFORMATION OF EUT	
	1.4	OPERATING MODES AND CONDITIONS	3
		EXPOSURE	
	2.1	Test Results	
	2.2	TEST METHOD	4
	2.3	SINGLE TRANSMISSION RF EXPOSURE LEVELS (MW/CM ²)	4
	2.4	SIMULTANEOUS CONDITIONS	5
3	RE	VISION HISTORY	6



1 General Information

1.1 Client Information

Name:Aegex Technologies, LLCAddress:84 Peachtree Street NWCity, State, Zip, Country:Atlanta, Georgia, 30303, USA

1.2 Test Laboratory

Name:SGS North America, Inc.Address:620 Old Peachtree Road NW, Suite 100City, State, Zip, Country:Suwanee, GA 30024, USA

Accrediting Body: A2LA Type of lab: Testing Laboratory Certificate Number: 3212.01

1.3 General Information of EUT

Type of Product: Model Number:	
Frequency Ranges:	WLAN 2.4GHz: 2412 – 2484 MHz WLAN 5GHz: 5160 – 5850 MHz Bluetooth: 2402 – 2480 MHz
	X1005 (W3006, Pulse), Ceramic chip 2.4/5GHz dual band 2.42GHz:2.0dBi, 5.15GHz: 3.2dBi, 5.51GHz 4.0dBi, 5.85GHz 5.0dBi
	X1000 (W3095 Pulse), Ceramic chip 2.4/5GHz dual band 2.4GHz:1.5dBi, 5.0GHz: 2.9dBi, 5.5GHz 3.9dBi, 6.0GHz 4.3dBi
Max Conducted Output Power:	Bluetooth: 10.86 dBm WLAN 2.4GHz: 16.0 dBm WLAN 5GHz: 10dBm

*Data was not measured by SGS laboratory and therefore not responsible for accuracy. Data obtained via customer, specification sheet, previous regulatory filing or other.

1.4 **Operating Modes and Conditions**

Maximum power levels were utilized for all calculations. Refer to table in section 2.4 for simultaneous combinations.



2 RF Exposure

2.1 Test Results

Test Description	Product Specific Standard	Test Result
RF Exposure	FCC Part 1.1310	Compliant

2.2 Test Method

The formula below calculates power density.

$$S = \frac{PG}{4\pi R^2} \qquad S = \frac{EIRP}{4\pi R^2}$$
Or

Where;

S = Power density (mW/cm^2)

P = Maximum sourced based average power delivered to antenna port (mW)

G = Maximum power gain of the antenna in the direction of interest relative to an isotropic radiator (dBi) R = Distance between by-stander and antenna (cm)

EIRP = Equivalent (or effective) isotropically radiated power

2.3 Single transmission RF Exposure Levels (mW/cm²)

FCC - Main Antenna											
Band of Operation		Conducted Power w/tolerance	Antenna Gain	Cable Loss	Averaç	Je EIRP	Distance (R)	Power Density EIRP _{Avg} /(4πR ²)		% of Limit	Verdict
Туре	MHz	dBm			dBm	mW	cm	mW/cm ²	mW/cm ²		
WLAN 2.4	2400-2483.5	16.0	2.0	0.0	18.0	63	20	0.013	1.00	1%	Pass
WLAN 5 GHz (UNII-1)	5150-5250	10.0	3.2	0.0	13.2	21	20	0.004	1.00	0%	Pass
WLAN 5 GHz (UNII-2)	5250-5700	10.0	4.0	0.0	14.0	25	20	0.005	1.00	0%	Pass
WLAN 5.8 GHz (UNII-3)	5725-5850	10.0	5.0	0.0	15.0	32	20	0.006	1.00	1%	Pass

Band of Conducted Power Gain Gain				FCC - Aux Antenna Cable Loss Average EIRP			Distance (R)	Power Density EIRP _{Avo} /(4πR ²)		% of Limit	Verdict
Туре	MHz	dBm			dBm	mW	cm	mW/cm ²	mW/cm ²		· craiot
WLAN 2.4	2400-2483.5	16.0	1.5	0.0	17.5	56	20	0.011	1.00	1%	Pass
Bluetooth	2400-2483.5	10.9	1.5	0.0	12.4	17	20	0.003	1.00	0%	Pass
WLAN 5 GHz (UNII-1)	5150-5250	10.0	2.9	0.0	12.9	19	20	0.004	1.00	0%	Pass
WLAN 5 GHz (UNII-2)	5250-5700	10.0	3.9	0.0	13.9	25	20	0.005	1.00	0%	Pass
WLAN 5.8 GHz (UNII-3)	5725-5850	10.0	4.3	0.0	14.3	27	20	0.005	1.00	1%	Pass



2.4 Simultaneous Conditions

Simultaneous transmissions are evaluated using the equation and highest results from each technology.

$$\frac{S_1}{S_1 Limit} + \frac{S_2}{S_2 Limit} \dots + \frac{S_n}{S_n Limit} \le 1.0$$

Simulaneous TX Antenna Combination					
Main	Aux				
WLAN 5GHz	WLAN 5GHz				
WLAN 5GHz	WLAN 5GHz + BT				
WLAN 5GHz	BT				
WLAN 2.4GHz	WLAN 2.4GHz				
WLAN 2.4GHz	BT				

WLAN 5GHz + WLAN 5GHz + BT < 1.0 1% + 1% + 0% < 100%



3 Revision History

Revision Level	Description of changes	Revision Date
0	Initial Release	27 August 2024