

# **Test Report**

FCC ID: XDQ-T2

Date of issue: Nov. 15, 2016

Sample Description:	POS terminal
Model(s):	T2
Applicant:	Shenzhen Xinguodu Technology Co., Ltd.
Address:	17B JinSong Mansion, Terra Industrial & Trade Park Chegongmiao, Futian District, Shenzhen, China
Date of Test:	Oct. 03, 2016 to Nov. 03, 2016

# Shenzhen Microtest Co., Ltd. http://www.mtitest.com

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.



- Page 2 of 15 -

# **Table of Contents**

Tal	ble of Contents	2
1.	General description	5
1.1	Feature of equipment under test (EUT)	5
1.2	EUT operation mode	5
1.3	Test conditions	5
1.4	Ancillary equipment list	5
1.5	Measurement uncertainty	5
2.	Testing site	6
3.	List of test equipment	7
4.	Test Result	8
4.1	Conducted emission	8
4.2	Antenna requirement	11
4.3	20dB emission bandwidth	12
4.4	Radiated emission	13
4.5	Frequency stability	15



- Page 3 of 15 -

Test Result Certification			
Applicant's name:	Shenzhen Xinguodu Technology Co., Ltd.		
Address:	17B JinSong Mansion, Terra Industrial & Trade Park Chegongmiao, Futian District, Shenzhen, China		
Manufacture's Name:	Shenzhen Xinguodu Technology Co., Ltd.		
Address: 17B JinSong Mansion, Terra Industrial & Trade Park Chegongmiao, Futian District, Shenzhen, China			
Product name:	POS terminal		
Trademark:	NEXGO		
Model name:	T2		
Standards:	FCC Part 15.225		
Test Procedure:	ANSI C63.10-2013		

This device described above has been tested by Shenzhen Toby Technology Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

David Chen

en chon

Reviewed by:

Leon Chen

David Chen

Nov. 15, 2016

Nov. 15, 2016

Approved by:

Anglin.

Ares Liu

Nov. 15, 2016



- Page 4 of 15 -

# SUMMARY OF TEST RESULT

ltem	FCC Part No.	Description of Test	Result
1	15.203	Antenna requirement	Pass
2	15.207	AC power line conducted P	
3	15.231(c)	20dB bandwidth	Pass
4	15.225	Radiated emission	Pass
5	15.225	Frequency stability	Pass



- Page 5 of 15 -

# 1. General description

# 1.1 Feature of equipment under test (EUT)

Product name:	POS terminal	
Model name:	T2	
Operating frequency:	13.56MHz	
Modulation type:	subcarrier load modulation	
Power supply:	DC 8.5V from adapter	
Adapter information:	Model: HKA02108525-8A Input: 100-240VAC 0.8A 50/60Hz Output: 8.5V 2.5A	
Antenna designation:	Loop antenna (Antenna Gain: 0dBi)	

## 1.2 EUT operation mode

During testing, the EUT is operated in a keeping TX mode.

## 1.3 Test conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 20°C~30°C
- Humidity: 30%~70%
- Atmospheric pressure: 98kPa~101kPa

## 1.4 Ancillary equipment list

Equipment	Model	S/N	Manufacturer
/	/	/	/

## 1.5 Measurement uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, U=2xUc(y)

RF frequency	1 x 10-7
RF power, conducted	± 1 dB
Conducted emission(150kHz~30MHz)	± 2.5 dB
Radiated emission(30MHz~1GHz)	± 4.2 dB
Radiated emission (above 1GHz)	± 4.3 dB
Temperature	±1 degree
Humidity	± 5 %



- Page 6 of 15 -

# 2. Testing site

Test Site	Shenzhen Toby Technology Co., Ltd.	
Test Site Location	1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467, Shenzhen, Guangdong, China	
FCC Registration No.:	811562	
CNAS Registration No.:	CNAS L5813	



- Page 7 of 15 -

# 3. List of test equipment

For AC power line conducted emission:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
LISN	R&S	ENV216	101313	2016.12.06
LISN	SCHWARZBECK	NNLK 8129	8129245	2016.12.25
Pulse Limiter	SCHWARZBECK	VTSD 9561F	9716	2016.12.25
Test Cable	N/A	N/A	C01	2016.12.06
EMI Test Receiver	R&S	ESCI	101160	2016.12.06

For Radiated emission:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
Log-Bicon Antenna	MESS-ELEKTRO NIK	VULB 9160	3058	2016.12.11
Horn Antenna	Schwarzbeck	BBHA 9120D	631	2016.12.05
Horn Antenna	Schwarzbeck	BBHA 9170	373	2016.12.05
Loop Antenna	Schwarzbeck	FMZB 1519 B	00005	2016.12.05
Test Cable	United Microwave	57793	1m	2016.12.05
Test Cable	United Microwave	A30A30-5006	10M	2016.12.05
Microwave Pre_amplifier	Agilent	8449B	3008A01714	2016.12.05
Pre-Amplifier	Anritsu	MH648A	M09961	2016.12.05
EMI Test Receiver	R&S	ESCI-7	101318	2016.12.05
Spctrum analyzer	Agient	E4470B	MY41441082	2017.06.01

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



- Page 8 of 15 -

# 4. Test Result

# 4.1 Conducted emission

#### 4.1.1 Limit

Frequency (MHz)	Limit		
	Quasi-peak	Average	
0.15-0.5	66 to 56	56 50 46	
0.5-5	56	46	
5-30	60	50	

Note: Decreases with the logarithm of the frequency from 0.15MHz to 0.5MHz.

#### 4.1.2 Test method

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/50uH of coupling impedance for the measuring instrument.

2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

4. LISN is at least 80 cm from nearest part of EUT chassis.

5. The resolution bandwidth of EMI test receiver is set at 9kHz.

#### 4.1.3 Test Result



## - Page 9 of 15 -

Temperature:	25°C	Relative	57%
Pressure:	101kPa	Polarization:	L
Test voltage:	AC 120V/60Hz	Test mode:	Transmitting
100.0 dBuV			
90			
80			
70			
60		FCC	Part15 ClassB AC Conduction(QP)
XX XX		FCCP	art15 ClassB AC Conduction(AVG)
50 MM X	<u> </u>		
40	Mar an ere and the start deal	www.astata	A the a state but at a solution of the attended the attended to be a solution
30 Mandah	and and an and an and an and an and and	a hundred a load of the for the forest of the second second second second second second second second second se	peak
20	VV "Connectored and a second second	norman and the company and a straight of the state of the	where where the second
20			
10			
0.0	0.5	(MHz)	5 30.000
		(a. (24))	
R	eading Correct Measur	e-	
No. Mk. Freq.	Level Factor ment	Limit Over	Comment
1 * 0.1863	21.06 30.02 51.08	64.20 -13.12 QP	Comment
2 0.1863	1.34 30.02 31.36	54.20 -22.84 AVG	
3 0.2033	18.06 30.02 48.08	63.47 -15.39 QP	
4 0.2033	-0.17 30.02 29.85	53.47 -23.62 AVG	
5 0.2714 6 0.2714	11.97 30.02 41.99 -2.60 30.02 27.42	61.07 -19.08 QP	
7 0.3105	5.41 30.02 35.43	59.95 -24.52 QP	
8 0.3105	-3.10 30.02 26.92	49.95 -23.03 AVG	
9 0.9247	-1.35 30.02 28.67	56.00 -27.33 QP	
10 0.9247	-4.42 30.02 25.60	46.00 -20.40 AVG	
11 1.8614	-1.79 30.02 28.23	56.00 -27.77 QP	
12 1.8614	-4.60 30.02 25.42	46.00 -20.58 AVG	



## - Page 10 of 15 -

Temperature:		25℃			Relative		57%		
Pressure:		101k	101kPa		Polarization:		Ν		
Test vo	Test voltage:		AC 120V/60Hz		Test mode:		Transmitting		
100.0 d	BuV								
90									
80									
70									
60						FCCF	Part15 ClassB A	C Conduction(QP)	
thit	No.					FCCPa	art15 ClassB AC	Conduction(AVG)	
50	MAN ×								
40	* Y INAM	North Martin	al al Marta	han Al Talatana	down date of the state of the	and be ph the	NA ANTANA	with white the second	ocerthinet neak
30 10	Munthead	INA	a l hata ta du la duna	uhanan. Indexaketen	a na ana ang ang ang ang ang ang ang ang	Maccontract on the	(VWWWWWWW	an Abrill all second training and an an	peak
20		w marwh	have have been	har have the production of the	man and the second as	were approached the property	mannant	anadhahammanana	where where AVG
10									
0.0		0.5			(MHz)	5	5		30.000
		Reading	Correct	Measure-					
No. M	lk. Freq.	Level	Factor	ment		Detector	Commont		
1 *	0.1745	18.40	30.02	48.42	64.74 -16.32	QP	Comment		
2	0.1745	2.08	30.02	32.10	54.74 -22.64	AVG			
3	0.2141	8.59	30.02	38.61	63.04 -24.43	QP			
4	0.2141	-1.45	30.02	28.57	53.04 -24.47	AVG			
5	0.2525	14.23	30.02	44.25	61.67 -17.42	QP			
6	0.2525	-1.85	30.02	28.17	59.48 -24.45	AVG			
	0.3286	-3.14	30.02	26.88	49.48 -22.60	AVG			
9	0.5577	-0.07	30.02	29.95	56.00 -26.05	QP			
10	0.5577	-4.01	30.02	26.01	46.00 -19.99	AVG			
11	1.2073	-1.79	30.02	28.23	56.00 -27.77	QP			
12	1.2073	-4.68	30.02	25.34	46.00 -20.66	AVG			



- Page 11 of 15 -

# 4.2 Antenna requirement

# 4.2.1 Requirement defined in FCC 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 4.2.2 EUT antenna description

The radio antenna of EUT is an internal permanently attached antenna, the maximum gain is 0dBi. So the antenna meets the requirement of this part.



- Page 12 of 15 -

## 4.3 20dB emission bandwidth

#### 4.3.1 Test method

Set Spectrum Analyzer centre Frequency= Fundamental Frequency, RBW=10 kHz, VBW= 30 kHz, Span= 200 kHz

Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

#### 4.3.2 Test result





- Page 13 of 15 -

## 4.4 Radiated emission

#### 4.4.1 Limit

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209, the field strength of emissions from intentional radiators shall not exceed the following:

Frequency (MHz)	Field strength µV/m	Field strength dBµV/m	Detector	Measurement distance
1.705-30	30	29.54	QP	
30-88	100	40	QP	
88-216	150	43.5	QP	
216-960	200	46	QP	3m
960-1000	500	46	QP	
Above 1000	500	54	AV	
Above 1000	5000	74	PK	

Note: the measurement distance is 30m for 1.705MHz to 30MHz, 3m for above 30MHz.

#### 4.4.2 Test method

The measuring distance of 3m shall be used for measurements at frequency up to 1GHz. The EUT was placed on a rotating 0.8m high above ground; the table was rotated 360 degrees to determine the position of the highest radiation.

For test frequency up to 30MHz, a loop antenna is used; the centre of the loop antenna is 1m above the ground.

For test frequency above 30MHz, he Test antenna shall vary between 1m and 4m, both Horizontal and Vertical polarizations are set to make measurement.

For the actual test configuration, please see the test setup photo.

#### 4.4.3 Test Result



- Page 14 of 15 -

Report No.: MTi160930E101

Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dBµV/m	dBµV/m		
13.56	/	52.3	124	Peak	
13.56	/	51.7	124	QP	
13.553	/	43.1	70.47	QP	
13.567	/	41.5	70.47	QP	
13.41	/	26.4	60.51	QP	
13.71	/	24.3	60.51	QP	
13.11	/	25.6	60.51	QP	Pass
14.01	/	24.1	60.51	QP	
27.12	/	25.8	69.54	QP	
40.68	V	27.6	40	QP	
40.68	Н	30.5	40	QP	
54.24	V	28.1	40	QP	
54.24	Н	27.3	40	QP	

Remark:

1, Performed pretest to three orthogonal axes (x, y, z axis), the worst case emissions(y axis) were reported.

2, other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).



- Page 15 of 15 -

#### 4.5 Frequency stability

#### 4.5.1 Limit

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### 4.5.2 Test Result

Voltage (VAC)	Temp. (°C)	Frequency (MHz)	Deviation (%)	Limit (%)	
230	-20	13.560378	0.003%		
230	-10	13.560384	0.003%		
230	0	13.560327	0.002%		
230	10	13.560335	0.002%		
230	20	13.560391	0.003%	+/ 0.01%	
230	30	13.560376	0.003%	±7=0.0176	
230	40	13.560330	0.002%		
230	50	13.560353	0.003%		
V <sub>up</sub> =138	20	13.560376	0.003%		
V <sub>low</sub> =102	20	13.560368	0.003%		

----END OF REPORT----