

TEST REPORT

FCC RULES Part 15 Subpart C §15.231

FCC ID : SY55WY8412

Equipment Under Test	:	Remote Keyless Entry System
Model No.	:	5WY8412
Serial No.	:	N/A
Applicant	:	Siemens Automotive Systems Corporation
Manufacturer	:	Siemens Automotive Systems Corporation
Date of Test(s)	:	2006-01-19~2006-02-06
Date of Issue	:	2006-02-06

In the configuration tested, the EUT complied with the standards specified above.

Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Testing Korea Co., Ltd. or testing done by SGS Testing Korea Co., Ltd. in connection with distribution or use of the product described in this report must be approved by SGS Testing Korea Co., Ltd. in writing.

VERIFICATION OF COMPLIANCE

Applicant : Siemens Automotive Systems Corporation
Kind of Product : Remote Keyless Entry System
Brand Name : N/A
Model Name : 5WY8412
Model Difference : -
Report File No. : STROR-06-015
Date of test : 2006-02-06
Receiver EUT : -

APPLICABLE STANDARDS	
STANDARD	TEST RES ULT
Part 15 Subpart C §15.231	Complied

The above equipment was tested by SGS Testing Korea Co., Ltd. for compliance with the requirements set forth in the FCC RULES Part 15 Subpart C §15.231. The results of testing in this report apply to the product system that was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Date
2006-02-06

 Leo Kim

Approved By

Date
2006-02-06

 Albert Lim

INDEX

<u>CONTENTS</u>	<u>Page</u>
1. General Description of EUT -----	<u>4</u>
2. General Information of EUT -----	<u>4</u>
3. Test Procedure -----	<u>5</u>
4. Test Condition-----	<u>6</u>
Test Results	
5. Field Strength of the Carrier -----	<u>7</u>
6. Spurious Emission ---- -----	<u>8</u>
7. Bandwidth of Operation Frequency -----	<u>9</u>
8. Transmission Time -----	<u>10</u>
9. Attachment A – Photos of the Test Set up -----	<u>11</u>
10.Attachment B – Photos of the EUT-----	<u>12</u>

1. General Description of EUT

Remote Keyless Entry:

The RKE transmitter transmits at 315MHz for NA an FSK modulated data signal to the SRx. The RF system of SRx receives this encrypted RF signal. The SRx send the signal to corresponding the host Body Control Module through single wired K-line bus then the host module broadcasts the requested remote commands to the appropriate control modules in the vehicle through CAN-communication line. In general the following functions are provided:

- Lock the car
- Unlock the car
- Unlock the trunk of the car
- Panic

2. General Information of EUT

Transmitter

Power Supply	DC3V(Lithium)
Operating Frequency	315 MHz
Modulation	FSK
Operating Temperature	-20 ~ +60
Frequency Generation	X-Tal
Communication method	One - Way
Size	35 mm(W) x 50 mm(L) x 10 mm(H)
Antenna Type	Integrated PCB Pattern

Details of Modification

N/A

3. Test Procedure

The test procedures are performed following the test standards ANSI C.63.4-2000, if applicable.

3.1 Conducted Emission

Testing was performed according to ANSI C.63.4-2000 in a shielded room with peripherals placed on a table, 0.8 m high over a metal floor.

It was located more than required distance away from the shield room wall.

3.2 Radiated Emission

Testing was performed according to ANSI C.63.4-2000 at an open field test site. The EUT was placed on a 0.8 m high table along with the peripherals.

The turn-table was separated from the antenna at a distance of 3 meters. Cables were placed in a position to produce maximum emissions as determined by experimentation and the operation mode was selected for maximum.

The frequencies and amplitudes of maximum emission were measured at various azimuths, antenna heights and antenna polarities.

Reported are maximized emission levels.

4. Test Condition

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it).

During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner, which tends to maximize its emission level in a typical application.

Conducted Emission Test

It needs not to test requirement, because the EUT supplies from a DC battery.

Radiated Emission Test

Preliminary radiated emission tests were conducted using the procedure in ANSI C63.4-2000 clause 8.3.1.1. to determine the worst operating condition. Final radiated emission tests were measured at 3 meter open field test site. To complete the test configuration required by the FCC, the EUT was tested in all three orthogonal planes.

4.2 EUT Operation

EUT was tested according to the following operation modes provided by the specifications given by the manufacturer, and reported the worst emissions.

4.3 Peripherals / Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement.

Type of Peripheral Equipment Used:

Description	Model Name	Serial NO	Manufacturer

5. Field Strength of the Carrier FCC Part 15, Subpart C, Section 15.231(b)

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 43 %

Temperature: 21

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Carrier Freq. (MHz)	Amp. (dBuV/m)	Detect Mode	Pol.	Ant. (dB/m)	Cable (dB)	Amp. (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
315	54.62	Peak	H	15.93	1.85	72.4	75.62	3.22

* Remark: To get a maximum emission level from the EUT, the EUT was moved throughout the XY,XZ, and YZ planes.

Note :

1.A peak limit is 20dB above the average limit.

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
EMI Test Receiver	R&S	ESIB26	2006-03-24
Turn Table	DI-1500	Daeil EMC	N/A
Antenna Master	1050	EMCO	N/A
Log-periodic antenna	Schwarzbeck	UHALP9107	2006-05-02

6. Spurious Emission FCC Part 15, Subpart C, Section 15.231(b)

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 43 %

Temperature: 21

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Freq. (MHz)	Amp. (dBuV/m)	Detect Mode	Pol.	Ant. (dB/m)	Cable (dB)	Amp. (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
630	26.81	Peak	H	21.75	2.64	51.2	55.62	4.42
945	24.08	Peak	H	25.19	3.33	52.6	55.62	3.02
1260	21.44	Peak	H	24.44	4.72	50.6	55.62	5.02
1575	20.66	Peak	H	25.48	5.26	51.4	54.00	2.60
1890	15.81	Peak	H	26.53	5.86	48.2	55.62	7.42
2205	14.83	Peak	H	27.51	6.56	48.9	55.62	6.72

Remark: Other spurious frequencies were not found up to 6000MHz

To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes.

Notes :

1. H: Horizontal polarization, V: Vertical polarization
2. Emission Level = Reading + Antenna Factor + Cable Loss
3. A peak limit is 20dB above the average limit

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
EMI Test Receiver	R&S	ESIB26	2006-03-24
Horn antenna	Electro-Metrics	RGA-60	2007-03-22
Pre-Amplifier	Agilent	8449B	2006-05-20
Pre-Amplifier	SONOMA INSTRUMENT	305	2006-06-07
Turn Table	DI-1500	Daeil EMC	N/A
Antenna Master	1050	EMCO	N/A
Horn antenna	Schwarzbeck	9120D	2006-07-23
Log-periodic antenna	Schwarzbeck	UHALP9107	2006-05-02
Biconical antenna	EMCO	3110	2006-04-04

7. Bandwidth of Operation Frequency FCC Part 15, Subpart C, Section 15.231(c)


Humidity Level : 43 %

Temperature: 21

Limit of 20dB Bandwidth : $315 \text{ MHz} \times 0.0025 = 787.5 \text{ kHz}$

Carrier Freq. (MHz)	Bandwidth of the emission. (kHz)	Limit (kHz)	Remark
315	91.8	787.5	The point 20dB down from the modulated carrier

The plot of test result is attached as below



Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum Analyzer	Agilent	E4440A	2006-05-20

8. Transmission Time

FCC Part 15, Subpart C, Section 15.231(a) (1)


Humidity Level : 43 %

Temperature: 21

Limit of Transmission Time : A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Carrier Freq. (MHz)	Transmission Time (sec)	Limit (sec)	Pass/Fail
315	0.492	5	Pass

The plot of test result is attached as below



Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum Analyzer	Agilent	E4440A	2006-05-20

9. Attachment A – Photos of the test set up

