FCC ID: 2AQBD-60245

RF Exposure Evaluation

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)								
(A) Limits for Occupational/Controlled Exposures												
0.3–3.0	614	(4) Jan 1.63 (4) Jan 1	*(100)	College College								
3.0–30	1842/f	4.89/f	*(900/f²)	6 6 5 1								
30–300	61.4	0.163	1.0° ct	STATE 6 STATE STATE								
300–1500	ABTURNE OF SET LE	THE CONTRACTOR OF THE PARTY OF	f/300	TESTING 6 STILL								
1500–100,000	OCTO THE TIME OF SE	THE LEST MADE OF STATE STATE AS	6 6 A 5 CH	6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6								
(B) Limits for General Population/Uncontrolled Exposure												
0.3–1.34	614	_	*(100)	30 76 15								
1.34–30	824/f	2.19/f	*(180/f²)	30 6 548								
30–300	27.5	(£) 8 0.073 (£) 8	0.2	6 (4 30 s								
300–1500	S OF THE THE CO	CALLER IN SECULIARIES	f/1500	30 30								
1500–100,000	INC CO CE TESTINA		1.0 ° (5)	30 75								

f = frequency in MHz

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm², Pout = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, and highest channel individually.



Test Result of RF Exposure Evaluation

For 2.4G Wi-Fi Antenna gain=2.21dBi

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm²)	Power Density At 20 cm (mW/cm²)	Test Results
2412	20.00	16.56	16±1	50.12	1.66	5 61 K	0.0166	Pass
2437	20.00	0 16.64	16±1	50.12	1.66	THE ST SON	0.0166	Pass
2462	20.00	16.54	16±1	50.12	1.66	ISTITUTE OF	0.0166	Pass

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.