

# **EMF TEST REPORT**

Test Report No. : OT-20D-RWD-082

**Reception No.** : 2011004695

Applicant : C&A Marketing Inc.

Address : 114 Tived Lane East, Edison NJ 08837

Manufacturer : C&A Marketing Inc.

Address : 114 Tived Lane East, Edison NJ 08837

Type of Equipment : HP Sprocket Select Photo Printer

FCC ID. : 2AD2W-HPISPSLE

Model Name : HPISPSLE

Multiple Model Name: N/A

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : November 25, 2020

Date of issue : December 21, 2020

#### **SUMMARY**

The equipment complies with the regulation; FCC PART 15 SUBPART C Section 15.247

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

オイン

/ Su-Min Yoo / Assistant Manager

Tested by

Reviewed by

/ Ha-Ram Lee / Manager

ONETECH Corp.

Approved by

/ Ki-Hong, Nam / General Manager

ONETECH Corp.

ONETECH Corp.





## **CONTENTS**

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	5
3. EUT MODIFICATIONS	5
4. RF EXPOSURE EVALUATION	6
4.1 RF Exposure Calculation	
4.2 EUT DESCRIPTION	6
4.3 TEST RESULT OF SAR EXCLUSION FOR DEVICES	7





**Revision History** 

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-20D-RWD-082	December 21, 2020	Initial Release	All





## 1. VERIFICATION OF COMPLIANCE

Applicant : C&A Marketing Inc.

Address : 114 Tived Lane East, Edison NJ 08837

Contact Person: Chaim Piekarski / Chief Executive Officer

Telephone No.: 8482442000

FCC ID : 2AD2W-HPISPSLE

Model Name : HPISPSLE

Brand Name : hp
Serial Number : N/A

Date : December 21, 2020

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	HP Sprocket Select Photo Printer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

<sup>-.</sup> The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



## 2. GENERAL INFORMATION

## 2.1 Product Description

The C&A Marketing Inc., Model HPISPSLE (referred to as the EUT in this report) is a HP Sprocket Select Photo Printer. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	HP Sprocket Select Photo Printer			
O	Bluetooth	2 402 MHz ~ 2 480 MHz		
Operating Frequency	Bluetooth LE			
RF Output Power	Bluetooth	1 Mbps	2.79 dBm	
		2 Mbps	0.74 dBm	
		3 Mbps	1.17 dBm	
	Bluetooth LE	0.26 dBm		
N. I. CCI. 1	Bluetooth	79 Channels		
Number of Channel	Bluetooth LE	40 Channels		
Madulatian Tana	Bluetooth	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps, 8-DPSK for 3 Mbps		
Modulation Type	Bluetooth LE	GFSK		
Antonno Tuno	Bluetooth	Dielectric Chip Antenna		
Antenna Type	Bluetooth LE			
Antenna Gain	Bluetooth	10.15:		
Amenna Gam	Bluetooth LE	1.8 dBi		
List of each Osc. or crystal	24 MIX			
Freq.(Freq. >= 1 MHz)	24 MHz			
Rated Supply Voltage	DC 7.4 V			

## 2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

#### 3. EUT MODIFICATIONS

-. None





## 4. RF EXPOSURE EVALUATION

## **4.1 RF Exposure Calculation**

According to the FCC rule 1.1310, the limit for General Population/Uncontrolled exposure is  $1 \text{ mW/cm}^2$  for the device operating  $1.500 \sim 100\,000 \text{ MHz}$ .

**4.2 EUT Description** 

Kind of EUT	HP Sprocket Select Photo Printer		
	■ Portable (< 20 cm separation)		
Device Category	☐ Mobile (> 20 cm separation)		
	□ Others		
_	□ MPE		
Exposure Evaluation Applied	□ SAR		
	■ SAR Test Exclusion Evaluation		

Report No.: OT-20D-RWD-082



#### 4.3 Test Result of SAR Exclusion for Devices

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is [(Max. Power of channel, including tune-up tolerance, mW)/(Min. test separation distance, mm)] X [  $\sqrt{f(GHz)}$ ] < 3 = (2.39/5) X  $\sqrt{2.441}$  =0.75

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

Mode	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
BDR (1 Mbps)	2 441	$2.79 \pm 1.0$	3.79	2.39	5	0.75
EDR (2 Mbps)	2 441	$0.74 \pm 1.0$	1.74	1.49	5	0.47
EDR (3 Mbps)	2 441	1.17 ± 1.0	2.17	1.65	5	0.52
BLE	2 440	$0.26 \pm 1.0$	1.26	1.34	5	0.42